



# APPENDIX I RADIO FREQUENCY EXPOSURE

## LIMIT

According to RSS-Gen §5.5, before equipment certification is granted, the applicable requirements of RSS-102 shall be met.

## EUT Specification

<b>EUT</b>	Wireless-N Selectable-Band Access Point with PoE
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others: <u>Bluetooth: 2.402GHz ~ 2.480GHz</u>
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm2) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure(S=1mW/cm2)
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	<b>Mode 1:</b> 2.4GHz: IEEE 802.11n HT 20 MHz mode: 25.04 dBm(319.15mW) IEEE 802.11n HT 40 MHz mode: 25.57 dBm(360.57mW) <b>Mode 2:</b> 2.4GHz: IEEE 802.11n HT 20 MHz mode: 24.91 dBm(309.74mW) IEEE 802.11n HT 40 MHz mode: 25.50 dBm(354.81mW) <b>Mode 3:</b> IEEE 802.11b mode: 21.76 dBm(149.96mW) IEEE 802.11g mode: 24.15 dBm(260.01mW) IEEE 802.11n HT 20 MHz mode: 25.10 dBm(323.59mW) IEEE 802.11n HT 40 MHz mode: 25.36 dBm(343.55mW)
<b>Antenna Specification</b>	Antenna Type: PIFA Antenna IEEE 802.11b/g mode: Antenna 1: 4.32 dBi Antenna 2: 4.67 dBi Antenna 3: 3.96 dBi MIMO: $10 * \text{LOG}(((10^{(4.32/20)} + 10^{(4.67/20)})^2) / 2) = 7.51 \text{ dBi}$ (Numeric gain: 5.63)



<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A
---------------------------	--

**Remark:**

*The maximum output power is 25.57dBm (360.571mW) at 2442MHz (with 5.63 numeric antenna gain.)*

**TEST RESULTS**

*No non-compliance noted.*

**MPE EVALUATION**

*No non-compliance noted.*



**Calculation**

Given  $E = \frac{\sqrt{30 \times P \times G}}{d}$  &  $S = \frac{E^2}{3770}$

Where  $E =$  Field strength in Volts / meter

$P =$  Power in Watts

$G =$  Numeric antenna gain

$d =$  Distance in meters

$S =$  Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where  $d =$  Distance in cm

$P =$  Power in mW

$G =$  Numeric antenna gain

$S =$  Power density in mW / cm<sup>2</sup>

**Maximum Permissible Exposure**

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where  $P =$  Power in mW

$G =$  Numeric antenna gain

$S =$  Power density in mW / cm<sup>2</sup>



**Mode 1**

**IEEE 802.11n HT 20 MHz mode:**

EUT output power = 319.15 mW

Numeric Antenna gain = 5.63

→ Power density = 0.3575 mW / cm<sup>2</sup>

**IEEE 802.11n HT 40 MHz mode:**

EUT output power = 360.57mW

Numeric Antenna gain = 5.63

→ Power density = 0.4039 mW / cm<sup>2</sup>

**Mode 2**

**IEEE 802.11n HT 20 MHz mode:**

EUT output power = 309.74 mW

Numeric Antenna gain = 5.63

→ Power density = 0.3470 mW / cm<sup>2</sup>

**IEEE 802.11n HT 40 MHz mode:**

EUT output power = 354.81mW

Numeric Antenna gain = 5.63

→ Power density = 0.3975 mW / cm<sup>2</sup>



**Mode 3**

**IEEE 802.11b mode:**

EUT output power = 149.96 mW

Numeric Antenna gain = 2.93

→ Power density = 0.0874 mW / cm<sup>2</sup>

**IEEE 802.11g mode:**

EUT output power = 260.01 mW

Numeric Antenna gain = 2.93

→ Power density = 0.1516 mW / cm<sup>2</sup>

**IEEE 802.11n HT 20 MHz mode:**

EUT output power = 323.59 mW

Numeric Antenna gain = 5.63

→ Power density = 0.362541 mW / cm<sup>2</sup>

**IEEE 802.11n HT 40 MHz mode:**

EUT output power = 343.55mW

Numeric Antenna gain = 5.63

→ Power density = 0.3849 mW / cm<sup>2</sup>

*(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.)*



<b>EUT</b>	Wireless-N Selectable-Band Access Point with PoE
<b>Frequency band (Operating)</b>	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> WLAN: 5.725GHz ~ 5.850GHz <input type="checkbox"/> Others: <u>Bluetooth: 2.402GHz ~ 2.480GHz</u>
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm2) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm2)
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	<b>Mode 1:</b> 5GHz: IEEE 802.11n HT 20 MHz mode: 23.68 dBm(233.34mW) IEEE 802.11n HT 40 MHz mode: 24.34 dBm(271.64mW) <b>Mode 2:</b> 5GHz: IEEE 802.11n HT 20 MHz mode: 23.97 dBm(249.45mW) IEEE 802.11n HT 40 MHz mode: 23.79 dBm(239.33mW) <b>Mode 3:</b> IEEE 802.11a mode: 22.45 dBm(175.7mW) IEEE 802.11n HT 20 MHz mode: 24.14 dBm(259.41mW) IEEE 802.11n HT 40 MHz mode: 24.48 dBm (280.54mW)
<b>Antenna gain (Max)</b>	Antenna Type: PIFA Antenna Antenna Gain: IEEE 802.11a: Antenna 1: 4.88 dBi Antenna 2: 4.97 dBi Antenna 3: 4.74 dBi MIMO: $10 \cdot \text{LOG}(((10^{(4.88/20)} + 10^{(4.74/20)})^2)/2) = 7.94 \text{ dBi}$ (Numeric gain: 6.22)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A
<b>Remark:</b>	
<i>The maximum output power is <u>24.34dBm (271.64mW)</u> at <u>5795MHz</u>, (with <u>6.22 numeric antenna gain</u>.)</i>	

**TEST RESULTS**

No non-compliance noted.

**MPE EVALUATION**

No non-compliance noted.



### Calculation

Given  $E = \frac{\sqrt{30 \times P \times G}}{d}$  &  $S = \frac{E^2}{3770}$

Where  $E =$  Field strength in Volts / meter

$P =$  Power in Watts

$G =$  Numeric antenna gain

$d =$  Distance in meters

$S =$  Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where  $d =$  Distance in cm

$P =$  Power in mW

$G =$  Numeric antenna gain

$S =$  Power density in mW / cm<sup>2</sup>

### Maximum Permissible Exposure

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where  $P =$  Power in mW

$G =$  Numeric antenna gain

$S =$  Power density in mW / cm<sup>2</sup>



**Mode 1**

**IEEE 802.11n HT 20 MHz mode:**

EUT output power = 233.34 mW

Numeric Antenna gain = 6.22

→ Power density = 0.2888 mW / cm<sup>2</sup>

**IEEE 802.11n HT 40 MHz mode:**

EUT output power = 271.64mW

Numeric Antenna gain = 6.22

→ Power density = 0.3362 mW / cm<sup>2</sup>

**Mode 2**

**IEEE 802.11n HT 20 MHz mode:**

EUT output power = 249.45 mW

Numeric Antenna gain = 6.22

→ Power density = 0.3087 mW / cm<sup>2</sup>

**IEEE 802.11n HT 40 MHz mode:**

EUT output power = 239.33mW

Numeric Antenna gain = 6.22

→ Power density = 0.2962 mW / cm<sup>2</sup>



**Mode 3**

**IEEE 802.11a mode:**

EUT output power = 175.7 mW

Numeric Antenna gain = 3.14

→ Power density = 0.1097 mW / cm<sup>2</sup>

**IEEE 802.11n HT 20 MHz mode:**

EUT output power = 259.41 mW

Numeric Antenna gain = 6.22

→ Power density = 0.3210 mW / cm<sup>2</sup>

**IEEE 802.11n HT 40 MHz mode:**

EUT output power = 280.54mW

Numeric Antenna gain = 6.22

→ Power density = 0.3472 mW / cm<sup>2</sup>

*(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.)*