

Report No	EE0040-1
Client	Locknetics Security Engineering 575 Birch Street Forestville, CT 06010
Phone	(860) 314-5248
Fax	(860) 314-2452
FRN	0005178298
Models	VIP5100 and VIP5500 Series
FCC ID	P2GVIP
Equipment Type Equipment Code	Low Power Communication Device Transmitter DXX
Results	As detailed within this report
Prepared by	 Evan Gould – Test Engineer
Authorized by	 Michael Buchholz – EMC Manager
Issue Date	2/2/04
Conditions of issue	This Test Report is issued subject to the conditions stated in ‘terms and conditions’ section of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.

Table Of Contents

Summary3

Test Methodology3

EUT Configuration4

Statement of Conformity5

Fundamental and Harmonic Emissions6

AC Line Conducted Emission Measurements7

Voltage Variation.....8

Test Equipment Used9

Terms And Conditions10

A2LA Accreditation12



Summary

This report is an application for certification of transmitters operating pursuant to 47 CFR 15.209. The products are the VIP5100 and VIP5500 Series locks. The specific product tested was the VIP5596. The 5100's are cylindrical locks, and the 5500's are mortise locks. The model variations within these groups are summarized in the accompanying manual exhibit.

Test Methodology

Radiated emissions testing is performed according to the procedures specified in ANSI C63.4 (2002). Receiving loop antenna was rotated in order to maximize radiated emission measurements.

Frequency range investigated: 9kHz – 1GHz

Measurement distance:	9kHz – 30MHz	1m
	30MHz – 1000MHz	3m

AC Line conducted emissions testing was performed with a 50 Ω /50 μ H LISN.

EUT Configuration

EUT Configuration				
Work Order: E0040				
Company: Locknetics Security Engineering				
Company Address: 575 Birch Street Forestville, CT 06010				
Contact: Adam O'Day				
Person Present: Adam O'Day				
MN		SN	FCC ID	
EUT: VIP5596		-	P2GVIP	
EUT Max Frequency: 4MHz				
Support Equipment:	MN	SN	FCC ID	
Panel Interface Board	PIB	-	-	
Keri System Panel	PXL-500/PXL-510	-	-	
RadioShack 12VDC adaptor	273-1779	-	-	
EUT Cables:	Qty	Shielded?	Length	Ferrites
RS485/DC cable	1	Yes	1m	No
Unpopulated EUT Ports:	Qty	Reason		
none				
Software / Operating Mode Description:				
Operating normally; locked; oscillators are running				

Statement of Conformity

The VIP5596 has been found to conform with the following parts of the 47 CFR as detailed below:

Part 2	Part 15	Comments
	15.15(b)	The product contains no user accessible controls that increase transmission power above allowable levels.
2.925	15.19	The label is shown in the label exhibit.
	15.21	Information to the user is shown in the instruction manual exhibit.
	15.27	No special accessories are required for compliance.
	15.203	The antenna is not accessible to the user and therefore cannot be easily removed. (The antenna and its connector are underneath the PCB assembly which is in turn professionally installed in the door lock enclosure.)
	15.205 15.209	The fundamental is not in a Restricted band and the spurious and harmonic emissions in the Restricted bands comply with the general emission limits of 15.209.
	15.207	The unit meets the AC line conducted emissions requirements of 15.207.

Fundamental and Harmonic Emissions

LIMITS

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

[15.209(a)]

MEASUREMENTS

Fundamental and Harmonics (9kHz-30MHz)										Curtis-Straus LLC		
Date: 19-Jan-04			Engineer: Evan Gould					Work Order: E0040				
Company: Locknetics			EUT: VIP5596 and PIB					Fundamental Frequency: 125kHz				
Test Site: "T"			Cable: 65 ft RG8A/U					Pre-amp: Green				
Antennas: Small Loop (9kHz-30MHz)			Filter/Attenuator: N/A					Analyzer: Yellow				
Measurement Distance: 1 meter							Resolution BW: 9kHz					
Detector Type: Peak							Video BW: 30kHz					
Notes: No spurious emissions were detected.												
Antenna Polarization (0° / 90°)	Frequency (MHz)	Reading (dBµV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Filter/Attenuator Factor (dB)	Distance Factor (dB)	Adjusted Reading (dBµV/m)	47 CFR 15.209			
									Limit (dBµV/m)	Margin (dB)	Result (Pass/Fail)	
0° pk	0.1258	53.7	21.5	62.7	0.0	0.0	99.0	-4.1	25.6	-29.7	Pass	
0° pk	0.2516	23.9	21.4	57.7	0.0	0.0	99.0	-38.8	19.6	-58.4	Pass	
0° pk	0.3774	25.2	21.4	55.3	0.0	0.0	99.0	-39.9	16.1	-56.0	Pass	

Radiated Emissions Table							Curtis-Straus LLC		
Date: 19-Jan-04			Company: Locknetics				Work Order: E0040		
Engineer: Evan Gould			EUT Desc: VIP5596 and PIB						
Frequency Range: 30-1000MHz					Measurement Distance: 3 m				
Notes:					EUT Max Freq: 4MHz				
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dBμV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dBμV/m)	47 CFR 15.209		
							Limit (dBμV/m)	Margin (dB)	Result (Pass/Fail)
noise floor	35.0	28.0	20.5	12.5	0.7	20.7	40.0	-19.3	Pass
noise floor	52.4	24.6	20.4	6.9	0.9	12.0	40.0	-28.0	Pass
noise floor	84.4	29.0	20.4	7.8	1.2	17.6	40.0	-22.4	Pass
V	90.6	33.6	20.4	7.5	1.2	21.9	43.5	-21.6	Pass
noise floor	116.0	20.6	20.4	6.9	1.4	8.5	43.5	-35.0	Pass
H	239.7	48.8	20.4	12.3	2.1	42.8	46.0	-3.2	Pass
Table Result: Pass by -3.2 dB Worst Freq: 239.7 MHz									
Test Site: "T"		Pre-Amp: Green		Cable: 65 ft RG8A/U		Analyzer: Yellow		Antenna: Red	

AC Line Conducted Emission Measurements

LIMITS

Frequency of emission (MHz)	Quasi-peak limit (dBμV)	Average limit (dBμV)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

[47 CFR 15.207(a)]

MEASUREMENTS

AC Mains Conducted Emissions											CurtisStraus LLC		
Date: 19-Jan-04				Company: Locknetics				Table No: 3					
Engineer: Josh LeBlanc				EUT Desc: Proximity Board				Work Order: E0040					
Notes:								Test Site: EMI 1					
LISN(s): Red													
Range: 0.15-30Mhz				Other Equipment: ---				Spectrum Analyzer: Red					
Frequency (MHz)	Q.P. Readings		Ave. Readings		Impedance Factor (dB)	FCC B Applicable until July 12, 2004		FCC/CISPR B		FCC/CISPR B		Overall Result (Pass/Fail)	
	QP1 (dBµV)	QP2 (dBµV)	AV1 (dBµV)	AV2 (dBµV)		Limit (dBµV)	Margin dB	qp Limit (dBµV)	qp Margin dB	AVE Limit (dBµV)	AVE Margin dB		
9.22	10.5	6.1			20.0	47.9	-17.4	60.0	-29.5	50.0	-19.5	Pass	
12.30	14.9	14.0			20.0	47.9	-13.0	60.0	-25.1	50.0	-15.1	Pass	
12.55	14.0	13.4			20.0	47.9	-13.9	60.0	-26.0	50.0	-16.0	Pass	
13.22	12.1	11.8			20.0	47.9	-15.8	60.0	-27.9	50.0	-17.9	Pass	
13.75	9.4	11.3			20.0	47.9	-16.6	60.0	-28.7	50.0	-18.7	Pass	
14.33	9.1	9.5			20.0	47.9	-18.4	60.0	-30.5	50.0	-20.5	Pass	
Table Result: Pass by -13.00 dB Worst Freq: 12.30 MHz													

Voltage Variation

REQUIREMENT

"For intentional radiators, measurements of the variation of the...radiated signal level of the fundamental frequency component of the emission...shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage." [15.31(e)]

MEASUREMENTS

Voltage Variation			Curtis-Straus LLC					
Date: 19-Jan-04			Engineer: Evan Gould			Work Order: E0040		
Company: Locknetics			EUT: VIP5596			Fundamental Frequency: 125kHz		
Test Site: "T"			Antenna: Small loop			Analyzer: Yellow		
Measurement Distance: 1m			Resolution BW: 9kHz					
Detector Type: Peak			Video BW: 120kHz					
Notes: Nominal voltage range: 12-24VDC								
Supply Voltage	Frequency (MHz)	Reading (dBµV)						
10.2V (85%)	0.1258	51.8						
18V	0.1258	51.6						
27.6V (115%)	0.1258	51.8						

Test Equipment Used

REV. 1/12/04

SPECTRUM ANALYZERS		RANGE	MN	MFR	SN	ASSET	CALIBRATION DUE
RED		9kHz-1.8GHz	8591E	HP	3441A03559	00024	21-MAY-2004
YELLOW		9kHz-2.9GHz	8594E	HP	3523A01958	00100	08-JUL-2004
LISNS/MEASUREMENT PROBES		RANGE	MN	MFR	SN	ASSET	CALIBRATION DUE
RED		10kHz-30MHz	8012-50-R-24-BNC	SOLAR	956348	00753	01-APR-2004
OPEN AREA TEST SITE (OATS)			FCC CODE	IC CODE	VCCI CODE	CALIBRATION DUE	
SITE T			93448	IC 2762-T	R-905	25-MAR-2005	
LINE CONDUCTED TEST SITES			FCC CODE	IC CODE	VCCI CODE	CALIBRATION DUE	
EMI 1			93448	N/A	C-1801	01-MAY-2006	
ANTENNAS	RANGE	MN	MFR	SN	ASSET	CALIBRATION DUE	
RED BILOG	30MHz-1GHz	3143	EMCO	1270	00042	17-MAR-2005	
SMALL LOOP	9kHz-30MHz	PLA-130/A	ARA	1024	00755	27-JAN-2004	
PREAMPS / ATTENUATORS / FILTERS		RANGE	MN	MFR	SN	ASSET	CALIBRATION DUE
GREEN		0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00802	17-MAR-2004
RMS VOLTMETERP		MN	MNFR	SN	ASSET	CALIBRATION DUE	
TRUE-RMS VOLTMETER		79III	FLUKE	71700298	00769	15-OCT-2004	

Unless otherwise noted the calibration interval is one year. All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Terms And Conditions

Paragraph 1. SERVICES. LABORATORY will:

- 1.1 Use the degree of care and skill ordinarily exercised by and consistent with the standards of the profession.
- 1.2 Perform all technical services in substantial accordance with the generally accepted laboratory principles and practices.
- 1.3 Retain all pertinent records relating to the services performed for a period of three (3) years following submission of the report describing such services, during which period the records will be made available to CLIENT upon reasonable request.

Paragraph 2. CLIENT'S RESPONSIBILITIES. CLIENT or his authorized representative will:

- 2.1 Provide LABORATORY with all plans, schematics, specifications, addenda, change orders, drawings and other information for the proper performance of technical services.
- 2.2 Designate a person to act as CLIENT's representative with respect to LABORATORY's services to be performed on behalf of the CLIENT; such person or firm to have complete authority to transmit instructions, receive information and data, interpret and define CLIENT's policies and decisions with respect to the LABORATORY's work on behalf of the CLIENT and to order, at CLIENT's expense, such technical services as may be required.
- 2.3 Designate a person who is authorized to receive copies of LABORATORY's reports.
- 2.4 Undertake the following:
 - (a) Secure and deliver to LABORATORY, without cost to LABORATORY, preliminary representative samples of the equipment proposed to require technical services, together with any relevant data.
 - (b) Furnish such labor and equipment needed by LABORATORY to handle samples at the LABORATORY and to facilitate the specified technical services.

Paragraph 3. GENERAL CONDITIONS:

- 3.1 LABORATORY, by the performance of services covered hereunder, does not in any way assume any of those duties or responsibilities customarily vested in the CLIENT, its employees, or any other party, agency or authority.
- 3.2 LABORATORY shall not be responsible for acts of omissions of any other party or parties involved in the design, manufacture or maintenance of the equipment or the failure of any employee, contractor or subcontractor to undertake any aspect of equipment's design, manufacture or maintenance.
- 3.3 LABORATORY is not authorized to revoke, alter, release, enlarge or release any requirement of the equipment's design, manufacture or maintenance unless specifically authorized by CLIENT or his authorized representative.
- 3.4 THE ONLY WARRANTY MADE BY LABORATORY IN CONNECTION WITH ITS SERVICE PERFORMED HEREUNDER IS THAT IT WILL USE THAT DEGREE OF CARE AND SKILL AS SET FORTH IN PARAGRAPH 1 ABOVE. NO OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE OR INTENDED FOR SERVICES PROVIDED HEREUNDER.
- 3.5 Where the LABORATORY indicates that additional testing is advisable to obtain more valid or useful data, and where such testing has not been authorized, CLIENT agrees to view such test reports as inconclusive and preliminary.
- 3.6 The LABORATORY will supply technical service and prepare a report based solely on the sample submitted to the LABORATORY by the CLIENT. The CLIENT understands that application of the data to other devices is highly speculative and should be applied with extreme caution.
- 3.7 The LABORATORY agrees to exercise ordinary care in receiving, preserving and shipping (F.O.B. Littleton, MA) any sample to be tested, but assumes no responsibility for damages, either direct or consequential, which arise from loss, damage or destruction of the samples due to the act of examination, modification or testing, or technical services or circumstances beyond LABORATORY's control.
- 3.8 The LABORATORY will hold samples for thirty (30) days after tests are completed, or until the CLIENT's outstanding debts to the LABORATORY are satisfied, whichever is later.
- 3.9 The CLIENT recognizes that generally accepted error variances apply and agrees to consider such error variances in its use of test data.
- 3.10 It is agreed between LABORATORY and CLIENT that no distribution of any tests, reports or analysis other than that described below shall be made to any third party without the prior written consent of both parties unless such distribution is mandated by operation of law. It is agreed that tests, reports, or analysis results may be disclosed to third party auditors of the laboratory at the laboratory facility in the course of accreditation maintenance audits. No reference to reports or technical services of the LABORATORY shall be made in any advertising or promotional literature without the express written permission of the LABORATORY.
- 3.11 The CLIENT acknowledges that all employees of LABORATORY operate under employment contracts with the LABORATORY and CLIENT agrees not to solicit employment of such employees or to solicit information related to other clients from said employees.
- 3.12 In recognition of the relative risks and benefits of the project to both CLIENT and LABORATORY, the risks have been allocated such that the CLIENT agrees, to the fullest extent permitted by law, to limit the liability of the LABORATORY to the CLIENT for any and all claims, losses, costs, damages of any nature whatsoever or claims expenses from any cause or causes, including attorneys' fees and costs and expert witness fees and costs, so that the total aggregate liability of the LABORATORY to the CLIENT shall not exceed \$100,000, or the LABORATORY'S total fee for services rendered on this project, whichever is greater. It is intended that this limitation apply to any and all liability or cause of action however alleged or arising, unless otherwise prohibited by law.

Paragraph 4. INSURANCE:

- 4.1 LABORATORY shall secure and maintain throughout the full period of the services provided to the CLIENT adequate insurance to protect it from claims under applicable Workmen's Compensation Acts and also shall maintain one million dollars of general liability coverage to cover claims for bodily injury, death or property damage as may arise from the performance of its services.
- 4.2 The CLIENT hereby warrants that it has sufficient insurance to protect its employees adequately under applicable Workmen's Compensation Acts and for bodily injury, death, or property damage.
- 4.3 No insurance of whatever kind or type, which may be carried by either party is to be considered as in any way limiting any other party's responsibility for damages resulting from their operations or for furnishing work and materials.

Paragraph 5. PAYMENT:

- 5.1 CLIENT shall pay to LABORATORY such fees for services as previously agreed, orally or in writing, within 30 days of presentment of a bill for such services performed. In the event CLIENT ordered, orally or in writing, services but such services were not assigned a rate for billing, such services shall be billed at the LABORATORY's reasonable and customary rate.
- 5.2 CLIENT shall be responsible for all shipping, customs and other expenses related to services provided by LABORATORY to the CLIENT, and shall fully insure any test sample or other equipment provided to LABORATORY by the CLIENT.
- 5.3 Amounts overdue from CLIENT to LABORATORY shall be charged interest at a rate of 1½% per month.

Paragraph 6. ISO/IEC GUIDE 17025 ADDITIONS:

- 6.1 CLIENT agrees that this test report will not be reproduced except in full, without written approval from the LABORATORY.
- 6.2 CLIENT agrees that this test report shall not be used to claim product endorsement by A2LA or ANSI or any agency of the U.S. Government.
- 6.3 CLIENT agrees that test results presented herein relate only to the sample tested by the LABORATORY.

N 300 386-2 1997, 1998, N 300 386 2000 v1.2.1, 2001 v1.3.1	Electromagnetic compatibility and radio spectrum matters (ERM); Telecommunication network equipment; Electromagnetic compatibility (EMC) requirements; Part 2: Product family standard.	0328-2:2001	Electromagnetic compatibility and Radio spectrum Matters (ERM)
00 132-1 1996	Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 1: Operated alternating current (ac) derived from direct current (dc) so	0489-1:2002	Wideband Transmission systems; Data transmission equipment operating in the 2.4 GHz ISM band and using spread spectrum modulation techniques; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive
00 132-2 1996	Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 2: Operated direct current (dc)	069-2-1:2002	Electromagnetic compatibility and Radio spectrum Matters (ERM) Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements
83 1997	Equipment Engineering (EE); Transient voltages at interfaces on telecommunications direct current (DC) power distribution	Radio Standards GL-36 1995	Switches for household and similar fixed electrical installations -- 2-1: Particular requirements -- Electronic switches
Radio standards EN 300 385 v1.2.1: 1998, 1999	Electromagnetic compatibility and Radio spectrum matters (ERM); Electromagnetic Compatibility (EMC) standard for fixed radio links and ancillary equipment (ETS)	an RSS-119 1999, 2000 Issue 6	Industry Canada -- technical requirements for low power Devices 2400 -- 2483.5 MHz band.
0 330 v1.2.1: 1998, 1999	Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices (SRD); Technical characteristics and test methods for radio equipment in the range 9 kHz to 1 MHz and inductive loop systems in the frequency range 9 to 30 MHz	an RSS-134 1996 & 2000, Issue 1	Industry Canada -- Land mobile and fixed radio Transmitters and receivers, 27.41 to 960.0 MHz
00 328 1996	Radio Equipment and Systems (RES); Wideband transmission systems; Technical characteristics and test conditions for transmission equipment operating in the 2.4 GHz ISM band using spread spectrum modulation techniques	an RSS-210 2000 Issue 3, 1998	Industry Canada -- 900 MHz narrowband personal communication services
N 300 440 v1.2.1 1999	Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices; Technical characteristics and test methods for radio equipment to be used in the 1 GHz to 40 GHz frequency range	standards R FCC low power transmitters operating on frequencies below 1 GHz, emergency alert systems, unintentional transmitters and ISM devices.	Industry Canada -- Low power license-exempt radio 2001 Issue 5 communication devices Specification for Restricted Radiation Radio Apparatus (New Zealand)
1 893:2002	Broadband Radio Access Networks (BRAN); 5 GHz (draft) high performance RLAN; Harmonized EN covering Essential requirements of article 3.2 of the R&TTE Directive	R FCC low power transmitters operating on frequencies above 1 GHz, with the exception of spread spectrum transmitters.	Scope A1
00 836-1:1998	Broadband Radio Access Networks (BRAN); High Performance Radio Local Area Network (HIPERLAN) Type 1; Conformance testing specification; Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification	R FCC Unlicensed Personal Scope Communications System (PCS) devices	A3
489-17:2002	Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions 2,4 GHz wideband transmission systems and 5 GHz high performance RLAN equipment	R FCC Unlicensed National Scope Infrastructure devices and lower transmitters using spread spectrum techniques. R FCC Personal mobile Scope Services in the following FCC Parts 22, 24, 25, 27. R FCC General Mobile Radio Services in the following FCC Parts 22, 74, 90, 95, 97. R FCC Maritime and Aviation Radio Services in 47 CFR Parts 87 R FCC Microwave Radio Services in 47 CFR Parts 21, 74 and 101.	A4 B1 B2 B3 B4
Cert. No. 1627-01) 10/31/03	Page 5 of 11	Cert. No. 1627-01) 10/31/03	Page 6 of 11
IST MP-5 1986	FCC (Federal Communications Commission) methods of measurement of radio noise emissions from industrial, scientific and medical equipment.	IA-IS-968	Telecommunications Telephone Terminal Equipment Technical Requirements for Connection of Terminal Equipment to the Telephone Network
89-CORE: 1997, 1999 issue 2/ issue 3	Belcore electromagnetic compatibility and electrical safety Generic criteria for network telecommunications equipment	IA-IS-883	Telecommunications Telephone Terminal Equipment Supplemental Technical Requirements for Connection of Stutter Dial Tone Detection Devices and ADSL Modems to the Telephone Network
EMC Standards C63.4: 1992, 1999, 2001	American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and electronic equipment in the range of 9 kHz to 40GHz.	88-A	Telecommunications Telephone Terminal Equipment Technical Requirements for Connection of Terminal Equipment to the Telephone Network
C63.5 1988	American National Standard for electromagnetic compatibility radiated emissions measurements in electromagnetic interference (EMI) control -- calibration of antennas.	Q 6-2001	Technical Requirements for SHDSL, HDSL2, HDSL4 Digital Subscriber Line Terminal Equipment to Prevent Harm to the Telephone Network Industry
EMC Standards C62.41: 1980, 1991	IEEE recommended practice on surge voltages in low-voltage AC power circuits	a VDSL January 2003	Terminal Attachment Program Requirements and Test Methods for Very-High-Bit-Rate Digital Subscriber Line (VDSL) Terminal Equipment
IEC EMC Standards M 3336.3 1995	Electromagnetic compatibility and electrical safety (EMC) for wired terminal equipment. Harmonization document information over the OFCOM requirements.	IEF S016-2001 IEF S031-2001 IEF S038-2001 IEF S043-2001	Analogue interworking and non-interference requirements for Customer Equipment for connection to the Public Switched Telephone Network Requirements for Customer Equipment for connection to hierarchical digital interfaces Requirements for ISDN Basic Access Interface Requirements for ISDN Primary Rate Access Interface Requirements for Customer Equipment for Connection to a Metal Local Loop Interface of a Telecommunications Network -- Part 1: General Part 2: Broadband Part 3: DC, Low Frequency AC and Voiceband
African EMC standards other than CISPR equivalents 1718-1: 1996	South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment.	G 703 2028	Physical/electrical characteristics of hierarchical digital interface Network connection specification for connection of CPE to the P-Hong Kong using digital leased circuits at data rate of 1544 kbit/s
ese VCCI Standards V-3/99.05 1999 V-4/99.05 1999	Technical Requirements Instruction for Test Conditions for Requirement under Test	2029	Network connection specification for connection of CPE to the P-Hong Kong using digital leased circuits at data rate of 2048 kbit/s
Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (ac and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing aid compatibility testing (excluding volume control); Protocol analysis and Jitter testing.		: 1995	Attachment requirements for terminal equipment to be connected to circuit switched data networks and leased circuits using a CCITT Recommendation X.21 interface, or at an interface physically, functionally and electrically compatible with CCITT Recommendation X.21 but operating at any data signaling rate up to, and including, 1 984 kbit/s
IEC Standards Title		: 1997	Attachment requirements for Data Terminal Equipment (DTE) to connect to Packet Switched Public Data Networks (PSPDNs) for CCITT Recommendation X.25 interfaces at data signaling rates up to 920 kbit/s utilizing interfaces derived from CCITT Recommendation X.21 and X.21 bit
7 CFR Part 68 Telephone Issue 8 1996 through amendment 5	Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB C1. Specification for terminal equipment, terminal systems, Network protection devices, connection arrangements and hearing aids compatibility.		
IA TSB31-B 1998	Bulletin Part 68 Rationale and Measurement Guidelines (February 1998)		
Cert. No. 1627-01) 10/31/03	Page 7 of 11	Cert. No. 1627-01)	10/31/03 Page 8 of 11

1995 + Amdt : 1997	Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN basic access	950 2000 950 1997, 1998, 2000 950-1 2001	Safety of information technology equipment Safety of information technology equipment, including Electrical business equipment.
1995 + Amdt : 1997	Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN primary rate access	950-1 2003 22.2 No. 60950-00 22.2 No. 60950-1 03	
12 : 1993 + Amdt : 1996	Business Telecommunications (BT); Open Network Provision (ONP) technical requirements; 2 048 kbit/s digital unstructured leased line (D2048U) Attachment requirements for terminal equipment	3260 1993 3260 Supp 1 1996	Approval and test specification – Safety of information technology equipment including electrical business equipment.
13 : 1996	Business Telecommunications (BTC); 2 048 kbit/s digital structured leased lines (D2048S); Attachment requirements for terminal equipment interface	001 1997	Approval and test specification – Safety of information technology equipment including electrical business equipment – Alphabetic reference index to IEC 950 (Supplement to AS/NZS 3260:1993) Australian Communications Authority – Safety requirements for customer equipment.
1 : 1998	Terminal Equipment (TE); Attachment requirements for public switched telephone networks (PSTNs) of TE (excluding supporting the voice telephony service) in which network addressing, if provided, is by means of Dual Tone Multi-Frequency (DTMF) signaling	59 1995 010-1 1990 010-1 1993 010-1 1993, 2001 010-1 2001 010B-1 2003	Telephone Equipment Safety requirements for electrical equipment for measurement, control, and laboratory use, Part 1: General requirements. Safety requirements for electrical equipment for measurement, control, and laboratory use, Part 1: General requirements.
4 : 1997	Business Telecommunications (BTC); 34 Mbit/s digital Unstructured and structured leased lines (D34U and D34S) Attachment requirements for terminal equipment interface	01-1 1993 CSA 1010-1 1999 (Including AM 2) 11-1 1996 21-1 1995 601-1 1995	Electrical equipment for laboratory use Part 1: General requirements Electrical measuring and test equipment. Part 1: General requirements
1997	Analogue Interworking and Non interference Requirements Customer Equipment Connected to the Public Switched Telephone Network	001-1 1995 (Including AM 2) 01-1 1997 065 1998, 2000	Medical electrical equipment. Part 1: General requirements for safety Medical electrical equipment Medical electrical equipment. Part 1: General Requirements for Audio, video and similar electronic apparatus – Safety requirements
1997	General Requirements for Customer Equipment Connected Hierarchical Digital Interfaces	UL 6500: 1998 CSA 60065-00	Audio/video and musical instrument apparatus for Household, commercial and similar general use
1997	Requirements for ISDN Basic Access Interface	3250 1995	Australian/New Zealand Standard – Approval and test
1997	Requirements for ISDN Primary Rate Access Interface	60065 2000	Specification – Mains operated electronic and related Equipment household and similar general use
IF S043.2:2001	Requirements for Customer Equipment for connection to a metallic loop interface of a Telecommunications Network 2 Broadband	an C22.2 No. 1-94 (1-98) 065 1994	Audio, video and similar electronic equipment. Consumer and household commercial products Safety requirements for main operated electronic and related apparatus for household and similar general use.
et Safety	Test methods; Input tests; Electric strength tests; Impulse tests; Permanency of marking tests; Accessibility tests; Hazard measurements; Capacitor discharge tests; Humidity conditioning; Earthing tests; Limited power source tests; Stability tests; Steel ball tests; Lithium Battery Reverse Current measurements; Leakage current tests; Former abnormal tests; Telecom leakage tests; Over voltage/power cross tests (excluding x-ray tests).	825 1990 825-1 1994 825-1 2001 825-2 2000-5 825-4 1997-11 335-1 1995 335-1 2001 335-1 1998 CSA E335-1 1994	Radiation safety of laser products, equipment Classification, requirements and user's guide Safety of laser products Part 1: equipment Classification, requirements and user's guide. Safety of laser products – Part 2: Safety of optical communication Safety of laser products – Part 4: Laser guards Safety of household and similar electrical appliances Part 1: General requirements
et Safety Standards	Title		
ic Product Safety Standards	Safety of information technology equipment including Amendments 1, 2, 3, and 4 electrical business equipment.		
0 1991	Safety of information technology equipment, including Electrical business equipment.		
50 1998	Safety of Information Technology Equipment (UL 1950)		
22.2 No.950-95	Safety of information technology equipment		
950 2000			
Cert. No. 1627-01) 10/31/03	Page 9 of 11	Cert. No. 1627-01) 10/31/03	Page 10 of 11
010A-1 : 2002	Electrical equipment for laboratory use; part 1: General requirements		
010-1 : 2001	Safety requirements for electrical equipment for measurement, control, and laboratory use - Part 1: General requirements		
2S 60950 : 2000	Safety information technology equipment		
nnmentat ²			
nnmental Standards	Title		
-CORE	NEBS Requirements: Physical Protection		
00 019	Environmental conditions and environmental tests For telecommunications equipment		
ion up to 1000Hz)			
onmental testing is performed at the satellite facility located at 168 Ayer Rd, Littleton, MA 01460			
Cert. No. 1627-01) 10/31/03	Page 11 of 11		