US Tech Test Report: FCC Part 15/ RSS 247 Class 1 Permissive Change

FCC ID: P2SL900M2
IC: 4171B-L900M2
Test Report Number: 18-0105

Issue Date: June 28, 2018

Customer: Neptune Technology Group Inc.

Model: L900

Maximum Public Exposure to RF (MPE) CFR 15.247 (i), CFR 1.1310 (e)

The maximum exposure level to the public from the RF power of the EUT shall not exceed a power density, **S** as per the respective limits in Table 1 below, at a distance, d, of 20 cm (Mobile condition) from the EUT.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

Therefore, for:

MPE for 915 MHz:

Limit: 0.61 mW/cm²

Peak Power (dBm) = 18.0 dBm (Based on original filing since not changed for this filing)

Peak Power (Watts) = 0.063 W

Gain of Transmit Antenna = $2.15 \text{ dB}_i = 1.64$, numeric (Whip antenna)

d = Distance = 20 cm = 0.2 m

S = (PG/ $4\pi d^2$) = EIRP/4A = 0.063(1.64)/4* π *0.2*0.2

 $= 0.1033/0.5030 = 0.2054 \text{ W/m}^2$

= $(0.2054 \text{ W/m}^2) (1 \text{ m}^2/\text{W}) (0.1 \text{ mW/cm}^2)$

 $= 0.02054 \text{ mW/cm}^2$

which is << less than S = 0.61 mW/cm²

US Tech Test Report:
FCC ID:
P2SL900M2
IC:
Test Report Number:
Issue Date:
Customer:
Model:
FCC Part 15/ RSS 247 Class 1 Permissive Change
P2SL900M2
171B-L900M2
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-0105
18-01

RF Exposure Evaluation – IC

According to RSS-102, 2.5.2 Exemption Limits for Routine Evaluation

At or above 300 MHz and below 6 GHz and the source based time averaged maximum EIRP of the device is equal to or less than $1.31 \times 10^{-2} \times f^{0.6834}$ in Watts (adjusted for tune up tolerance where applicable), where f= frequency in MHz

For 915 MHz Band:

Limit= $1.31 \times 10^{-2} \times 915^{0.6834} = 1.39 \text{ Watts}$

Max EIRP for WiFi = 18.0 dBm (0.063W) + 2.15 dB (0.0016W) = 0.0646 mW << 1390 mW