

*Testing Tomorrow's Technology*

## **Class 2 Permissive Change Test Report**

**For**

**Part 2, Subpart J, Paragraph 2.907 Equipment Authorization of Certification for an Intentional Radiator per Part 15, Subpart C, paragraphs 15.207, 15.209 and 15.247**

**And**

**RSS-247 Issue 3: Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and License-Exempt Local Area Network (LE-LAN) Devices**

**For the**

**Neptune Technology Group, Inc.**

**Model: R900M**

**FCC ID: P2SR900M**

**IC ID: 4171B-R900M**

**UST Project: 24-0085**

**Issue Date: April 15, 2024**

Total Pages: 21

**3505 Francis Circle Alpharetta, GA 30004**

**PH: 770-740-0717 Fax: 770-740-1508**

**[www.ustech-lab.com](http://www.ustech-lab.com)**



Testing Tomorrow's Technology

I certify that I am authorized to sign for the Test Agency and that all of the statements in this report and in the Exhibits attached hereto are true and correct to the best of my knowledge and belief:

US TECH (Agent Responsible For Test):

By: Alan Ghasiani

Name: Alan Ghasiani

Title: Compliance Engineer – President

Date: April 15, 2024



NVLAP LAB CODE 200162-0

This report shall not be reproduced except in full. This report may be copied in part only with the prior written approval of US Tech. The results contained in this report are subject to the adequacy and representative character of the sample provided. This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the U.S. Government.

**3505 Francis Circle Alpharetta, GA 30004**  
**PH : 770-740-0717 Fax : 770-740-1508**  
**[www.ustech-lab.com](http://www.ustech-lab.com)**

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

### MEASUREMENT TECHNICAL REPORT

<b>Company Name:</b>	Neptune Technology Group, Inc.
<b>Address:</b>	1600 Alabama Hwy 229 Tallasse, AL 36078, USA
<b>Model:</b>	R900M
<b>FCC ID:</b>	P2SR900M
<b>IC ID:</b>	4171B-R900M
<b>Date:</b>	April 15, 2024

**This report concerns (check one):**  Original  Class II Permissive Change

**Equipment type:** 900 MHz ISM Radio Transceiver

#### Technical Information:

Radio Technology:	FHSS
Frequency of Operation (MHz):	911.08 – 919.07
Output Power (dBm):	18 (OOK) and 29.99 (GFSK)
Type of Modulation:	OOK and GFSK
Data/Bit Rate (M)bps:	1200 Baud
Antenna Gain (dBi):	Refer to Tables 5
Software used to program EUT:	MIU Interface Tool V1.08
EUT firmware:	ESW244.03
Power setting:	100 (OOK) and 42 (High power PA Enabled) (GSFK)

Report prepared by:

**US Tech**

**3505 Francis Circle Alpharetta, GA 30004**

**PH : 770-740-0717 Fax : 770-740-1508**

**[www.ustech-lab.com](http://www.ustech-lab.com)**

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

## Table of Contents

<u>Title</u>	<u>Page</u>
<b>1 General Information .....</b>	<b>6</b>
1.1 Purpose of this Report .....	6
1.2 Characterization of Test Sample .....	6
1.3 Product Description .....	6
1.4 Configuration of Tested System .....	7
1.5 Test Facility .....	7
1.6 Related Submittal(s)/Grant(s).....	7
<b>2 Tests and Measurements .....</b>	<b>10</b>
2.1 Test Equipment .....	10
2.2 Modifications to EUT Hardware.....	10
2.3 Number of Measurements for Intentional Radiators (CFR 15.31(m)).....	11
2.4 Frequency Range of Radiated Measurements (CFR 15.33) .....	11
2.4.1 Intentional Radiator .....	11
2.4.2 Unintentional Radiator .....	11
2.5 Measurement Detector Function and Bandwidth (CFR 15.35).....	12
2.5.1 Detector Function and Associated Bandwidth .....	12
2.5.2 Corresponding Peak and Average Requirements.....	12
2.5.3 Pulsed Transmitter Averaging.....	12
2.6 Transmitter Duty Cycle (Part 15.35(c)).....	13
2.7 Restricted Bands of Operation (Part 15.205) .....	13
2.8 EUT Antenna Requirements (CFR 15.203).....	13
2.10 Intentional Radiator, Radiated Emissions (CFR 15.209, 15.247(d)) .....	14
2.10.1 EUT Worst Case Test Configuration .....	14
2.12 Intentional Radiator Power Line Conducted Emissions (CFR 15.207).....	19
2.13 Unwanted Emissions of the Intentional Radiator, (CFR 15.209 and 15.33(a)) 19	
2.14 Measurement Uncertainty .....	21
2.14.1 Conducted Emissions Measurement Uncertainty .....	21
2.14.2 Radiated Emissions Measurement Uncertainty .....	21
<b>3 Test Results .....</b>	<b>21</b>

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

**List of Figures**

<b><u>Title</u></b>	<b><u>Page</u></b>
Figure 1. EUT Test Configuration Diagram .....	9

**List of Tables**

<b><u>Title</u></b>	<b><u>Page</u></b>
Table 1. EUT and Peripherals .....	8
Table 2. Details of I/O Cables Attached to EUT .....	8
Table 3. Test Instruments.....	10
Table 4. Number of Test Frequencies for Intentional Radiators .....	11
Table 5. Antenna 1 (Internal Antenna) .....	13
Table 6. Peak Radiated Fundamental and Harmonic Emissions - OOK .....	15
Table 7. Average Radiated Fundamental and Harmonic Emissions - OOK .....	16
Table 8. Peak Radiated Fundamental and Harmonic Emissions - GSKF.....	17
Table 9. Average Radiated Fundamental and Harmonic Emissions - GSKF .....	18
Table 10. Spurious Radiated Emissions (30 MHz – 1 GHz) - OOK.....	19
Table 11. Spurious Radiated Emissions (1 GHz – 9 GHz) - OOK.....	20
Table 12. Spurious Radiated Emissions (30 MHz – 1 GHz) - GSKF.....	20
Table 13. Spurious Radiated Emissions (1 GHz – 9 GHz) - GSKF.....	20

**List of Attachments**

FCC Agency Agreement  
Application Forms  
RF Exposure

External Photos  
Test Configuration Photographs  
Letter of Confidentiality

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

## 1 General Information

### 1.1 Purpose of this Report

This report is prepared to demonstrate that the modifications made to the EUT (Equipment Under Test) do not impact its performance in a manner necessitating full retesting and submission under a new FCC or IC ID as a new product.

The modification consists of the following: An additional internal monopole antenna is being added to the list of approved antennas. Based on the addition of this antenna, the EUT was tested for continued compliance with Part 15.247 and RSS-247 requirements. This change was deemed to have an impact on the radiated spurious emissions characteristics of the radio; therefore, testing was performed to show that the limits were not exceeded and that the EUT continues to be in compliance. The results of the testing are presented in this test report.

### 1.2 Characterization of Test Sample

The samples used for testing were received by US Tech on October 17, 2023 in good operating condition.

### 1.3 Product Description

The Equipment Under Test (EUT) is the Neptune Technology Group Inc. Model R900M. The EUT is a transceiver designed to wirelessly provide RF telemetry readings for a water meter. It operates within the 902-928 MHz ISM band. The EUT is battery powered (3.6Vdc) and spends the majority of its time in a low power consumption mode (asleep). The on-board microprocessor utilizes an internal clock to briefly “wake up” the EUT for periodic wireless communication of telemetry information from the water meter.

The EUT provides for several communication modes to accommodate different installation site requirements. Available communication modes are as follows:

- Neptune Proprietary Standard
  - Mode 1- SURF (OOK modulation)
  - Mode 2- Enhanced fixed network
  - Mode 3- Enhanced mobile network uplink/downlink (GFSK, Data log Retrieval)

Modulation: GFSK (911.0815 - 919.0769 MHz)  
OOK (911.0815 - 919.0769 MHz)

Maximum Output Power: +30 dBm (GFSK) (Rated), +18 dBm (OOK) (Rated)

Antenna: refer to table 5.

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

The unit was tested with the High Gain monopole antenna that is permanently affixed to the module via solder point. This is an internal antenna design.

#### **1.4 Configuration of Tested System**

The Test Sample was tested per *ANSI C63.10:2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices* for the intentional radiator aspect of the device and *ANSI C63.4:2014, Methods of Measurement of Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (2014)* for the unintentional radiator aspect of the device as well as FCC subpart B and C of Part 15 and per FCC KDB Publication number 558074 v05r02 for Digital Transmission Systems Operating Under section 15.247.

Per FCC Parts 15.107 and 15.109, digital RF conducted and radiated emissions below 1 GHz were measured with the spectrum analyzer's resolution bandwidth (RBW) adjusted to 9 kHz and 120 kHz, respectively. All measurements performed above 1 GHz were made with a RBW of 1 MHz. All measurements are peak unless stated otherwise. The video filter associated with the spectrum analyzer was set to 3 times the RBW or as required per the standard throughout the evaluation process.

A list of EUT and Peripherals is found in Table 1 below. A block diagram of the tested system is shown in Figure 1. Test configuration photographs for spurious and fundamental emissions are provided in separate Appendices.

#### **1.5 Test Facility**

Testing was performed at US Tech's measurement facility at 3505 Francis Circle, Alpharetta, GA 30004. This site has been fully described and registered with the FCC. Its designation number is 186022. Additionally, this site has also been fully described and submitted to Industry Canada (IC), and has been approved under file number 9900A-1.

#### **1.6 Related Submittal(s)/Grant(s)**

The EUT is subject to the following FCC Equipment Authorizations:

- a) Certification under section 15.209 as an intentional transmitter.
- b) SDoC under 15.101 as a digital device.

US Tech Test Report:  
 FCC ID:  
 IC ID:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Class II Permissive Change  
 P2SR900M  
 4171B-R900M  
 24-0085  
 April 15, 2024  
 Neptune Technology Group, Inc.  
 R900M

**Table 1. EUT and Peripherals**

EUT MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC/IC ID	CABLES P/D
EUT Neptune Technology Group.	R900M	Engineering Sample	FCC ID: P2SR900M IC: 4171B-R900M	N/A
PERIPHERAL MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC/IC ID	CABLES P/D
HOST Neptune Technology Group.	MACH 10 2.0	Engineering Sample	Contains FCC ID: P2SR900M	N/A
Antenna See antenna details	--	--	--	--

S= Shielded, U= Unshielded, P= Power, D= Data

**Table 2. Details of I/O Cables Attached to EUT**

DESCRIPTION OF CABLE	DETAILS OF CABLE			CABLE LENGTH
	Manufacturer	Part Number		
N/A	N/A		N/A	N/A
	Shield Type	Shield Termination	Back-shell	
	N/A	N/A	N/A	

**Shield Type**

N/A = None  
 F = Foil  
 B = Braided  
 2B = Double Braided  
 CND = Could Not Determine

**Shield Termination**

N/A = None  
 360 = 360 Degrees  
 P = Pigtail/Drain Wire  
 CND = Could Not Determine  
 MU = Metal Unshielded

**Back-shell**

N/A = Not Applicable  
 PS = Plastic Shielded  
 PU = Plastic Unshielded  
 MS = Metal Shielded



US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M




Figure 1. EUT Test Configuration Diagram

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

## 2 Tests and Measurements

### 2.1 Test Equipment

The table below lists test equipment used to evaluate this product.

**Table 3. Test Instruments**

TEST INSTRUMENT	MODEL NUMBER	MANUFACTURER	SERIAL NUMBER	CALIBRATION DUE DATE
Spectrum Analyzer	E4404A	Agilent	MY45304803	7/21/2025 2 yr.
RF Preamp 100 kHz To 1.3 GHz	8447D	Hewlett-Packard	1937A01611	7/20/2024
Preamp 1.0 GHz To 26.0 GHz	8449B	Hewlett-Packard	3008A00914	3/04/2025
Biconical Antenna	3110B	EMCO	9307-1431	1/13/2025 2 yr.
Log Periodic Antenna	3146	EMCO	9305-3600	3/13/2026 2 yr.
Horn Antenna	3115	EMCO	9107-3723	3/13/2025 2 yr.
High Pass Filter	VHF- 1320+	Mini-Circuits, Inc.	9715	8/2/2024
High Pass Filter	H3R020G2	Microwave Circuits Inc.	001DC9528	8/2/2024
Attenuator 8dB	VAT-8 15542	Mini-Circuits, Inc.	30519	10/18/2024
Attenuator 10dB	AT141	US Tech	N/A	8/2/2024

Note: The calibration interval of the above test instruments are 12 months unless stated otherwise and all calibrations are traceable to NIST/USA.

### 2.2 Modifications to EUT Hardware

No modifications were made by US Tech to bring the EUT into compliance with FCC Part 15.247 and RSS-247 requirements.

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

### 2.3 Number of Measurements for Intentional Radiators (CFR 15.31(m))

Measurements of intentional radiators or receivers shall be performed and reported for each band in which the device can be operated, with the device operating at the number of frequencies in each band specified in Table 3 as follows:

**Table 4. Number of Test Frequencies for Intentional Radiators**

Frequency Range over which the device operates	Number of Frequencies	Location in the Range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near the top 1 near the bottom
Greater than 10 MHz	3	1 near top 1 near middle 1 near bottom

The EUT operates over the range of 911.08 MHz to 919.07 MHz (7.99 MHz); therefore, two test frequencies were evaluated.

### 2.4 Frequency Range of Radiated Measurements (CFR 15.33)

#### 2.4.1 Intentional Radiator

The spectrum shall be investigated for the intentional radiator from the lowest RF signal generated in the EUT, without going below 9 kHz to the 10<sup>th</sup> harmonic of the highest fundamental frequency generated or 40 GHz, whichever is the lowest.

#### 2.4.2 Unintentional Radiator

For the digital device, an unintentional radiator, the frequency range shall be 30 MHz to 1000 MHz, or to the range specified in 2.4.1 above; whichever is the higher range of investigation.

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

## **2.5 Measurement Detector Function and Bandwidth (CFR 15.35)**

The radiated and conducted emissions limits shown herein are based on the parameters listed in the following paragraphs.

### **2.5.1 Detector Function and Associated Bandwidth**

On frequencies below 1000 MHz, the limits herein are based upon measurement equipment employing a CISPR quasi-peak detector function and related measurement bandwidths (i.e. 9 kHz from 150 kHz to 30 MHz and 120 kHz from 30 MHz to 1000 MHz). Alternatively, measurements may be made with equipment employing a peak detector function as long as the same bandwidths specified for the quasi-peak device are used.

### **2.5.2 Corresponding Peak and Average Requirements**

Above 1000 MHz, radiated limits are based on measuring instrumentation employing an average detector function. When average radiated emissions are specified, there is also a corresponding peak requirement that is measured using a peak detector. The peak limit shall be 20 dB greater than the average limit. For all measurements above 1000 MHz, the Resolution Bandwidth shall be at least 1 MHz.

### **2.5.3 Pulsed Transmitter Averaging**

When the radiated emissions limit is expressed as an average value, and the transmitter is pulsed, the measured field strength shall be determined by applying a Duty Cycle Correction Factor based upon dividing the total ON time during the first 100 ms period by 100 ms (or by the period if less than 100 ms). The duty cycle may also be expressed logarithmically in dB. In this case, the Duty Cycle Correction Factor was determined from the manufacturer's claim.

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

## 2.6 Transmitter Duty Cycle (Part 15.35(c))

The Duty Cycle calculations are confidential and can be provided upon request by contacting Neptune Technology Group.

## 2.7 Restricted Bands of Operation (Part 15.205)

Only spurious emissions can fall in the frequency bands of CFR 15.205. The field strength of these emissions cannot exceed the limits of 15.209. Radiated harmonics and other spurious emissions are examined for this requirement see paragraph 2.10.

## 2.8 EUT Antenna Requirements (CFR 15.203)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The antenna details are as follows:

**Table 5. Antenna 1 (Internal Antenna)**

Manufacturer	Model	Type	Gain (dBi)	Connector
Neptune Technology Group	Integrated Antenna	Monopole Antenna	4.7	Soldered

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

## **2.10 Intentional Radiator, Radiated Emissions (CFR 15.209, 15.247(d))**

For radiated measurements, the EUT was set into a continuous transmission mode. Below 1 GHz, the RBW of the measuring instrument was set equal to 120 kHz. Peak measurements above 1 GHz were measured using a RBW = 1 MHz, with a VBW  $\geq$  3 x RBW. For average measurements above 1 GHz, the emissions were measured using an average detector. The measurement of each signal detected was maximized by rotating the turntable 360° clockwise and counterclockwise and raising and lowering the receive antenna between 1 and 4 meters in height while monitoring the ever-changing spectrum analyzer display with Trace A in the Max-Hold mode and Trace B in the Clear-Write mode for the largest signal visible. The emission from the EUT was measured and recorded when both maxima were simultaneously satisfied.

### **2.10.1 EUT Worst Case Test Configuration**

On the test site, the EUT was placed on top of a polystyrene table 80 cm above the ground for below 1 GHz testing and 1.5m above the ground plane for above 1 GHz testing inside a semi-anechoic test chamber. The EUT was evaluated in each of its three axes (X/Y/Z) while transmitting on the channel that produced the highest output power for worst case condition. The position of the EUT determined to be worst case was with the EUT positioned along its X axis (top of EUT facing up). The worst-case test results for each of the modulation and output power of the fundamental and harmonics are presented in the table below.

US Tech Test Report:  
 FCC ID:  
 IC ID:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Class II Permissive Change  
 P2SR900M  
 4171B-R900M  
 24-0085  
 April 15, 2024  
 Neptune Technology Group, Inc.  
 R900M

**Table 6. Peak Radiated Fundamental and Harmonic Emissions - OOK**

Test: FCC Part 15.247 / 15.209								
Frequency (MHz)	Test Data (dBuV)	Additional Factor	AF+CL-PA (dB/m)	Corrected Results (dBuV/m)	Limits (dBuV/m)	Distance / Polarization	Margin (dB)	Detector
<b>Low Channel</b>								
911.08	87.34	--	24.46	111.80	--	3m./VERT	--	PK
1822.16	73.07	--	-8.38	64.69	74.0	3.0m./VERT	9.3	PK
2733.24	48.43	--	-4.91	43.52	74.0	3.0m./VERT	30.5	PK
3644.33	49.62	--	-3.57	46.05	74.0	3.0m./VERT	27.9	PK
4555.41	51.34	--	0.25	51.59	74.0	3.0m./VERT	22.4	PK
5466.49	49.44	--	0.75	50.19	74.0	3.0m./VERT	23.8	PK
<b>Note 1</b>	--	--	--	--	--	--	--	--
<b>High Channel</b>								
919.07	86.47	--	24.46	110.93	--	3m./VERT	--	PK
1838.14	71.85	--	-8.32	63.53	74.0	3.0m./VERT	10.5	PK
2757.21	48.89	--	-4.95	43.94	74.0	3.0m./VERT	30.1	PK
3676.31	49.16	--	-2.95	46.21	74.0	3.0m./VERT	27.8	PK
4595.35	49.96	--	-0.20	49.76	74.0	3.0m./VERT	24.2	PK
5514.40	48.47	--	0.84	49.31	74.0	3.0m./VERT	24.7	PK
<b>Note 1</b>	--	--	--	--	--	--	--	--


Notes:

1. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic

Sample calculation at 911.08 MHz:

Magnitude of Measured Frequency	86.47	dBuV
+Additional Factor	0.00	dB
+Antenna Factor + Cable Loss - Amplifier Gain	24.46	dB/m
Corrected Result	110.93	dBuV/m

Test Date: March 19, 2024

Signature: 

Test Engineer: Gabriel Medina

US Tech Test Report:  
 FCC ID:  
 IC ID:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Class II Permissive Change  
 P2SR900M  
 4171B-R900M  
 24-0085  
 April 15, 2024  
 Neptune Technology Group, Inc.  
 R900M

**Table 7. Average Radiated Fundamental and Harmonic Emissions - OOK**

Test: FCC Part 15.247 / 15.209								
Frequency (MHz)	Test Data (dBuV)	Additional Factor	AF+CL-PA (dB/m)	Corrected Results (dBuV/m)	Limits (dBuV/m)	Distance / Polarity	Margin (dB)	Detector
<b>Low Channel</b>								
911.08	85.73	--	24.46	110.19	--	3m./VERT	--	<b>QP</b>
1822.16	53.64	--	-8.38	45.26	54.0	3.0m./VERT	8.7	<b>AVG</b>
2733.24	33.43	--	-4.91	28.52	54.0	3.0m./VERT	25.5	<b>AVG</b>
3644.33	35.15	--	-3.57	31.58	54.0	3.0m./VERT	22.4	<b>AVG</b>
4555.41	38.06	--	0.25	38.31	54.0	3.0m./VERT	15.7	<b>AVG</b>
5466.49	35.99	--	0.75	36.74	54.0	3.0m./VERT	17.3	<b>AVG</b>
<b>Note 1</b>	--	--	--	--	--	--	--	--
<b>High Channel</b>								
919.07	86.41	--	24.46	110.87	--	3m./VERT	--	<b>QP</b>
1838.14	52.97	--	-8.32	44.65	54.0	3.0m./VERT	9.3	<b>AVG</b>
2757.21	33.51	--	-4.95	28.56	54.0	3.0m./VERT	25.4	<b>AVG</b>
3676.31	36.47	--	-2.95	33.52	54.0	3.0m./VERT	20.5	<b>AVG</b>
4595.35	36.72	--	-0.20	36.52	54.0	3.0m./VERT	17.5	<b>AVG</b>
5514.40	35.42	--	0.84	36.26	54.0	3.0m./VERT	17.7	<b>AVG</b>
<b>Note 1</b>	--	--	--	--	--	--	--	--


Notes:

1. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic.

Sample calculation at 911.08 MHz:

Magnitude of Measured Frequency	85.73	dBuV
+Additional Factor (Duty cycle correction)	0.00	dB
+Antenna Factor + Cable Loss - Amplifier Gain	24.46	dB/m
Corrected Result	110.19	dBuV/m

Test Date: March 19, 2024

Signature: 

Test Engineer: Gabriel Medina



US Tech Test Report:  
 FCC ID:  
 IC ID:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Class II Permissive Change  
 P2SR900M  
 4171B-R900M  
 24-0085  
 April 15, 2024  
 Neptune Technology Group, Inc.  
 R900M

**Table 8. Peak Radiated Fundamental and Harmonic Emissions - GSKF**

Test: FCC Part 15.247 / 15.209								
Frequency (MHz)	Test Data (dBuV)	Additional Factor	AF+CL-PA (dB/m)	Corrected Results (dBuV/m)	Limits (dBuV/m)	Distance / Polarization	Margin (dB)	Detector
<b>Low Channel</b>								
911.08	95.33	--	25.39	120.72	--	3.0m./HORZ	--	PK
1822.16	85.22	--	-7.51	77.71	100.7	3.0m./HORZ	23.0	PK
2733.24	61.08	--	-5.66	55.42	74.0	3.0m./HORZ	18.6	PK
3644.33	46.62	--	-1.96	44.66	74.0	3.0m./HORZ	29.3	PK
4555.41	54.04	--	0.39	54.43	74.0	3.0m./HORZ	19.6	PK
5466.49	40.03	--	0.87	40.90	74.0	3.0m./HORZ	33.1	PK
<b>Note 1</b>	--	--	--	--	--	--	--	--
<b>High Channel</b>								
919.07	94.37	--	24.46	118.83	--	3.0m./VERT	--	PK
1838.14	94.37	--	-7.23	87.14	101.3	3.0m./VERT	14.1	PK
2757.21	66.65	--	-5.67	60.98	74.0	3.0m./VERT	13.0	PK
3676.31	52.62	--	-1.71	50.91	74.0	3.0m./VERT	23.1	PK
4595.35	54.48	--	-0.08	54.40	74.0	3.0m./VERT	19.6	PK
5514.40	39.75	--	0.90	40.65	74.0	3.0m./VERT	33.4	PK
<b>Note 1</b>	--	--	--	--	--	--	--	--


Notes:

- No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic

Sample calculation at 911.08 MHz:

Magnitude of Measured Frequency	95.33	dBuV
+Additional Factor	0.00	dB
+Antenna Factor + Cable Loss - Amplifier Gain	25.39	dB/m
Corrected Result	120.73	dBuV/m

Test Date: April 12, 2024

Signature: 

Test Engineer: Gabriel Medina

US Tech Test Report:  
 FCC ID:  
 IC ID:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Class II Permissive Change  
 P2SR900M  
 4171B-R900M  
 24-0085  
 April 15, 2024  
 Neptune Technology Group, Inc.  
 R900M

**Table 9. Average Radiated Fundamental and Harmonic Emissions - GSKF**

Test: FCC Part 15.247 / 15.209								
Frequency (MHz)	Test Data (dBuV)	Additional Factor	AF+CL-PA (dB/m)	Corrected Results (dBuV/m)	Limits (dBuV/m)	Distance / Polarity	Margin (dB)	Detector
<b>Low Channel</b>								
911.08	92.69	--	25.39	120.30	--	3m./HORZ	--	QP
1822.16	61.74	--	-7.51	54.23	80.7	3.0m./HORZ	26.5	AVG
2733.24	53.83	--	-5.66	35.11	54.0	3.0m./HORZ	18.9	AVG
3644.33	45.92	--	-1.96	38.02	54.0	3.0m./HORZ	16.0	AVG
4555.41	53.96	--	0.39	52.84	54.0	3.0m./HORZ	1.2	AVG
5466.49	39.75	--	0.87	40.90	54.0	3.0m./HORZ	13.1	PK
<b>Note 1</b>	--	--	--	--	--	--	--	--
<b>High Channel</b>								
919.07	92.69	--	25.16	117.85	--	3m./VERT	--	QP
1838.14	87.81	--	-7.23	80.58	81.3	3.0m./VERT	.7	AVG
2757.21	53.83	--	-5.67	48.16	54.0	3.0m./VERT	5.8	AVG
3676.31	45.92	--	-1.71	44.21	54.0	3.0m./VERT	9.8	AVG
4595.35	53.96	--	-0.08	53.88	54.0	3.0m./VERT	.1	AVG
5514.40	37.92	--	0.91	38.83	54.0	3.0m./VERT	15.2	AVG
<b>Note 1</b>	--	--	--	--	--	--	--	--


Notes:

- No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic.

Sample calculation at 911.08 MHz:

Magnitude of Measured Frequency	92.69	dBuV
+Additional Factor (Duty cycle correction)	0.00	dB
+Antenna Factor + Cable Loss - Amplifier Gain	25.39	dB/m
Corrected Result	120.30	dBuV/m

Test Date: April 12, 2024

Signature: 

Test Engineer: Gabriel Medina

US Tech Test Report:  
 FCC ID:  
 IC ID:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Class II Permissive Change  
 P2SR900M  
 4171B-R900M  
 24-0085  
 April 15, 2024  
 Neptune Technology Group, Inc.  
 R900M

**2.12 Intentional Radiator Power Line Conducted Emissions (CFR 15.207)**

The EUT is battery powered; therefore, this test is not applicable.

**2.13 Unwanted Emissions of the Intentional Radiator, (CFR 15.209 and 15.33(a))**

The test data provided herein is to support the verification requirement for unwanted radiated emissions coming from the EUT in a transmitting state per 15.209 and was investigated from 30 MHz to 9 GHz. The EUT was put into a continuous transmit mode of operation and tested as detailed in ANSI C63.10:2013, Clause 6.4.6. Data is presented in the table below.

The measurement bandwidths for each frequency scan that was evaluated were set as follows:

Frequency Span	RBW / VBW
30 MHz – 1 GHz	120 kHz / 360 kHz
Above 1 GHz	1 MHz / 3 MHz

**Table 10. Spurious Radiated Emissions (30 MHz – 1 GHz) - OOK**

30 MHz to 1 GHz with Class B Limits Test: Radiated Emissions per CFR 15.209							
Frequency (MHz)	Test Data (dBuV)	AF+CL-PA (dB)	Results (dBuV/m)	Limits (dBuV/m)	Distance / Polarity	Margin (dB)	Detector PK / QP
All Emissions were less than 6 dB off the noise floor or greater than 20 dB of margin from the applicable limit.							

Test Date: March 19, 2024

Signature:  Test Engineer: Gabriel Medina

US Tech Test Report:  
 FCC ID:  
 IC ID:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Class II Permissive Change  
 P2SR900M  
 4171B-R900M  
 24-0085  
 April 15, 2024  
 Neptune Technology Group, Inc.  
 R900M

**Table 11. Spurious Radiated Emissions (1 GHz – 9 GHz) - OOK**

1 GHz to 10 GHz with Class B Limits Test: Radiated Emissions per CFR 15.209							
Frequency (MHz)	Test Data (dBuV)	AF+CL-PA (dB)	Results (dBuV/m)	Limits (dBuV/m)	Distance / Polarization	Margin (dB)	Detector PK / AVG
No emissions other than harmonics of the fundamental frequency were detected.							

Test Date: March 19, 2024

Signature:  Test Engineer: Gabriel Medina

**Table 12. Spurious Radiated Emissions (30 MHz – 1 GHz) - GSKF**

30 MHz to 1 GHz with Class B Limits Test: Radiated Emissions per CFR 15.209							
Frequency (MHz)	Test Data (dBuV)	AF+CL-PA (dB)	Results (dBuV/m)	Limits (dBuV/m)	Distance / Polarity	Margin (dB)	Detector PK / QP
All Emissions were less than 6 dB off the noise floor or greater than 20 dB of margin from the applicable limit.							

Test Date: April 12, 2024

Signature:  Test Engineer: Gabriel Medina

**Table 13. Spurious Radiated Emissions (1 GHz – 9 GHz) - GFSK**

1 GHz to 10 GHz with Class B Limits Test: Radiated Emissions per CFR 15.209							
Frequency (MHz)	Test Data (dBuV)	AF+CL-PA (dB)	Results (dBuV/m)	Limits (dBuV/m)	Distance / Polarization	Margin (dB)	Detector PK / AVG
No emissions other than harmonics of the fundamental frequency were detected.							

Test Date: April 12, 2024

Signature:  Test Engineer: Gabriel Medina

US Tech Test Report:  
FCC ID:  
IC ID:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Class II Permissive Change  
P2SR900M  
4171B-R900M  
24-0085  
April 15, 2024  
Neptune Technology Group, Inc.  
R900M

## **2.14 Measurement Uncertainty**

The measurement uncertainties given were calculated using the method detailed in CISPR 16-4-2:2011. A coverage factor of  $k=2$  was used to give a level of confidence of approximately 95%.

### **2.14.1 Conducted Emissions Measurement Uncertainty**

Measurement Uncertainty (within a 95% confidence level) for this test is  $\pm 2.78$  dB.

### **2.14.2 Radiated Emissions Measurement Uncertainty**

For a measurement distance of 3 m the measurement uncertainty (with a 95% confidence level) for this test using a Biconical Antenna (30 MHz to 200 MHz) is  $\pm 5.3$  dB. This value includes all elements of measurement.

The measurement uncertainty (with a 95% confidence level) for this test using a Log Periodic Antenna (200 MHz to 1000 MHz) is  $\pm 5.1$  dB.

The measurement uncertainty (with a 95% confidence level) for this test using a Horn Antenna (Above 1000 MHz) is  $\pm 5.1$  dB.

## **3 Test Results**

The EUT is deemed to have met the requirements of the standards cited within the test report when tested as detailed in the test report.