

Date: 2001-11-29

TEST REPORT

Page 1 of 19

No.: HM106105

FCC PART 15 SUBPART C CERTIFICATION REPORT

FOR LOW POWER TRANSMITTER

TEST REPORT No.: HM106105

Equipment Under Test [EUT]:

Model Number:

Applicant:

FCC ID :

Wireless Converter

EK-2000

China Taly Aviation Technologies Corp.

P2VWIRELESSKIT

Date: 2001-11-29

TEST REPORT

Page 2 of 19

No.: HM106105

CONTENT:

Cover
Content
Conclusion

Page 1 of 19
Page 2-3 of 19
Page 4 of 19

1.0 General Details

- 1.1 Test Laboratory
- 1.2 Applicant Details
Applicant
HKSTC Code Number for Applicant
Manufacturer
- 1.3 Equipment Under Test [EUT]
Description of EUT operation
- 1.4 Date of Order
- 1.5 Submitted Sample
- 1.6 Test Duration
- 1.7 Country of Origin
- 1.8 Additional Information of EUT

Page 5 of 19

Page 5 of 19

Page 6 of 19

Page 6 of 19

Page 6 of 19

Page 6 of 19

Page 6 of 19

Page 7 of 19

2.0 Technical Details

- 2.1 Investigations Requested
- 2.2 Test Standards and Results Summary

Page 8 of 19

Page 8 of 19

3.0 Test Results

- 3.1 Emission
- 3.2 Bandwidth Measurement

Page 9-13 of 19

Page 14-15 of 19

Date: 2001-11-29

TEST REPORT

Page 3 of 19

No.: HM106105

Appendix A

List of Measurement Equipment

Page 16 of 19

Appendix B

Photographs

Page 17-18 of 19

Appendix C

Modification Method

Page 19 of 19

Date: 2001-11-29

TEST REPORT

Page 4 of 19

No.: HM106105

CONCLUSION

The submitted product was deemed to have **COMPLIED** with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Verify by

Patrick Wong
for Chief Executive

Date: 2001-11-29

TEST REPORT

Page 5 of 19

No.: HM106105

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd.
EMC Laboratory
10 Dai Wang Street, Taipo Industrial Estate
New Territories, Hong Kong

Telephone: 852 2666 1888

Fax: 852 2664 4353

1.2 Applicant Details

Applicant

CHINA TALY AVIATION TECHNOLOGIES CORP.
P.O. Box: 16018, No. 45 Yongfu Road,
Guangzhou, China 510500

Telephone: 86 20 87636241

Fax: 86 20 87636248

HKSTC Code Number for Applicant

CHT027

Manufacturer

CHINA TALY AVIATION TECHNOLOGIES CORP.
P.O. Box: 16018, No. 45 Yongfu Road,
Guangzhou, China 510500

Telephone: 86 20 87636241

Fax: 86 20 87636248

Date: 2001-11-29

TEST REPORT

Page 6 of 19

No.: HM106105

1.3 Equipment Under Test [EUT] Description of Sample

Product: Wireless Converter
Manufacturer: China Taly Aviation Technologies Corp.
Brand Name: EK
Model Number: EK-2000
Input Voltage: 3Vd.c ("CR2032" button cell x 1)

1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is an China Taly Aviation Technologies Corp., 88.67MHz Wireless Converter. The EUT continues to transmit while switch on. It is voice transmission, Modulation by Mic. and tape is frequency modulation.

1.4 Date of Order

2001-10-16

1.5 Submitted Sample(s):

1 Sample per model

1.6 Test Duration

2001-11-09

1.7 Country of Origin

China

Date: 2001-11-29
No.: HM106105

TEST REPORT

1.8 Additional Information of EUT

	Submitted	Not Available
User Manual	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Part List	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Circuit Diagram	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Printed Circuit Board [PCB] Layout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Rating Label	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Block diagram	<input checked="" type="checkbox"/>	<input type="checkbox"/>
FCC ID Label	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Date: 2001-11-29

TEST REPORT

Page 8 of 19

No.: HM106105

2.0 Technical Details

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4:2000 for FCC Certification.

2.2 Test Standards and Results Summary Tables

EMISSION Results Summary						
Test Condition	Test Requirement	Test Method	Class / Severity	Test Result		
				Pass	Failed	N/A
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.239	ANSI C63.4:2000	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiated Emissions, 30MHz to 1GHz	FCC 47CFR 15.209	ANSI C63.4:2000	Class B	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Conducted Emissions on AC, 0.45MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2000	Class B	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Note: N/A - Not Applicable


3.0 Test Results**3.1 Emission****3.1.1 Radiated Emissions**

Test Requirement:	FCC 47CFR 15.239 & 15.209
Test Method:	ANSI C63.4:2000
Test Date:	2001-11-09
Mode of Operation:	On mode

Test Method:

The sample was placed 0.8m above the ground plane on the OATS *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigate all operating modes, rotated about all 3 axis (X, Y & Z) to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

*: OATS [Open Area Test Site] located at HKSTC with a metal ground plane on filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 90657.

Test Setup:

Date: 2001-11-29

TEST REPORT

Page 10 of 19

No.: HM106105

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.239]:

Frequency Range of Fundamental [MHz]	Peak Limits [μV/m]	Average Limits [μV/m]
88-108	2,500	250

Results:

Field Strength of Fundamental Emissions Peak Value						
Frequency	Level @3m	Correction Factor	Field Strength	Field Strength	Limit ** @3m	Antenna Polarity
MHz	dBμV	dB/m	dBμV/m	μV/m	μV/m	
88.67	32.4	12.8	45.2	181.97	2,500.0	Horizontal

Field Strength of Fundamental Emissions Average Value *						
Frequency	Level @3m	Correction Factor	Field Strength	Field Strength	Limit ** @3m	Antenna Polarity
MHz	dBμV	dB/m	dBμV/m	μV/m	μV/m	
88.67	32.3	12.8	45.1	179.89	250.0	Vertical

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty = 30MHz to 300MHz ±3.7dB
300MHz to 1GHz +3.0dB / -2.7dB

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth = 3MHz
Video Bandwidth 1Hz

Date: 2001-11-29

TEST REPORT

Page 11 of 19

No.: HM106105

Limited for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results:

Radiated Emissions Quasi-Peak				
Frequency MHz	Level @3m dBμV/m	Limit @3m dBμV/m	Margin dBμV/m	Antenna Polarity
53.180	26.8	40.0	-13.2	Horizontal
70.935	21.7	40.0	-18.3	Horizontal
106.401	28.4	43.5	-15.1	Horizontal
124.129	28.9	43.5	-14.6	Horizontal
141.874	28.1	43.5	-15.4	Horizontal
159.603	29.4	43.5	-14.1	Horizontal
177.337	31.0	43.5	-12.5	Horizontal
195.140	29.4	43.5	-14.1	Horizontal
319.200	28.9	46.0	-17.1	Horizontal
337.000	32.1	46.0	-13.9	Horizontal
407.900	31.6	46.0	-14.4	Horizontal
531.995	35.2	46.0	-10.8	Horizontal
549.755	40.3	46.0	-5.7	Horizontal
567.600	41.5	46.0	-4.5	Horizontal
620.700	36.9	46.0	-9.1	Horizontal

Date: 2001-11-29

TEST REPORT

Page 12 of 19

No.: HM106105


3.1.1 Conducted Emissions (0.45MHz to 30MHz)

Test Requirement:	FCC 47CFR 15.207
Test Method:	ANSI C63.4:2000
Test Date:	2001-11-09
Mode of Operation:	Not Applicable

Test Method:

The test was performed in accordance with ANSI C63.4:2000, with the following: an initial measurement was performed in peak and average detection mode on the live line. Any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Test Setup:



Date: 2001-11-29

TEST REPORT

Page 13 of 19

No.: HM106105

Limit for Conducted Emissions (FCC 47 CFR 15.207):

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
0.45-30	250

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak) in the following diagram labelled as (QP).

Results:

The EUT is operated by a single source of internal battery power [located in the battery compartment], therefore power line conducted emission was deemed unnecessary.

Remarks:

Calculated measurement uncertainty = $\pm 2.3\text{dB}$

Date: 2001-11-29

TEST REPORT

Page 14 of 19

No.: HM106105

3.2 26dB Bandwidth of Fundamental Emission

Test Requirement:	FCC 47 CFR 15.239
Test Method:	ANSI C63.4:2000 (Section 13.1.7)
Test Date:	2001-11-09
Mode of Operation:	On mode

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.

Date: 2001-11-29

TEST REPORT

Page 15 of 19

No.: HM106105


Limits for 26 dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	26dB Bandwidth [KHz]	FCC Limits * [KHz]
88.67	79.5	200

Results:

The following figure is the measured bandwidth of Fundamental Emission.

26dB Bandwidth of Fundamental Emission



Date: 2001-11-29

TEST REPORT

Page 16 of 19

No.: HM106105

Appendix A

Test Equipment Audit

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL.
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	07/09/01
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	07/09/01
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	07/09/01
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	07/09/01
EM011	ATTENUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	07/09/01
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	07/09/01
EM013	CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE	HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD	HP9000 HP A1097C HP9133L	6226A60314 3151J39517 2623A02468	CM
EM131	PORTABLE SPECTRUM ANALYSER	HEWLETT PACKARD	8595EM	3710A00155	10/07/00
EM017	ANTENNA	ARA INC.	LPB-2513/A	1069	17/02/00
EM020	HORN ANTENNA	EMCO	3115	4032	09/08/00
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	30/03/98
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	15/02/01
EM145	EMI TEST RECEIVER	R & S	ESCS 30	830245/021	31/05/00

Conducted Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	CM
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	10/09/00
EM002	LISN	EMCO	3825-2	9005-1657	22/08/01
EM119	LISN	R & S	ESH3-Z5	0831.5518.52	31/08/00
EM145	EMI TEST RECEIVER	R & S	ESCS 30	830245/021	31/05/00
EM120	EMI TEST RECEIVER	R&S	ESHS10	1004.0401.10	04/09/00
EM127	ISOLATION TRANSFORMER 220 TO 300	WING SUN	N/A	N/A	N/A
EM142	PLUSE LIMITER	R & S	ESH3Z2	357.8810.52	TBD

Remarks:

CM Corrective Maintenance
N/A Not Applicable or Not Available
TBD To Be Determined

Date: 2001-11-29

TEST REPORT

Page 17 of 19

No.: HM106105

Appendix B

Photographs of EUT


Front View of the product




Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View



Date: 2001-11-29

TEST REPORT

Page 18 of 19

No.: HM106105


Photographs of EUT

Measurement of Radiated Emission Test Set Up



Appendix C**Modification Method**

1. Added a capacitor C 20pF between the b pole of the transistor Q2 and ground as shown in attached circuit diagram.



End of Document