



## CR Series SOHO In-building Repeater

AMPS • PCS • TDMA • GSM • CDMA • iDEN

### Description


The SignalReach™ CR Series Small Office Home Office (SOHO) In-building Repeaters extend cellular and iDEN services into buildings and other poor coverage areas. The CR Series Repeaters are designed for use with cellular and iDEN telephones (850 and 1900 MHz, and iDEN band) and offer a cost-effective solution for small business and residential applications. The repeaters are useful in areas where cellular or iDEN service is available outside of the building and marginal indoors. The two-way radio functionality of cellular and iDEN telephones is preserved.

The repeaters are network-compatible devices that amplify cellular or iDEN signals in both the uplink and downlink directions. The repeaters are simple to install, and contains circuitry to ensure proper operating power levels, and as well, include automatic low isolation and detection circuitry that detects low isolation between the indoor and outdoor antennas. In this condition, the repeaters will adjust their gain to compensate for the abnormality, and warn the user through an indicator LED. The CR Series Repeaters will enhance the cellular or iDEN telephone user's experience while complying with cellular and iDEN network specifications. The repeaters will also work with wireless PDAs (Wireless Digital Assistants) and laptop personal computers with wireless PC cards. Linear operation is guaranteed under all conditions.

The CR Series Repeaters allow up to two indoor antennas to be used without the need of external components. Their auxiliary indoor antenna port allows a second indoor zone to be easily connected. The repeaters can be battery-backed, by connecting the repeaters' 12VDC supply to the spades of a rechargeable battery with the repeaters' optional battery back-up interface cable. The rechargeable battery is then permanently connected to the battery manufacturer's recommended trickle charger keeping the battery charged indefinitely, ready in the event of a building power failure.

### Features

- Easy Installation – no calibration required,
- Up to 40,000 sq. ft. of free space coverage (with two interior antennas),
- Automatic Low Isolation Detection and Indication Circuitry,
- Feedback Overload Shutdown and Auto Start,
- Auto levelling circuitry ensures linear operation,
- Network-compatible operation,
- Auxiliary in-building antenna port provides enhanced coverage,
- FCC approved,
- Can be connected to battery back-up system for emergency powering,
- Optional battery back-up interface cable available.



### RF Specifications

	Specification	CR300 iDEN	Specification	All Products
<i>Up-link</i>	Frequency Range (MHz)	806-825	Low Isolation Detection	An amber LED indicator will indicate low isolation between indoor and outdoor antennas.
	Output Power (dBm)	+23	Maximum Possible Exposure (MPE)	At the interior antenna port, exposure to non-ionizing radiation meets or exceeds the permissible FCC mandated MPE specification.
	Maximum Gain (dB)	60	Group Delay	150 nS (Typical)
<i>Down-link</i>	Frequency Range (MHz)	851-870		
	Output Power (dBm)	+15		
	Maximum Gain (dB)	60		

For more Information Contact: [sales@signalreach.com](mailto:sales@signalreach.com)

© 2002-2004 SignalReach™. All rights reserved. All trademarks listed in this document are the property of their respective owners. Specifications are subject to change without notice.

 SignalReach™  
www.signalreach.com