NOTES:

1. Label Specifications:

Label Stock: 3M Tamper-Indicating Label for thermal transfer printing 866.

Face Stock: 2.0 Mil Gloss White or Silver Polyester

Destruct Pattern: "VOID"

Adhesive: 1.0 Mil #300 "Hi-Strength" Acrylic

Liner: 3.2 Mil #55 Densified Kraft

2. Text Color: All text Black

3. Text Size:

All text 55 Helvetica, 8 point (unless otherwise noted).

4. SignalReach Logo and Text:

See Artwork File C00001409_RevA_LGF for artwork details. Color: Black. Artwork to be supplied in EPS, Adobe Illustrator or Corel Draw Format.

5. A production sample must be approved for approval for first time orders.

75 Helvetica Roman Bold, 7.44 pt

0.15 c/l 🕏

Was previously C00000975 for the SA200 & C00000900 for the TP200

Was previously C00001193 for the SA200 & TP200

Was previously C00001199 for the SA200/210/110/220/TP200

Was previously C00001334 for the SA200/210/110/220/TP200

 C00001409
 Sheet 1

 REVISIONS

 REV
 EVENT
 dd/mm/yy
 DRAWN

 A
 i) Patent # nomenclature revised
 17/05/06
 MJL

 ii) Text revised (incl.removing model TP2xx)

See Note 4 for SignalReach Logo Symbol and text

See Note 4 for SignalReach Logo Symbol and text

Signal Reach TM

Model: SA1xx/SA2xx
Rating:12 - 24V = ; 1.5A

FCC ID: P35SSG-819-1W2W

IC: 4749A-39EJHT79
United States Patent Number 6,892,080

Made In Canada

UNLESS OTHERWISE SPECIFIED		ARRISTA Technologies Inc.	
TOLERANCE ON DIMENSIONS: .X .XX +.25 +.125 - 0 - 0	DO NOT SCALE DRAWING DIMENSIONS ARE IN INCHES AND APPLY TO FINISHED PART	Title LABEL, Rating Plate, SA1xx/SA Drawing No. C00001409 Type: MS Visio Size: A	2xxx Revision