TEST REPORT

Application No.:	GZCR2106020387HS
Applicant:	Milwaukee Electric Tool Corporation
Address of Applicant:	13135 W Lisbon Rd, Brookfield, WI 53005
Manufacturer:	Milwaukee Tool
Address of Manufacturer:	13135 W Lisbon Rd, Brookfield, WI 53005
Factory:	Computime Limited
Address of Factory:	Yuekenguangyu Industrial Park, Kangqiao Road 88#, Danzhutou Community, Nanwan Street Office, Longgang District, Shenzhen, Guangdong, China
Equipment Under Test (EUT):	
EUT Name:	ONE-KEY™ BLUETOOTH® Tracking Tag
Model No.:	48-21-2301, 48-21-2302, 48-21-2310 ♣
♣	Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.
Trade Mark:	Milwaukee
Standard(s) :	47 CFR Part 15, Subpart C 15.225
Date of Receipt:	2021-06-03
Date of Test:	2021-06-09 to 2021-06-16
Date of Issue:	2021-07-08
Test Result:	**Pass***

* In the configuration tested, the EUT complied with the standards specified above.

Kobe Jian
EMC Laboratory Manager

Revision Record				
Version	**Chapter**	**Date**	**Modifier**	**Remark**
01		*2021-07-08*		*Original*

Authorized for issue by				
Tested By		 **Jim Li/Project Engineer**		
Reviewed By		 **Ricky Liu/Reviewer**		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	**Standard**	**Method**	**Requirement**	**Result**
Antenna Requirement	47 CFR Part 15, Subpart C 15.225	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	**Standard**	**Method**	**Requirement**	**Result**
20dB Bandwidth	47 CFR Part 15, Subpart C 15.225	ANSI C63.10 (2013) Section 6.9	47 CFR Part 15, Subpart C 15.215	Pass
Emission Mask		ANSI C63.10 (2013) Section 6.4	47 CFR Part 15, Subpart C 15.225(a)&(b)&(C)	Pass
Frequency tolerance		ANSI C63.10 (2013) Section 6.8	47 CFR Part 15, Subpart C 15.225(e)	Pass
Radiated Emissions (30MHz-1GHz)		ANSI C63.10 (2013) Section 6.4&6.5	47 CFR Part 15, Subpart C 15.225(d) & 15.209	Pass
Radiated Emissions (9kHz-30MHz)		ANSI C63.10 (2013) Section 6.4&6.5	47 CFR Part 15, Subpart C 15.225(d) & 15.209	Pass

Note:

E.U.T./EUT means Equipment Under Test.

N/A: Not applicable.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

¤ Declaration of EUT Family Grouping:

Model No.: 48-21-2301, 48-21-2302, 48-21-2310

Only the model 48-21-2301 was tested.

According to the declaration from the applicant, the electrical circuit design, layout, components used and internal wiring were identical for all models, with only difference on the number of product in the package (1 for 48-21-2301, 2 for 48-21-2302 and 10 for 48-21-2310).

3 Contents

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3V=Size "CR3202" Battery x 1
Cable(s):	N/A
Operation Frequency:	13.56MHz
Function:	13.56MHz HF RFID Pad Reader
Modulation Type:	ASK declared by applicant
Antenna Gain	0dBi declared by applicant
Antenna Type	PCB Antenna
S/N	3011034
Hardware Version	3899-2982 Rev EB6
Firmware	SV01
Test Software	NFC Tap
Power Setting	Default

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Mobile Phone	APPLE	iPhone 12 mini	F71DP3NG0GQY

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
20dB Bandwidth	± 3%
Emission Mask	±5.06dB （3m） ±4.46dB （10m）
Frequency tolerance	± 3%
Radiated Emissions (30MHz-1GHz)	±5.06dB （3m） ±4.46dB （10m）
Radiated Emissions (9kHz-30MHz)	±5.06dB （3m） ±4.46dB （10m）

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2018 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of Testing Laboratories.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

- **ISED (Registration No.: 4620B, CAB identifier: CN0052)**

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

- **VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)**

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

20dB Bandwidth					
Equipment	**Manufacturer**	**Model No**	**Inventory No**	**Cal Date**	**Cal Due Date**
EXA Signal Analzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Test Software JS1120-3	HangTianXing	V2.6	GZE100-69	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01

Emission Mask					
Equipment	**Manufacturer**	**Model No**	**Inventory No**	**Cal Date**	**Cal Due Date**
EMI Test Receiver(10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable	HangTianXing	N/A	EMC0542	2019-06-28	2021-06-27
Amplifier(9kHz-1.3GHz)	HP	8447F	EMC2065	2021-05-19	2022-05-18
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2019-12-27	2021-12-26
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2019-10-20	2022-10-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

Frequency tolerance					
Equipment	**Manufacturer**	**Model No**	**Inventory No**	**Cal Date**	**Cal Due Date**
EXA Signal Analzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Test Software JS1120-3	HangTianXing	V2.6	GZE100-69	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01
Temperature Chamber	GZ GongWen Co.Ltd.	GDJW-100	EMC0039	2020-06-29	2021-06-28

Radiated Emissions (30MHz-1GHz)					
Equipment	**Manufacturer**	**Model No**	**Inventory No**	**Cal Date**	**Cal Due Date**
EMI Test Receiver(10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable	HangTianXing	N/A	EMC0542	2019-06-28	2021-06-27
Trilog Broadband Antenna(25MHz-1GHz)-Lab	SCHWARZBECK MESS-ELEKTRONIK	VULB 9168	SEM003-18	2019-02-22	2022-02-22
Amplifier(9kHz-1.3GHz)	HP	8447F	EMC2065	2021-05-19	2022-05-18
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2019-10-20	2022-10-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

Radiated Emissions (9kHz-30MHz)					
Equipment	**Manufacturer**	**Model No**	**Inventory No**	**Cal Date**	**Cal Due Date**
EMI Test Receiver(10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable	HangTianXing	N/A	EMC0542	2019-06-28	2021-06-27
Amplifier(9kHz-1.3GHz)	HP	8447F	EMC2065	2021-05-19	2022-05-18
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2019-12-27	2021-12-26
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2019-10-20	2022-10-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

General used equipment					
Equipment	**Manufacturer**	**Model No**	**Inventory No**	**Cal Date**	**Cal Due Date**
DMM	Fluke	73	EMC0006	2020-07-09	2021-07-08
DMM	Fluke	73	EMC0007	2020-07-09	2021-07-08

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.



EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement.

The best case gain of the antenna is 0dBi.

7 Radio Spectrum Matter Test Results

7.1 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.215
Test Method: ANSI C63.10 (2013) Section 6.9
Limit: N/A

7.1.1 E.U.T. Operation

Operating Environment:
Temperature: 25.1 °C Humidity: 59.1 % RH Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode with modulation

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

Cable Loss= 0.9dB



7.2 Emission Mask

Test Requirement 47 CFR Part 15, Subpart C 15.225(a)&(b)&(C)

Test Method: ANSI C63.10 (2013) Section 6.4

Limit:

(a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

(b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

Below 30MHz

The test was performed at a 10m test site.

The factor calculated by the following equation:

If both the single point and the limit distance are equal to or closer to the EUT than λ/2π, then extrapolation to the limit distance shall be calculated using Equation (4):

$$FS_{limit} = FS_{max} - 40\log\left(\frac{d_{limit}}{d_{measure}}\right) \quad (4)$$

where

FS_{limit} is the calculation of field strength at the limit distance, expressed in dBμV/m
FS_{max} is the measured field strength, expressed in dBμV/m
$d_{near\ field}$ is the λ/2π distance
$d_{measure}$ is the distance of the measurement point from the EUT
d_{limit} is the reference distance or the distance of the λ/2π point

Table 5—Relationship of frequency and wavelength (informative)

Frequency (MHz)	λ (m)	0.625λ (m)	λ/2π
0.009	33333.3	20833.3	5305.2
0.1	3000.0	1875.0	477.5
0.3	1000.0	625.0	159.2
1	300.0	187.5	47.7
4.76	63.0	39.4	10.0
16	18.8	11.7	3.0
30	10.0	6.3	1.6

The limit at 10m test distance is below:

The factor of field strength of any emissions within the band 13.553-13.567 MHz shall be 19.08 dB at 10 meters.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.6 °C Humidity: 55.2 % RH Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode with modulation

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Measured Level l=Read Level + Antenna Factor + Cable Loss - Preamp Factor + Extrapolation Correction

Test Mode: 02; Polarity: Horizontal




```
Site        : SGS
Condition   :                                              HORIZONTAL
Job         :
Model       :
Power       :
Test Mode   :
```

	Freq	Read Level	Anterna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/ Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	13.11	34.74	9.07	0.57	29.25	15.13			HORIZONTAL	QP
2	13.41	35.04	8.99	0.58	29.25	15.36			HORIZONTAL	QP
3	13.55	35.06	8.96	0.58	29.25	15.35			HORIZONTAL	QP
4	13.56	40.91	8.96	0.58	29.25	21.20			HORIZONTAL	QP
5	13.57	33.70	8.96	0.58	29.25	13.99			HORIZONTAL	QP
6	13.71	33.49	8.93	0.58	29.25	13.75			HORIZONTAL	QP
7	14.01	33.33	8.87	0.59	29.25	13.54			HORIZONTAL	QP

Frequency (MHz)	Level (dBuV/m) @10m	Limit (dBuV/m) @30m	Convert Factor (dB)	Level (dBuV/m) @30m	Over limit (dB)
13.11	15.13	29.54	19.08	-3.95	-33.49
13.41	15.36	40.51	19.08	-3.72	-44.23
13.55	15.35	50.47	19.08	-3.73	-54.20
**13.56	21.20	84.00	19.08	2.12	-81.88
13.57	13.99	50.47	19.08	-5.09	-55.56
13.71	13.75	40.51	19.08	-5.33	-45.84
14.01	13.54	29.54	19.08	-5.54	-35.08

**Remark: This is the main operating frequency of the EUT.

Test Mode: 02; Polarity: Vertical




```
Site        : SGS
Condition   :                                                VERTICAL
Job         :
Model       :
Power       :
Test Mode   :
```

	Freq	Read Level	Anterna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/ Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	13.11	34.54	9.07	0.57	29.25	14.93			VERTICAL	QP
2	13.41	33.74	8.99	0.58	29.25	14.06			VERTICAL	QP
3	13.55	35.92	8.96	0.58	29.25	16.21			VERTICAL	QP
4	13.56	41.30	8.96	0.58	29.25	21.59			VERTICAL	QP
5	13.57	33.60	8.96	0.58	29.25	13.89			VERTICAL	QP
6	13.71	33.82	8.93	0.58	29.25	14.08			VERTICAL	QP
7	14.01	34.11	8.87	0.59	29.25	14.32			VERTICAL	QP

Frequency (MHz)	Level (dBuV/m) @10m	Limit (dBuV/m) @30m	Convert Factor (dB)	Level (dBuV/m) @30m	Over limit (dB)
13.11	14.93	29.54	19.08	-4.15	-33.69
13.41	14.06	40.51	19.08	-5.02	-45.53
13.55	16.21	50.47	19.08	-2.87	-53.34
**13.56	21.59	84.00	19.08	2.51	-81.49
13.57	13.89	50.47	19.08	-5.19	-55.66
13.71	14.08	40.51	19.08	-5.00	-45.51
14.01	14.32	29.54	19.08	-4.76	-34.30

**Remark: This is the main operating frequency of the EUT.

7.3 Frequency tolerance

Test Requirement 47 CFR Part 15, Subpart C 15.225(e)
Test Method: ANSI C63.10 (2013) Section 6.8
Limit: ±0.01%(±1.356kHz)

7.3.1 E.U.T. Operation

Operating Environment:
Temperature: 25.1 °C Humidity: 59.1 % RH Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode with modulation

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

At startup:

Measurement Conditions		Limit: ±0.01%(1.356kHz)		Verdict
Voltage (V DC)	Temperature (℃)	Frequency Measured (MHz)	Deviation (kHz)	
V_{norm} : 3	-20	13.561218	0.144	PASS
	-10	13.561341	0.267	PASS
	0	13.561158	0.084	PASS
	+10	13.561213	0.139	PASS
	T_{normal} : +20	13.561074	REF	PASS
	+30	13.561249	0.175	PASS
	+40	13.561200	0.126	PASS
	+50	13.561245	0.171	PASS
V_{max} : 3.3	T_{normal} : +20	13.561173	0.099	PASS
V_{min} : 2.7		13.561178	0.104	PASS

At 2 minutes later:

Measurement Conditions		Limit: ±0.01%(1.356kHz)		Verdict
Voltage (V DC)	Temperature (℃)	Frequency Measured (MHz)	Deviation (kHz)	
V_{norm} : 3	-20	13.561232	0.108	PASS
	-10	13.561295	0.171	PASS
	0	13.561179	0.055	PASS
	+10	13.561339	0.215	PASS
	T_{normal} : +20	13.561124	REF	PASS
	+30	13.561317	0.193	PASS
	+40	13.561088	-0.036	PASS
	+50	13.561067	-0.057	PASS
V_{max} : 3.3	T_{normal} : +20	13.561233	0.109	PASS
V_{min} : 2.7		13.561207	0.083	PASS

At 5 minutes later:

Measurement Conditions		Limit: ±0.01%(1.356kHz)		Verdict
Voltage (V DC)	Temperature (℃)	Frequency Measured (MHz)	Deviation (kHz)	
V_{norm} : 3	-20	13.561077	-0.02	PASS
	-10	13.561101	0.004	PASS
	0	13.561252	0.155	PASS
	+10	13.561049	-0.048	PASS
	T_{normal} : +20	13.561097	REF	PASS
	+30	13.561130	0.033	PASS
	+40	13.561127	0.03	PASS
	+50	13.561342	0.245	PASS
V_{max} : 3.3	T_{normal} : +20	13.561315	0.218	PASS
V_{min} : 2.7		13.561294	0.197	PASS

At 10 minutes later:

Measurement Conditions		Limit: ±0.01%(1.356kHz)		Verdict
Voltage (V DC)	Temperature (℃)	Frequency Measured (MHz)	Deviation (kHz)	
V_{norm} : 3	-20	13.561159	-0.177	PASS
	-10	13.561242	-0.094	PASS
	0	13.561271	-0.065	PASS
	+10	13.561148	-0.188	PASS
	T_{normal} : +20	13.561336	REF	PASS
	+30	13.561134	-0.202	PASS
	+40	13.561056	-0.28	PASS
	+50	13.561188	-0.148	PASS
V_{max} : 3.3	T_{normal} : +20	13.561117	-0.219	PASS
V_{min} : 2.7		13.561196	-0.14	PASS

7.4 Radiated Emissions (30MHz-1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.225(d) & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4&6.5

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.7 °C Humidity: 55.9 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode with modulation

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Test Mode: 02; Polarity: Horizontal



Trace: (Discrete)

Site : SGS
Condition : FCC PART15 C (3M) HORIZONTAL
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Anterna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/ Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	40.56	30.66	13.55	1.10	27.18	18.13	40.00	-21.87	HORIZONTAL	QP
2	67.68	34.06	12.24	1.38	27.14	20.54	40.00	-19.46	HORIZONTAL	QP
3	135.51	31.46	12.73	2.03	26.96	19.26	43.50	-24.24	HORIZONTAL	QP
4	162.61	31.78	13.57	2.35	26.79	20.91	43.50	-22.59	HORIZONTAL	QP
5	455.91	26.00	17.42	4.22	27.75	19.89	46.00	-26.11	HORIZONTAL	QP
6	824.60	27.54	22.75	6.30	27.99	28.60	46.00	-17.40	HORIZONTAL	QP

Test Mode: 02; Polarity: Vertical



Trace: (Discrete)

Site : SGS
Condition : FCC PART15 C (3M) VERTICAL
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Anterna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/ Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	40.56	37.00	13.55	1.10	27.18	24.47	40.00	-15.53	VERTICAL	QP
2	67.68	40.62	12.24	1.38	27.14	27.10	40.00	-12.90	VERTICAL	QP
3	108.27	33.46	10.32	1.78	27.06	18.50	43.50	-25.00	VERTICAL	QP
4	157.01	25.20	13.70	2.31	26.81	14.40	43.50	-29.10	VERTICAL	QP
5	362.98	26.61	14.95	3.73	27.14	18.15	46.00	-27.85	VERTICAL	QP
6	737.07	26.56	21.95	5.93	28.12	26.32	46.00	-19.68	VERTICAL	QP

7.5 Radiated Emissions (9kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.225(d) & 15.209
Test Method: ANSI C63.10 (2013) Section 6.4&6.5
Measurement distance: 10 m
Limit:

Frequency(MHz)	Field strength (microvolts/meter)	Limit (dBuV/m)	Detector	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	-	300
0.490-1.705	24000/F(kHz)	-	-	30
1.705-30	30	-	-	30
30-88	100	40.0	QP	3
88-216	150	43.5	QP	3
216-960	200	46.0	QP	3
960-1000	500	54.0	QP	3
Above 1000	500	54.0	AV	3

According to ANSI C63.10 Section 6.4, the test data shall convert by below formula:

If both the single point and the limit distance are equal to or closer to the EUT than λ/2π, then extrapolation to the limit distance shall be calculated using Equation (4):

$$FS_{\text{limit}} = FS_{\text{max}} - 40\log\left(\frac{d_{\text{limit}}}{d_{\text{measure}}}\right) \quad (4)$$

where

FS_{limit} is the calculation of field strength at the limit distance, expressed in dBμV/m
FS_{max} is the measured field strength, expressed in dBμV/m
$d_{\text{near field}}$ is the λ/2π distance
d_{measure} is the distance of the measurement point from the EUT
d_{limit} is the reference distance or the distance of the λ/2π point

Table 5—Relationship of frequency and wavelength (informative)

Frequency (MHz)	λ (m)	0.625λ (m)	λ/2π
0.009	33333.3	20833.3	5305.2
0.1	3000.0	1875.0	477.5
0.3	1000.0	625.0	159.2
1	300.0	187.5	47.7
4.76	63.0	39.4	10.0
16	18.8	11.7	3.0
30	10.0	6.3	1.6

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.6 °C Humidity: 54.3 % RH Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode with modulation

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Measured Level l=Read Level + Antenna Factor + Cable Loss - Preamp Factor+ Extrapolation Correction

Mode:02; Polarization: Horizontal



All the test data below the background of emissions in the frequency band, and the peak field strength of any emission is not exceeding the maximum permitted average limits specified above. So, no measurement data was shown.

Mode:02; Polarization: Horizontal



The point 6 is the main operating frequency of the EUT and refer to section 7.3 for details.

All the test data below the background of emissions in the frequency band, and the peak field strength of any emission is not exceeding the maximum permitted average limits specified above. So, no measurement data was shown.

- End of the Report -