



849 NW STATE ROAD 45  
NEWBERRY, FL 32669 USA  
PH: 888.472.2424 OR  
352.472.5500  
FAX: 352.472.2030  
EMAIL: [INFO@TIMCOENGR.COM](mailto:INFO@TIMCOENGR.COM)  
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

---

## RF Exposure Evaluation Report

<b>APPLICANT</b>	FIPLEX COMMUNICATIONS INC.
	7331 N.W. 54TH STREET MIAMI FL 33166
<b>FCC ID</b>	P3TDHS40-HG-SCH
<b>MODEL NUMBER</b>	DHS40-HG-SCH
<b>PRODUCT DESCRIPTION</b>	PS800 SINGLE CARRIER AMPLIFIER
<b>STANDARD APPLIED</b>	CFR 47 Part 2.1091
<b>PREPARED BY</b>	Sid Sanders

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

## GENERAL REMARKS

### Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

**Timco Engineering Inc.**  
**849 NW State Road 45**  
**Newberry, FL 32669**

**Authorized Signatory Name:**



Sid Sanders, Engineer

**Date: 7/20/2017**

Applicant: FIPLEX COMMUNICATIONS INC.

FCC ID: P3TDHS40-HG-SCH

Report: F\FIPLEX\_P3T\1087AUT17\1087AUT17RF Exp MPE Rpt\_Rev.docx

## RF Exposure Requirements

### General information

Device type: PS800 SINGLE CARRIER AMPLIFIER

### Antenna

The manufacturer does not specify an antenna, but a typical antenna has a gain of 0 dBi.

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Fixed mounted	Any		0

### MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.11310, Table 1.

Applicant: FIPLEX COMMUNICATIONS INC.

FCC ID: P3TDHS40-HG-SCH

Report: F\FIPLEX\_P3T\1087AUT17\1087AUT17RF Exp MPE Rpt\_Rev.docx

**Insert values in yellow highlighted boxes to determine Minimum Separation Distance**

Max Power	10	W	<i>equals</i>	Max Power	10000	mW
Duty Cycle	100	%	<i>equals</i>	Duty Factor	1	numeric
Antenna Gain	0	dBi	<i>equals</i>	Gain numeric	1	numeric
Coax Loss	0	dB		Gain - Coax Los	1	numeric
Power Density	0.5	mW/cm <sup>2</sup>				
Frequency	824	MHz				

Enter power Density from the chart to the right

**Rule Part 1.1310, Table 1 (B)**

Frequency range	Power der	Enter this value
MHz	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>
0.3-1.34	100	100
1.34-30	180/f <sup>2</sup>	0.0
30-300	0.2	0.2
300-1,500	f/1500	0.5
1,500-100,000	1	1

f = frequency in MHz

<b>Minimum Separation Distance</b>	<b>40 cm</b>	<b>0.40 m</b>
------------------------------------	--------------	---------------

Minimum Separation in Inches      15.69439 Inches