



Test Report No.:RF2204WDG0452



TEST REPORT



| | |
|-----------|---|
| Applicant | FUJIAN TEAMDA PHOTOELECTRICITY CO., LTD |
| Address | Trangulation Point Shengqiao Town, Zhaoan County, Zhangzhou City, Fujian Province P.R .China |

| | |
|---------------------------------------|---|
| Manufacturer or Supplier | FUJIAN TEAMDA PHOTOELECTRICITY CO., LTD |
| Address | Trangulation Point Shengqiao Town, Zhaoan County, Zhangzhou City, Fujian Province P.R .China |
| Product | Toy RC Monster Spinning Car |
| Brand Name | SHARPER IMAGE |
| Model | 1012328 |
| Additional Models & Model Difference: | 1012329, 1013270, 1013271, 1014554, 1014555, 1014556, 1015631, 1015647, 1012327, 1013243,1014391,101XXXX (where XXXX can be digits 0000-9999 which represent different customers); see item 3.1 |
| Date of tests | May 03, 2022 ~ May 16, 2022 |

the tests have been carried out according to the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.227

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

| | |
|---|--|
| Tested by Loren Luo Project Engineer / EMC Department | Approved by Glyn He Assistant Manager / EMC Department |
|  |  Date: Jun 28, 2022 |

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com



Test Report No.:RF2204WDG0452

TABLE OF CONTENTS

| | |
|---|-----------|
| RELEASE CONTROL RECORD | 3 |
| 1 SUMMARY OF TEST RESULTS..... | 4 |
| 2 MEASUREMENT UNCERTAINTY | 4 |
| 3 GENERAL INFORMATION | 5 |
| 3.1 GENERAL DESCRIPTION OF EUT..... | 5 |
| 3.2 DESCRIPTION OF TEST MODES..... | 6 |
| 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS..... | 6 |
| 3.4 DESCRIPTION OF SUPPORT UNITS..... | 6 |
| 4 TEST TYPES AND RESULTS..... | 7 |
| 4.1 RADIATED EMISSION MEASUREMENT | 7 |
| 4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT | 7 |
| 4.1.2 TEST INSTRUMENTS..... | 8 |
| 4.1.3 TEST PROCEDURES | 9 |
| 4.1.4 DEVIATION FROM TEST STANDARD | 9 |
| 4.1.5 TEST SETUP | 10 |
| 4.1.6 EUT OPERATING CONDITIONS | 11 |
| 4.1.7 TEST RESULTS | 11 |
| 4.2 BANDWIDTH MEASUREMENT..... | 16 |
| 4.2.1 LIMITS OF BANDWIDTH MEASUREMENT | 16 |
| 4.2.2 TEST INSTRUMENTS..... | 16 |
| 4.2.3 TEST PROCEDURE..... | 17 |
| 4.2.4 DEVIATION FROM TEST STANDARD | 17 |
| 4.2.5 TEST SETUP..... | 17 |
| 4.2.6 EUT OPERATING CONDITIONS | 17 |
| 4.2.7 TEST RESULTS | 18 |
| 5 PHOTOGRAPHS OF THE TEST CONFIGURATION..... | 19 |
| 6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB | 20 |



Test Report No.:RF2204WDG0452

RELEASE CONTROL RECORD

| ISSUE NO. | REASON FOR CHANGE | DATE ISSUED |
|---------------|-------------------|--------------|
| RF2204WDG0452 | Original release | Jun 28, 2022 |

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC PART 15, SUBPART C , SECTION 15.227(2015-10) | | | |
|--|-----------------------------|--------|------------------------------|
| STANDARD SECTION | TEST TYPE AND LIMIT | RESULT | REMARK |
| §15.207 (a) | AC Power Conducted Emission | N/A | EUT is powered by battery |
| §15.209 §15.227 | Radiated Emission | PASS | Compliant |
| §15.215(c) | 20dB Bandwidth Test | PASS | Compliant |
| §15.203 | Antenna Requirement | PASS | No antenna connector is used |

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT | FREQUENCY | UNCERTAINTY |
|--------------------|--------------|-------------|
| Radiated emissions | 9KHz ~ 30MHz | 2.66dB |
| | 30MHz ~ 1GHz | 4.06dB |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | |
|----------------------------|--|
| PRODUCT | Toy RC Monster Spinning Car |
| MODEL NO. | 1012328 |
| ADDITIONAL MODELS | 1012329, 1013270, 1013271, 1014554, 1014555, 1014556, 1015631, 1015647, 1012327, 1013243, 1014391, 101XXXX (where XXXX can be digits 0000-9999 which represent different customers) |
| FCC ID | P45TD2022A27-1 |
| NOMINAL VOLTAGE | Remote control: DC 9V from battery |
| MODULATION TYPE | ASK |
| OPERATING FREQUENCY | 27.145 MHz |
| NUMBER OF CHANNEL | 1 |
| ANTENNA TYPE | Spring Antenna with 0dBi gain |
| I/O PORTS | Refer to user's manual |

NOTES:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 2204WDG0452) for detailed product photo.
4. Additional models (see above table) are identical with the test model 1012328 except the color of the appearance, trade name and model number for trading purpose.



3.2 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and packet type. The worst case was found when the EUT was positioned on X axis for radiated emission. The EUT was tested under the following mode.

| FREQUENCY | TEST MODES |
|------------|--------------|
| 27.145 MHz | Transmitting |

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, 15.227

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit without any other necessary accessories or support units.

4 TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

| FREQUENCIES (MHz) | FIELD STRENGTH (microvolts/meter) | MEASUREMENT DISTANCE (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

According to §15.227(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

| Frequency Range of Fundamental [MHz] | Field Strength of Fundamental Emission [Peak] [μ V/m] | Field Strength of Fundamental Emission [Average] [μ V/m] |
|--|---|--|
| 26.96 – 27.28 | 100,000 (100 dB μ V/m) | 10,000 (80 dB μ V/m) |

NOTES:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (μ V/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

For Below 30MHz

| Equipment | Manufacturer | Model No. | Serial No. | Next Cal. |
|-------------------|---------------|--------------------------|------------|------------|
| EMI Test Receiver | Rohde&Schwarz | ESC17 | 100962 | Apr.18.23 |
| Loop Antenna | COM-POWER | AL-130 | 121031 | Apr. 27,23 |
| Coaxial RF Cable | Joinfront | JFAA6-NMNM-8000 | 2100033742 | Aug.08, 22 |
| Coaxial RF Cable | Joinfront | JFAR-NMBNCM-2000 | 2100033742 | Aug.08, 22 |
| Coaxial RF Cable | Joinfront | JFAR-BNCMSMM-500 | 2100033742 | Aug.08, 22 |
| Test Software | ADT | ADT_Radiated_V7.6.15.9.2 | N/A | N/A |

- NOTES:**
1. The test was performed in 3m Chamber(Baodun)..
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 3. The FCC Site Registration No. is 749762

For 30MHz ~1GHz

| Equipment | Manufacturer | Model No. | Serial No. | Next Cal. |
|-----------------------------|---------------|--------------------------|--------------|-------------|
| Spectrum Analyzer | Rohde&Schwarz | FSV40-N | 101817 | July 04, 22 |
| Bilog Antenna | SCHWARZBECK | VULB 9168 | 01281 | July 30, 22 |
| Pre-Amplifier | Agilent | 8447D | 2944A10488 | Aug.08, 22 |
| 3m Semi-anechoic Chamber | ETS-Lindgren | 9m*6m*6m | D3040003DG-1 | July 30, 24 |
| Coaxial RF Cable | Joinfront | JFAA6-NMNM-8000 | 2100033742 | Aug.08, 22 |
| Coaxial RF Cable | Joinfront | JFAR-NMBNCM-2000 | 2100033742 | Aug.08, 22 |
| Coaxial RF Cable | Joinfront | JFAR-BNCMSMM-500 | 2100033742 | Aug.08, 22 |
| Test software | ADT | ADT_Radiated_V7.6.15.9.2 | N/A | N/A |
| Horn Antenna | ETS-Lindgren | 3117 | 00240041 | July 22, 22 |
| Horn Antenna | SCHWARZBECK | BBHA 9170 | 01024 | Dec. 25, 22 |
| Pre-Amplifier (1GHz-18GHz) | SCHWARZBECK | BBV 9718C | 00142 | Aug. 06, 22 |
| Pre-Amplifier (18GHz-40GHz) | Rohde&Schwarz | SCU40 | 100437 | Nov. 16, 22 |
| Coaxial RF Cable | Joinfront | JFAA6-NMNM-8000 | 2100033742 | Aug.08, 22 |
| Coaxial RF Cable | Joinfront | JFAA6-NMSMM-2000 | 2100033742 | Aug.08, 22 |
| Coaxial RF Cable | Joinfront | JFAA6-NMSMM-800 | 2100033742 | Aug.08, 22 |

- NOTES:**
1. The test was performed at 966 Chamber-3 (Baodun).
 2. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 3. The horn antenna is used only for the measurement of emission frequency above1GHz if tested.
 4. The FCC Site Registration No. is 749762.

4.1.3 TEST PROCEDURES

The basic test procedure was in accordance with ANSI C63.10 (section 6).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. (Below 1000MHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10m chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. (Below 30MHz)
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position Y, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level.
- h. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

NOTES:


1. The resolution bandwidth of test receiver/spectrum analyzer is 200Hz for Quasi-peak detection (QP) at fundamental frequency 9K-150KHz;
2. The resolution bandwidth of test receiver/spectrum analyzer is 9KHz for Quasi-peak detection (QP) at fundamental frequency 150K-30MHz;
3. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at radiated spurious emission frequency 30MHz-1GHz.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

4.1.5 TEST SETUP

Below 30MHz test setup



Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).



4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power of equipment.
- b. Hold down the TX of button, then the EUT was operating.
- c. EUT was operated according to the type used was description in manufacturer’s specifications or the User's Manual.

4.1.7 TEST RESULTS

Pre-Scan has been considered to determine the worst-case mode from all possible combinations between XYZ axis.

The worst case was found when the EUT was positioned on X axis for radiated emission.

FIELD STRENGTH OF FUNDAMENTAL

ANTENNA POLARITY (PARALLEL): 0°

| No. | Freq. (MHz) | Correction Factor (dB/m) | Raw Value (dBuV) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----|-------------|--------------------------|------------------|-------------------------|----------------|-------------|
| * | 27.14(PK) | -15.64 | 69.86 | 54.22 | 100 | -45.78 |
| * | 27.14(AV) | -5.39 | - | 48.83 | 80 | -31.17 |

ANTENNA POLARITY (PERPENDICULAR): 90°

| No. | Freq. (MHz) | Correction Factor (dB/m) | Raw Value (dBuV) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----|-------------|--------------------------|------------------|-------------------------|----------------|-------------|
| * | 27.14(PK) | -15.64 | 75.14 | 59.5 | 100 | -40.5 |
| * | 27.14(AV) | -5.39 | - | 54.11 | 80 | -25.89 |

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. Margin value = Emission level – Limit value.
 4. “ * “: Fundamental frequency.
 5. The average value of fundamental frequency is: Average value = Peak value +AV factor, where the AV factor is calculated from following formula: AV factor=20 log (Duty cycle) = 20 log (53.79%) = -5.39dB, Please see page 12~13 for plotted duty.
 6. all three antenna orientations(parallel, perpendicular, and ground-parallel) testing. But the worst orientation showed in report only.




Duty Cycle:

$T_p = 50.87\text{ms}$

$T_{on} = T_{on1} * \text{Number} + T_{on2} * \text{Number} = 1.6232 * 4 + 0.5217 * 40 = 27.3608\text{ms}$

$\text{Duty Cycle} = T_{on} / T_p * 100\% = 27.3608 / 50.87 * 100\% = 53.79\%$

$T_p = 50.87\text{ms}$






Test Report No.:RF2204WDG0452

Ton1=1.6232ms

Ton2=0.5217ms






Test Report No.:RF2204WDG0452

| | | | |
|------------------------|-------------|--------------------------|-----------------|
| FREQUENCY RANGE | 9KHz ~ 1GHz | DETECTOR FUNCTION | Quasi-Peak (QP) |
|------------------------|-------------|--------------------------|-----------------|

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 53.90 | 18.75 QP | 40.00 | -21.25 | 2.56 H | 166 | 32.83 | -14.08 |
| 2 | 146.68 | 13.03 QP | 43.50 | -30.47 | 1.90 H | 103 | 26.79 | -13.76 |
| 3 | 188.86 | 14.04 QP | 43.50 | -29.46 | 2.84 H | 273 | 29.59 | -15.55 |
| 4 | 278.83 | 12.81 QP | 46.00 | -33.19 | 2.74 H | 67 | 25.72 | -12.91 |
| 5 | 354.74 | 15.49 QP | 46.00 | -30.51 | 2.30 H | 210 | 26.89 | -11.40 |
| 6 | 409.57 | 16.87 QP | 46.00 | -29.13 | 1.02 H | 197 | 27.42 | -10.55 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value.




| | | | |
|------------------------|-------------|--------------------------|-----------------|
| FREQUENCY RANGE | 9KHz ~ 1GHz | DETECTOR FUNCTION | Quasi-Peak (QP) |
|------------------------|-------------|--------------------------|-----------------|

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 53.90 | 20.46 QP | 40.00 | -19.54 | 1.38 V | 127 | 34.54 | -14.08 |
| 2 | 160.74 | 13.54 QP | 43.50 | -29.96 | 2.45 V | 344 | 27.06 | -13.52 |
| 3 | 291.48 | 14.09 QP | 46.00 | -31.91 | 2.86 V | 34 | 26.75 | -12.66 |
| 4 | 405.35 | 16.70 QP | 46.00 | -29.30 | 2.26 V | 193 | 27.32 | -10.62 |
| 5 | 448.93 | 18.17 QP | 46.00 | -27.83 | 2.93 V | 8 | 28.07 | -9.90 |
| 6 | 502.35 | 18.48 QP | 46.00 | -27.52 | 1.03 V | 63 | 27.56 | -9.08 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value.





4.2 BANDWIDTH MEASUREMENT

4.2.1 LIMITS OF BANDWIDTH MEASUREMENT

The field strength of any emissions appearing between the band edges and out of band shall be attenuated at least 20 dB below the level of the unmodulated carrier or to the general limits in Section 15.209.

| FREQUENCY (MHz) | Limits |
|--------------------|--------------------|
| | [MHz] |
| 27.145 | within 26.96-27.28 |

4.2.2 TEST INSTRUMENTS

| Equipment | Manufacturer | Model No. | Serial No. | Next Cal. |
|---|---------------|-------------------------------|------------|-------------|
| Wireless Connectivity Tester | Rohde&Schwarz | CMW270 | 101601 | Nov. 21, 22 |
| MXA signal analyzer | Agilent | N9020A | MY49100060 | Apr. 18, 23 |
| Spectrum Analyzer | Rohde&Schwarz | FSV40 | 101094 | Jan. 16, 23 |
| Frequency Analyzer | Keysight | N9010B | MY60240432 | Nov. 25, 22 |
| Programmable Temperature&Humidity Chamber | Hongjin | HYC-TH-225DH | DG-180746 | Feb. 16, 23 |
| DC Source | Agilent | E3640A | MY40004013 | Feb. 23, 23 |
| Test software | ADT | ADT_RF Test Software V6.6.5.3 | N/A | N/A |
| Test software | ADT | ADT_RF Test Software V6.6.5.4 | N/A | N/A |

NOTES:

1. The test was performed in RF Oven room (Baodun).
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.


4.2.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



4.2.6 EUT OPERATING CONDITIONS


Same as item 4.1.6



4.2.7 TEST RESULTS

| Lower & Upper Test Frequency Point (MHz) | Test Frequency (MHz) | P/F |
|--|----------------------|------|
| Lower | 27.11311 | PASS |
| Upper | 27.16738 | PASS |

Test Data:





Test Report No.:RF2204WDG0452

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.:RF2204WDG0452

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---