

RF EXPOSURE REPORT



Report No.: 15071045-FCC-H2

Supersede Report No.: N/A

Applicant	Unimax Communications	
Product Name	3G Mobile Phone	
Model No.	MXW1	
Serial No.	N/A	
Test Standard	FCC 2.1093:2014	
Test Date	November 10 to December 02, 2015	
Issue Date	December 02, 2015	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
<i>Winnie Zhang</i>	<i>David Huang</i>	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15071045-FCC-H2
Page	3 of 10

This page has been left blank intentionally.

CONTENTS

- 1. REPORT REVISION HISTORY5
- 2. CUSTOMER INFORMATION5
- 3. TEST SITE INFORMATION.....5
- 4. EQUIPMENT UNDER TEST (EUT) INFORMATION6
- 5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES. 8
- 5.1 RF EXPOSURE.....8
- 5.2 TEST RESULT9

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15071045-FCC-H2	NONE	Original	December 02, 2015

2. Customer information

Applicant Name	Unimax Communications
Applicant Add	18201 McDermott Street West Suite E Irvine, CA 92614
Manufacturer	Shenzhen Fortuneship Technology Co., Ltd
Manufacturer Add	Room 701-716, 7th Floor, Kanghesheng Building, No.1 ChuangSheng Road, Nanshan District, Shenzhen, Guangdong, P. R. China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	3G Mobile Phone
Main Model:	MXW1
Serial Model:	N/A
Date EUT received:	November 09, 2015
Test Date(s):	November 10 to December 02, 2015
Antenna Gain:	<p>GSM850: -1.6dBi PCS1900: 1.0 dBi UMTS-FDD Band V: -0.4 dBi UMTS-FDD Band II: 0.9 dBi Bluetooth: -0.7 dBi WIFI: -0.7 dBi GPS: -0.5 dBi</p>
Type of Modulation:	<p>GSM / GPRS: GMSK EGPRS: GMSK ,8PSK UMTS-FDD: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK GPS:BPSK</p>
RF Operating Frequency (ies):	<p>GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz WIFI:802.11b/g/n(20M): 2412-2462 MHz Bluetooth: 2402-2480 MHz GPS RX:1575.42 MHz</p>
Number of Channels:	<p>GSM 850: 124CH PCS1900: 299CH</p>

Test Report	15071045-FCC-H2
Page	7 of 10

UMTS-FDD Band V : 102CH
UMTS-FDD Band II : 277CH
WIFI :802.11b/g/n(20M): 11CH
Bluetooth: 79CH
GPS:1CH

Port: Power Port, Earphone Port, USB Port

Adapter:
Model: MXW1CHG
Input: AC 100-240V; 50/60Hz;0.15A
Output: DC 5.0V,500mA
Battery:
Model: MXW1BAT
Spec:3.7V,1150mAh,4.255Wh

Input Power:

Trade Name : UMX

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: P46-MXW1

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission' s guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

5.2 Test Result

Bluetooth Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-0.354	-1±1	0	1.000	0.31	3
	Mid	2441	0.982	1±1	2	1.585	0.50	3
	High	2480	2.358	2±1	3	1.995	0.63	3
π /4 DQPSK	Low	2402	1.750	1±1	2	1.585	0.49	3
	Mid	2441	3.027	3±1	4	2.512	0.78	3
	High	2480	4.417	4±1	5	3.162	1.00	3
8-DPSK	Low	2402	2.295	3±1	4	2.512	0.78	3
	Mid	2441	3.592	3±1	4	2.512	0.78	3
	High	2480	4.872	4±1	5	3.162	1.00	3

WIFI Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
802.11b	Low	2412	7.87	8±1	9	7.943	2.47	3
	Mid	2437	7.92	8±1	9	7.943	2.48	3
	High	2462	8.58	8±1	9	7.943	2.49	3
802.11g	Low	2412	8.00	8±1	9	7.943	2.47	3
	Mid	2437	8.17	8±1	9	7.943	2.48	3
	High	2462	8.63	8±1	9	7.943	2.49	3
802.11n (20M)	Low	2412	7.26	8±1	9	7.943	2.47	3
	Mid	2437	7.61	8±1	9	7.943	2.48	3
	High	2462	7.77	8±1	9	7.943	2.49	3

BLE Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-8.152	-8±1	-7	0.200	0.06	3
	Mid	2440	-6.885	-6±1	-5	0.316	0.10	3
	High	2480	-6.072	-6±1	-5	0.316	0.10	3

Result: Compliance

No SAR measurement is required.