



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM171201298705
Page: 1 of 23

TEST REPORT

Application No.: SZEM1712012987RG
Applicant: Unimax communications
Address of Applicant: 18201 McDermott St. West Suite E, Irvine, CA 92614
Manufacturer: Unimaxcomm
Address of Manufacturer: Room 602, Building-B, Shenzhen Software Park T3, Hi-Tech Park South, Nan Shan District, Shenzhen, China
Factory: Unimaxcomm
Address of Factory: Room 602, Building-B, Shenzhen Software Park T3, Hi-Tech Park South, Nan Shan District.

Equipment Under Test (EUT):

EUT Name: Smartphone
Model No.: U452TL
FCC ID: P46-U452TL
Trade mark: UMX
Standard(s) : 47 CFR Part 15, Subpart B
Date of Receipt: 2018-02-02
Date of Test: 2018-02-07 to 2018-02-09
Date of Issue: 2018-03-05

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.




Keny Xu
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



<i>Revision Record</i>				
<i>Version</i>	<i>Chapter</i>	<i>Date</i>	<i>Modifier</i>	<i>Remark</i>
01		2018-03-05		Original

Authorized for issue by:				
				
		<hr/>		
		Gray Gao /Project Engineer		
				
		<hr/>		
		Eric Fu /Reviewer		



2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at Mains Terminals (150kHz-30MHz)	47 CFR Part 15, Subpart B	ANSI C63.4	Class B	Pass
Radiated Emissions (30MHz-1GHz)	47 CFR Part 15, Subpart B	ANSI C63.4	Class B	Pass
Radiated Emissions (above 1GHz)	47 CFR Part 15, Subpart B	ANSI C63.4	Class B	Pass

InternalSource	UpperFrequency
Below 1.705MHz	30MHz
1.705MHz to 108MHz	1GHz
108MHz to 500MHz	2GHz
500MHz to 1GHz	5GHz
Above 1GHz	5th harmonic of the highest frequency or 40GHz, whichever is lower



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 DETAILS OF E.U.T.....	5
4.2 DESCRIPTION OF SUPPORT UNITS.....	5
4.3 MEASUREMENT UNCERTAINTY	5
4.4 TEST LOCATION	6
4.5 TEST FACILITY	6
4.6 DEVIATION FROM STANDARDS	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
5 EQUIPMENT LIST	7
6 EMISSION TEST RESULTS.....	9
6.1 CONDUCTED EMISSIONS AT MAINS TERMINALS (150kHz-30MHz).....	9
6.1.1 <i>E.U.T. Operation</i>	10
6.1.2 <i>Test Setup Diagram</i>	10
6.1.3 <i>Measurement Data</i>	10
6.2 RADIATED EMISSIONS (30MHz-1GHz).....	15
6.2.1 <i>E.U.T. Operation</i>	16
6.2.2 <i>Test Setup Diagram</i>	16
6.2.3 <i>Measurement Data</i>	16
6.3 RADIATED EMISSIONS (ABOVE 1GHz).....	19
6.3.1 <i>E.U.T. Operation</i>	19
6.3.2 <i>Test Setup Diagram</i>	19
6.3.3 <i>Measurement Data</i>	19
7 PHOTOGRAPHS	22
7.1 CONDUCTED EMISSIONS AT MAINS TERMINALS (150kHz-30MHz) TEST SETUP.....	22
7.2 RADIATED EMISSIONS (30MHz-1GHz) TEST SETUP	23
7.3 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	23

4 General Information

4.1 Details of E.U.T.

Power supply:	AC input: 100-240V 50/60Hz 0.2A
Cable:	USB cable: 100cm shielded.

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Conduction emission	3.0dB (150kHz to 30MHz)
2	Radiated emission	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-6GHz)
3	Temperature test	1 °C
4	Humidity test	3%



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Emissions at Mains Terminals (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ChangZhou ZhongYu	GB-88	SEM001-06	2017-05-10	2018-05-09
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2017-07-13	2018-07-12
LISN	Rohde & Schwarz	ENV216	SEM007-01	2017-09-27	2018-09-26
LISN	ETS-LINDGREN	3816/2	SEM007-02	2017-04-14	2018-04-13
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2017-04-14	2018-04-13

Radiated Emissions (30MHz-1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2017-05-10	2018-05-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2017-07-13	2018-07-12
EMI Test Receiver (9kHz-3GHz)	Rohde & Schwarz	ESR	SEM004-03	2017-04-14	2018-04-13
Trilog-Broadband Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-28
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2017-06-05	2018-06-04

Radiated Emissions (above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-02	2020-05-01
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2017-07-13	2018-07-12
EXA Spectrum Analyzer	AgilentTechnologies Inc	N9010A	SEM004-09	2017-06-05	2018-06-04
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-06	2015-06-14	2018-06-13
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2017-09-27	2018-09-26



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM171201298705

Page: 8 of 23

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-17



6 Emission Test Results

6.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)

Test Requirement:	47 CFR Part 15, Subpart B
Test Method:	ANSI C63.4
Frequency Range:	150kHz to 30MHz
Limit:	
0.15M-0.5MHz	66dB(μV)-56dB(μV) quasi-peak, 56dB(μV)-46dB(μV) average
0.5M-5MHz	56dB(μV) quasi-peak, 46dB(μV) average
5M-30MHz	60dB(μV) quasi-peak, 50dB(μV) average
Detector:	Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

6.1.1 E.U.T. Operation


Operating Environment:

Temperature: 19.4 °C Humidity: 32.2 % RH Atmospheric Pressure: 1015 mbar

- Pretest these modes to find the worst case:
- d: Telecom Idle + BT(Idle)+ WLAN(Idle) + playing MP4 (SD card) + earphone + battery + adapter
 - e: Telecom Idle + BT(Idle)+ WLAN(Idle) + camera(Front) + earphone + battery + adapter
 - f: Telecom Idle + BT(Idle)+ WLAN(Idle) + camera(Back) + earphone + battery + adapter
 - g: Transfer data between the EUT and the PC(write)
 - h: Transfer data between the EUT and the PC(read)
 - i: single play mode, keep EUT working normally without adapter and earphone.

- The worst case for final test:
- e: Telecom Idle + BT(Idle)+ WLAN(Idle) + camera(Front) + earphone + battery + adapter
 - g: Transfer data between the EUT and the PC(write)


6.1.2 Test Setup Diagram



6.1.3 Measurement Data

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.


Mode:e; Line:Live Line



Site : Shielding Room
 Condition: Line
 Job No. : 12987RG
 Test mode: e

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15	0.02	9.51	25.53	35.06	55.87	-20.81	Average
2	0.15	0.02	9.51	37.67	47.20	65.87	-18.67	QP
3	0.22	0.02	9.50	20.71	30.23	52.70	-22.47	Average
4	0.22	0.02	9.50	30.87	40.39	62.70	-22.31	QP
5	0.41	0.01	9.49	21.14	30.64	47.68	-17.04	Average
6	0.41	0.01	9.49	29.52	39.02	57.68	-18.66	QP
7	1.88	0.02	9.51	20.27	29.80	46.00	-16.20	Average
8	1.88	0.02	9.51	29.74	39.27	56.00	-16.73	QP
9	2.16	0.02	9.51	21.02	30.55	46.00	-15.45	Average
10	2.16	0.02	9.51	30.33	39.86	56.00	-16.14	QP
11	3.07	0.02	9.55	15.95	25.52	46.00	-20.48	Average
12	3.07	0.02	9.55	24.06	33.63	56.00	-22.37	QP


Mode:e; Line:Neutral Line



Site : Shielding Room
 Condition: Neutral
 Job No. : 12987RG
 Test mode: e

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.16	0.02	9.59	22.45	32.06	55.25	-23.19	Average
2	0.16	0.02	9.59	36.00	45.61	65.25	-19.64	QP
3	0.23	0.02	9.58	20.46	30.06	52.57	-22.51	Average
4	0.23	0.02	9.58	31.69	41.29	62.57	-21.28	QP
5	0.30	0.01	9.58	18.48	28.07	50.28	-22.21	Average
6	0.30	0.01	9.58	25.52	35.11	60.28	-25.17	QP
7	0.37	0.01	9.58	19.20	28.79	48.61	-19.82	Average
8	0.37	0.01	9.58	27.85	37.44	58.61	-21.17	QP
9	0.66	0.02	9.62	15.46	25.10	46.00	-20.90	Average
10	0.66	0.02	9.62	22.26	31.90	56.00	-24.10	QP
11	1.64	0.02	9.64	19.53	29.19	46.00	-16.81	Average
12	1.64	0.02	9.64	28.75	38.41	56.00	-17.59	QP


Mode:g; Line:Live Line



Site : Shielding Room
 Condition: Line
 Job No. : 12987RG
 Test mode: g

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.16	0.02	9.52	30.40	39.94	55.34	-15.40	Average
2	0.16	0.02	9.52	48.63	58.17	65.34	-7.17	QP
3	0.18	0.02	9.51	22.17	31.70	54.50	-22.80	Average
4	0.18	0.02	9.51	45.69	55.22	64.50	-9.28	QP
5	0.23	0.02	9.51	23.11	32.64	52.61	-19.97	Average
6	0.23	0.02	9.51	40.90	50.43	62.61	-12.18	QP
7	0.27	0.01	9.51	14.34	23.86	51.07	-27.21	Average
8	0.27	0.01	9.51	35.23	44.75	61.07	-16.32	QP
9	0.34	0.01	9.50	9.35	18.86	49.27	-30.41	Average
10	0.34	0.01	9.50	28.72	38.23	59.27	-21.04	QP
11	0.41	0.01	9.49	8.08	17.58	47.64	-30.06	Average
12	0.41	0.01	9.49	22.53	32.03	57.64	-25.61	QP

Mode:g; Line:Neutral Line



Site : Shielding Room
 Condition: Neutral
 Job No. : 12987RG
 Test mode: g

	Freq	Cable Loss	LISN Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.16	0.02	9.58	30.08	39.68	55.52	-15.84	Average
2	0.16	0.02	9.58	47.31	56.91	65.52	-8.61	QP
3	0.17	0.02	9.59	28.41	38.02	54.94	-16.92	Average
4	0.17	0.02	9.59	45.94	55.55	64.94	-9.39	QP
5	0.21	0.02	9.57	23.35	32.94	53.14	-20.20	Average
6	0.21	0.02	9.57	39.72	49.31	63.14	-13.83	QP
7	0.27	0.01	9.58	18.49	28.08	51.07	-22.99	Average
8	0.27	0.01	9.58	34.96	44.55	61.07	-16.52	QP
9	0.30	0.01	9.58	17.50	27.09	50.37	-23.28	Average
10	0.30	0.01	9.58	32.22	41.81	60.37	-18.56	QP
11	0.34	0.01	9.58	11.73	21.32	49.09	-27.77	Average
12	0.34	0.01	9.58	27.80	37.39	59.09	-21.70	QP



6.2 Radiated Emissions (30MHz-1GHz)

Test Requirement:	47 CFR Part 15, Subpart B
Test Method:	ANSI C63.4
Frequency Range:	30MHz to 1GHz
Measurement Distance:	10m
Limit:	
30MHz -88MHz	29.5(dB μ V/m) quasi-peak
88MHz-216MHz	33.1(dB μ V/m) quasi-peak
216MHz-960MHz	35.6(dB μ V/m) quasi-peak
960MHz-1000MHz	43.5(dB μ V/m) quasi-peak
Detector:	Peak for pre-scan (120kHz resolution bandwidth) 30M to1000MHz

6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1015 mbar

Pretest these modes to find the worst case:

d: Telecom Idle + BT(Idle)+ WLAN(Idle) + playing MP4 (SD card) + earphone + battery + adapter

e: Telecom Idle + BT(Idle)+ WLAN(Idle) + camera(Front) + earphone + battery + adapter

f: Telecom Idle + BT(Idle)+ WLAN(Idle) + camera(Back) + earphone + battery + adapter

g: Transfer data between the EUT and the PC(write)

h: Transfer data between the EUT and the PC(read)


i: single play mode, keep EUT working normally without adapter and earphone.

The worst case for final test:

e: Telecom Idle + BT(Idle)+ WLAN(Idle) + camera(Front) + earphone + battery + adapter

g: Transfer data between the EUT and the PC(write)


6.2.2 Test Setup Diagram



6.2.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.

Mode:e; Polarization:Horizontal




Condition: 10m HORIZONTAL
 Job No. : 12987RG
 Test Mode: e

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	42.01	6.87	13.15	32.45	26.47	14.04	29.50	-15.46
2	54.26	6.28	12.43	32.43	27.85	14.13	29.50	-15.37
3	149.49	7.46	13.38	32.43	27.45	15.86	33.10	-17.24
4	438.66	8.57	15.90	32.31	27.83	19.99	35.60	-15.61
5	675.21	9.45	19.84	32.27	27.48	24.50	35.60	-11.10
6 pp	925.76	10.09	22.57	31.19	27.17	28.64	35.60	-6.96



Mode:e; Polarization:Vertical



Condition: 10m VERTICAL
Job No. : 12987RG
Test Mode: e

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	30.11	6.99	12.47	32.52	33.36	20.30	29.50	-9.20
2	43.81	6.69	13.00	32.45	32.62	19.86	29.50	-9.64
3	90.54	7.48	8.73	32.52	32.59	16.28	33.10	-16.82
4	148.44	7.46	13.31	32.43	27.94	16.28	33.10	-16.82
5	373.31	8.38	14.35	32.34	28.60	18.99	35.60	-16.61
6	549.02	8.96	17.71	32.28	28.81	23.20	35.60	-12.40

6.3 Radiated Emissions (above 1GHz)

Test Requirement: 47 CFR Part 15, Subpart B
 Test Method: ANSI C63.4
 Frequency Range: Above 1GHz
 Measurement Distance: 3m
 Limit:
 Above 1GHz 74(dB μ V/m) peak, 54(dB μ V/m) average
 Detector: Peak for pre-scan (1000kHz resolution bandwidth) 1000M to18000MHz

6.3.1 E.U.T. Operation

Operating Environment:

Temperature: 20.2 °C Humidity: 44.5 % RH Atmospheric Pressure: 1015 mbar

Pretest these modes to find the worst case:
 d: Telecom Idle + BT(Idle)+ WLAN(Idle) + playing MP4 (SD card) + earphone + battery + adapter

e: Telecom Idle + BT(Idle)+ WLAN(Idle) + camera(Front) + earphone + battery + adapter

f: Telecom Idle + BT(Idle)+ WLAN(Idle) + camera(Back) + earphone + battery + adapter


g: Transfer data between the EUT and the PC(write)

h: Transfer data between the EUT and the PC(read)

i: single play mode, keep EUT working normally without adapter and earphone.

The worst case for final test: g: Transfer data between the EUT and the PC(write)

6.3.2 Test Setup Diagram




6.3.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.



Mode:g; Polarization:Horizontal




Condition: 3m HORIZONTAL
Job No : 12987RG
Mode : g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1799.839	5.11	27.07	41.59	51.40	41.99	74.00	-32.01	Peak
2	2199.817	5.21	28.48	41.79	53.76	45.66	74.00	-28.34	Peak
3 pp	5302.233	8.56	34.44	42.21	48.72	49.51	74.00	-24.49	Peak



Mode:g; Polarization:Vertical



Condition: 3m VERTICAL
Job No : 12987RG
Mode : g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1796.617	5.12	27.05	41.59	56.74	47.32	74.00	-26.68	Peak
2	pp 2397.385	5.48	29.10	41.88	58.81	51.51	74.00	-22.49	Peak
3	5525.306	8.94	34.42	42.01	48.33	49.68	74.00	-24.32	Peak

7.2 Radiated Emissions (30MHz-1GHz) Test Setup



7.3 EUT Constructional Details (EUT Photos)

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1712012987CR.

- End of the Report -