



**TEST REPORT CONCERNING THE COMPLIANCE OF
AN INDUCTIVE PROXIMITY CARD READER,
BRAND INTEGRATED ENGINEERING, TYPE
PX007Z/XXSNR, WITH 47 CFR PART 15 (2001-5-24).**

FCC listed : 90828
Industry Canada : IC3501

TNO Electronic Products & Services (EPS) B.V.
P.O. Box 15
9822 ZG Niekerk (NL)
Smidshornerweg 18
9822 TL Niekerk (NL)

Telephone: +31 594 505005
Telefax: +31 594 504804

E-mail: info@eps.tno.nl



Test specification(s): 47 CFR Part 15 (2001-5-24)
Description of EUT: Inductive proximity card reader
Manufacturer: Integrated Engineering B.V.
Brand mark: Integrated Engineering
Type: PX007Z/XXSNR
FCC ID: P4EI-MSNRPOX-02

MEASUREMENT/TECHNICAL REPORT

INTEGRATED ENGINEERING B.V.

Model : PX007Z/XXSNR

FCC ID: P4EI-MSNRPOX-02

December 20, 2001

This report concerns:	Original grant/certification	Class 2 change	Verification
Equipment type:	Inductive proximity card reader operating on 13.56 MHz		
Deferred grant requested per 47 CFR 0.457(d)(1)(ii) ?	Yes	No	n.a.
Report prepared by:	Name	: P.A.J.M. Robben, B.Sc.E.E.	
	Company name	: TNO Electronic Products & Services (EPS) B.V.	
	Address	: Smidshornerweg 18	
	Postal code/city	: 9822 ZG Niekerk	
	Mailing address	: P.O. Box 15	
	Postal code/city	: 9822 TL Niekerk	
	Country	: The Netherlands	
	Telephone number	: + 31 594 505 005	
	Telefax number	: + 31 594 504 804	
	E-mail	: info@eps.tno.nl	

The data taken for this test and report herein was done in accordance with 47 CFR Part 15 and the measurement procedures of ANSI C63.4-1992. TNO Certification EPS at Niekerk, The Netherlands, certifies that the data is accurate and contains a true representation of the emission profile of the Equipment Under Test (EUT) on the date of the test as noted in the test report. I have reviewed the test report and find it to be an accurate description of the test(s) performed and the EUT so tested.

Date: December 20, 2001

Signature:

O.H. Hoektra
TNO Certification EPS



Test specification(s): 47 CFR Part 15 (2001-5-24)
Description of EUT: Inductive proximity card reader
Manufacturer: Integrated Engineering B.V.
Brand mark: Integrated Engineering
Type: PX007Z/XXSNR
FCC ID: P4EI-MSNRPOX-02

Description of test item

Test item : Inductive proximity card reader operating on 13.56 MHz
Manufacturer : Integrated Engineering B.V.
Brand : Integrated Engineering
Type : PX007Z/XXSNR
Serial number : 0050-104
Revision : n.a.
Receipt number : 1
Receipt date : August 22, 2001

Applicant information

Applicant's representative : Mr. R. Holslag
Company : Integrated Engineering B.V.
Address : Paasheuvelweg 20
Postal code : 1105 BJ
City : Amsterdam
PO-box : n.a.
Postal code : n.a.
City : n.a.
Country : The Netherlands
Telephone number : +31 20 462 0700
Telefax number : +31 20 462 0758
Order number : n.a.

Test(s) performed

Location : Niekkerk
Test(s) started : September 6, 2001
Test(s) completed : September 19, 2001
Purpose of test(s) : Compliance with standard
Test specification(s) : 47 CFR Part 15 (2001-5-24)

Test engineer : T.E.T. Koning 

Project leader : P. de Beer 

Report written by : P.A.J.M. Robben, B.Sc.E.E. 

Report approved by : O.H. Hoekstra 

Report date : December 20, 2001

This report is in conformity with NEN-EN-ISO/IEC 17025: 2000.

This report shall not be reproduced, except in full, without the written permission of TNO Electronic Products & Services (EPS) B.V.
The test results relate only to the item(s) tested.



Test specification(s): 47 CFR Part 15 (2001-5-24)
Description of EUT: Inductive proximity card reader
Manufacturer: Integrated Engineering B.V.
Brand mark: Integrated Engineering
Type: PX007Z/XXSNR
FCC ID: P4EI-MSNRPOX-02

Table of contents

1	General information.....	5
1.1	Product description.....	5
1.1.1	Introduction.....	5
1.1.2	Choice of operating frequency.....	5
1.1.3	Operating principles.....	5
1.2	Related submittal(s) and/or Grant(s).....	5
1.3	Tested system details.....	5
1.4	Test methodology.....	6
1.5	Test facility.....	6
1.6	Product labelling.....	6
2	System test configuration.....	7
2.1	Justification.....	7
2.2	EUT mode of operation.....	7
2.3	Special accessories.....	7
2.4	Equipment modifications.....	7
2.5	Configuration of the tested system.....	7
2.6	Block diagram of the EUT.....	8
2.7	Schematics of the EUT.....	8
2.8	Partlist of the EUT.....	8
3	Radiated emission data.....	9
3.1	Radiated field strength measurements (frequency range of 30-1000 MHz, E-field).....	9
3.2	Radiated field strength measurements (frequency range of 0.009-30 MHz, H-field).....	10
4	Conducted emission data.....	11
5	Frequency tolerance of the carrier signal.....	12
6	List of utilized test equipment.....	13



Test specification(s): 47 CFR Part 15 (2001-5-24)
Description of EUT: Inductive proximity card reader
Manufacturer: Integrated Engineering B.V.
Brand mark: Integrated Engineering
Type: PX007Z/XXSNR
FCC ID: P4EI-MSNRPOX-02

1 General information

1.1 Product description

1.1.1 Introduction.

The inductive proximity card reader, brand Integrated Engineering, type PX007Z/XXSNR, is designed to function as a security measure in order to prevent unauthorized access to buildings (or parts of buildings). A person who wants to enter a secure building, or a secure area in the building, must have a key card in which a valid access code is stored. When the key card is in close proximity of the card reader the code will be transmitted and validated by a computer system which is connected to the reader itself. Access will be granted to the secure area if it is determined that a valid code has been transmitted.

The XX in the type number indicates the technology used for code recognition. The XX may be replaced by either MF (Mifare technology) or IC (I-code technology).

1.1.2 Choice of operating frequency.

The operating frequency of the inductive proximity card reader, brand Integrated Engineering, type PX007Z/XXSNR, is 13.56 MHz (continuous carrier).

1.1.3 Operating principles.

The inductive proximity card reader is a DC powered system with an integral antenna. The inductive proximity card reader generates a RF-field at a frequency of 13.56 MHz (continuous carrier) which activates the electronics in the key card. The activated key card then sends an identification code to the inductive proximity card reader by modulating the RF-field. The modulation of the 13.56 MHz RF-field can be detected and then the code is demodulated by the inductive proximity card reader. The code is then transmitted by a wired connection to the computer system for validation.

1.2 Related submittal(s) and/or Grant(s)

Not applicable.

1.3 Tested system details

Details and an overview of the system and all of its components, as it has been tested, may be found in table 1 below. FCC ID's are stated in this overview where applicable. The EUT is listed in the first row of table 1.

Description	Manufacturer	Type number	Serial number	FCC ID	Cable descriptions
Inductive cardreader	Integrated Engineering B.V.	PX007Z/XXSNR	0050-104	P4EI-MSNRPOX-02	Shielded data/DC power cable.
AC/DC power adapter 120 VAC/60 Hz/15W to +9 VDC/1 Amps	Sceptre	PD9010APL05	n.a.	n.a. (DoC)	Shielded DC power cable to EUT. Unshielded power cord to AC mains.

Table 1 - Tested system details overview.



Test specification(s):	47 CFR Part 15 (2001-5-24)
Description of EUT:	Inductive proximity card reader
Manufacturer:	Integrated Engineering B.V.
Brand mark:	Integrated Engineering
Type:	PX007Z/XXSNR
FCC ID:	P4EI-MSNRPOX-02

1.4 Test methodology

The test methodology used is based on the requirements of 47 CFR Part 15, issue of May 24, 2001, sections 15.207, 15.209 and 15.225.

The test methods which have been used are based on ANSI C63.4: 1992.

Radiated emission tests above 30 MHz were performed at a measurement distance of 3 meters. Below 30 MHz the radiated emission tests were carried out at measurement distances of 3 and 10 meters. The test results regarding the radiated emission tests on frequencies below 30 MHz have been extrapolated in order to determine the field strength of the measured values at measurement distances of 30 and 300 meters (as required by 47 CFR Part 15).

The bandwidth of the receivers are switching automatically to the right bandwidth in accordance with CISPR 16. This is implemented in the receiver. The antenna factors are programmed in the test receiver. The receiver automatically calculates the appropriate correction factor for the utilized antenna and also the appropriate antenna factor for the cable loss. The total correction is automatically added to the measured value.

1.5 Test facility

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at TNO Certification EPS, located in Niekerk, 9822 TL Smidshornerweg 18, The Netherlands, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per October 23, 2000, with reference 31040/SIT.

The description of the test facilities has been filed at the Office of the Federal Communications Commission. The facility has been added to the list of those laboratories who perform these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at <http://www.fcc.gov>.

1.6 Product labelling

In accordance with 47 CFR Part 15.19 (a)(3) the following text shall be placed on a label which is attached to the EUT:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The FCC ID of the EUT must be placed on a label which is attached to the EUT.

For further details about the labelling requirements (size, legibility, etc.) as set by the Federal Communications Commission see 47 CFR Part 15.19 (a)(3), 47 CFR Part 15.19 (b)(2), 47 CFR Part 15.19 (b)(4), 47 CFR Part 2.925 and 47 CFR Part 2.926.



Test specification(s): 47 CFR Part 15 (2001-5-24)
Description of EUT: Inductive proximity card reader
Manufacturer: Integrated Engineering B.V.
Brand mark: Integrated Engineering
Type: PX007Z/XXSNR
FCC ID: P4EI-MSNRPOX-02

2 System test configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it). During all tests the EUT was set up to function in accordance with the manufacturer's instructions.

The justification and manipulation of cables and equipment in order to simulate a worst case behaviour of the test setup has been carried out as prescribed in ANSI C63.4: 1992.

2.2 EUT mode of operation

Radiated and conducted emission measurements were carried out when the system was active and was generating a continuous transmitting signal.

2.3 Special accessories

No special accessories are used and/or needed to achieve compliance with the appropriate sections of 47 CFR Part 15.

2.4 Equipment modifications

No modifications have been made to the equipment in order to achieve compliance with the appropriate sections of 47 CFR Part 15.

2.5 Configuration of the tested system

Unit title	:	Inductive proximity card reader
Model number	:	PX007Z/XXSNR
Part number	:	n.a.
FCC ID	:	P4EI-MSNRPOX-02
Frequency range	:	13.56 MHz (continuous carrier)
Description/details	:	see section 1.1 of this test report
Power supply	:	4.75 - 12.25 Volts DC
Clock Oscillator(s)	:	13.56 MHz
Cabinet & Screening	:	Plastic
Interface Cable(s)	:	Shielded data/DC power cable
Method of screening	:	Not applicable
Method of grounding	:	Not applicable
Operating configuration	:	see section 1.3 of this test report



Test specification(s):	47 CFR Part 15 (2001-5-24)
Description of EUT:	Inductive proximity card reader
Manufacturer:	Integrated Engineering B.V.
Brand mark:	Integrated Engineering
Type:	PX007Z/XXSNR
FCC ID:	P4EI-MSNRPOX-02

2.6 Block diagram of the EUT

The block diagram is available in the technical documentation package as an addendum to this test report.

2.7 Schematics of the EUT

The schematics are available in the technical documentation package as an addendum to this test report.

2.8 Partlist of the EUT

The partlist is available in the technical documentation package as an addendum to this test report.



Test specification(s): 47 CFR Part 15 (2001-5-24)
Description of EUT: Inductive proximity card reader
Manufacturer: Integrated Engineering B.V.
Brand mark: Integrated Engineering
Type: PX007Z/XXSNR
FCC ID: P4EI-MSNRPOX-02

3 Radiated emission data

3.1 Radiated field strength measurements (frequency range of 30-1000 MHz, E-field)

Frequency (MHz)	Measurement results dB(μ V)/m @ 3 metres Quasi-peak		Limits dB(μ V)/m @ 3 metres Quasi-peak	Margin (dB) Quasi-peak		Result
	Vertical	Horizontal		Vertical	Horizontal	
30.0 - 88.0	<10.0	<10.0	40.0	>-30.0	>-30.0	PASS
88.0 - 216.0	<15.0	<15.0	43.5	>-28.5	>-28.5	PASS
216.0 - 960.0	<20.0	<20.0	46.0	>-26.0	>-26.0	PASS
960.0 - 1000.0	<25.0	<25.0	54.0	>-29.0	>-29.0	PASS

Table 2

The results of the radiated emission tests, carried out in accordance with 47 CFR Part 15, sections 15.209 and 15.225 (a), with the EUT operating in continuous transmit mode on 13.56 MHz, are depicted in table 2.

Note: Field strength values of radiated emissions at frequencies not listed in table 2 are more than 20 dB below the applicable limit.

Test engineer

Signature

Name : T.E.T. Koning

Date : December 20, 2001



Test specification(s): 47 CFR Part 15 (2001-5-24)
Description of EUT: Inductive proximity card reader
Manufacturer: Integrated Engineering B.V.
Brand mark: Integrated Engineering
Type: PX007Z/XXSNR
FCC ID: P4EI-MSNRPOX-02

3.2 Radiated field strength measurements (frequency range of 0.009-30 MHz, H-field)

Frequency (MHz)	Measurement results dB μ V Quasi-peak	Antenna factor	Cable loss	Measurement results dB(μ V)/m Quasi-peak (calculated)	Limits Part 15.209 dB(μ V)/m (calculated)
	10 meters	dB	dB		
0.009 - 0.490	<10.0	19	1	<10.0	48.5 - 13.8 (300 m)
0.490 - 1.705	<10.0	19	1	<10.0	33.8 - 22.9 (30 m)
1.705 - 13.553	<10.0	19	1	<10.0	29.5 (30 m)
13.563	28.1	19	1	<25.0	80.0 (30 m)
13.567 - 30.00	<10.0	19	1	<10.0	29.5 (30 m)

Table 3

The results of the radiated emission tests, carried out in accordance with 47 CFR Part 15, sections 15.209, 15.225 (a) and 15.225 (b), with the EUT operating in continuous transmit mode on 13.56 MHz, are depicted in table 3.

- Notes:**
- Frequency range: 9-90 kHz Average detector used during measurements
110-490 kHz Average detector used during measurements
 - The radiated field strengths were measured at a distance of 10 meters.
Measured field strengths at a distance of 10 meters were already below the limit of 30/300 meters
 - Field strength values of radiated emissions at frequencies not listed in table 3 are more than 20 dB below the applicable limit.

Test engineer

Signature

Name : T.E.T. Koning

Date : December 20, 2001



Test specification(s): 47 CFR Part 15 (2001-5-24)
Description of EUT: Inductive proximity card reader
Manufacturer: Integrated Engineering B.V.
Brand mark: Integrated Engineering
Type: PX007Z/XXSNR
FCC ID: P4EI-MSNRPOX-02

4 Conducted emission data

Frequency (MHz)	Measurement results dB(μ V) Line 1	Measurement results dB(μ V) Line 2	Limits dB(μ V)	Margin (dB) Line 1	Margin (dB) Line 2	Result
	QP	QP	QP	QP	QP	
0.4500	18.0	14.2	48.0	-30.0	-33.8	PASS
13.564	37.2	40.8	48.0	-10.8	-7.2	PASS

Table 4

The results of the conducted emission tests, carried out in accordance with 47 CFR Part 15, section 15.207, at the 110 Volts AC mains connection terminals of the AC/DC adapter connected to the EUT and with the EUT operating in continuous transmit mode on 13.56 MHz, are depicted in table 4.

Note: During the measurement it was taken into account that the main operating frequency of 13.56 MHz of the EUT could be present on the 110 Volts AC mains connection terminals. The possible occurrence of this frequency of 13.56 MHz and its harmonics, throughout the range of 13.56 MHz to 30 MHz, was checked during the measurement. The conducted emissions on frequencies which are not listed in table 4 were found to be at least 20 dB below the limits.

Test engineer

Signature

Name : T.E.T. Koning

Date : December 20, 2001

5 Frequency tolerance of the carrier signal

Temperature variation (°C)	Measurement results (MHz)	Limits (MHz)
-20 to +50	13.5620 - 13.5637	13.5613 - 13.5640

Table 5

The results of the measurements regarding the frequency tolerance of the carrier signal, carried out in accordance with 47 CFR Part 15, section 15.225 (c), with the EUT operating in continuous transmit mode on 13.56 MHz, are depicted in table 5. The measurements were carried out with the AC mains input voltage of the AC/DC adapter set to 110 Volts AC, which was determined to be the nominal value, while the ambient temperature was varied between -20 and +50 °C.

The nominal frequency was determined to be 13.5627 MHz. The limits in table 5 were determined by taking the maximum allowable tolerance of $\pm 0.01\%$ into account, with respect to the nominal frequency, as set forth in 47 CFR Part 15, section 15.225 (c).

Input voltage variation (%)	Measurement results (MHz)	Limits (MHz)
85 - 115	13.5623 - 13.5632	13.5613 - 13.5640

Table 6

The results of the measurements regarding the frequency tolerance of the carrier signal, carried out in accordance with 47 CFR Part 15, section 15.225 (c), with the EUT operating in continuous transmit mode on 13.56 MHz, are depicted in table 6. The measurements were carried out at a nominal ambient temperature of +20 °C, while the AC mains input voltage of the AC/DC adapter was varied between 85% to 115% of the nominal AC mains input voltage of 110 Volts AC.

The nominal frequency was determined to be 13.5627 MHz. The limits in table 6 were determined by taking the maximum allowable tolerance of $\pm 0.01\%$ into account, with respect to the nominal frequency, as set forth in 47 CFR Part 15, section 15.225 (c).

Test engineer

Signature



Name

: T.E.T. Koning

Date

: December 20, 2001



Test specification(s): 47 CFR Part 15 (2001-5-24)
Description of EUT: Inductive proximity card reader
Manufacturer: Integrated Engineering B.V.
Brand mark: Integrated Engineering
Type: PX007Z/XXSNR
FCC ID: P4EI-MSNRPOX-02

6 List of utilized test equipment

Inventory number	Description	Brand	Type
12471	Biconical antenna 20MHz-200MHz	EATON	94455-1
12473	Log-per antenna 200-1000MHz	EATON	96005
12476	Antenna mast	EMCO	TR3
12477	Antenna mast 1-4 mtr	Poelstra	--
12482	Loop antenna	EMCO	6507
12483	Guidehorn	EMCO	3115
12484	Guidehorn	EMCO	3115
12488	Guidehorn 18 - 26.5 GHz	EMCO	RA42-K-F-4B-C
12533	Signalgenerator	MARCONI	2032
12559	Digital storage oscilloscope	Le Croy	9310M
12561	DC Power Supply 20A/70V	DELTA	SM7020D
12567	Plotter	HP	7440A
12605	calibrated dipole 28MHz-1GHz	Emco	3121c
12608	HF milliwattmeter	Hewlett Packard	HP435a
12609	Power sensor 10MHz-18GHz	Hewlett Packard	HP8481A
12636	Polyester chamber	Polyforce	--
12640	Temperature chamber	Heraeus	VEM03/500
13664	Spectrum analyzer	HP	HP8593E
13078	Preamplifier 0.1 GHz - 12 GHz	Miteq	AMF-3D-001120-35-14p
13452	Digital multi meter	HP	34401A
13526	Signalgenerator 20 GHz	Hewlett & Packard	83620A
13594	Preamplifier 10 GHz - 25 GHz	Miteq	AMF-6D-100250-10p
13886	Open Area testsite	Comtest	--
14051	Anechoic room	Comtest	--
14450	2.4 GHz bandrejectfilter	BSC	XN-1783
15633	Biconilog Testantenna	Chase	CBL 6111B
15667	Measuring receiver	R&S	ESCS 30
99045	DC Power Supply 3A/30V	DELTA	E030/3
99055	Non-conducting support	NMi	--
99061	Non-conducting support 150cm	NMi	--
99068	Detector N-F/BNC-F	Radiall	R451576000
99069	Cable 5m RG214	NMi	--
99071	Cable 10m RG214	NMi	--
99076	Bandpassfilter 4 - 10 GHz	Reactel	7AS-7G-6G-511
99077	Regulating trafo	RFT	LTS006
99112	Tripod	Chase	--
99136	Bandpassfilter 10 - 26.5 GHz	Reactel	9HS-10G/26.5G-S11