

Fujian Flaircomm Microelectronics, Inc.

Bluetooth module


Main Model: FLC-BTM805

Serial Model: See P5

November 28, 2012




Report No.: 12020792-FCC-R1

(This report supersedes NONE)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

		
Alan Lv Compliance Engineer	Alex Liu Technical Manager	

This test report may be reproduced in full only.
Test result presented in this test report is applicable to the representative sample only.

RF Test Report

To: FCC Part 15.247: 2012, ANSI C63.4 :2009

SIEMIC, INC.
Accessing global markets



Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to [testing](#) and [certification](#), SIEMIC provides initial design reviews and [compliance management](#) through out a project. Our extensive experience with [China](#), [Asia Pacific](#), [North America](#), [European](#), and [international](#) compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the [global markets](#).

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC , RF/Wireless , Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless , Telecom
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom , Safety
Hong Kong	OFTA , NIST	RF/Wireless ,Telecom
Australia	NATA, NIST	EMC, RF, Telecom , Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF , Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC , RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom , Safety

Accreditations for Product Certifications

Country/Region	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC , RF , Telecom
Canada	IC FCB , NIST	EMC , RF , Telecom
Singapore	iDA, NIST	EMC , RF , Telecom
EU	NB	EMC & R&TTE Directive
Japan	MIC, (RCB 208)	RF , Telecom
Hong Kong	OFTA (US002)	RF , Telecom



SIEMIC, Inc.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009

Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 3 of 88
www.siemic.com.cn

This page has been left blank intentionally.

CONTENTS

1 EXECUTIVE SUMMARY & EUT INFORMATION5

2 TECHNICAL DETAILS6

3 MODIFICATION.....7

4 TEST SUMMARY.....8

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS9

ANNEX A. TEST INSTRUMENT & METHOD71

ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS77

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....81

ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST85

ANNEX E. DECLARATION OF SIMILARITY86

1 EXECUTIVE SUMMARY & EUT INFORMATION

The purpose of this test programme was to demonstrate compliance of the Fujian Flaircomm Microelectronics, Inc., Bluetooth module and model: FLC-BTM805 against the current Stipulated Standards. The Bluetooth module has demonstrated compliance with the FCC Part 15.247: 2012, ANSI C63.4: 2009.

EUT Information

EUT
Description : **Bluetooth module**
Main Model : **FLC-BTM805**
Serial Model : **FLC-BTM805IL2A; FLC-BTM805CL2A; FLC-BTM805VL2A;**
FLC-BTM805IL2B; FLC-BTM805CL2B; FLC-BTM805VL2B
Antenna Gain : **0.5 dBi**
Input Power : **Voltage Range: 2.3 ~ 4.8V DC**
Temperature : **-40° C to +85° C for A and I grade**
-20° C to +70° C for V and C grade
Classification
Per Stipulated : **FCC Part 15.247: 2012, ANSI C63.4: 2009**
Test Standard

NOTE: in this report, we choice the model FLC-BTM805 to test, and the differences of them please refer to the Annex E. DECLARATION OF SIMILARITY.

2 TECHNICAL DETAILS

Purpose	Compliance testing of Bluetooth module with stipulated standard
Applicant / Client	Fujian Flaircomm Microelectronics, Inc. 7F, Guomai Building, 116 East JiangBin Ave, Fuzhou, Fujian, China
Manufacturer	Fujian Flaircomm Microelectronics, Inc. 7F, Guomai Building, 116 East JiangBin Ave, Fuzhou, Fujian, China
Laboratory performing the tests	SIEMIC Nanjing (China) Laboratories NO.2-1, Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel: +86(25)86730128/86730129 Fax: +86(25)86730127 Email: info@siemic.com
Test report reference number	12020792-FCC-R1
Date EUT received	September 20, 2012
Standard applied	FCC Part 15.247: 2012, ANSI C63.4: 2009
Dates of test (from – to)	September 25 and October 11, 2012
No of Units	#1
Equipment Category	DSS
Trade Name	N/A
RF Operating Frequency (ies)	2402-2480MHz
Number of Channels	79 CH
Modulation	GFSK, $\pi/4$-DQPSK, 8DPSK
FCC ID	P4IBTM805



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009

Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 7 of 88
www.siemic.com.cn

3 MODIFICATION

NONE

4 TEST SUMMARY

The product was tested in accordance with the following specifications.
All testing has been performed according to below product classification:

Spread Spectrum System/Device

Test Results Summary

Test Standard	Description	Product Class	Pass / Fail
§15.203	Antenna Requirement	See Above	Pass
§15.207(a)	AC Line Conducted Emissions	See Above	Pass
§15.205, §15.209, §15.247(d)	Radiated Emissions	See Above	Pass
§15.247(a)(1)	20 dB Bandwidth	See Above	Pass
§15.247(a)(1)	Channel Separation	See Above	Pass
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	See Above	Pass
§15.247(a)(1)(iii)	Quantity of Hopping Channel	See Above	Pass
§15.247(b)(1)	Peak Output Power	See Above	Pass
§15.247(d)	Band Edge	See Above	Pass

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 §15.203 – Antenna Requirement

Standard Requirement:

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

EUT antenna is integrated on PCB; It is in accordance to section 15.203(a); please refer to the internal photos.

Test Result: Pass

5.2 §15.207 (a) – AC Line Conducted Emissions

Standard Requirement:

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.


Procedures:

- All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
- A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is ±3.5dB.
- Environmental Conditions

Temperature	22°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
- Test date : October 11, 2012
Tested By : Alan Lv

Test Result: Pass

Test Mode 1:	GFSK Transmitting
---------------------	--------------------------




Test Data

Phase Line Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Factors (dB)
2.07	42.06	56.00	-13.94	31.64	46.00	-14.36	10.20
2.17	41.26	56.00	-14.74	31.42	46.00	-14.58	10.20
2.32	39.51	56.00	-16.49	30.17	46.00	-15.83	10.20
2.69	39.82	56.00	-16.18	30.73	46.00	-15.27	10.20
3.15	38.25	56.00	-17.75	29.28	46.00	-16.72	10.25
1.64	40.54	56.00	-15.46	30.77	46.00	-15.23	10.19

Test Mode:	GFSK Transmitting
-------------------	--------------------------




Test Data

Phase Neutral Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Factors (dB)
4.29	32.54	56.00	-23.46	24.47	46.00	-21.53	10.46
3.21	32.62	56.00	-23.38	27.62	46.00	-18.38	10.27
3.56	32.52	56.00	-23.48	26.13	46.00	-19.87	10.37
2.34	33.50	56.00	-22.50	28.46	46.00	-17.54	10.20
2.72	33.46	56.00	-22.54	28.51	46.00	-17.49	10.20
4.25	32.82	56.00	-23.18	24.93	46.00	-21.07	10.46

Test Mode:	π /4-DQPSK Transmitting
-------------------	---




Test Data

Phase Line Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
2.18	40.54	56.00	-15.46	30.43	46.00	-15.57	10.20
2.77	39.41	56.00	-16.59	29.94	46.00	-16.06	10.20
2.05	39.44	56.00	-16.56	29.66	46.00	-16.34	10.20
1.60	40.41	56.00	-15.59	30.74	46.00	-15.26	10.18
2.07	40.65	56.00	-15.35	30.45	46.00	-15.55	10.20
1.56	39.56	56.00	-16.44	29.11	46.00	-16.89	10.18

Test Mode:	π /4-DQPSK Transmitting
-------------------	---




Test Data

Phase Neutral Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
4.15	32.47	56.00	-23.53	24.95	46.00	-21.05	10.48
3.73	31.63	56.00	-24.37	25.37	46.00	-20.63	10.43
1.89	34.09	56.00	-21.91	28.47	46.00	-17.53	10.20
2.93	34.02	56.00	-21.98	28.41	46.00	-17.59	10.20
3.54	32.56	56.00	-23.44	26.21	46.00	-19.79	10.37
3.82	31.66	56.00	-24.34	24.63	46.00	-21.37	10.45

Test Mode:	8DPSK Transmitting
-------------------	---------------------------




Test Data

Phase Line Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Factors (dB)
4.13	32.73	56.00	-23.27	25.36	46.00	-20.64	10.49
3.99	32.22	56.00	-23.78	24.91	46.00	-21.09	10.51
3.81	32.10	56.00	-23.90	25.06	46.00	-20.94	10.45
2.95	33.61	56.00	-22.39	28.09	46.00	-17.91	10.20
3.98	32.31	56.00	-23.69	24.92	46.00	-21.08	10.50
3.69	31.68	56.00	-24.32	25.00	46.00	-21.00	10.41

Test Mode:	8DPSK Transmitting
-------------------	---------------------------



Test Data

Phase Neutral Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
2.12	33.53	56.00	-22.47	28.03	46.00	-17.97	10.20
1.80	33.48	56.00	-22.52	28.87	46.00	-17.13	10.19
3.59	32.40	56.00	-23.60	26.01	46.00	-19.99	10.38
4.57	29.40	56.00	-26.60	20.81	46.00	-25.19	10.41
3.48	35.73	56.00	-20.27	26.56	46.00	-19.44	10.35
3.76	31.85	56.00	-24.15	25.18	46.00	-20.82	10.44

5.3 §15.209, §15.205 & §15.247(d) - Spurious Emissions

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (3m & 10m) & 1GHz above (3m) is +5.6/-4.5dB.
4. Environmental Conditions

Temperature	22°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
5. Test date : October 11, 2012
Tested By : Alan Lv


Standard Requirement:

The emissions from the Low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges.

Test Result: Pass

Test Mode:	GFSK Transmitting
-------------------	--------------------------

Below 1GHz



Test Data

@3m

Frequency (MHz)	Quasi Peak (dBµV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBµV/m)	Margin (dB)
167.38	35.43	248.00	H	181.00	-32.42	43.50	-8.07
239.96	40.40	221.00	H	100.00	-33.05	46.00	-5.60
216.38	38.53	238.00	H	148.00	-33.59	46.00	-7.47
33.25	26.59	187.00	V	102.00	-22.27	40.00	-13.41
335.99	37.33	329.00	H	107.00	-30.95	46.00	-8.67
288.65	35.09	231.00	H	112.00	-31.52	46.00	-10.91

Test Mode:	GFSK Transmitting
-------------------	--------------------------

Above 1 GHz

Note: Other Bluetooth modes were verified; only the result of worst case DH5 mode was presented.

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
4804	75.26	PK	59	110	V	32.7	12.8	57	63.76	74	-10.24
4804	51.42	AV	59	110	V	32.7	12.8	57	39.92	54	-14.08
2387	70.25	PK	254	120	V	30.1	7.2	57	50.55	74	-23.45
2387	52.16	AV	254	120	V	30.1	7.2	57	32.46	54	-21.54
4804	75.46	PK	137	140	H	32.7	12.8	57	63.96	74	-10.04
4804	52.72	AV	137	140	H	32.7	12.8	57	41.22	54	-12.78
2388	68.17	PK	243	120	H	30.1	7.2	57	48.47	74	-25.53
2388	52.46	AV	243	120	H	30.1	7.2	57	32.76	54	-21.24

Middle Channel (2441 MHz)


Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
4882	74.19	PK	147	110	V	32.8	12.8	57	62.79	74	-11.21
4882	52.46	AV	147	110	V	32.8	12.8	57	41.06	54	-12.94
7326	66.52	PK	215	130	V	35.6	15.9	58	60.02	74	-13.98
7326	49.35	AV	215	130	V	35.6	15.9	58	42.85	54	-11.15
4882	73.05	PK	163	150	H	32.8	12.8	57	61.65	74	-12.35
4882	51.72	AV	163	150	H	32.8	12.8	57	40.32	54	-13.68
7326	68.36	PK	85	120	H	35.6	15.9	58	61.86	74	-12.14
7326	49.47	AV	85	120	H	35.6	15.9	58	42.97	54	-11.03

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
4960	74.18	PK	140	120	V	32.7	12.8	57	62.68	74	-11.32
4960	50.36	AV	140	120	V	32.7	12.8	57	38.86	54	-15.14
2485	71.49	PK	311	110	V	30.1	10.2	57	54.75	74	-19.25
2485	50.41	AV	311	110	V	30.1	10.2	57	33.67	54	-20.33
4960	74.59	PK	124	130	H	32.7	12.8	57	63.09	74	-10.91
4960	50.06	AV	124	130	H	32.7	12.8	57	38.56	54	-15.44
2488	69.36	PK	26	120	H	30.1	7.2	57	49.66	74	-24.34
2488	51.49	AV	26	120	H	30.1	7.2	57	31.79	54	-22.21

Test Mode:	π /4-DQPSK Transmitting
-------------------	---

Below 1GHz



Test Data

@3m

Frequency (MHz)	Quasi Peak (dB μ V/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dB μ V/m)	Margin (dB)
167.85	37.04	92.00	H	170.00	-32.45	43.50	-6.46
240.00	40.24	224.00	H	126.00	-33.05	46.00	-5.76
216.41	37.63	230.00	H	158.00	-33.59	46.00	-8.37
62.18	26.76	184.00	H	309.00	-37.23	40.00	-13.24
336.00	37.33	327.00	H	106.00	-30.95	46.00	-8.67
432.85	35.16	188.00	V	115.00	-29.19	46.00	-10.84

Test Mode:	$\pi/4$-DQPSK Transmitting
-------------------	--

Above 1 GHz

Note: Other Bluetooth modes were verified; only the result of worst case 2DH5 mode was presented.

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4804	72.42	PK	117	110	V	32.7	12.8	57	60.92	74	-13.08
4804	51.52	AV	117	110	V	32.7	12.8	57	40.02	54	-13.98
2387	71.25	PK	352	120	V	30.1	7.2	57	51.55	74	-22.45
2387	50.63	AV	352	120	V	30.1	7.2	57	30.93	54	-23.07
4804	72.47	PK	153	140	H	32.7	12.8	57	60.97	74	-13.03
4804	51.26	AV	153	140	H	32.7	12.8	57	39.76	54	-14.24
2389	68.42	PK	52	120	H	30.1	7.2	57	48.72	74	-25.28
2388	50.47	AV	52	120	H	30.1	7.2	57	30.77	54	-23.23

Middle Channel (2441 MHz)


Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4882	73.05	PK	185	110	V	32.8	12.8	57	61.65	74	-12.35
4882	50.46	AV	185	110	V	32.8	12.8	57	39.06	54	-14.94
7326	68.52	PK	244	130	V	35.6	15.9	58	62.02	74	-11.98
7326	47.56	AV	244	130	V	35.6	15.9	58	41.06	54	-12.94
4882	73.47	PK	163	150	H	32.8	12.8	57	62.07	74	-11.93
4882	50.16	AV	163	150	H	32.8	12.8	57	38.76	54	-15.24
7326	68.85	PK	175	120	H	35.6	15.9	58	62.35	74	-11.65
7326	47.56	AV	175	120	H	35.6	15.9	58	41.06	54	-12.94

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4960	72.48	PK	132	110	V	32.7	12.8	57	60.98	74	-13.02
4960	50.46	AV	132	110	V	32.7	12.8	57	38.96	54	-15.04
2488	71.89	PK	171	130	V	30.1	10.2	57	55.15	74	-18.85
2485	50.08	AV	171	130	V	30.1	10.2	57	33.34	54	-20.66
4960	71.48	PK	46	120	H	32.7	12.8	57	59.98	74	-14.02
4960	51.46	AV	46	120	H	32.7	12.8	57	39.96	54	-14.04
2488	68.44	PK	321	110	H	30.1	7.2	57	48.74	74	-25.26
2485	50.36	AV	321	110	H	30.1	7.2	57	30.66	54	-23.34

Test Mode:	8DPSK Transmitting
-------------------	---------------------------

Below 1GHz



Test Data

@3m

Frequency (MHz)	Quasi Peak (dBµV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBµV/m)	Margin (dB)
240.00	40.05	230.00	H	125.00	-33.05	46.00	-5.95
168.04	37.09	266.00	H	222.00	-32.48	43.50	-6.41
216.44	38.63	234.00	H	163.00	-33.59	46.00	-7.37
432.85	33.61	215.00	V	108.00	-29.19	46.00	-12.39
33.42	18.87	74.00	V	127.00	-22.41	40.00	-21.13
288.58	34.98	255.00	H	103.00	-31.52	46.00	-11.02

Test Mode:	8DPSK Transmitting
-------------------	---------------------------

Above 1 GHz

Note: Other Bluetooth modes were verified; only the result of worst case 3DH5 mode was presented.

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
4804	74.82	PK	147	130	V	32.7	12.8	57	63.32	74	-10.68
4804	50.63	AV	147	130	V	32.7	12.8	57	39.13	54	-14.87
2387	71.04	PK	241	130	V	30.1	7.2	57	51.34	74	-22.66
2387	51.16	AV	241	130	V	30.1	7.2	57	31.46	54	-22.54
4804	74.52	PK	123	110	H	32.7	12.8	57	63.02	74	-10.98
4804	50.42	AV	123	110	H	32.7	12.8	57	38.92	54	-15.08
2389	69.36	PK	82	130	H	30.1	7.2	57	49.66	74	-24.34
2388	51.52	AV	82	130	H	30.1	7.2	57	31.82	54	-22.18

Middle Channel (2441 MHz)

Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
4882	73.45	PK	246	120	V	32.8	12.8	57	62.05	74	-11.95
4882	51.42	AV	246	120	V	32.8	12.8	57	40.02	54	-13.98
7326	67.28	PK	264	110	V	35.6	15.9	58	60.78	74	-13.22
7326	48.69	AV	264	110	V	35.6	15.9	58	42.19	54	-11.81
4882	72.19	PK	89	140	H	32.8	12.8	57	60.79	74	-13.21
4882	50.72	AV	89	140	H	32.8	12.8	57	39.32	54	-14.68
7326	67.82	PK	142	130	H	35.6	15.9	58	61.32	74	-12.68
7326	48.76	AV	142	130	H	35.6	15.9	58	42.26	54	-11.74

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
4960	73.74	PK	142	110	V	32.7	12.8	57	62.24	74	-11.76
4960	51.09	AV	142	110	V	32.7	12.8	57	39.59	54	-14.41
2488	70.72	PK	315	130	V	30.1	10.2	57	53.98	74	-20.02
2485	50.75	AV	315	130	V	30.1	10.2	57	34.01	54	-19.99
4960	72.76	PK	42	110	H	32.7	12.8	57	61.26	74	-12.74
4960	50.08	AV	42	110	H	32.7	12.8	57	38.58	54	-15.42
2488	69.83	PK	125	120	H	30.1	7.2	57	50.13	74	-23.87
2485	51.42	AV	125	120	H	30.1	7.2	57	31.72	54	-22.28

5.4 §15.247(a) (1)-Channel Separation

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Environmental Conditions

Temperature	22°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
3. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ±1.5dB.
4. Test date : September 25 and October 11, 2012
Tested By : Alan Lv

Standard Requirement:

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Procedures:


1. Place the EUT on the table and set it in hopping function transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as Resolution (or IF) Bandwidth (RBW) \geq 1% of the span, Video (or Average) Bandwidth (VBW) \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold.
5. Max hold, mark 2 peaks of hopping channel and record the 2 peaks frequency.

Test Result: Pass

Test Mode:	GFSK Transmitting
-------------------	--------------------------


Channel	Channel Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
Low Channel	2402	1.002	0.960	Pass
Adjacency Channel	2403			
Mid Channel	2440	1.002	0.960	Pass
Adjacency Channel	2441			
High Channel	2480	1.002	0.960	Pass
Adjacency Channel	2479			

Please refer to the following plots.




Date: 25.SEP.2012 12:48:08

Middle Channel



Date: 11.OCT.2012 22:21:21

High Channel




Date: 25.SEP.2012 12:41:49

Test Mode:	$\pi/4$-DQPSK Transmitting
-------------------	--

Channel	Channel Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
Low Channel	2402	1.002	0.864	Pass
Adjacency Channel	2403			
Mid Channel	2440	1.002	0.860	Pass
Adjacency Channel	2441			
High Channel	2480	1.002	0.876	Pass
Adjacency Channel	2479			

Please refer to the following plots.



Date: 11.OCT.2012 21:51:00




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 28 of 88
www.siemec.com.cn

Middle Channel



Date: 11.OCT.2012 21:53:05

High Channel




Date: 11.OCT.2012 21:54:40

Test Mode:	8DPSK Transmitting
-------------------	---------------------------

Channel	Channel Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
Low Channel	2402	1.002	0.864	Pass
Adjacency Channel	2403			
Mid Channel	2440	1.008	0.860	Pass
Adjacency Channel	2441			
High Channel	2480	1.002	0.856	Pass
Adjacency Channel	2479			

Please refer to the following plots.



Date: 11.OCT.2012 21:09:58




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 30 of 88
www.siemec.com.cn

Middle Channel



Date: 11.OCT.2012 21:11:29

High Channel



Date: 11.OCT.2012 21:13:26

§15.247(a) (1) – 20dB Bandwidth

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Environmental Conditions

Temperature	22°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
3. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is $\pm 1.5\text{dB}$.
4. Test date : September 25 and October 11, 2012
Tested By : Alan Lv

Standard Requirement:

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Procedures:


1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel, RBW $\geq 1\%$ of the 20 dB bandwidth, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold.
4. Set the measured low, middle and high frequency and test 20dB bandwidth with spectrum analyzer.

Test Result: Pass

Test Mode:	GFSK Transmitting
-------------------	--------------------------

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2402	0.960
Middle	2441	0.960
High	2480	0.960

Please refer to the following plots.



Date: 25.SEP.2012 12:51:11




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 33 of 88
www.siemic.com.cn

Middle Channel



Date: 25.SEP.2012 12:52:00

High Channel




Date: 25.SEP.2012 12:52:33

Test Mode:	$\pi/4$-DQPSK Transmitting
-------------------	--

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2402	1.296
Middle	2441	1.290
High	2480	1.314

Please refer to the following plots.

Low Channel



Date: 11.OCT.2012 21:55:30




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 35 of 88
www.siemic.com.cn

Middle Channel



Date: 11.OCT.2012 21:56:41

High Channel




Date: 11.OCT.2012 21:57:25

Test Mode:	8DPSK Transmitting
-------------------	---------------------------

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2402	1.296
Middle	2441	1.290
High	2480	1.284

Please refer to the following plots.

Low Channel



Date: 11.OCT.2012 21:15:31




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 37 of 88
www.siemic.com.cn

Middle Channel



Date: 11.OCT.2012 21:16:56

High Channel



Date: 11.OCT.2012 21:18:43

5.5 §15.247(a) (1) (iii)-Number of Hopping Channels

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is $\pm 1.5\text{dB}$.
3. Environmental Conditions

Temperature	22°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test date : September 25 and October 11, 2012
Tested By : Alan Lv

Standard Requirement:

According to §15.247(a) (1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Procedures:


1. Place the EUT on the table and set it in hopping function transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as Start=2400MHz, Stop = 2483.5MHz, Span = the frequency band of operation, RBW $\geq 1\%$ of the span, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold.
4. Count the quantity of peaks to get the number of hopping channels.

Test Result: Pass

Test Mode:	Hopping Mode With GFSK Modulation
-------------------	--

Frequency Range (MHz)	Number of Hopping Channels	Limit
2400-2483.5	79	≥15

Please refer to following tables and plots




Date: 25.SEP.2012 12:55:47

Test Mode: Hopping Mode With $\pi/4$ -DQPSK Modulation

Frequency Range (MHz)	Number of Hopping Channels	Limit
2400-2483.5	79	≥ 15

Please refer to following tables and plots




Date: 11.OCT.2012 22:04:14

Test Mode:	Hopping Mode With 8DPSK Modulation
-------------------	---

Frequency Range (MHz)	Number of Hopping Channels	Limit
2400-2483.5	79	≥15

Please refer to following tables and plots



Date: 11.OCT.2012 21:24:54

5.6 §15.247(a) (1) (iii) -Time of Occupancy (Dwell Time)

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ± 1.5 dB.
3. Environmental Conditions

Temperature	22°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test date : September 25 and October 11, 2012
Tested By : Alan Lv

Standard Requirement:

According to §15.247(a)(1)(iii), The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Procedures:


1. Place the EUT on the table and set it in transmitting mode and switch on frequency hopping function.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as Span = zero span, centered on a hopping channel,
RBW=1MHz, VBW \geq RBW, Sweep = as necessary to capture the entire dwell time per hopping channel, Detector function = peak, Trace = max hold.
4. Calculate the time of occupancy in a period with time occupancy of a burst and quantity of bursts.

Test Result: Pass


Test Mode: Hopping Mode With GFSK Modulation

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH 1	Low	0.446	0.14272	0.4	Pass
	Middle	0.446	0.14272	0.4	Pass
	High	0.446	0.14272	0.4	Pass
	<i>Note: Dwell time=Pulse time (ms) × (1600 ÷ 2 ÷ 79) × 31.6 Second</i>				
DH 3	Low	1.708	0.27328	0.4	Pass
	Middle	1.708	0.27328	0.4	Pass
	High	1.708	0.27328	0.4	Pass
	<i>Note: Dwell time=Pulse time (ms) × (1600 ÷ 4 ÷ 79) × 31.6 Second</i>				
DH 5	Low	2.992	0.31915	0.4	Pass
	Middle	2.992	0.31915	0.4	Pass
	High	2.976	0.31744	0.4	Pass
	<i>Note: Dwell time=Pulse Time (ms) × (1600 ÷ 6 ÷ 79) × 31.6 Second</i>				

Please refer to the following plots.




Middle Channel for DH1



Date: 25.SEP.2012 13:05:57

High Channel for DH1



Date: 25.SEP.2012 13:05:23




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 45 of 88
www.siemec.com.cn

Low Channel for DH3




Date: 25.SEP.2012 13:02:22

Middle Channel for DH3




Date: 25.SEP.2012 13:03:08

Middle Channel for DH5



Date: 25.SEP.2012 12:59:25

High Channel for DH5




Date: 25.SEP.2012 12:58:32

Test Mode: Hopping Mode With $\pi/4$ -DQPSK Modulation

Time of Occupancy

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
2DH1	Low	0.454	0.14528	0.4	Pass
	Middle	0.454	0.14528	0.4	Pass
	High	0.454	0.14528	0.4	Pass
	<i>Note: Dwell time=Pulse time (ms) × (1600 ÷ 2 ÷ 79) × (79×0.4) Second</i>				
2DH3	Low	1.736	0.27776	0.4	Pass
	Middle	1.736	0.27776	0.4	Pass
	High	1.736	0.27776	0.4	Pass
	<i>Note: Dwell time=Pulse time (ms) × (1600 ÷ 4 ÷ 79) × (79×0.4) Second</i>				
2DH5	Low	3.008	0.32085	0.4	Pass
	Middle	3.008	0.32085	0.4	Pass
	High	3.008	0.32085	0.4	Pass
	<i>Note: Dwell time=Pulse Time (ms) × (1600 ÷ 6 ÷ 79) × (79×0.4)Second</i>				

Low Channel for 2DH1






SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 49 of 88
www.siemac.com.cn

Middle Channel for 2DH1



Date: 11.OCT.2012 22:16:31

High Channel for 2DH1



Date: 11.OCT.2012 22:17:07




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 50 of 88
www.siemac.com.cn

Low Channel for 2DH3



Date: 11.OCT.2012 22:12:46

Middle Channel for 2DH3



Date: 11.OCT.2012 22:12:08




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 51 of 88
www.siemac.com.cn

High Channel for 2DH3



Date: 11.OCT.2012 22:11:17

Low Channel for 2DH5



Date: 11.OCT.2012 22:09:09




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 52 of 88
www.siemic.com.cn

Middle Channel for 2DH5



Date: 11.OCT.2012 22:09:47

High Channel for 2DH5




Date: 11.OCT.2012 22:10:21

Test Mode: Hopping Mode With 8DPSK Modulation


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
3DH1	Low	0.450	0.14400	0.4	Pass
	Middle	0.450	0.14400	0.4	Pass
	High	0.450	0.14400	0.4	Pass
	<i>Note: Dwell time=Pulse time (ms) × (1600 ÷ 2 ÷ 79) × 31.6 Second</i>				
3DH3	Low	1.720	0.27520	0.4	Pass
	Middle	1.720	0.27520	0.4	Pass
	High	1.720	0.27520	0.4	Pass
	<i>Note: Dwell time=Pulse time (ms) × (1600 ÷ 4 ÷ 79) × 31.6 Second</i>				
3DH5	Low	2.968	0.31659	0.4	Pass
	Middle	2.984	0.31829	0.4	Pass
	High	2.984	0.31829	0.4	Pass
	<i>Note: Dwell time=Pulse Time (ms) × (1600 ÷ 6 ÷ 79) × 31.6 Second</i>				

Please refer to the following plots.




Date: 11.OCT.2012 21:30:32

Middle Channel for 3DH1



Date: 11.OCT.2012 21:31:33

High Channel for 3DH1



Date: 11.OCT.2012 21:32:09




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 55 of 88
www.siemac.com.cn

Low Channel for 3DH3




Date: 11.OCT.2012 21:34:09

Middle Channel for 3DH3




Date: 11.OCT.2012 21:33:39

High Channel for 3DH3



Date: 11.OCT.2012 21:32:51

Low Channel for 3DH5



Date: 11.OCT.2012 21:35:33




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 57 of 88
www.siemec.com.cn

Middle Channel for 3DH5



Date: 11.OCT.2012 21:36:21

High Channel for 3DH5



Date: 11.OCT.2012 21:37:27

5.7 §15.247(b) (1) - Peak Output Power

1. **Conducted Measurement**
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. **Conducted Emissions Measurement Uncertainty**
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is $\pm 1.5\text{dB}$.
3. **Environmental Conditions**

Temperature	22°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test date : September 25 and October 11, 2012
Tested By : Alan Lv

Standard Requirement:

According to §15.247(b)(2), For frequency hopping systems in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band: 0.125watts.

Procedures:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel, RBW > the 20 dB bandwidth of the emission being measured, VBW \geq RBW, Sweep=auto, Detector function=peak, Trace = max hold.
4. Then set the EUT to transmit at low, middle and high channel and measure the conducted output power separately.


Test Result: Pass

Test Mode:	GFSK Transmitting
-------------------	--------------------------

Channel	Channel frequency (MHz)	Peak output power (dBm)	Power output (mW)	Limit (mW)
Low channel	2402	4.10	2.57	1000
Middle channel	2441	6.93	4.93	1000
High channel	2480	7.69	5.87	1000

Please refer to the following plots.

Note: The data above was tested in conducted mode.



Date: 25.SEP.2012 13:08:07




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 60 of 88
www.siemic.com.cn

Middle Channel



Date: 25.SEP.2012 13:08:32

High Channel




Date: 25.SEP.2012 13:08:55

Test Mode:	π /4-DQPSK Transmitting
-------------------	---

Channel	Channel frequency (MHz)	Peak output power (dBm)	Power output (mW)	Limit (mW)
Low channel	2402	3.10	2.04	125
Middle channel	2441	6.36	4.33	125
High channel	2480	7.15	5.19	125

Please refer to the following plots.

Note: The data above was tested in conducted mode.



Date: 11.OCT.2012 22:18:39




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 62 of 88
www.siemec.com.cn

Middle Channel



Date: 11.OCT.2012 22:18:56

High Channel




Date: 11.OCT.2012 22:19:10

Test Mode:	8DPSK Transmitting
-------------------	---------------------------

Channel	Channel frequency (MHz)	Peak output power (dBm)	Power output (mW)	Limit (mW)
Low channel	2402	3.06	2.02	125
Middle channel	2441	6.33	4.30	125
High channel	2480	7.10	5.13	125

Please refer to the following plots.

Note: The data above was tested in conducted mode.



Date: 11.OCT.2012 21:40:02




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 64 of 88
www.siemic.com.cn

Middle Channel



Date: 11.OCT.2012 21:40:23

High Channel



Date: 11.OCT.2012 21:40:53

5.8 §15.247(d) - Band Edge

Standard Requirement:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Procedures:

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.


Test Result: Pass

Test Mode:	GFSK Transmitting
-------------------	--------------------------

Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)
2399.256	47.21	20
2483.536	55.20	20


Note: The point fall into the strict band was recorded in FCC 15.209, please refer to the restrict band testing.

Band Edge: Left Side



Date: 25.SEP.2012 13:12:50

Band Edge: Right Side



Date: 25.SEP.2012 13:11:06

Test Mode:	π /4-DQPSK Transmitting
-------------------	---

Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)
2399.984	51.72	20
2484.796	55.84	20

Note: The point fall into the strict band was recorded in FCC 15.209, please refer to the restrict band testing.

Test Mode:	8DPSK Transmitting
-------------------	---------------------------

Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)
2399.980	50.27	20
2483.578	55.26	20

Note: The point fall into the strict band was recorded in FCC 15.209, please refer to the restrict band testing.




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009


Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 70 of 88
www.siemec.com.cn

Band Edge: Left Side



Date: 11.OCT.2012 21:47:17

Band Edge: Right Side



Date: 11.OCT.2012 21:43:10

Annex A. TEST INSTRUMENT & METHOD


Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Model	Serial #	Calibration Date	Calibration Due Date
AC Line Conducted Emissions				
R&S EMI Test Receiver	ESPI3	101216	10/28/2011	10/27/2012
ROHDE&SCHWARZ V-LISN	ESH3-Z5	838979/005	10/28/2011	10/27/2012
Com-Power Transient Limiter	LIT-153	531021	11/04/2011	11/03/2012
SIEMIC Labview Conducted Emissions software	V1.0	N/A	N/A	N/A
Radiated Emissions				
Hp Spectrum Analyzer	8563E	3821A09023	01/10/2012	01/09/2013
R&S EMI Receiver	ESPI3	101216	10/28/2011	10/27/2012
Antenna (30MHz~6GHz)	JB6	A121411	12/28/2011	12/27/2012
EMCO Horn Antenna	3115	N/A	10/30/2011	10/29/2012
A- INFOMW Antenna (1 ~18GHz)	JXTXLB-10180	J2031081120092	06/24/2012	06/23/2013
Horn Antenna (18~40GHz)	AH-840	101013	04/22/2012	04/21/2013
Microwave Pre-Amp (18~40GHz)	PA-840	181250	05/30/2012	05/29/2013
Hp Agilent Pre-Amplifier	8447F	1937A01160	11/04/2011	11/03/2012
MITEQ Pre-Amplifier (0.1 ~ 18GHz)	AMF-7D-00101800-30-10P	1451710	11/04/2011	11/03/2012
Universal Radio Communication Tester	CMU200	104031	10/28/2011	10/27/2012
Chamber	3m	N/A	04/13/2012	04/12/2013
SIEMIC Labview Radiated Emissions software	V1.0	N/A	N/A	N/A

Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
2. The power supply for the EUT was fed through a 50Ω/50μH EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.



**Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.**

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration1.

Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Description of Conducted Emission Program

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the common scan range from 150 kHz to 30 MHz; the program will first start a peak and average scan on selectable measurement time and step size. After the program complete the pre-scan, this program will perform the Quasi Peak and Average measurement, based on the pre-scan peak data reduction result.

Sample Calculation Example

At 20 MHz

limit = 250 μ V = 47.96 dB μ V

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = 40.00 dB μ V
(Calibrated for system losses)

Therefore, Q-P margin = 47.96 – 40.00 = 7.96 i.e. **7.96 dB below limit**

Annex A. iii. RADIATED EMISSIONS TEST DESCRIPTION

Limit

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS) or 3m EMC chamber.

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on an open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
5. Repeat step 4 until all frequencies need to be measured was complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Description of Radiated Emissions Program

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the scan on four different antenna heights, 2 antenna polarity, and 360 degrees table rotation. For example, the program was set to run 30 MHz to 1 GHz scan; the program will first start from a meter antenna height and divide the 30 MHz to 1 GHz into 10 separate parts of maximum hold sweeps. Each parts of maximum hold sweep, the program will collect the data from 0 degree to 360 degrees table rotation. After the program complete the 1m scan, the antenna continues to rise to 2m and continue the scan. The step will repeated for all specified antenna height and polarity. This program will perform the Quasi Peak measurement after the signal maximization process and pre-scan routine. The final measurement will be base on the pre-scan data reduction result.

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any)

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor or}$$

Set RBW = 1MHz, VBW = 10Hz.

Note:


If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.

Radiated emission test facilities for frequencies above 1 GHz (ANSI C63.4-2009 Chapter 5.5)


Currently, test site reference validation requirements above 1 GHz have not been established. However, facilities suitable for measurements in the frequency range 30 MHz to 1000 MHz are considered suitable for the frequency range 1 GHz to 40 GHz with RF absorbing material covering the ground plane such that the site validation criterion called out in CISPR 16-1-4:2007 is met, or alternatively covering a minimum area of 2.4 m by 2.4 m (for a 3 m test distance) between the antenna and the EUT using RF absorbing material with a minimum-rated attenuation of 20 dB (for normal incidence) up to 18 GHz. For separation distances greater than 3 m, a proportional increase in the area of suitable absorbing material is required.

Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Annex B.i. Photograph 1: EUT External Photo




EUT - Front View




EUT - Rear View

Annex B.ii. Photograph 2: EUT Internal Photo



BT Antenna

Uncover Without Shielding - Front View



Uncover Without Shielding – Rear View


Annex B.iii. Photograph 3: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Emissions Test Setup Below 1GHz - Rear View



Radiated Emissions Test Setup Above 1GHz - Front View

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION


The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model	Calibration Date	Calibration Due Date
Gateway Laptop	MS2288 & LXWHF02013951C3CA92200	N/A	N/A

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	The EUT was continuously transmitting to stimulate the worst case.



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009

Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 85 of 88
www.siemic.com.cn

Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009

Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 86 of 88
www.siemic.com.cn

Annex E. DECLARATION OF SIMILARITY



福建慧翰微电子有限公司

Fujian Flaircomm Microelectronics, Inc.

Declaration letter

To: SIEMIC, INC.
775 Montague Expressway,
Milpitas, CA 95035
USA

Dear Sir,

For our business development and marketing requirement, we would like to list different models numbers on the FCC/CE certificates and reports, as following:

Model No.: FLC-BTM805

FLC-BTM805IL2A; FLC-BTM805CL2A; FLC-BTM805VL2A;
FLC-BTM805IL2B; FLC-BTM805CL2B; FLC-BTM805VL2B;

The difference between the seven models FLC-BTM805, FLC-BTM805IL2A, FLC-BTM805CL2A, FLC-BTM805VL2A, FLC-BTM805IL2B, FLC-BTM805CL2B and FLC-BTM805VL2B is as follows:
FLC-BTM805 is the main model.

1. FLC-BTM805IL2B is similar to FLC-BTM805. The only difference between them is the model names.
2. FLC-BTM805CL2B and FLC-BTM805VL2B are similar to FLC-BTM805. The only difference between them is the product grade.
3. FLC-BTM805IL2A, FLC-BTM805CL2A and FLC-BTM805VL2A are similar to FLC-BTM805. The difference is that both FLC-BTM805IL2A, FLC-BTM805CL2A and FLC-BTM805VL2A are not integrated with an internal antenna, but FLC-BTM805 is embedded with an internal antenna.

Like all the others,

Thank you!

Signature:

Printed name/title: Marvin Zhao/President

Fujian Flaircomm Microelectronics, Inc.
<http://www.flairmicro.com>



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009

Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 87 of 88
www.siemic.com.cn




FLAIRCOMM

福建慧翰微电子有限公司

Fujian Flaircomm Microelectronics, Inc.

Ordering information

FLC-BTM805XYZA



Ordering Information

Host Interface	Package		Order Number
	Type	Shipment	
UART	LGA	Tape and reel	BTM805CL2A BTM805CL2B

1、 Product Revision

Product Revision	Description	Availability
A	Without internal antenna	Yes
B	With an internal antenna	Yes

Product Revision

2、 Shipping Package

Shipping Package	Description	Quantity	Availability
0	Foam Tray	—	No
1	Plastic Tray	100x10x3 = 3000	Yes
2	Tape	—	Yes

Shipping Package

3、 Product Package

Product Package	Description	Availability
Q	QFN	No
L	LGA	Yes
B	BGA	No
C	Connector	No

Product Package

Fujian Flaircomm Microelectronics, Inc.

<http://www.flairmicro.com>



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Bluetooth module
Main Model: FLC-BTM805
Serial Model: See P5
To: FCC Part 15.247: 2012, ANSI C63.4: 2009

Report No: 12020792-FCC-R1
Issue Date: November 28, 2012
Page: 88 of 88
www.siemec.com.cn



FLAIRCOMM

福建慧翰微电子有限公司

Fujian Flaircomm Microelectronics, Inc.

4、Product Grade

Product Grade	Description	Availability
C	Consumer	Yes
I	Industrial	Yes
V	Automobile After-Market	Yes
A	Automobile Before-Market	No

Product Grade

Note:

- A、 Industrial Grade (I) : Operation temperature range from -40℃ to 85℃ .
Product can be used for industrial applications.
- B、 Automobile After-Market Grade (V) : Operation temperature range from -20℃ to 70℃ . Product can be used for after-market applications.