

13 FCC §2.1091 & IC RSS-102 – RF Exposure

13.1 Applicable Standards

According to FCC §2.1091 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

Before equipment certification is granted, the procedure of IC RSS-102 must be followed concerning the exposure of humans to RF fields.

According to IC RSS-102 Issue 2 section 4.1, RF limits used for general public will be applied to the EUT.

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Time Averaging (min)
0.003 - 1	280	2.19	-	6
1 - 10	280 / f	2.19 / f	-	6
10 - 30	28	2.19 / f	-	6
30 – 300	28	0.073	2*	6
300 – 1 500	1.585 f ^{0.5}	0.0042 f ^{0.5}	f / 150	6
1 500 – 15 000	61.4	0.163	10	6
15 000 – 150 000	61.4	0.163	10	616000 / f ^{1.2}
150 000- 300 000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000 / f ^{1.2}

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

13.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

13.3 MPE Results

824-849 MHz Band

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>24.34</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>271.6439</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>846.6</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>-3.0</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>0.5</u>
<u>Power density of prediction frequency at 20 cm (mW/cm²):</u>	<u>0.027085</u>
<u>MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>0.5655</u>
<u>Power density of prediction frequency at 20 cm (W/m²):</u>	<u>0.270851</u>
<u>MPE limit for uncontrolled exposure at prediction frequency (W/m²):</u>	<u>5.655</u>

1850-1910 MHz Band

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>23.74</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>236.592</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>1907.6</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>-3.0</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>0.5</u>
<u>Power density of prediction frequency at 20 cm (mW/cm²):</u>	<u>0.02359</u>
<u>MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>
<u>Power density of prediction frequency at 20 cm (W/m²):</u>	<u>0.235901</u>
<u>MPE limit for uncontrolled exposure at prediction frequency (W/m²):</u>	<u>10.0</u>

The device is compliant with the requirement MPE limit for uncontrolled exposure at 20 cm distance.