



FCC TEST REPORT

REPORT NO.: RF960418L27

MODEL NO.: Magellan CrossOverGPS 3150

RECEIVED: Apr. 18, 2007

TESTED: Apr. 25 ~ Apr. 27, 2007

ISSUED: May 07, 2007

APPLICANT: MITAC INTERNATIONAL CORP.

ADDRESS: 6TH FL., NO. 187, TIDING BLVD., SEC. 2, NEI-HU,
TAIPEI, TAIWAN, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang
244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 58 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



NO. 2177-01



0528



TABLE OF CONTENTS

1.	CERTIFICATION.....	4
2.	SUMMARY OF TEST RESULTS.....	5
2.1	MEASUREMENT UNCERTAINTY	6
3.	GENERAL INFORMATION.....	7
3.1.	GENERAL DESCRIPTION OF EUT.....	7
3.2.	DESCRIPTION OF TEST MODES.....	8
3.2.1.	CONFIGURATION OF SYSTEM UNDER TEST.....	9
3.2.2.	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	10
3.2.3.	GENERAL DESCRIPTION OF APPLIED STANDARDS	12
3.2.4.	DESCRIPTION OF SUPPORT UNITS	13
4.	TEST TYPES AND RESULTS.....	14
4.1.	CONDUCTED EMISSION MEASUREMENT.....	14
4.1.1.	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	14
4.1.2.	TEST INSTRUMENTS.....	14
4.1.3.	TEST PROCEDURES	15
4.1.4.	DEVIATION FROM TEST STANDARD.....	15
4.1.5.	TEST SETUP	16
4.1.6.	EUT OPERATING CONDITIONS.....	16
4.1.7.	TEST RESULTS	17
4.2.	RADIATED EMISSION MEASUREMENT.....	23
4.2.1.	LIMITS OF RADIATED EMISSION MEASUREMENT.....	23
4.2.2.	TEST INSTRUMENTS.....	24
4.2.3.	TEST PROCEDURES	25
4.2.4.	DEVIATION FROM TEST STANDARD.....	25
4.2.5.	TEST SETUP	26
4.2.6.	EUT OPERATING CONDITIONS.....	26
4.2.7.	TEST RESULTS	27
4.3.	NUMBER OF HOPPING FREQUENCY USED.....	31
4.3.1.	LIMIT OF HOPPING FREQUENCY USED.....	31
4.3.2.	TEST INSTRUMENTS.....	31
4.3.3.	TEST PROCEDURES	31
4.3.4.	DEVIATION FROM TEST STANDARD.....	32
4.3.5.	TEST SETUP	32
4.3.6.	TEST RESULTS	32
4.4.	DWELL TIME ON EACH CHANNEL	34
4.4.1.	LIMIT OF DWELL TIME USED.....	34
4.4.2.	TEST INSTRUMENTS.....	34
4.4.3.	TEST PROCEDURES	34
4.4.4.	DEVIATION FROM TEST STANDARD.....	34
4.4.5.	TEST SETUP	35




4.4.6.	TEST RESULTS	35
4.5.	CHANNEL BANDWIDTH	39
4.5.1.	LIMITS OF CHANNEL BANDWIDTH	39
4.5.2.	TEST INSTRUMENTS.....	39
4.5.3.	TEST PROCEDURE.....	39
4.5.4.	DEVIATION FROM TEST STANDARD.....	40
4.5.5.	TEST SETUP	40
4.5.6.	EUT OPERATING CONDITION	40
4.5.7.	TEST RESULTS	40
4.6.	HOPPING CHANNEL SEPARATION	43
4.6.1.	LIMIT OF HOPPING CHANNEL SEPARATION.....	43
4.6.2.	TEST INSTRUMENTS.....	43
4.6.3.	TEST PROCEDURES	43
4.6.4.	DEVIATION FROM TEST STANDARD.....	44
4.6.5.	TEST SETUP	44
4.6.6.	TEST RESULTS	44
4.7.	MAXIMUM PEAK OUTPUT POWER	47
4.7.1.	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT.....	47
4.7.2.	TEST INSTRUMENTS.....	47
4.7.3.	TEST PROCEDURES	47
4.7.4.	DEVIATION FROM TEST STANDARD.....	47
4.7.5.	TEST SETUP	48
4.7.6.	EUT OPERATING CONDITION	48
4.7.7.	TEST RESULTS	48
4.8.	BAND EDGES MEASUREMENT	51
4.8.1.	LIMITS OF BAND EDGES MEASUREMENT	51
4.8.2.	TEST INSTRUMENTS.....	51
4.8.3.	TEST PROCEDURE.....	51
4.8.4.	DEVIATION FROM TEST STANDARD.....	51
4.8.5.	EUT OPERATING CONDITION	51
4.8.6.	TEST RESULTS	52
4.9.	ANTENNA REQUIREMENT	55
4.9.1.	STANDARD APPLICABLE.....	55
4.9.2.	ANTENNA CONNECTED CONSTRUCTION	55
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	56
6.	INFORMATION ON THE TESTING LABORATORIES.....	57
	APPENDIX-A	A-1





1. CERTIFICATION

PRODUCT: Portable Navigator
MODEL NO.: Magellan CrossOverGPS 3150
BRAND NAME: MAGELLAN
APPLICANT: MITAC INTERNATIONAL CORP.
TESTED: Apr. 25 ~ Apr. 27, 2007
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: **FCC Part 15, Subpart C (Section 15.247),**
ANSI C63.4-2003

The above equipment (model: Magellan CrossOverGPS 3150) have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** May 07, 2007
Joanna Wang

TECHNICAL
ACCEPTANCE :  , **DATE:** May 07, 2007
Responsible for RF Long Chen

APPROVED BY :  , **DATE:** May 07, 2007
Gary Chang / Supervisor

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -15.23dB at 0.482MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used Spec.: At least 15 channels	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel Spec. : Max. 0.4 second within 31.6 second	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation Spec. : Min. 25 kHz or 20 dB bandwidth, whichever is greater 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Spec.: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -6.15dB at 66.84MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz ~ 30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.62 dB
	200MHz ~ 1000MHz	3.64 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3. GENERAL INFORMATION

3.1. GENERAL DESCRIPTION OF EUT

PRODUCT	Portable Navigator
MODEL NO.	Magellan CrossOverGPS 3150
FCC ID	P4Q-2007VEN2001
POWER SUPPLY	3.7 Vdc from battery 5.0 Vdc from adapter 5.0 Vdc from car charger
MODULATION TYPE	Bluetooth: GFSK GPS: C/A code
RADIO TECHNOLOGY	FHSS
TRANSFER RATE	Bluetooth: 723.2kbps
FREQUENCY RANGE	Bluetooth: 2402~2480 MHz GPS: 1575.42 MHz
NUMBER OF CHANNEL	Bluetooth: 79 GPS: 1
OUTPUT POWER	1.734mW
ANTENNA TYPE	PIFA antenna with 0dBi gain (For Bluetooth function)
I/O PORTS	Refer to user's manual
DATA CABLE	1.2m shielded USB cable with 2 cores
ACCESSORY DEVICE	adapter, car charger, battery, cradle, GPS antenna (2.0m), TMC cable (1.5m)

NOTE:

1. Bluetooth technology is used in this EUT.
2. The EUT was powered by the following adapter and car charger:

Adapter	
Brand	PHIHONG
Model	PSC11R-050
Input Power	100~240Vac, 0.3A, 50~60Hz
Output Power	5Vdc, 2A MAX
Power Cord	1.8 m non-shielded cable with one core

Car Charger	
Brand	Atech
Model	CT-PI68SDS
Input Power	12Vdc & 24Vdc, 1.3A MAX
Output Power	5Vdc, 2A
Power Cord	0.9 m shielded cable without core


3. The EUT is powered from car battery (12Vdc or 24Vdc) via car charger. In this report, 24Vdc is the worst case for final test.
4. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2. DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2431	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1. CONFIGURATION OF SYSTEM UNDER TEST



3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	Applicable to				Description
	PLC	RE<1G	RE ³ 1G	APCM	
-	√	√	√	√	-

Where **PLC**: Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz

RE³1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and packet types of the antenna and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, packet types and XYZ Axis.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	AXIS
0 to 78	78	FHSS	GFSK	DH5	Z

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, packet types and XYZ Axis.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	AXIS
0 to 78	0, 39, 78	FHSS	GFSK	DH5	Z



BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 78	FHSS	GFSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5



3.2.3. GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.2.4. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP05L	33898721680	E2K24CLNS
2	PRINTER	EPSON	LQ-300+	DCGY054146	FCC DoC Approved
3	MODEM	ACEEX	1414V/3	0401008260	IFAXDM1414
4	MICROPHONE	Labtec	LVA7313	N/A	N/A
5	EARPHONE	PHILIPS	SBC HL125	N/A	NA
6	EARPHONE	NA	NA	NA	NA
7	CAR BATTERY	YUASA	C36B20L	NA	NA
8	CAR BATTERY	YUASA	C36B20L	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.2m shielded USB cable with 2 cores
2	1.8m shielded cable
3	1.8m shielded cable
4	1.0m non-shielded cable
5	1.0m non-shielded cable
6	1.6m non-shielded cable
7	NA
8	NA

NOTE:

1. All power cords of the above support units are non shielded (1.8m).
2. Item 6 was supplied from client.

4. TEST TYPES AND RESULTS

4.1. CONDUCTED EMISSION MEASUREMENT

4.1.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2. TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Sep. 25, 2007
RF signal cable Woken	5D-FB	Cable-HYCO3-01	Jan. 06, 2008
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Jan. 08, 2008
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Jan. 16, 2008
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.


4.1.3. TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4. DEVIATION FROM TEST STANDARD

No deviation.

4.1.5. TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6. EUT OPERATING CONDITIONS

- a. Connected EUT with notebook system via USB cable and placed on a testing table.
- b. The notebook system ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.


4.1.7. TEST RESULTS

CONDUCTED WORST-CASE DATA

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	PHASE	Line 1
MODULATION TYPE	GFSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen		

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	44.37	-	44.47	-	64.79	54.79	-20.32	-
2	0.216	0.10	40.51	-	40.61	-	62.96	52.96	-22.35	-
3	0.259	0.10	39.09	-	39.19	-	61.45	51.45	-22.26	-
4	0.474	0.10	40.78	-	40.88	-	56.44	46.44	-15.56	-
5	0.513	0.10	39.88	-	39.98	-	56.00	46.00	-16.02	-
6	1.977	0.22	32.73	-	32.95	-	56.00	46.00	-23.05	-
7	8.391	0.32	31.15	-	31.47	-	60.00	50.00	-28.53	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	PHASE	Line 2
MODULATION TYPE	GFSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen		

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.173	0.10	47.90	-	48.00	-	64.79
2	0.220	0.10	43.51	-	43.61	-	62.81	52.81	-19.20	-
3	0.478	0.11	40.90	-	41.01	-	56.37	46.37	-15.36	-
4	0.521	0.12	39.44	-	39.56	-	56.00	46.00	-16.44	-
5	1.629	0.22	30.14	-	30.36	-	56.00	46.00	-25.64	-
6	2.914	0.25	29.10	-	29.35	-	56.00	46.00	-26.65	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	PHASE	Line 1
MODULATION TYPE	GFSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen		

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.173	0.10	44.69	-	44.79	-	64.79
2	0.216	0.10	40.98	-	41.08	-	62.96	52.96	-21.88	-
3	0.259	0.10	39.48	-	39.58	-	61.45	51.45	-21.87	-
4	0.470	0.10	40.03	-	40.13	-	56.51	46.51	-16.38	-
5	2.000	0.22	31.90	-	32.12	-	56.00	46.00	-23.88	-
6	8.336	0.32	30.97	-	31.29	-	60.00	50.00	-28.71	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	PHASE	Line 2
MODULATION TYPE	GFSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen		

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.173	0.10	45.52	-	45.62	-	64.79
2	0.216	0.10	41.77	-	41.87	-	62.96	52.96	-21.09	-
3	0.255	0.10	38.61	-	38.71	-	61.58	51.58	-22.87	-
4	0.474	0.11	40.61	-	40.72	-	56.44	46.44	-15.72	-
5	1.977	0.22	32.71	-	32.93	-	56.00	46.00	-23.07	-
6	8.754	0.40	30.35	-	30.75	-	60.00	50.00	-29.25	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	PHASE	Line 1
MODULATION TYPE	GFSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen		

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.170	0.10	43.26	-	43.36	-	64.98
2	0.220	0.10	39.73	-	39.83	-	62.81	52.81	-22.98	-
3	0.259	0.10	39.01	-	39.11	-	61.45	51.45	-22.34	-
4	0.474	0.10	40.86	-	40.96	-	56.44	46.44	-15.48	-
5	1.977	0.22	32.65	-	32.87	-	56.00	46.00	-23.13	-
6	8.867	0.32	30.95	-	31.27	-	60.00	50.00	-28.73	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	PHASE	Line 2
MODULATION TYPE	GFSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen		

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.177	0.10	41.16	-	41.26	-	64.61
2	0.220	0.10	39.97	-	40.07	-	62.81	52.81	-22.74	-
3	0.482	0.12	40.96	-	41.08	-	56.30	46.30	-15.23	-
4	1.508	0.22	30.82	-	31.04	-	56.00	46.00	-24.96	-
5	2.406	0.23	29.69	-	29.92	-	56.00	46.00	-26.08	-
6	8.176	0.38	30.04	-	30.42	-	60.00	50.00	-29.58	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2. RADIATED EMISSION MEASUREMENT

4.2.1. LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2. TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	838496/016	Dec. 29, 2007
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Dec. 01, 2007
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Jan. 04, 2008
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-405	Dec. 18, 2007
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170242	Jan. 16, 2008
Preamplifier Agilent	8449B	3008A1960	Oct. 30, 2007
Preamplifier Agilent	8447D	2944A10631	Oct. 30, 2007
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	230128/4	Nov. 14, 2007
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	233233/4	Nov. 14, 2007
Software ADT.	ADT_Radiated_V7.6	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA
Turn Table ADT.	TT100.	TT93021704	NA
Turn Table Controller ADT.	SC100.	SC93021704	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 4.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The IC Site Registration No. is IC3789B-4.

4.2.3. TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.

4.2.4. DEVIATION FROM TEST STANDARD

No deviation

4.2.5. TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6. EUT OPERATING CONDITIONS

Same as 4.1.6



4.2.7. TEST RESULTS

RADIATED WORST CASE DATA: BELOW 1GHz

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	GFSK	DETECTOR FUNCTION	Quasi-Peak
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY	Morgan Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	178.05	34.25 QP	43.50	-9.25	2.00 H	139	21.22	13.03
2	288.49	37.44 QP	46.00	-8.56	1.00 H	250	22.94	14.50
3	300.16	37.91 QP	46.00	-8.09	1.00 H	232	23.16	14.74
4	383.76	36.73 QP	46.00	-9.27	1.00 H	211	19.82	16.92
5	401.26	34.15 QP	46.00	-11.85	2.00 H	340	16.78	17.37
6	492.64	37.32 QP	46.00	-8.68	2.00 H	13	17.03	20.29
7	527.64	34.80 QP	46.00	-11.20	1.50 H	310	13.56	21.24

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	53.23	32.55 QP	40.00	-7.45	2.00 V	160	18.38	14.17
2	66.84	33.85 QP	40.00	-6.15	1.00 V	136	21.16	12.69
3	123.23	37.04 QP	43.50	-6.46	1.50 V	91	24.62	12.42
4	177.67	36.56 QP	43.50	-6.94	1.00 V	145	23.47	13.09
5	305.99	32.45 QP	46.00	-13.55	1.50 V	109	17.56	14.90
6	492.64	38.78 QP	46.00	-7.22	1.00 V	292	18.49	20.29
7	654.02	33.70 QP	46.00	-12.30	1.00 V	130	9.36	24.34

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



RADIATED WORST CASE DATA: ABOVE 1GHz

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	GFSK	DETECTOR FUNCTION	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY	Morgan Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1602.00	41.02 PK	74.00	-32.98	1.13 H	325	11.03	29.99
2	1602.00	31.85 AV	54.00	-22.15	1.13 H	325	1.86	29.99
3	2390.00	41.98 PK	74.00	-32.02	1.12 H	312	9.73	32.25
4	2390.00	37.56 AV	54.00	-16.44	1.12 H	312	5.31	32.25
5	*2402.00	89.79 PK			1.15 H	318	57.49	32.30
6	*2402.00	59.69 AV			1.15 H	318	27.39	32.30
7	4804.00	51.89 PK	74.00	-22.11	1.05 H	346	13.35	38.54
8	4804.00	21.79 AV	54.00	-32.21	1.05 H	346	-16.75	38.54

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1602.00	42.56 PK	74.00	-31.44	1.00 V	19	12.56	29.99
2	1602.00	33.56 AV	54.00	-20.44	1.00 V	19	3.56	29.99
3	2390.00	45.88 PK	74.00	-28.12	1.05 V	3	13.63	32.25
4	2390.00	41.56 AV	54.00	-12.44	1.05 V	3	9.31	32.25
5	*2402.00	95.00 PK			1.10 V	7	62.70	32.30
6	*2402.00	64.90 AV			1.10 V	7	32.60	32.30
7	4804.00	53.49 PK	74.00	-20.51	1.09 V	13	14.95	38.54
8	4804.00	23.39 AV	54.00	-30.61	1.09 V	13	-15.15	38.54

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The DH5 packet was the worst case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:
 $20\log(3.125/100) = -30.1 \text{ dB}$.
 7. Average value = peak reading+20log(duty cycle).



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	GFSK	DETECTOR FUNCTION	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY	Morgan Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1628.00	41.35 PK	74.00	-32.65	1.15 H	310	11.31	30.04
2	1628.00	31.98 AV	54.00	-22.02	1.15 H	310	1.94	30.04
3	*2441.00	89.99 PK			1.08 H	306	57.54	32.45
4	*2441.00	59.89 AV			1.08 H	306	27.44	32.45
5	4882.00	52.12 PK	74.00	-21.88	1.09 H	336	13.36	38.76
6	4882.00	22.02 AV	54.00	-31.98	1.09 H	336	-16.74	38.76

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1628.00	42.89 PK	74.00	-31.11	1.00 V	25	12.85	30.04
2	1628.00	33.76 AV	54.00	-20.24	1.00 V	25	3.72	30.04
3	*2441.00	95.99 PK			1.11 V	357	63.54	32.45
4	*2441.00	65.89 AV			1.11 V	357	33.44	32.45
5	4882.00	53.89 PK	74.00	-20.11	1.05 V	25	15.13	38.76
6	4882.00	23.79 AV	54.00	-30.21	1.05 V	25	-14.97	38.76

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:
 $20\log(3.125/100) = -30.1 \text{ dB}$.
 7. Average value = peak reading+20log(duty cycle).



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	GFSK	DETECTOR FUNCTION	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY	Morgan Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1653.00	41.45 PK	74.00	-32.55	1.09 H	315	11.36	30.09
2	1653.00	32.01 AV	54.00	-21.99	1.09 H	315	1.92	30.09
3	*2480.00	90.10 PK			1.05 H	325	57.51	32.59
4	*2480.00	60.00 AV			1.05 H	325	27.41	32.59
5	2483.50	46.58 PK	74.00	-27.42	1.12 H	325	13.97	32.61
6	2483.50	42.16 AV	54.00	-11.84	1.12 H	325	9.55	32.61
7	4960.00	52.35 PK	74.00	-21.65	1.05 H	305	13.38	38.97
8	4960.00	22.25 AV	54.00	-31.75	1.05 H	305	-16.72	38.97

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1654.00	42.78 PK	74.00	-31.22	1.00 V	13	12.69	30.09
2	1654.00	33.65 AV	54.00	-20.35	1.00 V	13	3.56	30.09
3	*2480.00	95.94 PK			1.05 V	315	63.35	32.59
4	*2480.00	65.84 AV			1.05 V	315	33.25	32.59
5	2483.50	49.76 PK	74.00	-24.24	1.09 V	6	17.15	32.61
6	2483.50	45.51 AV	54.00	-8.49	1.09 V	6	12.90	32.61
7	4960.00	54.15 PK	74.00	-19.85	1.12 V	5	15.18	38.97
8	4960.00	24.05 AV	54.00	-29.95	1.12 V	5	-14.92	38.97

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:
 $20\log(3.125/100) = -30.1 \text{ dB}$.
 7. Average value = peak reading+20log(duty cycle).



4.3. NUMBER OF HOPPING FREQUENCY USED

4.3.1. LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2. TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3. TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.3.4. DEVIATION FROM TEST STANDARD



No deviation.

4.3.5. TEST SETUP



4.3.6. TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.





4.4. DWELL TIME ON EACH CHANNEL

4.4.1. LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2. TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3. TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

4.4.4. DEVIATION FROM TEST STANDARD

No deviation.

4.4.5. TEST SETUP





4.4.6. TEST RESULTS

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	50 (times / 5 sec) *6.32=316.00 times	0.493	155.788	400
DH3	27 (times / 5 sec) *6.32=170.64 times	1.751	298.791	400
DH5	17 (times / 5 sec) *6.32=107.44 times	3.006	322.965	400



NOTE: Test plots of the transmitting time slot are shown on next 3 pages.



DH1





DH3





DH5





4.5. CHANNEL BANDWIDTH

4.5.1. LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, the 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2. TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3. TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.5.4. DEVIATION FROM TEST STANDARD

No deviation.

4.5.5. TEST SETUP



4.5.6. EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.


4.5.7. TEST RESULTS

MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	26deg. C, 70%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Morgan Chen


CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.945
39	2441	0.940
78	2480	0.940



CH 0




Ch 39





CH 78





4.6. HOPPING CHANNEL SEPARATION

4.6.1. LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or 20dB hopping channel bandwidth (whichever is greater).

4.6.2. TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.6.3. TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.6.4. DEVIATION FROM TEST STANDARD

No deviation.

4.6.5. TEST SETUP



4.6.6. TEST RESULTS


MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	26deg. C, 70%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Morgan Chen

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	PASS / FAIL
0	2402	1.003	0.945	PASS
39	2441	1.006	0.940	PASS
78	2480	1.008	0.940	PASS


NOTE: The minimum limit is 20dB bandwidth. Test results please refer to next two pages.



CH 0




CH 39





CH 78





4.7. MAXIMUM PEAK OUTPUT POWER

4.7.1. LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.7.2. TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.7.3. TEST PROCEDURES

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

4.7.4. DEVIATION FROM TEST STANDARD

No deviation

4.7.5. TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.7.6. EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.


4.7.7. TEST RESULTS

MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	26deg. C, 70%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Morgan Chen


CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
0	2402	1.603	2.05	30	PASS
39	2441	1.486	1.72	30	PASS
78	2480	1.734	2.39	30	PASS




CH 0



Ch 39



Ch 78





4.8. BAND EDGES MEASUREMENT

4.8.1. LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2. TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.8.3. TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4. DEVIATION FROM TEST STANDARD

No deviation.

4.8.5. EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest and highest channel frequencies individually.

4.8.6. TEST RESULTS

The spectrum plots are attached on the following 4 images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

NOTE 1:

The band edge emission plot on the next page shows 45.07dBc between carrier maximum power and local maximum emission in restrict band (2.34060GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 95.00dBuV/m (Peak), so the maximum field strength in restrict band is $95.00 - 45.07 = 49.93$ dBuV/m, which is under 74 dBuV/m limit.

Average value = $49.93 - 30.10 = 19.83$ dBuV/m, which is under 54dBuV/m limit.

*The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 5$ per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125/100) = -30.1$ dB.

Average value = peak reading -30.10



NOTE 2:



The band edge emission plot on the next second page shows 46.28dBc between carrier maximum power and local maximum emission in restrict band (2.49700GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 95.94dBuV/m (Peak), so the maximum field strength in restrict band is $95.94 - 46.28 = 49.66$ dBuV/m, which is under 74 dBuV/m limit.

Average value = $49.66 - 30.10 = 19.56$ dBuV/m, which is under 54dBuV/m limit.

*The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 5$ per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125/100) = -30.1$ dB.

Average value = peak reading -30.10







4.9. ANTENNA REQUIREMENT

4.9.1. STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.9.2. ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is PIFA antenna without antenna connector. The maximum gain of this antenna is 0dBi.



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, NCC
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.