



RF EXPOSURE REPORT

REPORT NO.: SA960418L27

MODEL NO.: Magellan CrossOverGPS 3150

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: MITAC INTERNATIONAL CORP.

ADDRESS: 6TH FL., NO. 187, TIDING BLVD., SEC. 2, NEI-HU,
TAIPEI, TAIWAN, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang 244,
Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

	Pout (dBm)	Pout (mW)
Conducted Power	2.390	1.734
EIRP Power	2.390	1.734

***Note:** The antenna is PIFA antenna with 0dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 1.734mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold