

TEST REPORT

of

FCC/IC SAR

New Application; Class I PC; Class II PC

Product: Outdoor Navigation Device
Brand: Magellan, Mio, Navman, Mitac
Mode: N429
Model Difference: N/A
FCC ID: P4Q-N429
IC: 2420C-N429
Standard: FCC 47 CFR Part2(2.1093)
IEEE C95.1-1999; IEEE 1528: 2013
FCC OET 65 Supplement C(Edition 01-10)
RSS-102 issue 4: 2010
Applicant: Mitac International Corporation
Address: Building B, No. 209, Sec. 1, Nan Gang Rd.,
Nan Gang Dist., Taipei, 11568, Taiwan, R.O.C.

Test Performed by:
International Standards Laboratory

<Lung-Tan LAB>

*Site Registration No.: TAF: 0997

*Address:

No. 120, Lane 180, San Ho Tsuen, Hsin Ho Rd.

Lung-Tan Hsiang, Tao Yuan County 325, Taiwan

*Tel : 886-3-407-1718; Fax: 886-3-407-1738

Report No.: ISL-14LR081FSAR
Issue Date : 2014/04/16



Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This report MUST not be used to claim product endorsement by TAF or any agency of the Government.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory.

VERIFICATION OF COMPLIANCE

Applicant: Mitac International Corporation
Product Description: Outdoor Navigation Device
Brand Name: Magellan, Mio, Navman, Mitac
Model No.: N429
Model Difference: N/A
FCC ID: P4Q-N429
IC: 2420C-N429
Date of Receipt: 2014/04/01
Date of Test: 2014/04/15
Standard: FCC 47 CFR Part2(2.1093)
IEEE C95.1-1999; IEEE 1528: 2013
FCC OET 65 Supplement C(Edition 01-10)
RSS-102 issue 4: 2010

We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By: Dino Chen **Date:** 2014/04/16
Dino Chen / Engineer

Prepared By: Arno Hsieh **Date:** 2014/04/16
Arno Hsieh / Supervisor

Approved By: Vincent Su **Date:** 2014/04/16
Vincent Su / Technical Manager

Version

Version No.	Date	Description
00	2014/04/16	Initial creation of document

Table of Contents

1 STATEMENT OF COMPLIANCE..... 5

2 GENERAL INFORMATION..... 7

2.1 DESCRIPTION OF DEVICE UNDER TEST (DUT)..... 7

2.2 DUT PHOTOS..... 9

2.3 APPLIED STANDARDS 9

2.4 DEVICE CATEGORY AND SAR LIMITS 9

2.5 TEST ENVIRONMENT..... 9

2.6 TEST CONFIGURATION..... 9

3 SPECIFIC ABSORPTION RATE (SAR) 10

3.1 INTRODUCTION 10

3.2 SAR DEFINITION 10

4 SAR MEASUREMENT SYSTEM..... 11

4.1 ALSAS-10U SYSTEM DESCRIPTION 11

4.2 E-FIELD PROBE ALS-E-020S 12

4.3 DAQ-PAQ (ANALOG TO DIGITAL ELECTRONICS) ALS-DAQ-PAQ-3 BOUNDARY DETECTION
UNIT ALS-PMDPS-3..... 14

4.4 AXIS ARTICULATED ROBOT ALS-F3 16

4.5 ALSAS UNIVERSAL WORKSTATION ALS-UWS..... 16

4.6 SAM PHANTOMS ALS-P-SAM-L / ALS-P-SAM-R..... 17

4.7 UNIVERSAL DEVICE POSITIONER 19

4.8 TEST EQUIPMENT LIST 20

5 TISSUE SIMULATING LIQUIDS..... 21

6 SAR MEASUREMENT EVALUATION 23

7 DUT TESTING POSITION 25

8 SAR MEASUREMENT PROCEDURES..... 28

9 SAR TEST RESULTS..... 30

9.1 CONDUCTED POWER TABLE:..... 30

9.2 TEST RECORDS FOR BODY SAR TEST 32

9.3 RSS 102, IC NOTICE 2012-DRS0529: SAR CORRECTION FOR MEASURED
CONDUCTIVITY AND RELATIVE PERMITTIVITY BASED ON IEC 62209-2
STANDARD 33

10 EXPOSURE ASSESSMENT MEASUREMENT UNCERTAINTY 35

APPENDIX A TEST SETUP PHOTOS..... 36

APPENDIX B DUT PHOTOS..... 39

APPENDIX C: SYSTEM PERFORMANCE CHECK..... 39

APPENDIX D: SAR MEASUREMENT DATA 39

APPENDIX E: PROBE CALIBRATION CERTIFICATE..... 39

APPENDIX F: DIPOLE CALIBRATION CERTIFICATE..... 39

1 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) were found during testing for EUT, which are as follows (with expanded uncertainty 21.4 % for 300 MHz to 3 GHz).

Wifi mode:

Type	FCC Equipment Class	Position	SAR 1g(W/kg)
802.11b	DTS	Body, 0cm distance	0.283
802.11n 20n	DTS	Body, 0cm distance	0.207

BT mode(Worst Case):

Type	FCC Equipment Class	Position	SAR 1g(W/kg)
BT (BLE)	DTS	Body, 0cm distance	0.001

Simultaneous transmission mode:

Type	FCC Equipment Class	Position	SAR 1g(W/kg)
802.11 b+BT(by Calculated), Note 1	DTS+DSS	Body, 0cm distance	0.283+0.001=0.284

Note 1: Simultaneous transmission mode: The BT share same antenna with Wifi, the stand-alone of worst mode(BLE mode) of BT SAR was evaluated.

FCC SAR test exclusion for BT mode:

The Max average output power of BT(BDR, EDR1, EDR2 and BLE) is 7.05dBm (0.00507 W), According to FCC SAR test exclusion and IC Exemption from Routine Evaluation Limits, BT SAR measurement is not necessary.

According to KDB 447498 D01 V5, Appendix A: SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm, the thresholds power level is 10mW (10dBm) at 5 mm.

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distance ≤ 50mm are determined by

$$\frac{\text{max. power of channel [mW]}}{\text{min. test separation distance [mm]} \cdot \sqrt{f[\text{GHz}]}} \leq \begin{cases} 3.0 & 1g \text{ SAR} \\ 7.5 & 10g \text{ SAR} \end{cases}$$

- f [GHz] is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

IC Exemption from Routine Evaluation Limits – SAR Evaluation: RSS 102 Issue 4

SAR evaluation is required if the separation distance between the user and the radiating element of the device is less than or equal to 20 cm, except when the device operates as follows:

above 2.2 GHz and up to 3 GHz inclusively, and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 20 mW for general public use and 100 mW for controlled use;

The device is in compliance with Specific Absorption Rate (SAR) for general population /uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093), RSS-102 Issue4:2010 and ANSI/IEEE C95.1-1999, and had been tested in accordance with the measurement methods and procedures specified in IEEE1528: 2013 and FCC OET Bulletin 65 Supplement C (Edition 01-01).

2 General Information

2.1 Description of Device Under Test (DUT)

General:

Product Name	Outdoor Navigation Device	
Brand Name	Magellan, Mio, Navman, Mitac	
Model Name	N429	
Model Difference	N/A	
USB port	One provided for Data link and battery charger	
Power Supply	5Vdc from AC/DC adapter or 3.7Vdc, 1500mAh Li-ion Battery	
	Adapter:	Model: MII050100; Supplier: TPT
GPS Receiver	1575MHz Receiver	
VOIP	N/A	

Bluetooth:

Bluetooth Version	V2.1 + EDR (GFSK + $\pi/4$ DQPSK + 8DPSK)	V4.0(GFSK)
Frequency Range	2402 – 2480MHz	2402 – 2480MHz
Channel number	79 channels	40 channels
Modulation type	Frequency Hopping Spread Spectrum	Wide band Modulation
Rated power	4 dBm(Peak)	8 dBm(Peak)
Max Measured Transmit Power	3.72 (Peak)	7.05 dBm (Peak)
Dwell Time	$\leq 0.4s$	N/A
Antenna Designation	PIFA Antenna 1.6dBi , share the same antenna with Wifi	

The EUT is compliance with Bluetooth EDR V2.1 +V4.0 Standard.

WLAN: 1Tx / 1Rx

Frequency Range:	802.11b/g/n HT20: 2412 – 2462MHz			
Channel number:	802.11b/g/n HT20: 11 channels			
Transmit Power:		Measured Peak Power at each Chain	Rated AV Power at each Chain	Tolerance
	802.11b:	16.296dBm	15.0 dBm	+/- 1dB
	802.11g:	22.78dBm	13.0 dBm	+/- 1dB
	802.11n HT20 :	22.78dBm	13.0 dBm	+/- 1dB
Modulation Technology	11b/g: DSSS, OFDM 11n: OFDM			
Modulation type:	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM			
Transition Rate:	802.11 b: 1/2/5.5/11 Mbps 802.11 g: 6/9/12/18/24/36/48/54 Mbps 802.11 n HT20MHz: 6.5 – 65Mbps			
Antenna Designation:	PIFA Antenna 1.6dBi			

The EUT is compliance with IEEE 802.11 b/g/n Standard.

ANT: 1Tx / 1Rx

Frequency Range:	2403 – 2481MHz
Modulation type:	GFSK
Transition Rate:	1M bps
Antenna Designation:	Fixed PIFA Antenna, 1.0dBi

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

2.2 DUT Photos

Please refer to Appendix B. see rf report.

2.3 Applied Standards

The Specific Absorption Rate (SAR) testing specification, method and procedure for this Notebook Computer is in accordance with the following standards:

FCC 47 CFR Part 2 (2.1093)

IEEE C95.1-1999

IEEE 1528: 2013

FCC OET Bulletin 65 Supplement C (Edition 01-01)

RSS-102 Issue 4: 2010

FCC KDB 447498 D01 General RF Exposure Guidance v05r01: 5/28/2013

FCC KDB 248227 v1.2: 05/2007

FCC KDB 558074 D01 DTS Meas Guidance v03r01: April 9, 2013

FCC KDB 941225 D07 UMPC Mini Tablet Devices v01: 5/28/2013

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r01: May 28, 2013

FCC KDB 865664 D02 RF Exposure Reporting v01r01: May 28, 2013

2.4 Device Category and SAR Limits

This device belongs to **portable** device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for **General Population/Uncontrolled** exposure should be applied for this device, it is **1.6 W/kg** as averaged over any 1 gram of tissue.

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit
Spatial Peak SAR (1g cube tissue for brain or body)	1.60 W/kg
Spatial Average SAR (whole body)	0.08 W/kg
Spatial Peak SAR (10g for hands, feet, ankles and wrist)	4.00 W/kg

2.5 Test Environment

Item	Required	Actual
Temperature (°C)	18-25°C	20 to 24 °C
Humidity (%RH)	30-70 %	< 60 %

2.6 Test Configuration

The device was controlled by using a test software to transmit TX power level at max continuously. Modulation type and Channel number are selected by software also.

3 Specific Absorption Rate (SAR)

3.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

4 SAR Measurement System

4.1 ALSAS-10U System Description

APREL Laboratories ALSAS-10U is fully optimized for the dosimetric evaluation of a broad range of wireless transceivers and antennas. Developed in line with the latest methodologies it is fully compliant with the technical and scientific requirements of IEEE 1528: 2013, IEC 62209 Part 1 & 2 (draft), CENELEC, ARIB, ACA, and the Federal Communications Commission. The system comprises of a six axes articulated robot which utilizes a dedicated controller.

ALSAS-10U uses the latest methodologies and FDTD modeling to provide a platform which is repeatable with minimum uncertainty.

Applications

ALSAS-10U is designed to cover the frequency range from 30MHz to 6GHz as per the IEC 62209 Part II (draft) standard. There is no limiting factor to the operating RF carrier frequency range for the ALSAS-10U system other than the phantoms chosen for testing. The ALSAS-10U has been designed to be modular and phantoms are integrated onto the Universal Workstation™ so as to allow for complete flexibility of the measurement process. This unique design allows for a fully flexible system which can be built around the exact needs of the user.

Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm² step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.



Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the ALSAS-10U software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 5x5x8 (8mmx8mmx5mm) providing a volume of 32mm in the X & Y axis, and 35mm in the Z axis.

ALSAS-10U Interpolation and Extrapolation Uncertainty

The overall uncertainty for the methodology and algorithms the used during the SAR calculation was evaluated using the data from IEEE 1528: 2013 based on the example f3 algorithm:


$$f_3(x, y, z) = A \frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2} \cdot \left(e^{-\frac{2z}{a}} + \frac{a^2}{2(a + 2z)^2} \right)$$

Refer to raw data for measurement uncertainty

4.2 E-Field Probe ALS-E-020S

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change. A number of methods is used for calibrating probes, and these are outlined in the table below:

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



SAR is assessed with a calibrated probe which moves at a default height of 5mm from the center of the diode, which is mounted to the sensor, to the phantom surface (in the Z Axis). The 5mm offset height has been selected so as to minimize any resultant boundary effect due to the probe being in close proximity to the phantom surface.

The following algorithm is an example of the function used by the system for linearization of the output from the probe when measuring complex modulation schemes.

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

4.2.1 E-Field Probe Specification

Model: ALS-E-020S

Compliant Standards	IEEE 1528: 2013, IEC 62209 Part 1 & 2 (draft)
Frequency Range	30 MHz ~ 6 GHz
Sensitivity	Better than 0.8 μ V/(V/m) ²
Dynamic Range SAR	0.001 W/kg to 100 W/kg
Isotropic Response Axial	Typically ± 0.1dB
Hemispherical isotropy	±0.3 dB or better
Linearity	±0.2 dB or better
Probe Tip Radius	User selectable all <5 mm
Sensor Offset	1.56 (± 0.02 mm)
Probe Length	290 mm
Video Bandwidth	@ 500 Hz: 1 dB @ 1K Hz: 3 dB
Boundary Effect	Less than 2% for distances greater than 2.4 mm
Material	Ertalyte™
Connector	6 Pin Bayonet

E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than ± 10%. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

Boundary Detection Unit and Probe Mounting Device


ALSAS-10U incorporates a boundary detection unit with a sensitivity of 0.05mm for detecting all types of surfaces. The robust design allows for detection during probe tilt (probe normalize) exercises, and utilizes a second stage emergency stop. The signal electronics are fed directly into the robot controller for high accuracy surface detection in lateral and axial detection modes (X, Y, & Z).

The probe is mounted directly onto the Boundary Detection unit for accurate tooling and displacement calculations controlled by the robot kinematics. The probe is connect to an isolated probe interconnect where the output stage of the probe is fed directly into the amplifier stage of the Daq-Paq.

4.3 DAQ-PAQ (Analog to Digital Electronics) ALS-DAQ-PAQ-3 Boundary Detection Unit ALS-PMDPS-3

ALSAS-10U incorporates a fully calibrated Daq-Paq (analog to digital conversion system) which has a 4 channel input stage, sent via a 2 stage auto-set amplifier module. The input signal is amplified accordingly so as to offer a dynamic range from 4 μV to 330 mV. Integration of the fields measured is carried out at board level utilizing a Co-Processor which then sends the measured fields down into the main computational module in digitized form via an RS232 communications port. Probe linearity and duty cycle compensation is carried out within the main Daq-Paq module.

PMDPS is used to hold a probe and to detect complex boundary locations (curved and flat surfaces) during a SAR or HAC assessment process. It utilizes relative movements of internal components to trigger integrated micro-sensor mechanisms in order to detect boundary(s) and consequently position the probe at the specified distance relative to a boundary in order to achieve accurate and repeatable measurements.



Amplifier Range	4 μ V to 330 mV
ADC	16 Bit optically isolated
Built-in E-Stop Feature	Emergency Stop feature to prevent damage of equipment and for user safety purposes
Field Integration	Local Co-Processor utilizing proprietary integration algorithms
SAR Dynamic Range	0.001 W/kg -100 W/kg.
Ambient Noise	Below 0.001 W/kg measured with probe in tissue
LED Indication	Boundary detection and DAQ-PAQ State
Number of Input Channels	4 in total 3 dedicated and 1 spare for future upgrades (when and if needed)
Communication	Optically isolated packet data via RS232
Robot Arm Integration	DAQ-PAQ and Boundary Detection Unit are mounted directly onto joint 6 of the F3 arm utilizing joint 6 tool (ISO Standard M8 Mounting Plate) to allow easy integration and removal (no angular interface)
Supply	DC supply powered by an isolated external supply unit (no battery required)
LED Indicators	Probe status (amplifier on) and boundary detection

PMDPS Specification details

Accuracy of Positioning	Better than 10 μ m at 6GHz
SAR Uncertainty	Better than 0.01 W/kg SAR at 6Gz
Detection Mechanism	2 x 360° Stage Axial and Lateral Detection at 6GHz
Emergency Stop	4 Stage 360° Axial and Lateral Detection at 6GHz
Probe Mounting	6 Pin Bayonet for Fast Probe Change
Calibration	Every PMDPS is Calibrated to 0.01 W/kg SAR at 6GHz
Reliability Expectations	Better Than 10,000,000 Cycles

4.4 Axis Articulated Robot ALS-F3




ALSAS-10U utilizes a six axis articulated robot, which is controlled using a Pentium based real-time movement controller. The movement kinematics engine utilizes proprietary (Thermo CRS) interpolation and extrapolation algorithms, which allow full freedom of movement for each of the six joints within the working envelope. Utilization of joint 6 allows for full probe rotation with a tolerance better than 0.05mm around the central axis.


Robot/Controller Manufacturer	Thermo CRS
Number of Axis	Six independently controlled axis
Positioning Resolution	0.05mm
Controller Type	Single phase Pentium based C500C
Robot Reach	710mm
Repeatability	0.05mm or better
Communication	RS232 and LAN compatible

4.5 ALSAS Universal Workstation ALS-UWS

ALSAS Universal workstation allows for repeatability and fast adaptability. It allows users to do calibration, testing and measurements using different types of phantoms with one set up, which significantly speeds up the measurement process.



Workstation.
Top view (rendering)




Workstation
without robot (rendering)

4.6 SAM Phantoms ALS-P-SAM-L / ALS-P-SAM-R

The ALSAS-10U allows the integration of multiple phantom types. SAM Phantoms fully compliant with IEEE 1528: 2013, Universal Phantom, and Universal Flat.

APREL SAM Phantoms

The SAM phantoms developed using the IEEE SAM CAD file. They are fully compliant with the requirements for both IEEE 1528: 2013 and FCC Supplement C. Both the left and right SAM phantoms are interchangeable, transparent and include the IEEE 1528: 2013 grid with visible NF and MB lines.



Compliant Standards	IEEE-1528: 2013, IEC 62209 Part 1 & 2 (draft)
SAM	In accordance with the IEEE 1528: 2013 standard
Material	Composite urethane which allows for the device to be viewed through the phantom, resistant to DGBE
Phantom Shell Shape Tolerance	Fully calibrated to be better than ± 0.2 mm
Frame Material	Corian®
Tissue Simulation Volume	7 liter with 15.0 ± 0.5 cm tissue
Thickness	2 mm ± 0.2 mm 6 mm ± 0.2 mm at NF/MB intersection
Loss Tangent	<0.05
Relative Permittivity	<5
Resistant to Solvents	Resistant to all solvents used for tissue manufacturing detailed in IEEE 1528: 2013
Load Deflection	<1mm with sugar water compositions
Manufacturing Process	Injection Molded
Phantom Weight	Less than 10kg when filled with 15cm of simulation tissue

Universal Phantom ALS-P-UP-1

The Universal Phantom is used on the ALSAS-10U as a system validation phantom. The Universal Phantom has been fully validated both experimentally from 800MHz to 6GHz and numerically using XFDTD numerical software. The shell thickness is 2mm overall, with a 4mm spacer located at the NF/MB intersection providing an overall thickness of 6mm in line with the requirements of IEEE-1528: 2013.



The design allows for fast and accurate measurements, of handsets, by allowing the conservative SAR to be evaluated at on frequency for both left and right head experiments in one measurement.


Compliant Standards	IEEE-1528: 2013, IEC 62209 Part 1 & 2 (draft), CENELEC, and others
Manufacturing Process	Injection molded
Material	Vivac
Phantom Shell Shape Tolerance	Less than ± 0.2 mm
Frame Material	Corian®
Tissue Simulation Volume	8 liter with 15.0 ± 0.5 cm tissue
Thickness	2mm ± 0.2 mm 6mm at NF/MB intersection
Loss Tangent	<0.05
Relative Permittivity	<5
Resistant to Solvents	Resistant to all solvents detailed in IEEE 1528: 2013
Load Deflection	<1mm with heaviest tissue (sugar water compositions)
Dimensions	Length 220mm x breadth 170mm
Phantom Weight	Less than 10kg when filled with 15cm of simulation tissue

4.7 Universal Device Positioner

ALS-H-E-SET-2

The universal device positioner allows complete freedom of movement of the EUT. Developed to hold a EUT in a free-space scenario any additional loading attributable to the material used in the construction of the positioner has been eliminated. Repeatability has been enhanced through the linear scales which form the design used to indicate positioning for any given test scenario in all major axes. A 15° tilt indicator is included for the of aid cheek to tilt movements for head SAR analysis. Overall uncertainty for measurements has been reduced due to the design of the Universal device positioner, which allows positioning of a device in as near to a free-space scenario as possible, and by providing the means for complete repeatability.

Compliant Standards	IEEE 1528: 2013, IEC 62209 Part 1 & 2 (draft)
Dielectric constant	Less than 5.0
Loss Tangent	Less than 0.05
Number of Axis	6 axis freedom of movement (8 when utilized with ALSAS-10U Workstation)
Translation Along MB Line	± 76.2 mm
Translation Along NF Line	± 38.1 mm
Translation Along Z Axis	± 25.4 mm (expandable up to 500 mm)
Rotation Around MB Line (yaw)	±10°
Rotation Around NF (pitch)	± 30°
Line Rotation (roll)	360° full circle
Maximum Grip Range	0 mm to 150 mm
Material	Resistant to DGBE and all other tissue stimulant materials as listed in IEEE 1528: 2013 Annex C.1.
Tilt Movement	Full movement with built-in 15° gauge



4.8 Test Equipment List

Equipment Type	MFR	Model No.	Serial No.	Last Cal.	Cal. Due Date
Vector Network Analyzer	Agilent	E5071B	MY42402726	11/23/2013	11/22/2014
Dielectric Probe Kit	Agilent	85070E	MY44300124	N/A	N/A
Vector Signal Generator	R&S	SMU200A	102330	02/19/2014	02/18/2015
Power Meter	Anritsu	ML2495A	1116010	04/19/2013	04/18/2014
Power Sensor	Anritsu	MA2411B	34NKF50	04/19/2013	04/18/2014
Data Acquisition Package	Apriel	ALS-DAQ-PAQ-3	110-00220	NA	NA
Apriel Laboratories Probe	Apriel	ALS-E020	266	03/19/2014	03/18/2015
Apriel Reference Dipole 1900MHz	Apriel	ALS-D-1900-S-2	1900-210-00703-Re-Issue	08/24/2012	08/23/2015
Apriel Reference Dipole 900MHz	Apriel	ALS-D-900-S-2	900-190-00603	08/20/2012	08/19/2015
Apriel Reference Dipole 1750MHz	Apriel	ALS-D-1750-S-2	198-00303	02/20/2013	08/19/2015
Boundary Detection Sensor System	Apriel	ALS-PMDPS-3	120-00266	N/A	N/A
Universal Work Station	Apriel	ALS-UWS	100-00153	N/A	N/A
Device Holder 2.0	Apriel	ALS-H-E-SET-2	170-00503	N/A	N/A
Left Head SAM Phantom	Apriel	ALS-P-SAM-L	130-00305	N/A	N/A
Right Head SAM Phantom	Apriel	ALS-P-SAM-R	140-00359	N/A	N/A
Universal Phantom	Apriel	ALS-P-UP-1	150-00405	N/A	N/A
Apriel Dipole Spacer	Apriel	ALS-DS-U	250-00903	N/A	N/A
SAR Software	Apriel	ALSAS-10U Ver.2.5.0.261	B0D5F-112FE	N/A	N/A
CRS C500C Controller	Thermo	ALS-C500	RCF0440278	N/A	N/A
CRF F3 Robot	Thermo	ALS-F3	RAF0440252	N/A	N/A
Power Amplifier	Mini-Circuit	ZVE-8G	D030305	N/A	N/A

Note: All equipment upon which need to be calibrated are with calibration period of 1 year.

5 Tissue Simulating Liquids

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in IEEE1528: 2013 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in IEEE1528: 2013 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in IEEE1528: 2013.

Target Frequency (MHz)	Parameters(Body) IEEE1528: 2013 OTE 65		Parameters(Head) 62209-1/-2 IEEE1528: 2013 OET65	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
835	55.2	0.97	41.5	0.90
900	55.0	1.05	41.5	0.97
1800 – 2000	53.3	1.52	40.0	1.4
2450	52.7	1.95	39.2	1.8
5800	48.2	6.00	35.3	5.27

(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using Agilent Dielectric Probe Kit 85070E and Agilent E5071B Vector Network Analyzer


Body Tissue Simulant Measurement				
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		ϵ_r	σ [s/m]	
2450MHz	Reference result ± 5% window	52.7 50.065 to 55.335	1.95 1.8525 to 2.0475	N/A
	Apr 15, 2014	53.4409	1.9137	21.4
2412MHz	Apr 15, 2014	53.1203	1.9096	21.4
2442MHz	Apr 15, 2014	53.2866	1.9101	21.4
2462MHz	Apr 15, 2014	53.7413	1.9288	21.4

6 SAR Measurement Evaluation

Each system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the APREL SAR software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole

Validation Dipoles

The dipoles used is based on the IEEE-1528: 2013 standard, and is complied with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical specifications for the dipoles.

*	Frequency	L (mm)	h (mm)	d (mm)
	835MHz	161.0	89.8	3.6
	900MHz	149.0	83.3	3.6
	1800MHz	72.0	41.7	3.6
	1900MHz	68.0	39.5	3.6
v	2450MHz	51.5	30.4	3.6
	5200MHz	23.6	14.0	3.6
	5600MHz	21.61	18.22	3.6
	5800MHz	21.6	12.6	3.6

*Note: “V” indicates Frequency used of EUT

The output power on dipole port must be calibrated to 30 dBm (1W) before dipole is connected.

Validation Result



Comparing to the Yearly Calibration SAR value provided by A P R E L , the validation data should be within its specification of 5 %. Table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix E of this report.


Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
2450 MHz	Reference result ± 5% window	55.57 52.79 to 58.38	25.8 24.51 to 27.09	N/A
	Apr 15, 2014	54.069	24.462	21.6

Note: All SAR values are normalized 1W.

7 DUT Testing Position

Test Positions of Device Relative to Head

This specifies exactly two test positions for the handset against the head phantom, the “cheek” position and the “tilted” position. The handset should be tested in both positions on the left and right sides of the SAM phantom. If the handset construction is such that it cannot be positioned using the handset positioning procedures described in 4.2.2.1 and 4.2.2.2 to represent normal use conditions (e.g., asymmetric handset), alternative alignment procedures should be considered with details provided in the test report.




Definition of the “Cheek” Position

The “cheek” position is defined as follows:

- a. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece, open the cover. (If the handset can also be used with the cover closed both configurations must be tested.)
- b. Define two imaginary lines on the handset: the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A on Figures 4.1a and 4.1b), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 4.1a). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output. However, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 4.1b), especially for clamshell handsets, handsets with flip pieces, and other irregularly-shaped handsets.
- c. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 4.2), such that the plane defined by the vertical center line and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.


- d. Translate the handset towards the phantom along the line passing through RE and LE until the handset touches the pinna.
- e. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to MB-NF including the line MB (called the reference plane).
- f. Rotate the handset around the vertical centerline until the handset (horizontal line) is symmetrical with respect to the line NF.
- g. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE and maintaining the handset contact with the pinna, rotate the handset about the line NF until any point on the handset is in contact with a phantom point below the pinna (cheek). See Figure 4.2 the physical angles of rotation should be noted.



Definition of the “Tilted” Position

The “tilted” position is defined as follows:

- a. Repeat steps (a) – (g) of 4.2.1.1 to place the device in the “cheek position.”
- b. While maintaining the orientation of the handset move the handset away from the pinna along the line passing through RE and LE in order to enable a rotation of the handset by 15 degrees.
- c. Rotate the handset around the horizontal line by 15 degrees.
- d. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilted position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna (e.g., the antenna with the back of the phantom head), the angle of the handset should be reduced. In this case, the tilted position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is contact with the phantom (e.g., the antenna with the back of the head).



Test Positions for body-worn

Body-worn operating configurations should be tested without the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. A separation distance of **0.5** cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distance may be use, but not exceed 2.5 cm.

The DUT has only body mode test positions and test mode refer to section 8.2

8 SAR Measurement Procedures

The measurement procedures are as follows:

- (a) through software control to continuous transmit
- (b) Set software to maximum output power and data rate
- (c) Measure output power through RF cable and power meter
- (d) Place the DUT in the positions described in the last section
- (e) Set scan area, grid size and other setting on the APREL software
- (f) Taking data for the maximum power on each testing position
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for the other channels in worst SAR testing position

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The APREL SAR software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

SAR Averaged Methods

In APREL, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

9 SAR Test Results

9.1 Conducted power table:

WIFI power measurement

802.11b

Cable loss = 0		Output Power		Limit (dBm)
CH	Frequency (MHz)	Detector		
		PK (dBm)	AV (dBm)	
1	2412	16.29	14.27	30
7	2442	16.21	14.16	
11	2462	16.17	14.11	

802.11g

Cable loss = 0		Output Power		Limit (dBm)
CH	Frequency (MHz)	Detector		
		PK (dBm)	AV (dBm)	
1	2412	22.67	12.56	30
7	2442	22.78	12.78	
11	2462	22.65	12.56	

802.11N 20MHz

Cable loss = 0		Output Power		Limit (dBm)
CH	Frequency (MHz)	Detector		
		PK (dBm)	AV (dBm)	
1	2412	22.7	12.12	30
7	2442	22.78	12.24	
11	2462	22.75	12.35	

BT power measurement

BDR Mode

Frequency (MHz)	Peak Reading Power (dBm)	Output Power (dBm)	Output Power (W)	Limit (W)
2402.00	3.72	3.72	0.00236	1
2441.00	3.67	3.67	0.00233	1
2480.00	3.39	3.39	0.00218	1

EDR 2M Mode

Frequency (MHz)	Peak Reading Power (dBm)	Output Power (dBm)	Output Power (W)	Limit (W)
2402.00	2.89	2.89	0.00195	1
2441.00	2.85	2.85	0.00193	1
2480.00	2.83	2.83	0.00192	1

EDR 3M Mode

Frequency (MHz)	Peak Reading Power (dBm)	Output Power (dBm)	Output Power (W)	Limit (W)
2402.00	3.37	3.37	0.00217	1
2441.00	3.31	3.31	0.00214	1
2480.00	3.27	3.27	0.00212	1

LE Mode

Frequency (MHz)	Peak Reading Power (dBm)	Output Power (dBm)	Output Power (W)	Limit (W)
2402.00	6.67	6.67	0.00465	1
2442.00	7.07	7.07	0.00509	1
2480.00	7.05	7.05	0.00507	1

9.2 Test Records for Body SAR Test

Ambient Temperature (°C) : 21.5	Relative Humidity (%) : 60
Liquid Temperature (°C) : 22	Depth of Liquid (cm) : >15

Data No:	Test Mode	Test Position	Separation Distance (cm)	Ch.	Measured Avg Power(dBm)	Tune-up maximum limit(dBm)	Scaling factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)
1	802.11b	Bottom	0	1	14.27	16	1.12	0.156	0.175
2	802.11b	Top Side	0	1	14.27	16	1.12	0.036	0.040
3	802.11b	Right Side	0	1	14.27	16	1.12	0.252	0.283
4	802.11b	Right Side	0	7	14.16	16	1.13	0.223	0.252
5	802.11b	Right Side	0	11	14.11	16	1.13	0.238	0.270
6	802.11n 20	Right Side	0	11	12.24	14	1.14	0.181	0.207
7	BLE	Right Side	0	20	7.07	9	1.27	0.001	0.001
Note:	Scaling factor=Conducted Power/Tune-up maximum limit Scaled SAR=Measure SAR*Scaling factor								

Remark:

1. According KDB 248227 not required for 802.11g less than 1/4 higher than 802.11b Refer to section 8.1 for power measurement data.
2. According KDB 447498 D01 section 1(e) for highest output channel is less than 0.8 W/kg for <100MHz bandwidth or 0.4 W/kg for <200MHz Bandwidth testing for the other channels is not required
3. According KDB 447498 D01 Appendix A, the power level is lower than the SAR Test Exclusion Thresholds VS real distance between edge of EUT to TX antenna then the position will not require for SAR measurement.

9.3 RSS 102, IC NOTICE 2012-DRS0529: SAR CORRECTION FOR MEASURED CONDUCTIVITY AND RELATIVE PERMITTIVITY BASED ON IEC 62209-2 STANDARD

Body Tissue Simulant Measurement									
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]	C_{ϵ}	C_{σ}	$\Delta\epsilon$	$\Delta\sigma$	ΔSAR SAR
		ϵ_r	s [s/m]						
	Reference result	52.7	1.95	N/A					
	± 5% window	50.065 to 55.335	1.852 to 2.047						
2412	Apr. 15, 2014	53.1203	1.9096	21.4	-0.23	0.49	0.80	-2.07	-1.19
2442	Apr. 15, 2014	53.2866	1.9101	21.4	-0.22	0.48	1.11	-2.05	-1.24
2462	Apr. 15, 2014	53.7413	1.9288	21.4	-0.22	0.48	1.98	-1.09	-0.96

Data No:	Test Mode	Test Position	Separation Distance (cm)	Ch.	ΔSAR_i	Measured SAR 1g(W/kg)	Corrected SAR 1g(W/kg)
1	802.11b	Bottom	0	1	-1.19	0.156	0.158
2	802.11b	Top Side	0	1	-1.19	0.036	0.036
3	802.11b	Right Side	0	1	-1.19	0.252	0.255
4	802.11b	Right Side	0	7	-1.24	0.223	0.226
5	802.11b	Right Side	0	11	-0.96	0.238	0.240
6	802.11n 20	Right Side	0	11	-0.96	0.181	0.183
7	BLE	Right Side	0	20	-1.24	0.001	0.001

Note:

Scaling factor=Conducted Power/Tune-up maximum limit

Scaled SAR=Measure SAR*Scaling factor

F.2 SAR correction formula

From [13] and [14], a linear relationship was found between the percent change in SAR (denoted ΔSAR) and the percent change in the permittivity and conductivity from the target values in Table 1 (denoted $\Delta \epsilon_r$ and $\Delta \sigma$, respectively). This linear relationship agrees with the results of Kuster and Balzano [48] and Bit-Babik et al. [2]. The relationship is given by:

$$\Delta SAR = c_\epsilon \Delta \epsilon_r + c_\sigma \Delta \sigma \tag{F.1}$$

where

- $c_\epsilon = \partial(\Delta SAR)/\partial(\Delta \epsilon)$ is the coefficients representing the sensitivity of SAR to permittivity where SAR is normalized to output power;
- $c_\sigma = \partial(\Delta SAR)/\partial(\Delta \sigma)$ is the coefficients representing the sensitivity of SAR to conductivity, where SAR is normalized to output power.

The values of c_ϵ and c_σ have a simple relationship with frequency that can be described using polynomial equations. For the 1 g averaged SAR c_ϵ and c_σ are given by

$$c_\epsilon = -7,854 \times 10^{-4} f^3 + 9,402 \times 10^{-3} f^2 - 2,742 \times 10^{-2} f - 0,2026 \tag{F.2}$$


$$c_\sigma = 9,804 \times 10^{-3} f^3 - 8,661 \times 10^{-2} f^2 + 2,981 \times 10^{-2} f + 0,7829 \tag{F.3}$$

where

f is the frequency in GHz.

$$\text{Corrected SAR} = \text{Measured SAR} * ((100 + (\Delta SAR \times -1)) / 100) \tag{Equation 1}$$

Antenna Location




10 Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	c_i^{-1} (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	\sqrt{cp}	4.4	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	1	2.7	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	1	0.5	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1	1.7	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	1.2	rectangular	$\sqrt{3}$	1	1	0.7	0.7
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	1	2.0	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	0.5	2.0	1.4
Liquid Conductivity(meas.)	2.9	normal	1	0.7	0.5	2.0	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	0.5	1.7	1.4
Liquid Permittivity(meas.)	3.3	normal	1	0.6	0.5	2.0	1.6
Combined Uncertainty		RSS				9.7	9.3
Combined Uncertainty (coverage factor=2)		Normal(k=2)				19.4	18.7

Appendix A Test Setup Photos

Bottom



Top Side



Right Side



Appendix B DUT Photos

Refer to FCC Part15.247 report.

Appendix C: System Performance Check

Refer to Appendix C

Appendix D: SAR Measurement Data

Refer to Appendix D

Appendix E: Probe Calibration Certificate

Refer to Appendix E

Appendix F: Dipole Calibration Certificate

Refer to Appendix F

~ end of Report ~

Appendix C: System Performance Check

Report Date : 15-Apr-2014
By Operator : Dino Chen
DUT : Dipole
Frequency : 2450.00 MHz
Max. Transmit Pwr : 1 W

APREL ALSAS-10U System Description

Phantom Data

Name : Universal Phantom
Type : ALS-P-UP-1

Tissue Data

Type : Body
Frequency : 2450.00 MHz


Probe Data

Name : E-field Probe
Model : ALS-E-020
Serial No. : 266
Last Calib. Date : 19-Mar-2015

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 21.6 °C
Ambient Temp. : 21.6 °C
Area Scan : 9x9x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
DUT Position : Touch
Separation : 10mm





1 gram SAR value : 54.069 W/kg
10 gram SAR value : 24.462 W/kg
Area Scan Peak SAR : 65.341 W/kg
Zoom Scan Peak SAR : 106.565 W/kg

Appendix D: SAR Measurement Data

Data No.	Band	Mode	Test Position	Separation Distance (cm)	Channel	SAR 1g(W/kg)
1	Wifi	802.11b	Bottom	0	1	0.156
2	Wifi	802.11b	Top Side	0	1	0.036
3	Wifi	802.11b	Right Side	0	1	0.252
4	Wifi	802.11b	Right Side	0	7	0.223
5	Wifi	802.11b	Right Side	0	11	0.238
6	Wifi	802.11n	Right Side	0	11	0.181
7	BT	BLE	Right Side	0	20	0.001

Data No. 1:

Report Date : 15-Apr-2014
By Operator : 123
Measurement Date : 15-Apr-2014
Starting Time : 15-Apr-2014 10:18:26 AM
End Time : 15-Apr-2014 10:42:36 AM
Scanning Time : 1450 secs
Product Data
Device Name : 14LR081
Serial No. : NA
Type : Other
Model : N429
Frequency : 2450.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 1 min(s)
Length : 105 mm
Width : 63 mm
Depth : 25 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.119 W/kg
Power Drift-Finish: 0.128 W/kg
Power Drift (%) : 7.790
Picture : C:\alsas\bitmap\Device-6.bmp

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 2450B
Frequency : 2450.00 MHz
Last Calib. Date : 15-Apr-2014
Temperature : 21.40 °C
Ambient Temp. : 21.40 °C
Humidity : 62.00 RH%
Epsilon (Dielectric Constant): 53.44
Sigma : 1.91 S/m
Density : 1000.00 kg/cu. m



Probe Data


Name : E-field
Model : E-020
Type : E-Field Triangle
Serial No. : 266
Last Calib. Date : 19-Mar-2015
Frequency : 2450.00 MHz
Duty Cycle Factor (CreF): 1
Conversion Factor : 4.6
Probe Sensitivity : 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point : 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 21.40 °C
Ambient Temp. : 21.40 °C
Set-up Date : 15-Apr-2014
Set-up Time : 8:01:50 AM
Area Scan : 9x10x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Low



The system detected 1 maxima.
 Selected highest maxima # = 1.
 Maxima #1 coordinates: X = -9.980, Y = -5.000
 1 gram SAR value : 0.156 W/kg
 10 gram SAR value : 0.059 W/kg
 Area Scan Peak SAR : 0.167 W/kg
 Zoom Scan Peak SAR : 0.370 W/kg

Maxima Summary:
 Maxima #1
 Maxima coordinates: X = -9.980, Y = -5.000
 1 gram SAR value : 0.156 W/kg
 10 gram SAR value : 0.059 W/kg
 Area Scan Peak SAR : 0.167 W/kg
 Zoom Scan Peak SAR : 0.370 W/kg



Data No. 2:

Report Date : 15-Apr-2014
By Operator : 123
Measurement Date : 15-Apr-2014
Starting Time : 15-Apr-2014 10:48:00 AM
End Time : 15-Apr-2014 11:12:03 AM
Scanning Time : 980 secs
Product Data
Device Name : 14LR081
Serial No. : NA
Type : Other
Model : N429
Frequency : 2450.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 1 min(s)
Length : 25 mm
Width : 63 mm
Depth : 105 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.071 W/kg
Power Drift-Finish: 0.064 W/kg
Power Drift (%) : -9.958
Picture : C:\alsas\bitmap\Device-3.bmp

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 2450B
Frequency : 2450.00 MHz
Last Calib. Date : 15-Apr-2014
Temperature : 21.40 °C
Ambient Temp. : 21.40 °C
Humidity : 62.00 RH%
Epsilon (Dielectric Constant): 53.44
Sigma : 1.91 S/m
Density : 1000.00 kg/cu. m



Probe Data


Name : E-field
Model : E-020
Type : E-Field Triangle
Serial No. : 266
Last Calib. Date : 19-Mar-2015
Frequency : 2450.00 MHz
Duty Cycle Factor (CreF): 1
Conversion Factor : 4.6
Probe Sensitivity : 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point : 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 21.40 °C
Ambient Temp. : 21.40 °C
Set-up Date : 15-Apr-2014
Set-up Time : 8:01:50 AM
Area Scan : 9x10x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Low



The system detected 1 maxima.
Selected highest maxima # = 1.
Maxima #1 coordinates: X = -2.900, Y = 0.000
1 gram SAR value : 0.036 W/kg
10 gram SAR value : 0.012 W/kg
Area Scan Peak SAR : 0.044 W/kg
Zoom Scan Peak SAR : 0.100 W/kg

Maxima Summary:
Maxima #1
Maxima coordinates: X = -2.900, Y = 0.000
1 gram SAR value : 0.036 W/kg
10 gram SAR value : 0.012 W/kg
Area Scan Peak SAR : 0.044 W/kg
Zoom Scan Peak SAR : 0.100 W/kg



Data No. 3:

Report Date : 15-Apr-2014
By Operator : 123
Measurement Date : 15-Apr-2014
Starting Time : 15-Apr-2014 08:59:17 AM
End Time : 15-Apr-2014 09:23:29 AM
Scanning Time : 1053 secs
Product Data
Device Name : 14LR081
Serial No. : NA
Type : Other
Model : N429
Frequency : 2450.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 1 min(s)
Length : 25 mm
Width : 105 mm
Depth : 63 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.260 W/kg
Power Drift-Finish: 0.232 W/kg
Power Drift (%) : -10.613
Picture : C:\alsas\bitmap\Device-4.bmp

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 2450B
Frequency : 2450.00 MHz
Last Calib. Date : 15-Apr-2014
Temperature : 21.40 °C
Ambient Temp. : 21.40 °C
Humidity : 62.00 RH%
Epsilon (Dielectric Constant): 53.44
Sigma : 1.91 S/m
Density : 1000.00 kg/cu. m



Probe Data


Name : E-field
Model : E-020
Type : E-Field Triangle
Serial No. : 266
Last Calib. Date : 19-Mar-2015
Frequency : 2450.00 MHz
Duty Cycle Factor (CreF): 1
Conversion Factor : 4.6
Probe Sensitivity : 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point : 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 21.40 °C
Ambient Temp. : 21.40 °C
Set-up Date : 15-Apr-2014
Set-up Time : 8:01:50 AM
Area Scan : 9x10x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Low



The system detected 1 maxima.
 Selected highest maxima # = 1.
 Maxima #1 coordinates: X = -7.960, Y = -5.000
 1 gram SAR value : 0.252 W/kg
 10 gram SAR value : 0.079 W/kg
 Area Scan Peak SAR : 0.349 W/kg
 Zoom Scan Peak SAR : 0.690 W/kg

Maxima Summary:
 Maxima #1
 Maxima coordinates: X = -7.960, Y = -5.000
 1 gram SAR value : 0.252 W/kg
 10 gram SAR value : 0.079 W/kg
 Area Scan Peak SAR : 0.349 W/kg
 Zoom Scan Peak SAR : 0.690 W/kg

Data No. 4:

Report Date : 15-Apr-2014
By Operator : 123
Measurement Date : 15-Apr-2014
Starting Time : 15-Apr-2014 09:51:18 AM
End Time : 15-Apr-2014 10:15:30 AM
Scanning Time : 1150 secs
Product Data
Device Name : 14LR081
Serial No. : NA
Type : Other
Model : N429
Frequency : 2450.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 1 min(s)
Length : 25 mm
Width : 105 mm
Depth : 63 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.288 W/kg
Power Drift-Finish: 0.171 W/kg
Power Drift (%) : -40.767
Picture : C:\alsas\bitmap\Device-4.bmp

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 2450B
Frequency : 2450.00 MHz
Last Calib. Date : 15-Apr-2014
Temperature : 21.40 °C
Ambient Temp. : 21.40 °C
Humidity : 62.00 RH%
Epsilon (Dielectric Constant): 53.44
Sigma : 1.91 S/m
Density : 1000.00 kg/cu. m



Probe Data


Name : E-field
Model : E-020
Type : E-Field Triangle
Serial No. : 266
Last Calib. Date : 19-Mar-2015
Frequency : 2450.00 MHz
Duty Cycle Factor (CreF): 1
Conversion Factor : 4.6
Probe Sensitivity : 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point : 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 21.40 °C
Ambient Temp. : 21.40 °C
Set-up Date : 15-Apr-2014
Set-up Time : 8:01:50 AM
Area Scan : 9x10x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Mid



The system detected 1 maxima.
Selected highest maxima # = 1.
Maxima #1 coordinates: X = -4.920, Y = -5.000
1 gram SAR value : 0.223 W/kg
10 gram SAR value : 0.067 W/kg
Area Scan Peak SAR : 0.367 W/kg
Zoom Scan Peak SAR : 0.650 W/kg

Maxima Summary:
Maxima #1
Maxima coordinates: X = -4.920, Y = -5.000
1 gram SAR value : 0.223 W/kg
10 gram SAR value : 0.067 W/kg
Area Scan Peak SAR : 0.367 W/kg
Zoom Scan Peak SAR : 0.650 W/kg



Data No. 5:

Report Date : 15-Apr-2014
By Operator : 123
Measurement Date : 15-Apr-2014
Starting Time : 15-Apr-2014 11:20:10 AM
End Time : 15-Apr-2014 11:44:31 AM
Scanning Time : 1055 secs
Product Data
Device Name : 14LR081
Serial No. : NA
Type : Other
Model : N429
Frequency : 2450.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 1 min(s)
Length : 25 mm
Width : 105 mm
Depth : 63 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.230 W/kg
Power Drift-Finish: 0.215 W/kg
Power Drift (%) : -6.684
Picture : C:\alsas\bitmap\Device-4.bmp

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 2450B
Frequency : 2450.00 MHz
Last Calib. Date : 15-Apr-2014
Temperature : 21.40 °C
Ambient Temp. : 21.40 °C
Humidity : 62.00 RH%
Epsilon (Dielectric Constant): 53.44
Sigma : 1.91 S/m
Density : 1000.00 kg/cu. m



Probe Data


Name : E-field
Model : E-020
Type : E-Field Triangle
Serial No. : 266
Last Calib. Date : 19-Mar-2015
Frequency : 2450.00 MHz
Duty Cycle Factor (CreF): 1
Conversion Factor : 4.6
Probe Sensitivity : 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point : 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 21.40 °C
Ambient Temp. : 21.40 °C
Set-up Date : 15-Apr-2014
Set-up Time : 8:01:50 AM
Area Scan : 9x10x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : High



The system detected 1 maxima.
Selected highest maxima # = 1.
Maxima #1 coordinates: X = -7.930, Y = 2.900
1 gram SAR value : 0.238 W/kg
10 gram SAR value : 0.073 W/kg
Area Scan Peak SAR : 0.307 W/kg
Zoom Scan Peak SAR : 0.650 W/kg

Maxima Summary:

Maxima #1

Maxima coordinates: X = -7.930, Y = 2.900

1 gram SAR value : 0.238 W/kg

10 gram SAR value : 0.073 W/kg

Area Scan Peak SAR : 0.307 W/kg

Zoom Scan Peak SAR : 0.650 W/kg

Data No. 6:

Report Date : 15-Apr-2014
By Operator : 123
Measurement Date : 15-Apr-2014
Starting Time : 15-Apr-2014 06:54:15 PM
End Time : 15-Apr-2014 07:11:58 PM
Scanning Time : 1063 secs
Product Data
Device Name : 14LR081
Serial No. : NA
Type : Other
Model : N429
Frequency : 2450.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 1 min(s)
Length : 25 mm
Width : 105 mm
Depth : 63 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.172 W/kg
Power Drift-Finish: 0.182 W/kg
Power Drift (%) : 5.636
Picture : C:\alsas\bitmap\Device-4.bmp

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 2450B
Frequency : 2450.00 MHz
Last Calib. Date : 15-Apr-2014
Temperature : 21.40 °C
Ambient Temp. : 21.40 °C
Humidity : 62.00 RH%
Epsilon (Dielectric Constant): 53.44
Sigma : 1.91 S/m
Density : 1000.00 kg/cu. m



Probe Data


Name : E-field
Model : E-020
Type : E-Field Triangle
Serial No. : 266
Last Calib. Date : 19-Mar-2015
Frequency : 2450.00 MHz
Duty Cycle Factor (CreF): 1
Conversion Factor : 4.6
Probe Sensitivity : 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point : 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 21.40 °C
Ambient Temp. : 21.40 °C
Set-up Date : 15-Apr-2014
Set-up Time : 8:01:50 AM
Area Scan : 9x10x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Mid



The system detected 1 maxima.
Selected highest maxima # = 1.
Maxima #1 coordinates: X = -7.930, Y = -5.000
1 gram SAR value : 0.181 W/kg
10 gram SAR value : 0.056 W/kg
Area Scan Peak SAR : 0.236 W/kg
Zoom Scan Peak SAR : 0.530 W/kg

Maxima Summary:
Maxima #1
Maxima coordinates: X = -7.930, Y = -5.000
1 gram SAR value : 0.181 W/kg
10 gram SAR value : 0.056 W/kg
Area Scan Peak SAR : 0.236 W/kg
Zoom Scan Peak SAR : 0.530 W/kg

Data No. 7:

Report Date : 15-Apr-2014
By Operator : 123
Measurement Date : 15-Apr-2014
Starting Time : 15-Apr-2014 11:20:10 AM
End Time : 15-Apr-2014 11:44:31 AM
Scanning Time : 1062 secs
Product Data
Device Name : 14LR081
Serial No. : NA
Type : Other
Model : N429
Frequency : 2450.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 1 min(s)
Length : 25 mm
Width : 105 mm
Depth : 63 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.001 W/kg
Power Drift-Finish: 0.000 W/kg
Power Drift (%) : 0.000
Picture : C:\alsas\bitmap\Device-4.bmp

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 2450B
Frequency : 2450.00 MHz
Last Calib. Date : 15-Apr-2014
Temperature : 21.40 °C
Ambient Temp. : 21.40 °C
Humidity : 62.00 RH%
Epsilon (Dielectric Constant): 53.44
Sigma : 1.91 S/m
Density : 1000.00 kg/cu. m



Probe Data


Name : E-field
Model : E-020
Type : E-Field Triangle
Serial No. : 266
Last Calib. Date : 19-Mar-2015
Frequency : 2450.00 MHz
Duty Cycle Factor (CreF): 1
Conversion Factor : 4.6
Probe Sensitivity : 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point : 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 21.40 °C
Ambient Temp. : 21.40 °C
Set-up Date : 15-Apr-2014
Set-up Time : 8:01:50 AM
Area Scan : 9x10x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Mid



The system detected 1 maxima.
Selected highest maxima # = 1.
Maxima #1 coordinates: X = 3.100, Y = 27.900
1 gram SAR value : 0.001 W/kg
10 gram SAR value : 0.001 W/kg
Area Scan Peak SAR : 0.001 W/kg
Zoom Scan Peak SAR : 0.000 W/kg

Maxima Summary:

Maxima #1

Maxima coordinates: X = 3.100, Y = 27.900


1 gram SAR value : 0.001 W/kg

10 gram SAR value : 0.001 W/kg

Area Scan Peak SAR : 0.001 W/kg

Zoom Scan Peak SAR : 0.000 W/kg

SAR-Z Axis
at Hotspot x:-7.96 y:-5.06



NCL CALIBRATION LABORATORIES

Calibration File No: DC-1400
Project Number: ISL-D2450-cal-5639

CERTIFICATE OF CALIBRATION

It is certified that the equipment identified below has been calibrated in the
NCL CALIBRATION LABORATORIES by qualified personnel following recognized
procedures and using transfer standards traceable to NRC/NIST.

ISL Body Validation Dipole

Manufacturer: APREL Laboratories

Part number: ALS-D-2450-S-2

Frequency: 2450 MHz

Serial No: 2450-220-00753

Customer: ISL

Calibrated: 25th January 2012
Released on: 25th January, 2012

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: _____



Art Brennan, Quality Manager

NCL CALIBRATION LABORATORIES

Suite 102, 303 Terry Fox Dr,
OTTAWA, ONTARIO
CANADA K2K 3J1

Division of APREL Lab.
TEL: (613) 435-8300
FAX: (613) 435-8306

Conditions

Dipole 2450-220-00753 was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C
Temperature of the Tissue: 21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this subject has been accurately conducted and that all information contained within the results pages have been reviewed for accuracy.



Art Brennan, Quality Manager



Constantin Teodorian, Test Engineer

Calibration Results Summary

The following results relate the Calibrated Dipole and should be used as a quick reference for the user.

Mechanical Dimensions

Length: 51.5 mm
Height: 30.4 mm


Electrical Specification

S11 R/L	-16.32 dB
SWR	1.37 U
Impedance	10.33 Ω

System Validation Results

Calibrated @ 100mW

Frequency	1 Gram	10 Gram	Peak
2450 MHz	55.57	25.80	112.98



Introduction

This Calibration Report has been produced in line with the SSI Dipole Calibration Procedure SSI-TP-018-ALSAS. The results contained within this report are for Validation Dipole 235-00801. The calibration routine consisted of a three-step process. Step 1 was a mechanical verification of the dipole to ensure that it meets the mechanical specifications. Step 2 was an Electrical Calibration for the Validation Dipole, where the SWR, Impedance, and the Return loss were assessed. Step 3 involved a System Validation using the ALSAS-10U, along with APREL E-030 130 MHz to 26 GHz E-Field Probe Serial Number 215.

References

SSI-TP-018-ALSAS Dipole Calibration Procedure

SSI-TP-016 Tissue Calibration Procedure

IEEE 1528 “Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques”

IEC-62209 “Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures”

Part 1: “Procedure to determine the Specific Absorption Rate (SAR) for hand-held devices used in close proximity of the ear (frequency range of 300 MHz to 3 GHz)”

IEC-62209 “Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures”

Part 2 *Draft*: “Procedure to determine the Specific Absorption Rate (SAR) for hand-held devices used in close proximity of the ear (frequency range of 30 MHz to 6 GHz)”

Conditions

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C

Temperature of the Tissue: 20 °C +/- 0.5°C

This was a recalibration.

Dipole Calibration uncertainty

The calibration uncertainty for the dipole is made up of various parameters presented below.

Mechanical	1%
Positioning Error	1.22%
Electrical	1.7%
Tissue	2.2%
Dipole Validation	2.2%
TOTAL	8.32% (16.64% K=2)

Dipole Calibration Results

Mechanical Verification

APREL Length	APREL Height	Measured Length	Measured Height
51.5 mm	30.4 mm	52.1 mm	31.0 mm

Tissue Validation


Body Tissue 2450 MHz	Measured
Dielectric constant, ϵ_r	51.2
Conductivity, σ [S/m]	2.16

Electrical Calibration

Test	Result
S11 R/L	-16.32 dB
SWR	1.37 U
Impedance	10.33 Ω

The Following Graphs are the results as displayed on the Vector Network Analyzer.

S11 Parameter Return Loss




SWR

S11 FORWARD REFLECTION

SWR

REF=0.000 pU

2.000 U/DIV



CH 1 - S11

0.0000 mm REF

0.000 dB OFFSET

0.00° OFFSET

MARKER 2

2.450000 GHz

1.021 U

MARKER TO MAX
MARKER TO MIN


1 2.350000 GHz
1.368 U

3 2.550000 GHz
1.430 U

MARKER READOUT
FUNCTIONS

Smith Chart Dipole Impedance

S11 FORWARD REFLECTION
IMPEDANCE



CH 1 - S11
0.0000 mm REF
0.000 dB OFFSET
0.00° OFFSET

MARKER 2
2.450000 GHz
50.713 Ω
-649.365 jΩ

MARKER TO MAX
MARKER TO MIN

1 2.350000 GHz
64.146 Ω
10.325 jΩ
3 2.550000 GHz
49.559 Ω
18.033 jΩ

▶ MARKER READOUT
FUNCTIONS

NCL Calibration Laboratories

Division of APREL Laboratories.

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2011.