

## Variant FCC Test Report

### (PART 27)

**Report No.:** RF140312C09F-7

**FCC ID:** P4Q-N435

**Test Model:** N435

**Received Date:** Dec. 22, 2015

**Test Date:** Jan. 07, 2016

**Issued Date:** Feb. 16, 2016

**Applicant:** MiTAC International Corp.

**Address:** Building B, No. 209, Sec. 1, Nan Gang Rd., Nan Gang Dist., Taipei 11568, Taiwan, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan ( R.O.C )

**Test Location (1):** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

**Test Location (2):** No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan, R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agency



## Table of Contents

|   |           |
|---|-----------|
| <b>Release Control Record</b> .....                             | <b>3</b>  |
| <b>1 Certificate of Conformity</b> .....                        | <b>4</b>  |
| <b>2 Summary of Test Results</b> .....                          | <b>5</b>  |
| 2.1 Measurement Uncertainty .....                               | 5         |
| 2.2 Test Site and Instruments .....                             | 6         |
| <b>3 General Information</b> .....                              | <b>7</b>  |
| 3.1 General Description of EUT .....                            | 7         |
| 3.2 Configuration of System under Test.....                     | 9         |
| 3.2.1 Description of Support Units .....                        | 9         |
| 3.3 Test Mode Applicability and Tested Channel Detail .....     | 10        |
| 3.4 EUT Operating Conditions .....                              | 10        |
| 3.5 General Description of Applied Standards.....               | 10        |
| <b>4 Test Types and Results</b> .....                           | <b>11</b> |
| 4.1 Output Power Measurement .....                              | 11        |
| 4.1.1 Limits of Output Power Measurement .....                  | 11        |
| 4.1.2 Test Procedures.....                                      | 11        |
| 4.1.3 Test Setup.....   | 12        |
| 4.1.4 Test Results .....  | 12        |
| 4.2 Radiated Emission Measurement.....                          | 13        |
| 4.2.1 Limits of Radiated Emission Measurement .....             | 13        |
| 4.2.2 Test Procedure .....                                      | 13        |
| 4.2.3 Deviation from Test Standard .....                        | 13        |
| 4.2.4 Test Setup.....   | 13        |
| 4.2.5 Test Results .....  | 14        |
| <b>5 Pictures of Test Arrangements</b> .....                    | <b>16</b> |
| <b>Appendix – Information on the Testing Laboratories</b> ..... | <b>17</b> |



A D T

### Release Control Record

| Issue No.      | Description      | Date Issued   |
|----------------|------------------|---------------|
| RF140312C09F-7 | Original Release | Feb. 16, 2016 |



# 1 Certificate of Conformity

**Product:** Tablet PC  
**Brand:** Mio ; Mitac ; Code ; Janam ; Stryker  
**Test Model:** N435  
**Sample Status:** Production Unit  
**Applicant:** MiTAC International Corp.  
**Test Date:** Jan. 07, 2016  
**Standards:** FCC Part 27, Subpart C, L

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Evonne Liu , **Date:** Feb. 16, 2016  
Evonne Liu / Specialist

**Approved by :** Stanley Wu , **Date:** Feb. 16, 2016  
Stanley Wu / Assistant Manager

## 2 Summary of Test Results

| Applied Standard: FCC Part 27 & Part 2 (WCDMA) |                                     |        |   |
|--|-------------------------------------|--------|---|
| FCC Clause                                     | Test Item                           | Result | Remarks   |
| 2.1046<br>27.50(d)(4)                          | Equivalent Isotropic Radiated Power | Pass   | Meet the requirement of limit.  |
| 2.1055<br>27.54                                | Frequency Stability                 | Pass   | Refer to Note   |
| 2.1049<br>27.53(h)                             | Occupied Bandwidth                  | Pass   | Refer to Note   |
| 27.50(d)(5)                                    | Peak to Average Ratio               | Pass   | Refer to Note   |
| 27.53(h)                                       | Band Edge Measurements              | Pass   | Refer to Note   |
| 2.1051<br>27.53(h)                             | Conducted Spurious Emissions        | Pass   | Refer to Note   |
| 2.1053<br>27.53(h)                             | Radiated Spurious Emissions         | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -30.08 dB at 3465.20 MHz. |

Note: Only EIRP and RSE tests were performed for this addendum. Refer to original report for other test data.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                    | Frequency         | Expanded Uncertainty (k=2) (±) |
|--------------------------------|-------------------|--------------------------------|
| Radiated Emissions up to 1 GHz | 30 MHz ~ 200 MHz  | 2.0153 dB                      |
|                                | 200 MHz ~1000 MHz | 2.0224 dB                      |
| Radiated Emissions above 1 GHz | 1 GHz ~ 18 GHz    | 1.0121 dB                      |
|                                | 18 GHz ~ 40 GHz   | 1.1508 dB                      |



**2.2 Test Site and Instruments**

| Description & Manufacturer                     | Model No.       | Serial No.  | Date of Calibration | Due Date of Calibration |
|--|-----------------|---|---------------------|-------------------------|
| Test Receiver<br>Agilent Technologies          | N9038A          | MY52260177  | May 19, 2015        | May 18, 2016            |
| Spectrum Analyzer<br>ROHDE & SCHWARZ           | FSU43           | 101261  | Dec. 17, 2015       | Dec. 16, 2016           |
| BILOG Antenna<br>SCHWARZBECK                   | VULB9168        | 9168-472  | Feb. 04, 2015       | Feb. 03, 2016           |
| BILOG Antenna<br>SCHWARZBECK                   | VULB 9168       | 9168-153  | Jan. 07, 2016       | Jan. 06, 2017           |
| HORN Antenna<br>ETS-Lindgren                   | BBHA 9120 D     | 9120D-969   | Feb. 09, 2015       | Feb. 08, 2016           |
| HORN Antenna<br>SCHWARZBECK                    | BBHA 9170       | 9170-480  | Jan. 04, 2016       | Jan. 03, 2017           |
| Bluetooth Tester                               | CBT             | 100980  | Apr. 27, 2015       | Apr. 26, 2017           |
| Loop Antenna                                   | EM-6879         | 269   | Jul. 31, 2015       | Jul. 30, 2016           |
| Agilent Communications<br>Tester-Wireless      | 8960 Series 10  | MY53201073  | Jul. 03, 2015       | Jul. 02, 2017           |
| Preamplifier<br>Agilent                        | 310N            | 187226  | Jun. 29, 2015       | Jun. 28, 2016           |
| Preamplifier<br>Agilent                        | 83017A          | MY39501357  | Jun. 29, 2015       | Jun. 28, 2016           |
| Power Meter<br>Anritsu                         | ML2495A         | 1232002   | Sep. 21, 2015       | Sep. 20, 2016           |
| Power Sensor<br>Anritsu                        | MA2411B         | 1207325   | Sep. 21, 2015       | Sep. 20, 2016           |
| RF signal cable<br>ETS-LINDGREN                | 5D-FB           | Cable-CH1-01(R<br>FC-SMS-100-SM<br>S-120+RFC-SMS<br>-100-SMS-400) | Jun. 27, 2015       | Jun. 26, 2016           |
| RF signal cable<br>ETS-LINDGREN                | 8D-FB           | Cable-CH1-02(R<br>FC-SMS-100-SM<br>S-24)                          | Jun. 27, 2015       | Jun. 26, 2016           |
| Software<br>BV ADT                             | E3<br>8.130425b | NA  | NA                  | NA                      |
| Antenna Tower<br>MF                            | NA              | NA  | NA                  | NA                      |
| Turn Table<br>MF                               | NA              | NA  | NA                  | NA                      |
| Antenna Tower & Turn<br>Table Controller<br>MF | MF-7802         | NA  | NA                  | NA                      |
| Communications<br>Tester-Wireless<br>Agilent   | 8960 Series 10  | MY53201073  | Jul. 03, 2015       | Jul. 02, 2017           |
| Radio Communication<br>Analyzer<br>Anritsu     | MT8820C         | 6201240432  | Jul. 06, 2015       | Jul. 05, 2017           |

- Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HsinTien Chamber 1.
3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The FCC Site Registration No. is 149147.
5. The IC Site Registration No. is IC7450I-1.

### 3 General Information

#### 3.1 General Description of EUT

|                            |   |                     |
|----------------------------|---|---------------------|
| <b>Product</b>             | Tablet PC                                     |                     |
| <b>Brand</b>               | Mio ; Mitac ; Code ; Janam ; Stryker          |                     |
| <b>Test Model</b>          | N435  |                     |
| <b>Status of EUT</b>       | Production Unit                               |                     |
| <b>Power Supply Rating</b> | 5.0 Vdc (adapter)<br>3.7 Vdc (Li-ion battery) |                     |
| <b>Modulation Type</b>     | WCDMA   | QPSK, BPSK          |
| <b>Frequency Range</b>     | WCDMA   | 1712.4 ~ 1752.6 MHz |
| <b>Emission Designator</b> | WCDMA   | 4M18F9W             |
| <b>Max. EIRP Power</b>     | 241.82mW                                      |                     |
| <b>Antenna Type</b>        | Fixed Internal Antenna                        |                     |
| <b>Accessory Device</b>    | Refer to Note as below                        |                     |
| <b>Data Cable Supplied</b> | Refer to Note as below                        |                     |

Note:

- This report is issued as a supplementary report to BV ADT report no.: RF140312C09-2. The differences compared with original report are adding LCD Panel 2. Therefore, only EIRP and RSE had been retest.
- The EUT contains following accessory devices.

| Product                     | Brand                                    | Model                         | Description  |
|-----------------------------|--|-------------------------------|--|
| Adapter 1                   | TPT                                      | MII050200                     | I/P: 100-240Vac, 50-60Hz, 0.3A<br>O/P: 5Vdc, 2A            |
| Adapter 2                   | SINPRO                                   | MPU16A-102                    | I/P: 100-240Vac, 47-63Hz,<br>0.33-0.18A<br>O/P: 5Vdc, 2.6A |
| Battery                     | Tian Yu                                  | SJS3060                       | 3.7Vdc, 3060mAh  |
| BCR Scanner 1<br>(2D LED)   | Honeywell                                | N5600, N56X3, N56X0,<br>N5603 | --   |
| BCR Scanner 2 (2D)          | Code                                     | CR8012                        | --   |
| BCR Scanner 3<br>(2D Laser) | Honeywell                                | N5603, N56X3                  | --   |
| LCD Panel 1                 | TIANME                                   | TM059YDH01                    | 5.88 inch  |
| LCD Panel 2                 | SHANGHAI TIANMA<br>MICRO-ELECTRONI<br>CS | TM057JDHP04                   | 5.7 inch   |
| Front Camera                | LITE-ON                                  | 10P2SA511                     | --   |
| Rear Camera                 | LITE-ON                                  | 10P2SF130                     | --   |
| WWAN Module                 | Ublox                                    | LISA-U200                     | --   |
| WLAN, BT Module             | Jorjin                                   | WG7833-B0 &                   | --   |





|  |  |           |  |
|--|--|-----------|--|
|  |  | WX7833-B0 |  |
|--|--|-----------|--|

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.





### 3.2 Configuration of System under Test

#### <Radiated Emission Test>



#### <E.R.P. / E.I.R.P. Test>



#### 3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| No. | Product  | Brand | Model No. | Serial No. | FCC ID |
|-----|----------|-------|-----------|------------|--------|
| 1.  | Earphone | N/A   | N/A       | N/A        | N/A    |

| No. | Signal Cable Description Of The Above Support Units |
|-----|---|
| 1.  | N/A   |

Note:

1. All power cords of the above support units are non-shielded (1.8m).

### 3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

| Band  | ERP / EIRP | Radiated Emission |
|-------|------------|-------------------|
| WCDMA | Z-plane    | Z-axis            |

| EUT Configure Mode | Test Item         | Available Channel | Tested Channel   | Mode  |
|--------------------|-------------------|-------------------|------------------|-------|
| -                  | EIRP              | 1312 to 1513      | 1312, 1413, 1513 | WCDMA |
| -                  | Radiated Emission | 1312 to 1513      | 1413             | WCDMA |

#### Test Condition:

| Test Item         | Environmental Conditions | Input Power    | Tested By     |
|-------------------|--------------------------|----------------|---------------|
| EIRP              | 25 deg. C, 65 % RH       | 3.7 Vdc        | Charles Hsiao |
| Radiated Emission | 25 deg. C, 65 % RH       | 120 Vac, 60 Hz | Charles Hsiao |

### 3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 27**

**KDB 971168 D01 Power Meas License Digital Systems v02r02**

**ANSI/TIA/EIA-603-D 2010**

**NOTE:** All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Output Power Measurement

#### 4.1.1 Limits of Output Power Measurement

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.


#### 4.1.2 Test Procedures

##### **EIRP / ERP Measurement:**

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5 MHz for WCDMA and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G.
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$  E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi.}$

### 4.1.3 Test Setup

#### EIRP / ERP Measurement:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 4.1.4 Test Results

#### EIRP Power (dBm)

| WCDMA |         |                 |           |                        |            |           |                    |
|-------|---------|-----------------|-----------|------------------------|------------|-----------|--------------------|
| Plane | Channel | Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (mW) | Polarization (H/V) |
| Z     | 1312    | 1712.4          | -18.65    | 42.49                  | 23.84      | 241.82    | H                  |
|       | 1413    | 1732.6          | -18.75    | 42.33                  | 23.58      | 227.88    |                    |
|       | 1513    | 1752.6          | -19.01    | 42.10                  | 23.09      | 203.70    |                    |
| V     | 1312    | 1712.4          | -22.14    | 42.99                  | 20.85      | 121.62    | V                  |
|       | 1413    | 1732.6          | -22.32    | 42.74                  | 20.42      | 110.15    |                    |
|       | 1513    | 1752.6          | -22.18    | 42.21                  | 20.03      | 100.69    |                    |

## 4.2 Radiated Emission Measurement

### 4.2.1 Limits of Radiated Emission Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB. The limit of emission is equal to -13 dBm.

### 4.2.2 Test Procedure


- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ .
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$ .

**NOTE:** The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

### 4.2.3 Deviation from Test Standard

No deviation.

### 4.2.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.5 Test Results




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2016-01-07



Site : 966 chamber 1  
 Condition: PART 27(B4/B17) 3m Horizontal  
 Remark : Band IV\_Link\_CH1413  
 Tested by: Charles Hsiao  
 Plane : Z

|      | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark |
|------|---------|--------|------------|------------|------------|--------|--------|
|      | MHz     | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |
| 1    | 90.75   | -60.21 | -49.59     | -13.00     | -47.21     | -10.62 | Peak   |
| 2    | 166.35  | -61.42 | -54.43     | -13.00     | -48.42     | -6.99  | Peak   |
| 3    | 240.33  | -61.61 | -55.97     | -13.00     | -48.61     | -5.64  | Peak   |
| 4    | 317.50  | -67.74 | -61.98     | -13.00     | -54.74     | -5.76  | Peak   |
| 5    | 547.10  | -70.97 | -69.10     | -13.00     | -57.97     | -1.87  | Peak   |
| 6    | 692.70  | -68.86 | -68.52     | -13.00     | -55.86     | -0.34  | Peak   |
| 7 pp | 3465.20 | -43.08 | -57.42     | -13.00     | -30.08     | 14.34  | Peak   |
| 8    | 5197.80 | -44.69 | -64.81     | -13.00     | -31.69     | 20.12  | Peak   |




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2016-01-07



Site : 966 chamber 1  
 Condition: PART 27(B4/B17) 3m Vertical  
 Remark : Band IV\_Link\_CH1413  
 Tested by: Charles Hsiao  
 Plane : Z

|      | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark |
|------|---------|--------|------------|------------|------------|--------|--------|
|      | MHz     | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |
| 1    | 48.90   | -64.09 | -50.66     | -13.00     | -51.09     | -13.43 | Peak   |
| 2    | 79.68   | -68.14 | -56.29     | -13.00     | -55.14     | -11.85 | Peak   |
| 3    | 168.78  | -65.66 | -58.86     | -13.00     | -52.66     | -6.80  | Peak   |
| 4    | 300.00  | -70.35 | -64.39     | -13.00     | -57.35     | -5.96  | Peak   |
| 5    | 580.00  | -69.21 | -68.79     | -13.00     | -56.21     | -0.42  | Peak   |
| 6    | 708.80  | -68.62 | -68.08     | -13.00     | -55.62     | -0.54  | Peak   |
| 7 pp | 3465.20 | -43.78 | -58.12     | -13.00     | -30.78     | 14.34  | Peak   |
| 8    | 5197.80 | -44.90 | -65.02     | -13.00     | -31.90     | 20.12  | Peak   |



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).





A D T

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### **Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

### **Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

### **Hwa Ya EMC/RF/Safety**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---