



FCC ID: P4Q-N653
Report No.: T200407W01-RP14

Page: 1 / 24
Rev.: 01

FCC 47 CFR PART 90

TEST REPORT

For

PRO 8475

**Trade Name:
MiTAC, Webfleet Solutions**

Model: N653

Issued to

**Mitac Digital Technology Corporation
No.200, Wen Hwa 2nd Rd.,Kuei Shan Dist. Taoyuan, 33383 Taiwan**

Issued by

**Compliance Certification Services Inc.
Wugu Laboratory
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan. (R.O.C.)
Issued Date: June 9, 2020**

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	May 21, 2020	Initial Issue	ALL	Allison Chen
01	June 9, 2020	See the following note Rev.(01)	ALL	Allison Chen

Rev.(01)

1. Added test data for power table and radiated emission.
2. Revised product name: PRO 8475, and model name: N653.

TABLE OF CONTENTS

1.	TEST RESULT CERTIFICATION.....	4
2.	EUT DESCRIPTION.....	5
3.	TEST METHODOLOGY.....	6
3.1	EUT CONFIGURATION.....	6
3.2	DESCRIPTION OF TEST MODES.....	6
3.3	THE WORST MODE OF MEASUREMENT.....	7
4.	TEST SUMMERY.....	8
5.	INSTRUMENT CALIBRATION.....	9
5.1	MEASURING INSTRUMENT CALIBRATION.....	9
5.2	MEASUREMENT EQUIPMENT USED.....	9
5.3	MEASUREMENT UNCERTAINTY.....	11
6.	FACILITIES AND ACCREDITATIONS.....	12
6.1	FACILITIES.....	12
6.2	EQUIPMENT.....	12
6.3	LABORATORY ACCREDITATIONS AND LISTING.....	12
7.	SETUP OF EQUIPMENT UNDER TEST.....	13
7.1	SETUP CONFIGURATION OF EUT.....	13
7.2	SUPPORT EQUIPMENT.....	13
8.	FCC PART 22 REQUIREMENTS.....	14
8.1	ERP MEASUREMENT.....	14
8.2	SPURIOUS RADIATION MEASUREMENT.....	19
8.3	TEST DATA RE-USE SUMMARY.....	23
9.	APPENDIX A PHOTOGRAPHS OF TEST SETUP.....	A-1
	APPENDIX 1 - PHOTOGRAPHS OF EUT	

1. TEST RESULT CERTIFICATION

Applicant: Mitac Digital Technology Corporation
No.200, Wen Hwa 2nd Rd.,Kuei Shan Dist. Taoyuan, 33383
Taiwan

Manufacturer: MITAC COMPUTER (KUNSHAN) CO., LTD.
No. 269, 2nd Avenue, District A, Comprehensive Free Trade
Zone, Kunshan, Jiangsu, P.R. China

Equipment Under Test: PRO 8475

Trade Name: MiTAC, Webfleet Solutions

Model: N653

Date of Test: June 1 ~ 6, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR PART 90	No non-compliance noted
Statements of Conformity	
Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	

We hereby certify that:

The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Kevin Tsai
Deputy Manager
Compliance Certification Services Inc.

2. EUT DESCRIPTION

Product	PRO 8475	
Model	N653	
Model Discrepancy	Difference of the those trade names (list on this report) are just for marketing purpose only.	
Trade	MiTAC, Webfleet Solutions	
Received Date	April 7, 2020	
Power Supply	1. Powered from Rechargeable Li-ion Polymer Battery. Rating: 3.7VDC, 4000mAh, 14.8Wh 2. Powered from Cradle Fleet cable 12/24V (Pogo power pin) USB Type-C 5V	
Frequency Range	LTE Band 26 Channel Bandwidth: 1.4MHz	814.7MHz ~ 823.3MHz
	LTE Band 26 Channel Bandwidth: 3MHz	815.5MHz ~ 822.5MHz
	LTE Band 26 Channel Bandwidth: 5MHz	816.5MHz ~ 821.5MHz
	LTE Band 26 Channel Bandwidth: 10MHz	819MHz
Modulation Technique	LTE Band 26	QPSK, 16QAM
Antenna Specification	Antenna type: Integral Band 26: 1.62 dBi	

Remark: The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

Report No.: T200407W01-RP14

3. TEST METHODOLOGY

Both conducted and radiated testing were performed according to the procedures document on chapter 13 of TIA-603-E and FCC CFR 47, Part 2 and Part 90, KDB 971168 D01 Power Meas License Digital Systems.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 DESCRIPTION OF TEST MODES

The EUT (Model: N653) had been tested under operating condition.

The EUT be set in maximum power transmission via call box during testing.

LTE Band 26: 814 MHz ~ 824 MHz

Three channels had been tested for each channel bandwidth.

Channel Bandwidth	1.4MHz		3MHz		5MHz	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
Low channel (L)	26697	814.7	26705	815.5	26715	816.5
Middle channel (M)	26740	819	26740	819	26740	819
High channel (H)	26783	823.3	26775	822.5	26765	821.5
Channel Bandwidth	10MHz					
	Channel	Frequency (MHz)				
Low channel (L)	-	-				
Middle channel (M)	26740	819				
High channel (H)	-	-				

3.3 THE WORST MODE OF MEASUREMENT

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Battery Mode 2: EUT+Cradle
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4
Worst Position	<input type="checkbox"/> Placed in fixed position. <input type="checkbox"/> Placed in fixed position at X-Plane (E2-Plane) <input type="checkbox"/> Placed in fixed position at Y-Plane (E1-Plane) <input checked="" type="checkbox"/> Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Battery Mode 2: EUT+Cradle
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Z-Plane) were recorded in this report

4. TEST SUMMERY

FCC Standard Sec.	Report Section	Test Item	Result
-	2	Antenna Requirement	Pass
2.1046, 90.635(b), 90.542 (a)(7)	8.1	ERP Measurement	Pass
2.1053, 90.691	8.2	Spurious Radiation Measurement	Pass

5. INSTRUMENT CALIBRATION

5.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

5.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Remark: Each piece of equipment is scheduled for calibration once a year.

RF Conducted Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
Coaxial Cable	Woken	WC12	CC003	06/28/2019	06/27/2020
Wideband Radio Communication Tester	R&S	CMW 500	116875	07/29/2019	07/28/2020
Software	N/A				

Report No.: T200407W01-RP14

3M 966 Chamber Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
Band Reject Filters	MICRO TRONICS	BRM 50702	120	02/25/2020	02/24/2021
Bilog Antenna	Sunol Sciences	JB3	A030105	07/26/2019	07/25/2020
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/25/2020	02/24/2021
Coaxial Cable	EMCI	EMC105	190914+25111	09/20/2019	09/19/2020
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/15/2020	01/14/2021
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	10/04/2019	10/03/2020
High Pass Filter	SOLVANG TECHNOLOGY INC.	STI15	9923	02/25/2020	02/24/2021
High Pass Filters	MICRO TRONICS	HPM13195	003	02/25/2020	02/24/2021
Horn Antenna	ETS LINDGREN	3116	00026370	12/18/2019	12/17/2020
Horn Antenna / Harmonic Mixer	A-INFOMW / ROHDE&SCHWARZ	LB-19-20-A / FS-Z60	J202020872 / 100142	12/09/2019	12/08/2021
Horn Antenna / Harmonic Mixer	ROHDE&SCHWARZ	FH-PP-110 / FS-Z110	10003 / 100096	12/09/2019	12/08/2021
Horn Antenna / Harmonic Mixer	ROHDE&SCHWARZ	FH-PP-75 / FS-Z75	10001 / 100162	12/09/2019	12/08/2021
Horn Antenna / Spectrum Analyzer Mixer	Radiometer Physics GmbH	FH-PP-170 / SAM-170	10003 / 20011	12/09/2019	12/08/2021
Horn Antenna / Spectrum Analyzer Mixer	Radiometer Physics GmbH	FH-PP-220 / SAM-220	10003 / 20013	12/09/2019	12/08/2021
Horn Antenna / Spectrum Analyzer Mixer	Radiometer Physics GmbH	FH-PP-325 / SAM-325	10007 / 20048	12/09/2019	12/08/2021
Loop Ant	COM-POWER	AL-130	121051	03/27/2020	03/26/2021
Pre-Amplifier	EMEC	EM330	060609	02/25/2020	02/24/2021
Pre-Amplifier	HP	8449B	3008A00965	02/25/2020	02/24/2021
Pre-Amplifier	MITEQ	AMF-6F-180040 00-37-8P	985646	06/18/2019	06/17/2020
Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2020	03/18/2021
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

5.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Report No.: T200407W01-RP14

6. FACILITIES AND ACCREDITATIONS

6.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.199, Chungshen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10: 2013 and CISPR Publication 22.

6.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.3 LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by American Association for Laboratory Accreditation Program for the specific scope accreditation under Lab Code: 0824-01 to perform Electromagnetic Interference tests according to FCC Part 15 and CISPR 22 requirements. In addition, the test facilities are listed with Industry Canada, Certification and Engineering Bureau, IC 2324G-1 for 3M Semi Anechoic Chamber A, 2324G-2 for 3M Semi Anechoic Chamber B.

7. SETUP OF EQUIPMENT UNDER TEST

7.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

7.2 SUPPORT EQUIPMENT

Support Equipment						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC ID
1	NB(L)	Toshiba	PORTEGE R30-A	N/A	PD97260H	N/A
2	DC Power Source	Agilent	E3640A	N/A	N/A	N/A

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8. FCC PART 22 REQUIREMENTS

8.1 ERP MEASUREMENT

LIMIT

According to FCC §2.1046

FCC 90.635(b): The maximum output power of the transmitter for mobile stations is 100 watts (20 dBw).

TEST PROCEDURES

CONDUCTED POWER MEASUREMENT:

1. The transmitter output power was connected to the call box.
2. Set EUT at maximum output power via call box.
3. Set Call box at lowest, middle and highest channels for each band and modulation.

TEST RESULTS

No non-compliance noted.

LTE Band 26

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power (dBm)	ERP Power		
Band 26	1.4M	26697	814.7	QPSK	1	0	0	23.17	22.64		
					1	2	0	22.89	22.36		
					1	5	0	22.93	22.40		
					3	0	1	22.43	21.90		
					3	2	1	22.04	21.51		
					3	3	1	22.00	21.47		
				16QAM	6	0	1	22.20	21.67		
					1	0	1	22.34	21.81		
					1	2	1	22.06	21.53		
					1	5	1	22.04	21.51		
					3	0	2	21.41	20.88		
					3	2	2	21.11	20.58		
		26740	819.0	QPSK	819.0	QPSK	3	3	1	22.00	21.47
							6	0	1	22.20	21.67
							1	0	0	23.28	22.75
							1	2	0	22.99	22.46
							1	5	0	23.05	22.52
							3	0	1	22.76	22.23
				16QAM	3	2	1	22.24	21.71		
					3	3	1	22.21	21.68		
					6	0	1	22.61	22.08		
					1	0	1	22.49	21.96		
					1	2	1	22.40	21.87		
					1	5	1	22.08	21.55		
		26783	823.3	QPSK	823.3	QPSK	3	0	2	21.64	21.11
							3	2	2	21.32	20.79
							3	3	2	21.18	20.65
							6	0	2	21.39	20.86
							1	0	0	23.22	22.69
							1	2	0	22.94	22.41
				16QAM	1	5	0	22.99	22.46		
					3	0	1	22.66	22.13		
					3	2	1	22.49	21.96		
					3	3	1	22.31	21.78		
					6	0	1	22.56	22.03		
					1	0	1	22.27	21.74		
16QAM	1	2	1	22.12	21.59						
	1	5	1	22.00	21.47						
	3	0	2	21.24	20.71						
	3	2	2	21.58	21.05						
	3	3	2	21.08	20.55						
	6	0	2	21.42	20.89						

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power (dBm)	ERP Power	
Band 26	3M	26705	815.5	QPSK	1	0	0	23.18	22.65	
					1	7	0	22.90	22.37	
					1	14	0	22.94	22.41	
					8	0	1	22.44	21.91	
					8	4	1	22.05	21.52	
					8	7	1	22.01	21.48	
				15	0	1	22.21	21.68		
				16QAM	1	0	1	22.35	21.82	
					1	7	1	22.07	21.54	
					1	14	1	22.05	21.52	
					8	0	2	21.42	20.89	
					8	4	2	21.12	20.59	
		8	7		2	20.97	20.44			
		26740	819.0	QPSK	819.0	1	0	0	23.29	22.76
						1	7	0	23.00	22.47
						1	14	0	23.06	22.53
						8	0	1	22.77	22.24
						8	4	1	22.25	21.72
						8	7	1	22.22	21.69
				15	0	1	22.62	22.09		
				16QAM	1	0	1	22.50	21.97	
					1	7	1	22.41	21.88	
					1	14	1	22.09	21.56	
					8	0	2	21.65	21.12	
					8	4	2	21.33	20.80	
		8	7		2	21.19	20.66			
		26775	822.5	QPSK	822.5	1	0	0	23.24	22.71
						1	7	0	22.96	22.43
						1	14	0	23.01	22.48
						8	0	1	22.68	22.15
8	4					1	22.51	21.98		
8	7					1	22.33	21.80		
15	0			1	22.58	22.05				
16QAM	1			0	1	22.29	21.76			
	1			7	1	22.14	21.61			
	1			14	1	22.02	21.49			
	8			0	2	21.26	20.73			
	8			4	2	21.60	21.07			
	8	7	2	21.10	20.57					
15	0	2	21.44	20.91						

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power (dBm)	ERP Power	
Band 26	5M	26715	816.5	QPSK	1	0	0	23.23	22.70	
					1	7	0	22.95	22.42	
					1	14	0	22.99	22.46	
					8	0	1	22.49	21.96	
					8	4	1	22.10	21.57	
					8	7	1	22.06	21.53	
				15	0	1	22.26	21.73		
				16QAM	1	0	1	22.40	21.87	
					1	7	1	22.12	21.59	
					1	14	1	22.10	21.57	
					8	0	2	21.47	20.94	
					8	4	2	21.17	20.64	
		8	7		2	21.02	20.49			
		26740	819.0	QPSK	819.0	1	0	0	23.33	22.80
						1	7	0	23.04	22.51
						1	14	0	23.10	22.57
						8	0	1	22.81	22.28
						8	4	1	22.29	21.76
						8	7	1	22.26	21.73
				15	0	1	22.66	22.13		
				16QAM	1	0	1	22.54	22.01	
					1	7	1	22.45	21.92	
					1	14	1	22.13	21.60	
					8	0	2	21.69	21.16	
					8	4	2	21.37	20.84	
		8	7		2	21.23	20.70			
		26765	821.5	QPSK	821.5	1	0	0	23.29	22.76
						1	7	0	23.01	22.48
						1	14	0	23.06	22.53
						8	0	1	22.73	22.20
8	4					1	22.56	22.03		
8	7					1	22.38	21.85		
15	0			1	22.63	22.10				
16QAM	1			0	1	22.34	21.81			
	1			7	1	22.19	21.66			
	1			14	1	22.07	21.54			
	8			0	2	21.31	20.78			
	8			4	2	21.65	21.12			
	8	7	2	21.15	20.62					
15	0	2	21.49	20.96						

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power (dBm)	ERP Power
Band 26	10M	26740	819.0	QPSK	1	0	0	23.42	22.89
					1	25	0	23.13	22.60
					1	49	0	23.19	22.66
					25	0	1	22.90	22.37
					25	12	1	22.38	21.85
					25	25	1	22.35	21.82
					50	0	1	22.75	22.22
				16QAM	1	0	1	22.63	22.10
					1	25	1	22.54	22.01
					1	49	1	22.22	21.69
					25	0	2	21.78	21.25
					25	12	2	21.46	20.93
					25	25	2	21.32	20.79
					50	0	2	21.53	21.00


8.2 SPURIOUS RADIATION MEASUREMENT

LIMIT


The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm


Test Configuration

Below 1 GHz



Above 1 GHz



Substituted Method Test Set-up**TEST PROCEDURE**

1. According to KDB 971168 D01 Power Meas License Digital Systems and TIA-603-E Section 2.2.12.
2. The EUT was placed on a turntable
 - (1) Below 1G : 0.8m
 - (2) Above 1G : 0.8m
 - (3) EUT set 3m from the receiving antenna
 - (4) The table was rotated 360 degrees of the highest spurious emission to determine the position.
3. Set the spectrum analyzer , RBW=1MHz, VBW=3MHz.
4. A horn antenna was driven by a signal generator.
5. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission

$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)} - 2.15$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$$

TEST RESULTS

Refer to the attached tabular data sheets.

Remark: Above 1GHz

Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Report No.: T200407W01-RP14

LTE Band 26 / BW: 10MHz / QPSK / RB =1, RB Offset = 0

Operation Mode: Tx / Mid CH


Test Date: June 6, 2020

Temperature: 24.9°C

Tested by: Jerry Chang

Humidity: 51% RH

Polarity: Ver.




Freq. (MHz)	ERP/EIRP (dBm)	SG Output Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	Limit (dBm)	Margin (dB)	Antenna Polarization (V/H)
176.47	-68.30	-62.51	-4.70	-1.09	-13.00	-55.30	V
314.21	-72.86	-69.39	-2.00	-1.47	-13.00	-59.86	V
539.25	-65.30	-62.07	-1.30	-1.93	-13.00	-52.30	V
682.81	-64.01	-60.51	-1.30	-2.20	-13.00	-51.01	V
881.66	-61.09	-57.35	-1.23	-2.51	-13.00	-48.09	V
943.74	-61.39	-57.55	-1.23	-2.61	-13.00	-48.39	V
1638.00	-61.20	442.34	-500.00	-3.54	-13.00	-48.20	V
2457.00	-40.98	463.54	-500.00	-4.52	-13.00	-27.98	V
4095.00	-46.18	459.84	-500.00	-6.02	-13.00	-33.18	V

Report No.: T200407W01-RP14

Operation Mode: Tx / Mid CH
Temperature: 24.9°C
Humidity: 51% RH

Test Date: June 6, 2020
Tested by: Jerry Chang
Polarity: Hor.



Freq. (MHz)	ERP/EIRP (dBm)	SG Output Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	Limit (dBm)	Margin (dB)	Antenna Polarization (V/H)
221.09	-74.87	-71.67	-1.98	-1.22	-13.00	-61.87	H
294.81	-74.34	-70.82	-2.10	-1.42	-13.00	-61.34	H
459.71	-70.60	-66.72	-2.10	-1.78	-13.00	-57.60	H
665.35	-64.59	-60.92	-1.49	-2.18	-13.00	-51.59	H
745.86	-65.25	-61.55	-1.40	-2.30	-13.00	-52.25	H
886.51	-63.27	-59.48	-1.27	-2.52	-13.00	-50.27	H
1638.00	-60.38	443.16	-500.00	-3.54	-13.00	-47.38	H
2457.00	-44.32	460.20	-500.00	-4.52	-13.00	-31.32	H
4095.00	-46.84	459.18	-500.00	-6.02	-13.00	-33.84	H

8.3 TEST DATA RE-USE SUMMARY

The application re-uses data collected on a similar device. The subject device of this application (Model: N653, FCC ID: P4Q-N653) is electrically identical to the reference device (Model: N635, FCC ID: P4Q-N635A) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 484596 D01.

Differences Brief Description:

The WLAN, WWAN, BT and RFID hardware of this device are identical to the implementation in

FCC ID: P4Q-N653.

The Product Equality Declaration document includes detailed information about the changes between the devices. The data from that application has been verified through appropriate spot checks to demonstrate compliance for this device as shown in the summary table below.



Report No.: T200407W01-RP14

Page: 24 / 24

Rev.: 01

Spot Check Verification Result Summary

Equipment Class	Reference FCC ID	Folder Test	Report Title/Section
Part 90	P4Q-N635A	T191105W01-RP14	All Section (<i>Except for ERP Measurement, Spurious Radiation Measurement</i>)

Summary of the spot check for Unlicensed bands and Licensed bands

In order to confirm hardware similarity of the subject device with the reference device, we used same setting power to radiated emission measurement were performed on the subject device for the Band edge and Harmonic, the test result were similar with FCC ID: P4Q-N635A.

WWAN: LTE

Report	Test Item	Frequency (MHz)	Channel	P4Q-N635A		P4Q-N653		Gap (dB)
				Measured Frequency (MHz)	EIRP/ERP	Measured Frequency (MHz)	EIRP/ERP	
Band 26	RSE	841.5	26965	2524.5	-18.99	2524.5	-20.13	1.14

- End of Test Report -