



FCC RADIO TEST REPORT

FCC ID : P4Q-N672B
Equipment : LTE Module
Brand Name : MiTAC, Mio, NAVMAN, MAGELLAN
Model Name : SC600T-NA
Applicant : MiTAC Digital Technology Corporation
4F., NO. 1, R&D ROAD 2, HSINCHU SCIENCE
PARK, HSINCHU 30076, TAIWAN, R.O.C.
Manufacturer : MITAC Computer (Kunshan) Co., Ltd.
No. 269, 2nd Avenue, District A,
Comprehensive Free Trade Zone, 300
Kunshan, China
Standard : FCC 47 CFR Part 2, 22(H), 24(E), 27

The product was received on Dec. 09, 2020 and testing was started from Jan. 12, 2021 and completed on Jan. 14, 2021. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report	3
Summary of Test Result	4
1 General Description	6
1.1 Product Feature of Equipment Under Test.....	6
1.2 Modification of EUT	7
1.3 Testing Location	8
1.4 Applicable Standards.....	8
2 Test Configuration of Equipment Under Test	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System.....	10
2.3 Support Unit used in test configuration and system	10
2.4 Frequency List of Low/Middle/High Channels	11
3 Radiated Test Items	13
3.1 Measuring Instruments	13
3.2 Radiated Spurious Emission Measurement	15
4 List of Measuring Equipment	16
5 Uncertainty of Evaluation	17
Appendix A. Test Results of Radiated Test	
Appendix B. Test Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FG0D1806B	01	Initial issue of report	Feb. 28, 2021



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
-	§2.1046	Conducted Output Power	-	See Note
	§22.913 (a)(2)	Effective Radiated Power (Band 26)	-	
	§27.50 (b)(10) §27.50 (c)(10)	Effective Radiated Power (Band 12) (Band 13) (Band 71)		
	§24.232 (c) §27.50 (h)(2)	Equivalent Isotropic Radiated Power (Band 25) (Band 7) (Band 41)		
	§27.50 (d)(4)	Equivalent Isotropic Radiated Power (Band 66)		
-	§24.232 (d) §27.50 (d)(5)	Peak-to-Average Ratio		-
-	§2.1049	Occupied Bandwidth	-	See Note
-	§2.1051 §22.917 (a) §24.238 (a) §27.53 (c)(2)(4) §27.53 (g) §27.53 (h)	Conducted Band Edge Measurement (Band 12) (Band 13) (Band 25) (Band 26) (Band 66) (Band 71)	-	See Note
	§2.1051 §27.53 (m)(4)	Conducted Band Edge Measurement (Band 7) (Band 41)		
-	§2.1051 §22.917 (a) §24.238 (a) §27.53 (c)(2) §27.53 (g) §27.53 (h)	Conducted Spurious Emission (Band 12) (Band 13) (Band 25) (Band 26) (Band 66) (Band 71)	-	See Note
	§2.1051 §27.53 (m)(4)	Conducted Spurious Emission (Band 7) (Band 41)		
-	§2.1055 §22.355 §24.235 §27.54	Frequency Stability Temperature & Voltage	-	See Note



Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1053 §22.917 (a) §24.238 (a) §27.53 (c)(2) §27.53 (f) §27.53 (g) §27.53 (h)	Radiated Spurious Emission (Band 12) (Band 13) (Band 25) (Band 26) (Band 66) (Band 71)	Pass	Under limit 9.68 dB at 3392.000 MHz
	§2.1051 §27.53 (m)(4)	Radiated Spurious Emission (Band 7) (Band 41)		

Note: The module (Model: SC600T-NA) makes no difference after verifying output power, this report reuses test data from the module report.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Tina Chuang



1 General Description

1.1 Product Feature of Equipment Under Test

WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, and GNSS.

Product Specification subjective to this standard	
Sample 1	EUT with Host 1
Sample 2	EUT with Host 2
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna GPS / Glonass : Patch Antenna
Antenna Gain	LTE Band 7 : Main: -3.8 dBi Aux: -3.2 dBi LTE Band 12: -6.0 dBi LTE Band 13: -5.5 dBi LTE Band 25: Main: -4.0 dBi Aux: -2.5 dBi LTE Band 26: -4.7 dBi LTE Band 41: Main: -3.6 dBi Aux: -2.3 dBi LTE Band 66: Main: -3.3 dBi Aux: -2.6 dBi LTE Band 71: -6.1 dBi

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.



The product was installed into Tablet (Brand Name: MiTAC, Mio, NAVMAN, MAGELLAN, Model Name: N672B) during test, and the host information was recorded in the following table.

Host Information	
Host 1	Host with SKU A
Host 2	Host with SKU B

Sample Information		
Functions	SKU A	SKU B
Screen	5" 720x1280 (HD), IPS, 350nits (w/ touch)	5" 720x1280 (HD), IPS, 350nits (w/ touch)
CPU	SD625 octa core 2.0GHz	SD625 octa core 2.0GHz
Battery	4110mAh (hard pack)	4110mAh (hard pack)
RAM	3GB	3GB
Storage	32GB	32GB
External storage	Support	Support
WWAN + WLAN Module	Support (SC600T-NA)	Support (SC600T-NA)
NFC/RFID(HF)	Support	Support
GPS	Support	Support
Barcode	Support(N6603)	Support(N3601)

Functions	SKU C	SKU D
Screen	5" 720x1280 (HD), IPS, 350nits (w/ touch)	5" 720x1280 (HD), IPS, 350nits (w/ touch)
CPU	SD625 octa core 2.0GHz	SD625 octa core 2.0GHz
Battery	4110mAh (hard pack)	4110mAh (hard pack)
RAM	2GB	2GB
Storage	16GB	16GB
External storage	Support	Support
WWAN + WLAN Module	Support (SC600T-NA)	Support (SC600T-NA)
NFC/RFID(HF)	Support	Support
GPS	Support	Support
Barcode	Support(N6603)	Support(N3601)

1.2 Modification of EUT

No modifications are made to the EUT during all test items.



1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH15-HY
Test Engineer	Leo Lee, Mancy Chou and Bigshow Wang
Temperature	22.6~23.2°C
Relative Humidity	46~53%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW0007

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ FCC 47 CFR Part 2, 22(H), 24(E), 27
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X Plane for LTE Band 13; Y Plane for LTE Band 12, 25, 26; Z Plane for LTE Band 7, 41, 66,71) were recorded in this report.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Radiated Spurious Emission	7	-	-				v	v			v			v	v	v
	12				v	-	-	v			v			v	v	v
	13	-	-	v	v	-	-	v			v			v	v	v
	25						v	v			v			v	v	v
	26					v	-	v			v			v	v	v
	41	-	-				v	v			v			v	v	v
	66						v	v			v			v	v	v
	71	-	-				v	v			v			v	v	v
Remark	<ol style="list-style-type: none"> The mark "v" means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. All the radiated test cases were performed with Sample 2 															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A



2.4 Frequency List of Low/Middle/High Channels

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
LTE Band 12 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23060	23095	23130
	Frequency	704	707.5	711
LTE Band 13 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23230	-
	Frequency	-	782	-
5	Channel	23205	23230	23255
	Frequency	779.5	782	784.5
LTE Band 25 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	26140	26340	26590
	Frequency	1860	1880	1905
LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26865	26915	26965
	Frequency	831.5	836.5	841.5
LTE Band 41 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	39750	40620	41490
	Frequency	2506.0	2593.0	2680.0



LTE Band 66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	132072	132322	132572
	Frequency	1720	1745	1770
15	Channel	132047	132322	132597
	Frequency	1717.5	1745	1772.5
10	Channel	132022	132322	132622
	Frequency	1715	1745	1775
5	Channel	131997	132322	132647
	Frequency	1712.5	1745	1777.5
3	Channel	131987	132322	132657
	Frequency	1711.5	1745	1778.5
1.4	Channel	131979	132322	132665
	Frequency	1710.7	1745	1779.3

LTE Band 71 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	133222	133297	133372
	Frequency	673.0	680.5	688.0
15	Channel	133197	133297	133397
	Frequency	670.5	680.5	690.5
10	Channel	133172	133297	133422
	Frequency	668.0	680.5	693.0
5	Channel	133147	133297	133447
	Frequency	665.5	680.5	695.5


3 Radiated Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup

For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.1.2 Test Result of Radiated Test

Please refer to Appendix A.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



3.2 Radiated Spurious Emission Measurement

3.2.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For LTE Band 7, 41

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

For LTE Band 13

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.2.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

For LTE Band 7, 41

The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)

EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain

ERP (dBm) = EIRP - 2.15



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	37059 & 01	30MHz~1GHz	Oct. 11, 2020	Jan. 12, 2021~Jan. 14, 2021	Oct. 10, 2021	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL6111D&00800N1D01N-06	41912&05	30MHz to 1GHz	Feb. 09, 2020	Jan. 12, 2021~Jan. 14, 2021	Feb. 08, 2021	Radiation (03CH15-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jan. 04, 2021	Jan. 12, 2021~Jan. 14, 2021	Jan. 03, 2022	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 28, 2020	Jan. 12, 2021~Jan. 14, 2021	Dec. 27, 2021	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-02114	1-18GHz	Aug. 04, 2020	Jan. 12, 2021~Jan. 14, 2021	Aug. 03, 2021	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz~18GHz	Nov. 03, 2020	Jan. 12, 2021~Jan. 14, 2021	Nov. 02, 2021	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz- 40GHz	Dec. 02, 2020	Jan. 12, 2021~Jan. 14, 2021	Dec. 01, 2021	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz~40GHz	May 22, 2020	Jan. 12, 2021~Jan. 14, 2021	May 21, 2021	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55-303	1710001800055006	1GHz~18GHz	May 07, 2020	Jan. 12, 2021~Jan. 14, 2021	May 06, 2021	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY53270195	1GHz~26.5GHz	Aug. 21, 2020	Jan. 12, 2021~Jan. 14, 2021	Aug. 20, 2021	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz ~ 40GHz	Jun. 15, 2020	Jan. 12, 2021~Jan. 14, 2021	Jun. 14, 2021	Radiation (03CH15-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz~44GHz	Feb. 10, 2020	Jan. 12, 2021~Jan. 14, 2021	Feb. 09, 2021	Radiation (03CH15-HY)
Spectrum Analyzer	Agilent	E4446A	MY50180136	3Hz~44GHz	May 04, 2020	Jan. 12, 2021~Jan. 14, 2021	May 03, 2021	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jan. 12, 2021~Jan. 14, 2021	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jan. 12, 2021~Jan. 14, 2021	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24(k5)	RK-000451	N/A	N/A	Jan. 12, 2021~Jan. 14, 2021	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104, 102E	MY36980/4, MY9838/4PE, 508405/2E	30MHz~18G	Nov. 16, 2020	Jan. 12, 2021~Jan. 14, 2021	Nov. 15, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz-40GHz	Feb. 25, 2020	Jan. 12, 2021~Jan. 14, 2021	Feb. 24, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz-40GHz	Feb. 25, 2020	Jan. 12, 2021~Jan. 14, 2021	Feb. 24, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz~30MHz	Mar. 12, 2020	Jan. 12, 2021~Jan. 14, 2021	Mar. 11, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN4	1.53G Low Pass	Jul. 03, 2020	Jan. 12, 2021~Jan. 14, 2021	Jul. 02, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WHKX12-1080-1200-15000-60ST	SN5	1.2GHz High Pass Filter	Jul. 01, 2020	Jan. 12, 2021~Jan. 14, 2021	Jun. 30, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN4	3GHz High Pass Filter	Sep. 16, 2020	Jan. 12, 2021~Jan. 14, 2021	Sep. 15, 2021	Radiation (03CH15-HY)
Signal Generator	Anritsu	MG3694C	163401	0.1Hz~40GHz	Feb. 15, 2020	Jan. 12, 2021~Jan. 14, 2021	Feb. 14, 2021	Radiation (03CH15-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.98
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.31
---	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.92
---	------



Appendix A. Test Results of Radiated Test

LTE Band 26

LTE Band 26 / 15MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-56.37	-13	-43.37	-68.34	-61.67	1.83	9.28	H
	2472	-53.70	-13	-40.70	-70.28	-59.93	2.25	10.63	H
	3299	-57.84	-13	-44.84	-76.54	-65.36	2.62	12.30	H
									H
									H
	1648	-57.02	-13	-44.02	-69.45	-62.32	1.83	9.28	V
	2472	-55.10	-13	-42.10	-71.91	-61.33	2.25	10.63	V
	3299	-57.23	-13	-44.23	-76.34	-64.75	2.62	12.30	V
									V
									V
Middle	1656	-54.37	-13	-41.37	-66.4	-59.72	1.84	9.34	H
	2488	-52.26	-13	-39.26	-68.95	-58.58	2.25	10.73	H
	3319	-57.58	-13	-44.58	-76.23	-65.25	2.63	12.45	H
									H
									H
	1656	-54.98	-13	-41.98	-67.47	-60.33	1.84	9.34	V
	2488	-53.24	-13	-40.24	-70.05	-59.56	2.25	10.73	V
	3319	-57.13	-13	-44.13	-76.18	-64.80	2.63	12.45	V
									V
									V



Highest	1672	-49.63	-13	-36.63	-61.78	-55.07	1.85	9.43	H
	2504	-48.45	-13	-35.45	-65.21	-54.84	2.26	10.80	H
	3339	-57.56	-13	-44.56	-76.16	-65.38	2.64	12.61	H
									H
									H
									H
									H
	1672	-54.17	-13	-41.17	-66.79	-59.61	1.85	9.43	V
	2504	-50.85	-13	-37.85	-67.68	-57.24	2.26	10.80	V
	3339	-57.27	-13	-44.27	-76.26	-65.09	2.64	12.61	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 25

LTE Band 25 / 20MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-44.16	-13	-31.16	-65.04	-53.79	2.77	12.40	H
	5555	-43.71	-13	-30.71	-68.73	-53.64	3.46	13.39	H
	7404	-47.01	-13	-34.01	-76.52	-54.21	3.98	11.18	H
									H
									H
									H
									H
	3700	-50.40	-13	-37.40	-71.69	-60.03	2.77	12.40	V
	5555	-41.59	-13	-28.59	-66.69	-51.52	3.46	13.39	V
	7404	-46.57	-13	-33.57	-76.56	-53.77	3.98	11.18	V
									V
									V
									V
									V
Middle	3742	-46.27	-13	-33.27	-67.3	-55.98	2.78	12.48	H
	5611	-46.05	-13	-33.05	-70.91	-55.92	3.48	13.34	H
	7484	-47.28	-13	-34.28	-76.8	-54.45	4.00	11.17	H
									H
									H
									H
									H
	3742	-50.76	-13	-37.76	-72.19	-60.47	2.78	12.48	V
	5611	-40.62	-13	-27.62	-65.7	-50.49	3.48	13.34	V
	7484	-47.09	-13	-34.09	-76.98	-54.26	4.00	11.17	V
									V
									V
									V
									V



Highest	3791	-43.18	-13	-30.18	-64.38	-52.81	2.79	12.42	H
	5688	-44.54	-13	-31.54	-6.981	-54.47	3.50	13.42	H
	7584	-46.99	-13	-33.99	-76.1	-54.30	4.03	11.34	H
									H
									H
									H
									H
	3791	-49.23	-13	-36.23	-70.81	-58.86	2.79	12.42	V
	5688	-38.46	-13	-25.46	-63.96	-48.39	3.50	13.42	V
	7584	-47.22	-13	-34.22	-76.85	-54.53	4.03	11.34	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 13

LTE Band 13 / 5MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1552	-51.50	-13	-38.50	-63.52	-56.18	1.78	8.61	H
	2328	-43.58	-13	-30.58	-59.50	-48.92	2.18	9.67	H
	3112	-57.90	-13	-44.90	-76.24	-64.54	2.53	11.32	H
									H
									H
									H
									H
	1552	-54.49	-13	-41.49	-66.59	-59.17	1.78	8.61	V
	2328	-45.31	-13	-32.31	-61.94	-50.65	2.18	9.67	V
	3112	-57.43	-13	-44.43	-76.32	-64.07	2.53	11.32	V
									V
									V
									V
									V
Middle	1560	-53.97	-42.15	-11.82	-65.92	-58.70	1.78	8.66	H
	2336	-44.25	-13	-31.25	-60.18	-49.63	2.18	9.72	H
	3120	-57.96	-13	-44.96	-76.35	-64.61	2.54	11.34	H
									H
									H
									H
									H
	1560	-54.87	-42.15	-12.72	-66.96	-59.60	1.78	8.66	V
	2336	-45.77	-13	-32.77	-62.41	-51.15	2.18	9.72	V
	3120	-57.30	-13	-44.30	-76.23	-63.95	2.54	11.34	V
									V
									V
									V
									V
								V	



Highest	1560	-53.63	-42.15	-11.48	-65.58	-58.36	1.78	8.66	H
	2344	-43.23	-13	-30.23	-59.16	-48.66	2.19	9.76	H
	3128	-57.65	-13	-44.65	-76.10	-64.31	2.54	11.36	H
									H
									H
									H
									H
	1560	-55.20	-42.15	-13.05	-67.29	-59.93	1.78	8.66	V
	2344	-46.44	-13	-33.44	-63.09	-51.87	2.19	9.76	V
	3128	-57.21	-13	-44.21	-76.19	-63.87	2.54	11.36	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 13 / 10MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1552	-53.73	-13	-40.73	-65.75	-58.41	1.78	8.61	H
	2336	-41.38	-13	-28.38	-57.31	-46.76	2.18	9.72	H
	3112	-57.68	-13	-44.68	-76.02	-64.32	2.53	11.32	H
									H
									H
									H
									H
	1552	-55.19	-13	-42.19	-67.29	-59.87	1.78	8.61	V
	2336	-43.38	-13	-30.38	-60.02	-48.76	2.18	9.72	V
	3112	-57.17	-13	-44.17	-76.06	-63.81	2.53	11.32	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 12

LTE Band 12 / 10MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1400	-47.42	-13.00	-34.42	-58.72	-50.48	1.69	6.90	H
	2096	-45.97	-13.00	-32.97	-60.55	-51.28	2.07	9.53	H
	2800	-48.02	-13.00	-35.02	-65.60	-54.68	2.39	11.20	H
	3496	-55.55	-13.00	-42.55	-74.97	-63.10	2.72	12.42	H
	4197	-55.51	-13.00	-42.51	-77.22	-63.12	2.94	12.70	H
	4896	-49.27	-13.00	-36.27	-72.89	-56.58	3.23	12.69	H
									H
	1400	-42.57	-13.00	-29.57	-54.06	-45.63	1.69	6.90	V
	2096	-46.46	-13.00	-33.46	-61.50	-51.77	2.07	9.53	V
	2800	-48.87	-13.00	-35.87	-66.71	-55.53	2.39	11.20	V
	3497	-56.20	-13.00	-43.20	-76.00	-63.74	2.72	12.41	V
	4197	-54.33	-13.00	-41.33	-76.63	-61.94	2.94	12.70	V
	4896	-50.04	-13.00	-37.04	-74.26	-57.35	3.23	12.69	V
									V
Middle	1408	-43.62	-13.00	-30.62	-55.01	-46.74	1.69	6.96	H
	2112	-48.63	-13.00	-35.63	-63.39	-53.78	2.08	9.38	H
	2808	-47.21	-13.00	-34.21	-64.79	-53.86	2.40	11.20	H
	3512	-55.50	-13.00	-42.50	-75.03	-62.98	2.72	12.35	H
	4218	-55.26	-13.00	-42.26	-77.02	-62.86	2.95	12.70	H
	4920	-49.86	-13.00	-36.86	-73.51	-57.17	3.24	12.70	H
									H
	1408	-41.98	-13.00	-28.98	-53.52	-45.10	1.69	6.96	V
	2112	-45.36	-13.00	-32.36	-60.62	-50.51	2.08	9.38	V
	2816	-47.26	-13.00	-34.26	-65.13	-53.91	2.40	11.20	V
	3515	-56.22	-13.00	-43.22	-76.14	-63.69	2.72	12.34	V
	4218	-54.80	-13.00	-41.80	-77.15	-62.40	2.95	12.70	V
	4920	-49.21	-13.00	-36.21	-73.48	-56.52	3.24	12.70	V
									V



Highest	1416	-45.49	-13.00	-32.49	-57.18	-48.67	1.70	7.03	H
	2120	-47.42	-13.00	-34.42	-62.27	-52.48	2.09	9.30	H
	2824	-46.78	-13.00	-33.78	-64.36	-53.43	2.40	11.20	H
	3536	-54.39	-13.00	-41.39	-74.03	-61.77	2.73	12.26	H
	4239	-54.94	-13.00	-41.94	-76.75	-62.53	2.96	12.70	H
	4944	-49.91	-13.00	-36.91	-73.58	-57.21	3.25	12.70	H
									H
	1416	-42.41	-13.00	-29.41	-54.01	-45.59	1.70	7.03	V
	2120	-47.33	-13.00	-34.33	-62.69	-52.39	2.09	9.30	V
	2824	-47.16	-13.00	-34.16	-65.05	-53.81	2.40	11.20	V
	3536	-55.15	-13.00	-42.15	-75.18	-62.53	2.73	12.26	V
	4239	-54.04	-13.00	-41.04	-76.45	-61.63	2.96	12.70	V
	4944	-46.70	-13.00	-33.70	-71.00	-54.00	3.25	12.70	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 66

LTE Band 66 / 20MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3420	-44.34	-13	-31.34	-63.76	-54.26	2.68	12.60	H
	5135	-50.26	-13	-37.26	-74.61	-59.38	3.32	12.44	H
	6843	-46.14	-13	-33.14	-74.19	-54.68	3.86	12.40	H
									H
									H
									H
									H
	3420	-36.28	-13	-23.28	-56.07	-46.20	2.68	12.60	V
	5135	-48.12	-13	-35.12	-73.03	-57.24	3.32	12.44	V
	6843	-46.87	-13	-33.87	-75.29	-55.41	3.86	12.40	V
									V
									V
									V
									V
Middle	3469	-47.06	-13	-34.06	-66.92	-56.88	2.71	12.52	H
	5205	-47.88	-13	-34.88	-72.47	-57.38	3.34	12.84	H
	6941	-45.93	-13	-32.93	-74.28	-54.04	3.89	12.00	H
									H
									H
									H
									H
	3469	-39.15	-13	-26.15	-59.38	-48.97	2.71	12.52	V
	5205	-49.10	-13	-36.10	-74.17	-58.60	3.34	12.84	V
	6941	-45.87	-13	-32.87	-74.27	-53.98	3.89	12.00	V
									V
									V
									V
									V



Highest	3525	-43.47	-13	-30.47	-63.72	-53.04	2.73	12.30	H
	5282	-48.28	-13	-35.28	-72.91	-58.24	3.37	13.33	H
	7046	-46.40	-13	-33.40	-74.97	-54.11	3.92	11.62	H
									H
									H
									H
									H
	3525	-38.06	-13	-25.06	-58.7	-47.63	2.73	12.30	V
	5282	-49.13	-13	-36.13	-74.11	-59.09	3.37	13.33	V
	7046	-45.61	-13	-32.61	-74.16	-53.32	3.92	11.62	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 7

LTE Band 7 / 20MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	5002	-48.27	-25	-23.27	-72.12	-57.59	3.27	12.59	H
	7503	-43.80	-25	-18.80	-73.28	-51.00	4.00	11.20	H
	10004	-43.07	-25	-18.07	-76.44	-49.61	4.67	11.21	H
									H
									H
									H
									H
	5002	-50.66	-25	-25.66	-75.19	-59.98	3.27	12.59	V
	7503	-42.50	-25	-17.50	-72.35	-49.70	4.00	11.20	V
	10004	-43.31	-25	-18.31	-76.44	-49.85	4.67	11.21	V
									V
									V
									V
									V
Middle	5052	-50.34	-25	-25.34	-74.37	-59.45	3.29	12.40	H
	7578	-42.68	-25	-17.68	-71.83	-49.96	4.03	11.31	H
	10104	-42.95	-25	-17.95	-76.57	-49.64	4.70	11.40	H
									H
									H
									H
									H
	5052	-51.67	-25	-26.67	-76.33	-60.78	3.29	12.40	V
	7578	-42.81	-25	-17.81	-72.46	-50.09	4.03	11.31	V
	10104	-42.97	-25	-17.97	-76.16	-49.66	4.70	11.40	V
									V
									V
									V
									V



Highest	5100	-50.32	-25	-25.32	-74.54	-59.31	3.31	12.30	H
	7650	-42.90	-25	-17.90	-71.98	-50.35	4.05	11.50	H
	10205	-42.53	-25	-17.53	-76.38	-49.09	4.73	11.29	H
									H
									H
									H
									H
	5100	-51.62	-25	-26.62	-76.42	-60.61	3.31	12.30	V
	7650	-41.77	-25	-16.77	-71.39	-49.22	4.05	11.50	V
	10205	-43.09	-25	-18.09	-76.34	-49.65	4.73	11.29	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 41

LTE Band 41 / 20MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	4992	-50.15	-25	-25.15	-73.98	-59.50	3.27	12.62	H
	7488	-39.13	-25	-14.13	-68.64	-46.31	4.00	11.18	H
	9990	-42.94	-25	-17.94	-76.3	-49.45	4.67	11.18	H
									H
									H
									H
									H
	4992	-49.70	-25	-24.70	-74.2	-59.05	3.27	12.62	V
	7488	-37.85	-25	-12.85	-67.72	-45.03	4.00	11.18	V
	9990	-42.55	-25	-17.55	-75.66	-49.06	4.67	11.18	V
									V
									V
									V
									V
Middle	5166	-51.64	-25	-26.64	-76.11	-60.91	3.33	12.60	H
	7752	-41.10	-25	-16.10	-70.29	-48.90	4.09	11.89	H
	10338	-41.81	-25	-16.81	-75.98	-47.95	4.77	10.91	H
									H
									H
									H
									H
	5166	-49.56	-25	-24.56	-74.55	-58.83	3.33	12.60	V
	7752	-38.62	-25	-13.62	-68.31	-46.42	4.09	11.89	V
	10338	-42.69	-25	-17.69	-76.02	-48.83	4.77	10.91	V
									V
									V
									V
									V



Highest	5340	-51.52	-25	-26.52	-76.16	-61.61	3.39	13.48	H
	8010	-41.27	-25	-16.27	-71.23	-47.93	4.18	10.84	H
	10683	-41.42	-25	-16.42	-75.9	-47.63	4.86	11.07	H
									H
									H
									H
									H
	5340	-48.73	-25	-23.73	-73.63	-58.82	3.39	13.48	V
	8010	-42.19	-25	-17.19	-72.27	-48.85	4.18	10.84	V
	10683	-42.55	-25	-17.55	-76.2	-48.76	4.86	11.07	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 71

LTE Band 71 / 20MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1328	-43.52	-13	-30.52	-54.55	-48.34	1.64	6.46	H
	1992	-42.58	-13	-29.58	-56.1	-50.45	2.03	9.90	H
	2656	-53.65	-13	-40.65	-70.37	-62.12	2.33	10.80	H
	3320	-50.16	-13	-37.16	-68.8	-59.99	2.63	12.46	H
	3984	-55.12	-13	-42.12	-76.18	-64.92	2.84	12.64	H
	4648	-51.45	-13	-38.45	-74.49	-60.81	3.15	12.51	H
									H
	1328	-42.69	-13	-29.69	-53.71	-47.51	1.64	6.46	V
	1992	-40.27	-13	-27.27	-54.05	-48.14	2.03	9.90	V
	2656	-50.81	-13	-37.81	-68.09	-59.28	2.33	10.80	V
	3320	-42.79	-13	-29.79	-61.83	-52.62	2.63	12.46	V
	3984	-54.46	-13	-41.46	-75.95	-64.26	2.84	12.64	V
	4648	-52.51	-13	-39.51	-76	-61.87	3.15	12.51	V
									V
Middle	1352	-46.30	-13	-33.30	-57.43	-51.16	1.66	6.52	H
	2024	-39.25	-13	-26.25	-53.05	-47.11	2.04	9.90	H
	2696	-51.42	-13	-38.42	-68.38	-59.87	2.35	10.80	H
	3368	-49.48	-13	-36.48	-68	-59.49	2.66	12.66	H
	4044	-54.87	-13	-41.87	-76.09	-64.71	2.86	12.70	H
	4720	-51.29	-13	-38.29	-74.55	-60.62	3.17	12.50	H
									H
	1344	-47.55	-13	-34.55	-58.67	-52.39	1.65	6.49	V
	2024	-38.69	-13	-25.69	-52.8	-46.55	2.04	9.90	V
	2696	-51.31	-13	-38.31	-68.74	-59.76	2.35	10.80	V
	3368	-44.00	-13	-31.00	-62.9	-54.01	2.66	12.66	V
	4044	-54.60	-13	-41.60	-76.29	-64.44	2.86	12.70	V
	4718	-52.73	-13	-39.73	-76.47	-62.06	3.17	12.50	V
									V



Highest	1360	-46.48	-13	-33.48	-57.63	-51.40	1.66	6.58	H
	2040	-29.54	-13	-16.54	-43.52	-37.39	2.05	9.90	H
	2720	-50.68	-13	-37.68	-67.77	-59.20	2.36	10.88	H
	3392	-27.72	-13	-14.72	-46.18	-37.67	2.67	12.62	H
	4072	-52.03	-13	-39.03	-73.33	-61.85	2.88	12.70	H
	4752	-32.41	-13	-19.41	-55.77	-41.73	3.19	12.51	H
	5432	-52.13	-13	-39.13	-76.73	-61.90	3.43	13.20	H
	6112	-37.65	-13	-24.65	-63.39	-47.29	3.61	13.25	H
	1360	-44.13	-13	-31.13	-55.36	-49.05	1.66	6.58	V
	2040	-31.46	-13	-18.46	-45.78	-39.31	2.05	9.90	V
	2712	-46.11	-13	-33.11	-63.6	-54.60	2.35	10.85	V
	3392	-22.68	-13	-9.68	-41.52	-32.63	2.67	12.62	V
	4072	-53.74	-13	-40.74	-75.53	-63.56	2.88	12.70	V
	4752	-35.25	-13	-22.25	-59.11	-44.57	3.19	12.51	V
	5432	-51.90	-13	-38.90	-76.58	-61.67	3.43	13.20	V
	6112	-35.67	-13	-22.67	-61.52	-45.31	3.61	13.25	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.