

FCC SAR TEST REPORT

FCC ID : P4Q-N672B
Equipment : LTE Module
Brand Name : MITAC,MIO, Magellen,Teletrac Navman
Model Name : SC600T-NA
Applicant : MiTAC Digital Technology Corporation
4F., NO. 1, R&D ROAD 2, HSINCHU SCIENCE PARK,
HSINCHU 30076, TAIWAN, R.O.C.
Manufacturer 1 : MITAC Computer (Kunshan) Co., Ltd.
No. 269, 2nd Avenue, District A, Comprehensive
Free Trade Zone, 300 Kunshan, China
Manufacturer 2 : MITAC DIGITAL TECHNOLOGY CORPORATION
NO.4, R&D ROAD 2, HSINCHU SCIENCE PARK,
HSINCHU, TAIWAN, R.O.C.
Standard : FCC 47 CFR Part 2 (2.1093)

The product was installed into Tablet (Brand Name: MITAC,MIO, Magellen,Teletrac Navman, Model Name: N672B) during test.

The product was received on Jun. 07, 2022 and testing was started from Jun. 27, 2022 and completed on Jul. 07, 2022. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample provide by manufacturer and the test data has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been pass the FCC requirement.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager



Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan



Table of Contents

1. Statement of Compliance 4

2. Guidance Applied..... 4

3. Equipment Under Test (EUT) Information 5

 3.1 General Information 5

 3.2 General LTE SAR Test and Reporting Considerations 7

4. RF Exposure Limits.....10

 4.1 Uncontrolled Environment.....10

 4.2 Controlled Environment.....10

5. Specific Absorption Rate (SAR).....11

 5.1 Introduction11

 5.2 SAR Definition.....11

6. System Description and Setup12

 6.1 Test Site Location.....12

 6.2 E-Field Probe13

 6.3 Data Acquisition Electronics (DAE)13

 6.4 Phantom.....14

 6.5 Device Holder.....15

7. Measurement Procedures16

 7.1 Spatial Peak SAR Evaluation16

 7.2 Power Reference Measurement.....17

 7.3 Area Scan17

 7.4 Zoom Scan.....18

 7.5 Volume Scan Procedures.....18

 7.6 Power Drift Monitoring.....18

8. Test Equipment List19

9. System Verification20

 9.1 Tissue Verification20

 9.2 System Performance Check Results.....21

10. RF Exposure Positions22

 10.1 Ear and handset reference point22

 10.2 Definition of the cheek position23

 10.3 Definition of the tilt position24

 10.4 Body Worn Accessory24

 10.5 Product Specific Exposure25

 10.6 Wireless Router.....25

11. UMTS/LTE Output Power (Unit: dBm)26

12. WiFi/Bluetooth Output Power (Unit: dBm)58

13. Antenna Location62

14. SAR Test Results63

 14.1 Head SAR65

 14.2 Hotspot SAR66

 14.3 Body Worn Accessory SAR.....67

 14.4 Product Specific SAR.....68

15. Simultaneous Transmission Analysis68

 15.1 Head Exposure Conditions69

 15.2 Hotspot Exposure Conditions.....70

 15.3 Body-Worn Accessory Exposure Conditions72

 15.4 Product Specific Exposure Conditions72

16. Uncertainty Assessment73

17. References73

Appendix A. Plots of System Performance Check

Appendix B. Plots of High SAR Measurement

Appendix C. DASYS Calibration Certificate

Appendix D. Test Setup Photos



History of this test report

Report No.	Version	Description	Issued Date
FA000714-06	01	Initial issue of report	Jul. 19, 2022



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for MiTAC Digital Technology Corporation, LTE Module, SC600T-NA, are as follows.

Equipment Class	Frequency Band		Highest SAR Summary				Highest Simultaneous Transmission 1g SAR (W/kg)
			Head (Separation 0mm)	Body-worn (Separation 10mm)	Hotspot (Separation 10mm)	Product Specific (Separation 0mm)	
			1g SAR (W/kg)			10g SAR (W/kg)	
Licensed	WCDMA	WCDMA II	0.52	0.81	0.81		1.02
		WCDMA IV	0.58	0.85	0.85		
		WCDMA V	0.17	0.16	0.16		
	LTE	LTE Band 7	0.26	0.90	0.90		
		LTE Band 12/17	0.23	0.39	0.39		
		LTE Band 13	0.13	0.22	0.22		
		LTE Band 14	0.14	0.21	0.21		
		LTE Band 2/25	0.39	0.62	0.62		
		LTE Band 5/26	0.19	0.15	0.15		
		LTE Band 41	0.14	0.46	0.46		
		LTE Band 4/66	0.42	0.71	0.71		
		LTE Band 71	0.30	0.41	0.41		
DTS	WLAN	2.4GHz WLAN	0.04	0.06	0.06		1.02
NII		5GHz WLAN	0.06	0.06	0.09	0.11	1.02
DSS	2.4GHz Band	Bluetooth	0.01	0.04	0.04		1.00
Date of Testing:			2022/6/27 ~ 2022/7/7				

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation and the FCC designation No. TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Reviewed by: Jason Wang
Report Producer: Carlie Tsai

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards, the below KDB standard may not including in the TAF code without accreditation.

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01
- FCC KDB 941225 D07 UMPC Mini Tablet v01r02



3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	LTE Module
Brand Name	MITAC,MIO, Magellen,Teletrac Navman
Model Name	SC600T-NA
FCC ID	P4Q-N672B
Integrated WWAN + WLAN Module	Brand Name: Quectel Model Name: SC600T-NA
Wireless Technology and Frequency Range	WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 14: 788 MHz ~ 798 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 66: 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz WLAN U-NII 1: 5150 MHz ~ 5250 MHz WLAN U-NII 2: 5250 MHz ~ 5350 MHz WLAN U-NII 3: 5470 MHz ~ 5725 MHz WLAN U-NII 4: 5725 MHz ~ 5825 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz NFC : 13.56 MHz
Mode	RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA LTE: QPSK, 16QAM WLAN: 802.11a/b/g/n/ac HT20/HT40/VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE NFC: ASK
EUT Stage	Production Unit
Remark:	
<ol style="list-style-type: none"> This device adds two samples without barcode, SKU E and SKU F. Verifying the worst cases from Sporton SAR Test Report, Report No.: FA0D1806. RF exposure evaluation selects SKU E as the main test only, the difference between SKU E and SKU F is NFC, which were listed below table. This device WLAN 2.4GHz / 5.2GHz / 5.8GHz supports Hotspot operation and Bluetooth support tethering applications. 	

Host Information	
Equipment Name	Tablet
Brand Name	MITAC,MIO, Magellen,Teletrac Navman
Model Name	N672B



Functions	SKU A	SKU B
Screen:	5" 720x1280 (HD), IPS, 350nits (w/ touch)	5" 720x1280 (HD), IPS, 350nits (w/ touch)
CPU:	SD625 octa core 2.0GHz	SD625 octa core 2.0GHz
battery:	4110mAh (hard pack),	4110mAh (hard pack),
RAM:	3GB	3GB
Storage:	32GB	32GB
External storage:	Support	Support
WWAN + WLAN Module	Support (SC600T-NA)	Support (SC600T-NA)
NFC/RFID(HF)	Support	Support
GPS	Support	Support
Barcode	Support(N6603)	Support(N3601)

Functions	SKU C	SKU D
Screen:	5" 720x1280 (HD), IPS, 350nits (w/ touch)	5" 720x1280 (HD), IPS, 350nits (w/ touch)
CPU:	SD625 octa core 2.0GHz	SD625 octa core 2.0GHz
battery:	4110mAh (hard pack),	4110mAh (hard pack),
RAM:	2GB	2GB
Storage:	16GB	16GB
External storage:	Support	Support
WWAN + WLAN Module	Support (SC600T-NA)	Support (SC600T-NA)
NFC/RFID(HF)	Support	Support
GPS	Support	Support
Barcode	Support(N6603)	Support(N3601)

Functions	SKU E	SKU F
Screen	5" 720x1280 (HD), IPS, 350nits (w/ touch)	5" 720x1280 (HD), IPS, 350nits (w/ touch)
CPU	SD625 octa core 2.0GHz	SD625 octa core 2.0GHz
Battery	4110mAh (hard pack),	4110mAh (hard pack),
RAM	3GB	3GB
Storage	32GB	32GB
External storage	Support	Support
WWAN + WLAN Module	Support (SC600T-NA)	Support (SC600T-NA)
NFC/RFID(HF)	Support	Not Support
GPS	Support	Support



3.2 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05																																																															
FCC ID	P4Q-N672B																																																														
Equipment Name	LTE Module																																																														
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 14: 788 MHz ~ 798 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 66: 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz																																																														
Channel Bandwidth	LTE Band 2: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 4: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 5: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 12: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 13: 5MHz, 10MHz LTE Band 14: 5MHz, 10MHz LTE Band 17: 5MHz, 10MHz LTE Band 25: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 26: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 66: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 71: 5MHz, 10MHz, 15MHz, 20MHz																																																														
uplink modulations used	QPSK / 16QAM																																																														
LTE Voice / Data requirements	Data only																																																														
LTE MPR permanently built-in by design	<p align="center">Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3</p> <table border="1"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (N_{RB})</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 3</td> </tr> <tr> <td>256 QAM</td> <td colspan="6">≥ 1</td> <td>≤ 5</td> </tr> </tbody> </table>	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	256 QAM	≥ 1						≤ 5
Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)																																																								
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																									
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																								
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																								
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																								
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2																																																								
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3																																																								
256 QAM	≥ 1						≤ 5																																																								
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																														
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																														



Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829	20450	829	20450	829
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5
H	20643	848.3	20635	847.5	20625	846.5	20600	844	20600	844	20600	844
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510	20850	2510	20850	2510
M	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560	21350	2560	21350	2560
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	23017	699.7	23025	700.5	23035	701.5	23060	704	23060	704	23060	704
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5	23095	707.5	23095	707.5
H	23173	715.3	23165	714.5	23155	713.5	23130	711	23130	711	23130	711
LTE Band 13												
	Bandwidth 5 MHz				Bandwidth 10 MHz				Bandwidth 10 MHz			
	Channel #		Freq.(MHz)		Channel #		Freq.(MHz)		Channel #		Freq.(MHz)	
L	23205		779.5		23230		782		23230		782	
M	23230		782									
H	23255		784.5									
LTE Band 14												
	Bandwidth 5 MHz				Bandwidth 10 MHz				Bandwidth 10 MHz			
	Channel #		Channel #		Channel #		Freq.(MHz)		Channel #		Freq.(MHz)	
L	23305		790.5		23330		793		23330		793	
M	23330		793									
H	23355		795.5									
LTE Band 17												
	Bandwidth 5 MHz				Bandwidth 10 MHz				Bandwidth 10 MHz			
	Channel #		Freq.(MHz)		Channel #		Freq. (MHz)		Channel #		Freq. (MHz)	
L	23755		706.5		23780		709		23780		709	
M	23790		710		23790		710		23790		710	
H	23825		713.5		23800		711		23800		711	



LTE Band 25												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26047	1850.7	26055	1851.5	26065	1852.5	26090	1855	26115	1857.5	26140	1860
M	26340	1880	26340	1880	26340	1880	26340	1880	26340	1880	26340	1880
H	26683	1914.3	26675	1913.5	26665	1912.5	26640	1910	26615	1907.5	26590	1905
LTE Band 26												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26697	814.7	26705	815.5	26715	816.5	26740	819	26740	819	26765	821.5
M	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5
H	27033	848.3	27025	847.5	27015	846.5	26990	844	26990	844	26965	841.5
LTE Band 41												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	39675	2498.5	39700	2501	39725	2503.5	39750	2506	39750	2506	39750	2506
L	40148	2545.8	40160	2547	40173	2548.3	40185	2549.5	40185	2549.5	40185	2549.5
M	40620	2593	40620	2593	40620	2593	40620	2593	40620	2593	40620	2593
H	41093	2640.3	41080	2639	41068	2637.8	41055	2636.5	41055	2636.5	41055	2636.5
H	41565	2687.5	41540	2685	41515	2682.5	41490	2680	41490	2680	41490	2680
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770
LTE Band 71												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	133147	665.5	133172	668	133197	670.5	133222	673	133222	673	133222	673
M	133297	680.5	133297	680.5	133297	680.5	133297	680.5	133297	680.5	133297	680.5
H	133447	695.5	133422	693	133397	690.5	133372	688	133372	688	133372	688



4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- The DASY system in SAR Configuration is shown above
- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running windows software and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 Test Site Location


The SAR measurement facilities used to collect data are within both Sporton Lab list below test site location are accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190 and 3786) and the FCC designation No. TW1190 and TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test.

Test Site	EMC & Wireless Communications Laboratory		Wensan Laboratory		
Test Site Location	TW1190 No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan		TW3786 No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan		
Test Site No.	SAR01-HY	SAR03-HY	SAR08-HY	SAR09-HY	SAR15-HY
	SAR04-HY	SAR05-HY	SAR11-HY	SAR12-HY	
	SAR06-HY	SAR10-HY	SAR13-HY	SAR14-HY	


6.2 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.3 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.





Fig 5.1 Photo of DAE


6.4 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.5 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

		≤ 3 GHz	> 3 GHz	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm	
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1117	Mar. 24, 2022	Mar. 23, 2023
SPEAG	835MHz System Validation Kit ⁽²⁾	D835V2	4d167	Nov. 25, 2019	Nov. 22, 2022
SPEAG	1750MHz System Validation Kit	D1750V2	1120	Mar. 25, 2022	Mar. 24, 2023
SPEAG	1900MHz System Validation Kit	D1900V2	5d093	Mar. 25, 2022	Mar. 24, 2023
SPEAG	2450MHz System Validation Kit	D2450V2	736	Aug. 17, 2021	Aug. 17, 2022
SPEAG	2600MHz System Validation Kit	D2600V2	1008	Aug. 17, 2021	Aug. 16, 2022
SPEAG	2600MHz System Validation Kit	D2600V2	1089	Mar. 24, 2022	Mar. 23, 2023
SPEAG	5GHz System Validation Kit ⁽²⁾	D5GHzV2	1128	Dec. 16, 2019	Dec. 13, 2022
SPEAG	Data Acquisition Electronics	DAE4	699	Feb. 24, 2022	Feb. 23, 2023
SPEAG	Data Acquisition Electronics	DAE4	1399	Feb. 28, 2022	Feb. 27, 2023
SPEAG	Data Acquisition Electronics	DAE4	1424	Jan. 20, 2022	Jan. 19, 2023
SPEAG	Data Acquisition Electronics	DAE4	1696	Nov. 03, 2021	Nov. 02, 2022
SPEAG	Dosimetric E-Field Probe	ES3DV3	3270	Sep. 21, 2021	Sep. 20, 2022
SPEAG	Dosimetric E-Field Probe	EX3DV4	7625	Jan. 27, 2022	Jan. 26, 2023
SPEAG	Dosimetric E-Field Probe	EX3DV4	7694	Jan. 24, 2022	Jan. 23, 2023
SPEAG	Dosimetric E-Field Probe	EX3DV4	7695	Nov. 19, 2021	Nov. 18, 2022
Testo	Hygro meter	608-H1	45196600	Oct. 22, 2021	Oct. 21, 2022
Testo	Hygro meter	608-H1	45207528	Oct. 22, 2021	Oct. 21, 2022
RCPTWN	Thermometer	HTC-1	TM685-1	Oct. 28, 2021	Oct. 27, 2022
RCPTWN	Thermometer	HTC-1	TM560-2	Oct. 28, 2021	Oct. 27, 2022
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Oct. 21, 2021	Oct. 20, 2022
Keysight	Wireless Communication Test Set	E5515C	MY50266977	May. 10, 2022	May. 09, 2023
R&S	BT Base Station	CBT32	101136	Oct. 17, 2021	Oct. 16, 2022
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Oct. 24, 2021	Oct. 23, 2022
Keysight	ENA Network Analyzer	E5071C	MY46104758	Sep. 19, 2021	Sep. 18, 2022
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 24, 2021	Sep. 23, 2022
LINE SEIKI	Digital Thermometer	DTM3000-spezial	2942	Oct. 26, 2021	Oct. 25, 2022
Anritsu	Power Meter	ML2495A	1419002	Aug. 18, 2021	Aug. 17, 2022
Anritsu	Power Sensor	MA2411B	1911176	Aug. 18, 2021	Aug. 17, 2022
Anritsu	Power Meter	ML2495A	1804003	Oct. 09, 2021	Oct. 08, 2022
Anritsu	Power Sensor	MA2411B	1726150	Oct. 09, 2021	Oct. 08, 2022
Anritsu	Spectrum Analyzer	N9010A	MY53470118	Jan. 12, 2022	Jan. 11, 2023
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 19, 2021	Aug. 18, 2022
Mini-Circuits	Power Amplifier	ZVE-8G+	6418	Oct. 12, 2021	Oct. 11, 2022
Mini-Circuits	Power Amplifier	ZVE-8G+	479102029	Sep. 06, 2021	Sep. 05, 2022
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Warison	Directional Coupler	WCOU-10-50S-10	WR889BMC4B1	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. The dipole calibration interval can be extended to 3 years with justification according to KDB 865664 D01. The dipoles are also not physically damaged, or repaired during the interval. The justification data in appendix C can be found which the return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration for each dipole.



9. System Verification

9.1 Tissue Verification

The tissue dielectric parameters of tissue-equivalent media used for SAR measurements must be characterized within a temperature range of 18°C to 25°C, measured with calibrated instruments and apparatuses, such as network analyzers and temperature probes. The temperature of the tissue-equivalent medium during SAR measurement must also be within 18°C to 25°C and within ± 2°C of the temperature when the tissue parameters are characterized. The tissue dielectric measurement system must be calibrated before use. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements.

The liquid tissue depth was at least 15cm in the phantom for all SAR testing

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ε _r)	Conductivity Target (σ)	Permittivity Target (ε _r)	Delta (σ) (%)	Delta (ε _r) (%)	Limit (%)	Date
750	22.5	0.886	41.755	0.89	41.90	-0.45	-0.35	±5	2022/6/27
835	22.5	0.920	41.459	0.90	41.50	2.22	-0.10	±5	2022/6/27
1750	22.7	1.373	40.418	1.37	40.10	0.22	0.79	±5	2022/6/28
1900	22.7	1.450	38.870	1.40	40.00	3.57	-2.83	±5	2022/6/28
2450	22.6	1.840	40.110	1.80	39.20	2.22	2.32	±5	2022/6/29
2600	22.7	1.999	39.165	1.96	39.00	1.99	0.42	±5	2022/6/28
2600	22.8	1.992	38.230	1.96	39.00	1.63	-1.97	±5	2022/6/30
5250	22.6	4.800	36.871	4.71	35.95	1.91	2.56	±5	2022/6/29
5250	22.5	4.754	36.714	4.71	35.95	0.93	2.13	±5	2022/7/7
5600	22.6	5.177	36.360	5.07	35.50	2.11	2.42	±5	2022/6/29
5600	22.5	5.128	36.203	5.07	35.50	1.14	1.98	±5	2022/7/7
5750	22.6	5.345	36.177	5.22	35.35	2.39	2.34	±5	2022/6/29
5750	22.5	5.295	36.020	5.22	35.35	1.44	1.90	±5	2022/7/7

9.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Test Site	Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
SAR11	2022/6/27	750	50	D750V3-1117	EX3DV4 - SN7694	DAE4 Sn1424	0.410	8.52	8.2	-3.76
SAR11	2022/6/27	835	50	D835V2-4d167	EX3DV4 - SN7694	DAE4 Sn1424	0.490	9.55	9.8	2.62
SAR11	2022/6/28	1750	50	D1750V2-1120	EX3DV4 - SN7694	DAE4 Sn1424	1.740	36.40	34.8	-4.40
SAR11	2022/6/28	1900	50	D1900V2-5d093	EX3DV4 - SN7694	DAE4 Sn1424	1.980	39.90	39.6	-0.75
SAR08	2022/6/29	2450	250	D2450V2-736	EX3DV4 - SN7625	DAE4 Sn1696	13.200	54.20	52.8	-2.58
SAR11	2022/6/28	2600	50	D2600V2-1089	EX3DV4 - SN7694	DAE4 Sn1424	2.860	55.40	57.2	3.25
SAR13	2022/6/30	2600	250	D2600V2-1008	ES3DV3 - SN3270	DAE4 Sn1399	14.700	58.00	58.8	1.38
SAR08	2022/6/29	5250	100	D5GHZV2-1128-5250	EX3DV4 - SN7625	DAE4 Sn1696	7.620	80.00	76.2	-4.75
SAR12	2022/7/7	5250	100	D5GHZV2-1128-5250	EX3DV4 - SN7695	DAE4 Sn699	8.660	80.00	86.6	8.25
SAR08	2022/6/29	5600	100	D5GHZV2-1128-5600	EX3DV4 - SN7625	DAE4 Sn1696	8.390	82.40	83.9	1.82
SAR12	2022/7/7	5600	100	D5GHZV2-1128-5600	EX3DV4 - SN7695	DAE4 Sn699	8.980	82.40	89.8	8.98
SAR08	2022/6/29	5750	100	D5GHZV2-1128-5750	EX3DV4 - SN7625	DAE4 Sn1696	7.920	79.10	79.2	0.13
SAR12	2022/7/7	5750	100	D5GHZV2-1128-5750	EX3DV4 - SN7695	DAE4 Sn699	8.600	79.10	86	8.72

Test Site	Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
SAR08	2022/6/29	5250	100	D5GHZV2-1128-5250	EX3DV4 - SN7625	DAE4 Sn1696	2.160	22.90	21.6	-5.68
SAR12	2022/7/7	5250	100	D5GHZV2-1128-5250	EX3DV4 - SN7695	DAE4 Sn699	2.480	22.90	24.8	8.30
SAR08	2022/6/29	5600	100	D5GHZV2-1128-5600	EX3DV4 - SN7625	DAE4 Sn1696	2.370	23.60	23.7	0.42
SAR12	2022/7/7	5600	100	D5GHZV2-1128-5600	EX3DV4 - SN7695	DAE4 Sn699	2.560	23.60	25.6	8.47




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

10. RF Exposure Positions

10.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom



Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

10.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 9.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

10.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

10.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-chip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position



10.5 Product Specific Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.6 The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

10.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9$ cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.



11. UMTS/LTE Output Power (Unit: dBm)

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{HS} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCl
 - viii. Confirm that E-TFCl is equal to the target E-TFCl of 75 for sub-test 1, and other subtest's E-TFCl
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCl
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration

DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Factor to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

Setup Configuration



<WCDMA Conducted Power>

General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938	1537	1638	1738	4357	4407	4458			
Frequency (MHz)		1852.4	1880	1907.6	1712.4	1732.6	1752.6	826.4	836.4	846.6			
3GPP Rel 99	AMR 12.2Kbps	21.24	21.10	21.37	22.50	21.50	21.35	21.75	23.00	22.07	22.15	22.21	23.00
3GPP Rel 99	RMC 12.2Kbps	21.25	21.11	21.38	22.50	21.51	21.38	21.77	23.00	22.08	22.17	22.23	23.00
3GPP Rel 6	HSDPA Subtest-1	21.04	21.08	20.99	21.50	21.36	21.39	21.36	22.00	22.05	22.12	22.08	22.50
3GPP Rel 6	HSDPA Subtest-2	21.02	21.02	21.01	21.50	21.27	21.37	21.27	22.00	22.11	22.15	22.08	22.50
3GPP Rel 6	HSDPA Subtest-3	20.91	21.00	20.91	21.00	21.25	21.35	21.25	21.50	21.93	21.99	21.90	22.00
3GPP Rel 6	HSDPA Subtest-4	20.92	21.00	20.94	21.00	21.32	21.36	21.32	21.50	21.94	21.99	21.94	22.00
3GPP Rel 8	DC-HSDPA Subtest-1	21.02	21.02	20.91	21.50	21.29	21.38	21.36	22.00	20.85	21.12	20.89	22.00
3GPP Rel 8	DC-HSDPA Subtest-2	20.98	20.96	21.00	21.50	21.18	21.30	21.24	22.00	20.97	21.12	20.85	22.00
3GPP Rel 8	DC-HSDPA Subtest-3	20.89	20.90	20.89	21.00	21.19	21.34	21.18	21.50	20.50	20.61	20.52	21.50
3GPP Rel 8	DC-HSDPA Subtest-4	20.88	20.93	20.90	21.00	21.22	21.31	21.30	21.50	20.58	20.58	20.41	21.50
3GPP Rel 6	HSUPA Subtest-1	19.78	20.00	20.10	21.50	20.35	20.61	20.46	22.00	21.27	21.40	21.45	22.00
3GPP Rel 6	HSUPA Subtest-2	17.76	18.04	18.13	19.50	18.30	18.56	18.47	20.00	19.28	19.39	19.44	20.00
3GPP Rel 6	HSUPA Subtest-3	18.78	18.98	19.04	20.50	19.41	19.61	19.55	21.00	20.33	20.34	20.46	21.00
3GPP Rel 6	HSUPA Subtest-4	17.81	18.04	18.06	19.50	18.28	18.56	18.54	20.00	19.41	19.32	19.46	20.00
3GPP Rel 6	HSUPA Subtest-5	19.86	20.09	20.12	21.50	20.32	20.57	20.59	22.00	21.30	21.32	21.45	22.00

**<LTE Conducted Power>****General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4/B12/B26 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 2/4/5/17 SAR test was covered by Band 25/66/26/12; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band



<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				18700	18900	19100	
Frequency (MHz)				1860	1880	1900	
20	QPSK	1	0	21.33	21.29	21.40	
20	QPSK	1	49	21.02	21.06	21.02	22.5
20	QPSK	1	99	21.18	21.28	21.21	
20	QPSK	50	0	19.97	20.06	19.96	
20	QPSK	50	24	20.26	20.36	20.36	21.5
20	QPSK	50	50	20.14	20.21	20.13	
20	QPSK	100	0	20.19	20.22	20.20	
20	16QAM	1	0	20.25	20.32	20.30	21.5
20	16QAM	1	49	20.22	20.28	20.19	
20	16QAM	1	99	20.42	20.43	20.41	
20	16QAM	50	0	19.14	19.19	19.11	20.5
20	16QAM	50	24	19.12	19.13	19.11	
20	16QAM	50	50	18.96	19.02	18.94	
20	16QAM	100	0	18.95	19.05	19.00	20.5
20	64QAM	1	0	19.99	19.99	19.89	
20	64QAM	1	49	19.96	20.05	19.96	
20	64QAM	1	99	19.97	20.01	20.01	20.5
20	64QAM	50	0	18.91	19.00	18.90	
20	64QAM	50	24	18.85	18.92	18.85	
20	64QAM	50	50	18.93	19.01	18.96	19.5
20	64QAM	100	0	18.92	18.98	18.88	
Channel				18675	18900	19125	
Frequency (MHz)				1857.5	1880	1902.5	
15	QPSK	1	0	21.32	21.22	21.35	
15	QPSK	1	37	21.02	21.39	21.00	22.5
15	QPSK	1	74	21.13	21.36	21.11	
15	QPSK	36	0	19.90	19.99	19.90	
15	QPSK	36	20	20.18	19.98	20.30	21.5
15	QPSK	36	39	20.04	20.20	20.05	
15	QPSK	75	0	20.12	19.97	20.17	
15	16QAM	1	0	20.21	20.44	20.25	21.5
15	16QAM	1	37	20.21	20.22	20.12	
15	16QAM	1	74	20.39	20.38	20.40	
15	16QAM	36	0	19.08	18.89	19.09	20.5
15	16QAM	36	20	19.06	19.05	19.09	
15	16QAM	36	39	18.90	19.16	18.88	
15	16QAM	75	0	18.94	19.14	18.92	20.5
15	64QAM	1	0	19.89	20.19	19.84	
15	64QAM	1	37	19.96	19.87	19.92	
15	64QAM	1	74	19.94	19.95	19.94	20.5
15	64QAM	36	0	18.88	18.98	18.86	
15	64QAM	36	20	18.77	18.95	18.76	
15	64QAM	36	39	18.90	18.88	18.89	19.5
15	64QAM	75	0	18.82	19.04	18.78	
Channel				18650	18900	19150	
Frequency (MHz)				1855	1880	1905	
10	QPSK	1	0	21.30	21.19	21.30	
10	QPSK	1	25	21.02	20.96	21.00	22.5
10	QPSK	1	49	21.11	21.19	21.03	
10	QPSK	25	0	19.90	19.95	19.88	
10	QPSK	25	12	20.12	20.27	20.20	21.5



FCC SAR TEST REPORT

Report No. : FA000714-06

10	QPSK	25	25	20.02	20.16	20.00	
10	QPSK	50	0	20.12	20.10	20.15	
10	16QAM	1	0	20.11	20.21	20.21	
10	16QAM	1	25	20.20	20.19	20.05	21.5
10	16QAM	1	49	20.36	20.29	20.38	
10	16QAM	25	0	18.99	19.10	19.08	
10	16QAM	25	12	19.04	18.98	19.03	20.5
10	16QAM	25	25	18.90	18.94	18.85	
10	16QAM	50	0	18.89	18.96	18.84	
10	64QAM	1	0	19.83	19.85	19.79	20.5
10	64QAM	1	25	19.94	19.86	19.85	
10	64QAM	1	49	19.86	19.90	19.89	
10	64QAM	25	0	18.88	18.97	18.80	19.5
10	64QAM	25	12	18.68	18.83	18.76	
10	64QAM	25	25	18.83	18.87	18.82	
10	64QAM	50	0	18.73	18.92	18.72	
Channel				18625	18900	19175	
Frequency (MHz)				1852.5	1880	1907.5	
5	QPSK	1	0	21.25	21.11	21.25	22.5
5	QPSK	1	12	20.98	20.83	20.89	
5	QPSK	1	24	20.98	21.23	21.01	
5	QPSK	12	0	19.83	19.86	19.81	21.5
5	QPSK	12	7	20.02	20.25	20.13	
5	QPSK	12	13	19.90	20.07	20.01	
5	QPSK	25	0	19.99	20.04	20.08	
5	16QAM	1	0	20.13	20.10	20.07	
5	16QAM	1	12	20.16	20.18	20.02	21.5
5	16QAM	1	24	20.32	20.35	20.35	
5	16QAM	12	0	18.96	19.05	19.01	
5	16QAM	12	7	18.89	18.92	19.00	20.5
5	16QAM	12	13	18.73	18.95	18.73	
5	16QAM	25	0	18.87	18.96	18.89	
5	64QAM	1	0	19.83	19.84	19.70	
5	64QAM	1	12	19.88	19.87	19.87	
5	64QAM	1	24	19.86	19.90	19.94	20.5
5	64QAM	12	0	18.80	18.86	18.82	
5	64QAM	12	7	18.73	18.83	18.68	
5	64QAM	12	13	18.81	18.84	18.81	
5	64QAM	25	0	18.81	18.86	18.78	
Channel				18615	18900	19185	Tune-up limit (dBm)
Frequency (MHz)				1851.5	1880	1908.5	
3	QPSK	1	0	21.23	21.08	21.15	22.5
3	QPSK	1	8	20.97	20.77	20.83	
3	QPSK	1	14	20.90	21.22	21.00	
3	QPSK	8	0	19.81	19.86	19.78	21.5
3	QPSK	8	4	19.95	20.24	20.10	
3	QPSK	8	7	19.81	20.02	19.98	
3	QPSK	15	0	19.91	19.98	20.08	
3	16QAM	1	0	20.04	20.07	19.98	
3	16QAM	1	8	20.16	20.09	19.92	21.5
3	16QAM	1	14	20.24	20.31	20.26	
3	16QAM	8	0	18.90	18.99	19.00	
3	16QAM	8	4	18.88	18.89	18.92	20.5
3	16QAM	8	7	18.67	18.90	18.63	
3	16QAM	15	0	18.87	18.86	18.81	
3	64QAM	1	0	19.78	19.83	19.67	



3	64QAM	1	8	19.81	19.77	19.80	19.5
3	64QAM	1	14	19.82	19.85	19.84	
3	64QAM	8	0	18.75	18.78	18.76	
3	64QAM	8	4	18.69	18.81	18.59	
3	64QAM	8	7	18.80	18.83	18.79	
3	64QAM	15	0	18.75	18.76	18.74	
Channel				18607	18900	19193	Tune-up limit (dBm)
Frequency (MHz)				1850.7	1880	1909.3	
1.4	QPSK	1	0	21.21	21.00	21.09	22.5
1.4	QPSK	1	3	20.89	20.73	20.78	
1.4	QPSK	1	5	20.86	21.20	20.98	
1.4	QPSK	3	0	21.20	20.98	21.05	
1.4	QPSK	3	1	20.87	20.63	20.69	
1.4	QPSK	3	3	20.78	21.11	20.92	
1.4	QPSK	6	0	19.81	19.94	20.02	21.5
1.4	16QAM	1	0	20.02	20.06	19.91	21.5
1.4	16QAM	1	3	20.12	20.05	19.85	
1.4	16QAM	1	5	20.22	20.23	20.17	
1.4	16QAM	3	0	20.01	19.97	19.81	
1.4	16QAM	3	1	20.04	19.95	19.85	
1.4	16QAM	3	3	20.13	20.21	20.10	
1.4	16QAM	6	0	18.78	18.77	18.80	20.5
1.4	64QAM	1	0	19.73	19.79	19.67	20.5
1.4	64QAM	1	3	19.71	19.71	19.71	
1.4	64QAM	1	5	19.81	19.76	19.79	
1.4	64QAM	3	0	18.67	18.68	18.74	
1.4	64QAM	3	1	18.69	18.73	18.55	
1.4	64QAM	3	3	18.71	18.80	18.74	
1.4	64QAM	6	0	18.69	18.74	18.64	19.5

<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				20050	20175	20300	Tune-up limit (dBm)
Frequency (MHz)				1720	1732.5	1745	
20	QPSK	1	0	21.13	21.18	21.12	
20	QPSK	1	49	21.11	21.16	21.10	
20	QPSK	1	99	21.02	21.04	21.02	
20	QPSK	50	0	20.14	20.16	20.10	22
20	QPSK	50	24	20.10	20.18	20.18	
20	QPSK	50	50	20.06	20.15	20.06	
20	QPSK	100	0	20.20	20.22	20.12	22
20	16QAM	1	0	20.22	20.32	20.23	
20	16QAM	1	49	20.41	20.45	20.36	
20	16QAM	1	99	20.35	20.37	20.37	21
20	16QAM	50	0	19.03	19.13	19.11	
20	16QAM	50	24	19.25	19.26	19.23	
20	16QAM	50	50	19.17	19.18	19.09	21
20	16QAM	100	0	19.09	19.15	19.13	
20	64QAM	1	0	19.88	19.95	19.87	
20	64QAM	1	49	19.93	20.00	19.97	21
20	64QAM	1	99	20.03	20.09	19.99	
20	64QAM	50	0	18.98	19.08	19.01	
20	64QAM	50	24	19.09	19.12	19.08	



FCC SAR TEST REPORT

Report No. : FA000714-06

20	64QAM	50	50	19.09	19.17	19.11	
20	64QAM	100	0	19.12	19.13	19.05	
Channel				20025	20175	20325	Tune-up limit (dBm)
Frequency (MHz)				1717.5	1732.5	1747.5	
15	QPSK	1	0	21.03	21.15	21.07	23
15	QPSK	1	37	21.01	21.11	21.02	
15	QPSK	1	74	21.00	21.05	21.03	
15	QPSK	36	0	20.13	20.10	20.03	22
15	QPSK	36	20	20.05	20.18	20.16	
15	QPSK	36	39	20.03	20.09	20.05	
15	QPSK	75	0	20.12	20.21	20.09	
15	16QAM	1	0	20.17	20.29	20.20	22
15	16QAM	1	37	20.38	20.45	20.26	
15	16QAM	1	74	20.33	20.35	20.33	
15	16QAM	36	0	19.05	19.13	19.05	21
15	16QAM	36	20	19.21	19.25	19.16	
15	16QAM	36	39	19.09	19.11	19.02	
15	16QAM	75	0	19.03	19.08	19.08	
15	64QAM	1	0	19.81	19.92	19.83	21
15	64QAM	1	37	19.88	19.96	19.88	
15	64QAM	1	74	20.01	20.04	19.95	
15	64QAM	36	0	18.93	19.00	18.95	20
15	64QAM	36	20	19.04	19.03	19.05	
15	64QAM	36	39	19.02	19.12	19.06	
15	64QAM	75	0	19.05	19.06	19.05	
Channel				20000	20175	20350	Tune-up limit (dBm)
Frequency (MHz)				1715	1732.5	1750	
10	QPSK	1	0	21.00	21.12	21.02	23
10	QPSK	1	25	21.03	21.04	21.02	
10	QPSK	1	49	21.08	21.04	21.05	
10	QPSK	25	0	20.13	20.05	20.05	22
10	QPSK	25	12	20.05	20.10	20.07	
10	QPSK	25	25	20.03	20.09	20.01	
10	QPSK	50	0	20.08	20.16	20.08	
10	16QAM	1	0	20.10	20.24	20.14	22
10	16QAM	1	25	20.34	20.37	20.23	
10	16QAM	1	49	20.24	20.30	20.24	
10	16QAM	25	0	19.04	19.03	19.01	21
10	16QAM	25	12	19.16	19.17	19.15	
10	16QAM	25	25	19.04	19.10	19.05	
10	16QAM	50	0	19.01	19.08	19.03	
10	64QAM	1	0	19.71	19.86	19.81	21
10	64QAM	1	25	19.83	19.93	19.78	
10	64QAM	1	49	19.92	20.02	19.90	
10	64QAM	25	0	18.93	18.93	18.91	20
10	64QAM	25	12	19.03	18.98	18.98	
10	64QAM	25	25	18.99	19.11	19.05	
10	64QAM	50	0	18.97	19.06	19.01	
Channel				19975	20175	20375	Tune-up limit (dBm)
Frequency (MHz)				1712.5	1732.5	1752.5	
5	QPSK	1	0	21.04	21.12	21.02	23
5	QPSK	1	12	21.06	21.04	21.02	
5	QPSK	1	24	21.07	21.00	21.01	
5	QPSK	12	0	20.04	20.05	20.03	22
5	QPSK	12	7	20.04	20.10	20.05	
5	QPSK	12	13	20.05	20.07	20.03	



FCC SAR TEST REPORT

Report No. : FA000714-06

5	QPSK	25	0	20.05	20.06	20.04	
5	16QAM	1	0	20.07	20.22	20.08	22
5	16QAM	1	12	20.26	20.37	20.18	
5	16QAM	1	24	20.18	20.23	20.16	
5	16QAM	12	0	19.02	19.06	19.07	21
5	16QAM	12	7	19.11	19.11	19.11	
5	16QAM	12	13	19.01	19.09	19.05	
5	16QAM	25	0	19.02	19.01	19.07	
5	64QAM	1	0	19.69	19.78	19.71	21
5	64QAM	1	12	19.77	19.85	19.73	
5	64QAM	1	24	19.88	20.01	19.82	
5	64QAM	12	0	18.87	18.93	18.81	20
5	64QAM	12	7	19.03	18.92	18.91	
5	64QAM	12	13	18.89	19.01	18.99	
5	64QAM	25	0	18.96	19.03	18.93	
Channel				19965	20175	20385	
Frequency (MHz)				1711.5	1732.5	1753.5	
3	QPSK	1	0	21.05	21.09	21.02	23
3	QPSK	1	8	21.02	21.06	21.02	
3	QPSK	1	14	21.06	21.00	21.03	
3	QPSK	8	0	20.05	20.04	20.05	22
3	QPSK	8	4	20.40	20.05	20.04	
3	QPSK	8	7	20.07	20.02	20.05	
3	QPSK	15	0	20.00	20.01	20.03	
3	16QAM	1	0	20.07	20.15	20.07	22
3	16QAM	1	8	20.18	20.36	20.18	
3	16QAM	1	14	20.12	20.19	20.12	
3	16QAM	8	0	19.05	19.00	19.01	21
3	16QAM	8	4	19.01	19.01	19.11	
3	16QAM	8	7	19.04	19.01	19.04	
3	16QAM	15	0	19.06	19.04	19.02	
3	64QAM	1	0	19.65	19.71	19.71	
3	64QAM	1	8	19.69	19.77	19.63	21
3	64QAM	1	14	19.83	19.97	19.78	
3	64QAM	8	0	18.85	18.83	18.73	
3	64QAM	8	4	19.00	18.87	18.83	20
3	64QAM	8	7	18.88	18.92	18.90	
3	64QAM	15	0	18.94	18.99	18.92	
Channel				19957	20175	20393	Tune-up limit (dBm)
Frequency (MHz)				1710.7	1732.5	1754.3	
1.4	QPSK	1	0	21.06	21.01	21.02	23
1.4	QPSK	1	3	21.03	21.04	21.05	
1.4	QPSK	1	5	21.03	21.01	21.00	
1.4	QPSK	3	0	21.06	21.04	21.05	
1.4	QPSK	3	1	21.05	21.02	21.02	
1.4	QPSK	3	3	21.05	21.03	21.03	
1.4	QPSK	6	0	20.05	20.07	20.08	22
1.4	16QAM	1	0	20.03	20.02	20.00	22
1.4	16QAM	1	3	20.14	20.27	20.04	
1.4	16QAM	1	5	20.10	20.08	20.07	
1.4	16QAM	3	0	20.06	20.03	20.01	
1.4	16QAM	3	1	20.05	20.03	20.04	
1.4	16QAM	3	3	20.04	20.07	20.05	
1.4	16QAM	6	0	19.01	19.02	19.01	21
1.4	64QAM	1	0	19.51	19.71	19.62	21
1.4	64QAM	1	3	19.67	19.72	19.70	



1.4	64QAM	1	5	19.69	19.86	19.73	
1.4	64QAM	3	0	19.01	19.01	19.02	
1.4	64QAM	3	1	19.08	19.04	19.05	
1.4	64QAM	3	3	19.00	19.05	19.01	
1.4	64QAM	6	0	18.95	18.87	18.85	
							20

<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				20450	20525	20600	
Frequency (MHz)				829	836.5	844	
10	QPSK	1	0	22.07	22.54	22.47	24
10	QPSK	1	25	22.40	22.44	22.44	
10	QPSK	1	49	22.44	22.52	22.47	
10	QPSK	25	0	21.33	21.38	21.32	23
10	QPSK	25	12	21.34	21.43	21.43	
10	QPSK	25	25	21.43	21.45	21.41	
10	QPSK	50	0	21.53	21.56	21.50	23
10	16QAM	1	0	21.83	21.86	21.85	
10	16QAM	1	25	21.59	21.59	21.58	
10	16QAM	1	49	21.76	21.82	21.77	22
10	16QAM	25	0	20.44	20.48	20.48	
10	16QAM	25	12	20.36	20.41	20.32	
10	16QAM	25	25	20.46	20.47	20.39	22
10	16QAM	50	0	20.36	20.41	20.32	
10	64QAM	1	0	21.22	21.32	21.28	
10	64QAM	1	25	21.24	21.25	21.23	22
10	64QAM	1	49	21.04	21.10	21.06	
10	64QAM	25	0	20.44	20.44	20.35	
10	64QAM	25	12	20.31	20.34	20.26	21
10	64QAM	25	25	20.28	20.38	20.38	
10	64QAM	50	0	20.37	20.37	20.28	
Channel				20425	20525	20625	Tune-up limit (dBm)
Frequency (MHz)				826.5	836.5	846.5	
5	QPSK	1	0	22.06	22.48	22.44	24
5	QPSK	1	12	22.32	22.44	22.43	
5	QPSK	1	24	22.37	22.44	22.40	
5	QPSK	12	0	21.32	21.31	21.22	23
5	QPSK	12	7	21.33	21.33	21.37	
5	QPSK	12	13	21.43	21.42	21.34	
5	QPSK	25	0	21.49	21.47	21.46	23
5	16QAM	1	0	21.73	21.82	21.77	
5	16QAM	1	12	21.52	21.50	21.54	
5	16QAM	1	24	21.68	21.81	21.70	22
5	16QAM	12	0	20.36	20.44	20.42	
5	16QAM	12	7	20.31	20.37	20.24	
5	16QAM	12	13	20.42	20.42	20.33	22
5	16QAM	25	0	20.35	20.37	20.22	
5	64QAM	1	0	21.17	21.32	21.21	
5	64QAM	1	12	21.15	21.21	21.15	22
5	64QAM	1	24	20.98	21.02	21.01	
5	64QAM	12	0	20.40	20.43	20.30	
5	64QAM	12	7	20.25	20.34	20.20	21
5	64QAM	12	13	20.18	20.37	20.33	



5	64QAM	25	0	20.35	20.29	20.26	
Channel				20415	20525	20635	Tune-up limit (dBm)
Frequency (MHz)				825.5	836.5	847.5	
3	QPSK	1	0	22.01	22.40	22.38	24
3	QPSK	1	8	22.31	22.37	22.35	
3	QPSK	1	14	22.37	22.40	22.32	
3	QPSK	8	0	21.22	21.23	21.20	23
3	QPSK	8	4	21.33	21.32	21.37	
3	QPSK	8	7	21.37	21.38	21.28	
3	QPSK	15	0	21.41	21.44	21.37	
3	16QAM	1	0	21.73	21.78	21.71	23
3	16QAM	1	8	21.52	21.48	21.51	
3	16QAM	1	14	21.59	21.76	21.62	
3	16QAM	8	0	20.29	20.37	20.34	22
3	16QAM	8	4	20.31	20.32	20.17	
3	16QAM	8	7	20.32	20.32	20.27	
3	16QAM	15	0	20.31	20.33	20.22	
3	64QAM	1	0	21.08	21.24	21.14	
3	64QAM	1	8	21.05	21.13	21.05	22
3	64QAM	1	14	20.88	21.02	20.98	
3	64QAM	8	0	20.30	20.39	20.20	
3	64QAM	8	4	20.25	20.33	20.14	21
3	64QAM	8	7	20.12	20.36	20.27	
3	64QAM	8	0	20.28	20.22	20.23	
3	64QAM	15	0	20.28	20.22	20.23	
Channel				20407	20525	20643	Tune-up limit (dBm)
Frequency (MHz)				824.7	836.5	848.3	
1.4	QPSK	1	0	22.05	22.31	22.29	24
1.4	QPSK	1	3	22.21	22.34	22.33	
1.4	QPSK	1	5	22.27	22.33	22.22	
1.4	QPSK	3	0	22.04	22.24	22.19	
1.4	QPSK	3	1	22.11	22.24	22.24	
1.4	QPSK	3	3	22.25	22.28	22.12	
1.4	QPSK	6	0	21.31	21.38	21.37	23
1.4	16QAM	1	0	21.65	21.78	21.70	23
1.4	16QAM	1	3	21.45	21.47	21.50	
1.4	16QAM	1	5	21.50	21.74	21.56	
1.4	16QAM	3	0	21.57	21.75	21.62	
1.4	16QAM	3	1	21.35	21.40	21.43	
1.4	16QAM	3	3	21.46	21.72	21.56	
1.4	16QAM	6	0	20.29	20.29	20.22	22
1.4	64QAM	1	0	21.04	21.14	21.07	22
1.4	64QAM	1	3	20.95	21.06	20.95	
1.4	64QAM	1	5	20.87	21.02	20.98	
1.4	64QAM	3	0	20.27	20.30	20.11	
1.4	64QAM	3	1	20.25	20.30	20.09	
1.4	64QAM	3	3	20.05	20.32	20.26	
1.4	64QAM	3	0	20.22	20.19	20.13	
1.4	64QAM	6	0	20.22	20.19	20.13	



<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				20850	21100	21350	
Frequency (MHz)				2510	2535	2560	
20	QPSK	1	0	21.26	21.08	21.33	
20	QPSK	1	49	20.92	20.96	20.96	22.5
20	QPSK	1	99	20.81	20.88	20.85	
20	QPSK	50	0	20.10	20.14	20.08	
20	QPSK	50	24	20.01	20.07	20.06	21.5
20	QPSK	50	50	20.04	20.04	19.99	
20	QPSK	100	0	19.98	20.03	20.03	
20	16QAM	1	0	20.18	20.27	20.21	21.5
20	16QAM	1	49	20.14	20.22	20.14	
20	16QAM	1	99	20.10	20.14	20.08	
20	16QAM	50	0	19.08	19.14	19.11	20.5
20	16QAM	50	24	19.04	19.13	19.03	
20	16QAM	50	50	19.03	19.06	18.97	
20	16QAM	100	0	19.09	19.18	19.13	20.5
20	64QAM	1	0	20.16	20.20	20.13	
20	64QAM	1	49	20.03	20.06	19.99	
20	64QAM	1	99	19.87	19.92	19.92	19.5
20	64QAM	50	0	18.96	19.05	19.03	
20	64QAM	50	24	19.06	19.09	18.99	
20	64QAM	50	50	19.01	19.05	18.96	19.5
20	64QAM	100	0	18.74	18.79	18.71	
Channel				20825	21100	21375	
Frequency (MHz)				2507.5	2535	2562.5	
15	QPSK	1	0	21.26	21.03	21.28	
15	QPSK	1	37	20.82	20.88	20.93	22.5
15	QPSK	1	74	20.86	20.82	20.84	
15	QPSK	36	0	20.03	20.07	20.00	
15	QPSK	36	20	20.00	20.01	19.96	21.5
15	QPSK	36	39	20.03	19.97	19.96	
15	QPSK	75	0	19.91	19.98	20.00	
15	16QAM	1	0	20.17	20.20	20.19	21.5
15	16QAM	1	37	20.12	20.14	20.04	
15	16QAM	1	74	20.10	20.07	19.98	
15	16QAM	36	0	18.98	19.04	19.06	20.5
15	16QAM	36	20	19.02	19.10	18.97	
15	16QAM	36	39	18.99	19.00	18.93	
15	16QAM	75	0	19.02	19.10	19.12	20.5
15	64QAM	1	0	20.07	20.12	20.03	
15	64QAM	1	37	20.01	19.99	19.93	
15	64QAM	1	74	19.83	19.88	19.88	20.5
15	64QAM	36	0	18.92	19.03	18.97	
15	64QAM	36	20	19.01	18.99	18.90	
15	64QAM	36	39	18.93	19.02	18.96	19.5
15	64QAM	75	0	18.71	18.77	18.70	
Channel				20800	21100	21400	
Frequency (MHz)				2505	2535	2565	
10	QPSK	1	0	21.20	21.02	21.21	
10	QPSK	1	25	20.74	20.80	20.91	22.5
10	QPSK	1	49	20.75	20.77	20.76	
10	QPSK	25	0	19.98	20.04	19.93	
10	QPSK	25	12	19.90	19.92	19.95	21.5



FCC SAR TEST REPORT

Report No. : FA000714-06

10	QPSK	25	25	19.94	19.92	19.92	
10	QPSK	50	0	19.89	19.90	19.98	
10	16QAM	1	0	20.16	20.13	20.15	21.5
10	16QAM	1	25	20.11	20.10	19.94	
10	16QAM	1	49	20.00	20.07	19.93	
10	16QAM	25	0	18.90	18.96	18.96	20.5
10	16QAM	25	12	19.02	19.02	18.96	
10	16QAM	25	25	18.89	19.00	18.89	
10	16QAM	50	0	18.92	19.03	19.08	
10	64QAM	1	0	19.99	20.08	19.97	20.5
10	64QAM	1	25	19.99	19.97	19.90	
10	64QAM	1	49	19.77	19.79	19.85	
10	64QAM	25	0	18.84	19.02	18.87	19.5
10	64QAM	25	12	18.96	18.90	18.85	
10	64QAM	25	25	18.84	18.99	18.96	
10	64QAM	50	0	18.69	18.76	18.70	
Channel				20775	21100	21425	Tune-up limit (dBm)
Frequency (MHz)				2502.5	2535	2567.5	
5	QPSK	1	0	21.14	20.98	21.17	22.5
5	QPSK	1	12	20.73	20.73	20.88	
5	QPSK	1	24	20.72	20.70	20.74	
5	QPSK	12	0	19.90	19.99	19.87	21.5
5	QPSK	12	7	19.88	19.83	19.94	
5	QPSK	12	13	19.84	19.82	19.86	
5	QPSK	25	0	19.84	19.90	19.97	
5	16QAM	1	0	20.12	20.05	20.15	21.5
5	16QAM	1	12	20.07	20.05	19.89	
5	16QAM	1	24	19.96	20.05	19.87	
5	16QAM	12	0	18.84	18.87	18.91	20.5
5	16QAM	12	7	18.93	18.95	18.93	
5	16QAM	12	13	18.80	18.98	18.84	
5	16QAM	25	0	18.84	18.96	19.03	
5	64QAM	1	0	19.92	19.99	19.87	20.5
5	64QAM	1	12	19.96	19.90	19.88	
5	64QAM	1	24	19.72	19.78	19.78	
5	64QAM	12	0	18.83	19.00	18.85	19.5
5	64QAM	12	7	18.94	18.84	18.77	
5	64QAM	12	13	18.81	18.97	18.88	
5	64QAM	25	0	18.68	18.72	18.63	



<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23060	23095	23130	
Frequency (MHz)				704	707.5	711	
10	QPSK	1	0	22.26	22.31	22.33	
10	QPSK	1	25	21.98	22.02	21.93	23
10	QPSK	1	49	21.96	22.00	21.91	
10	QPSK	25	0	21.18	21.27	21.27	
10	QPSK	25	12	21.11	21.18	21.14	22
10	QPSK	25	25	21.27	21.28	21.19	
10	QPSK	50	0	21.28	21.32	21.24	
10	16QAM	1	0	21.22	21.23	21.15	22
10	16QAM	1	25	21.07	21.07	20.99	
10	16QAM	1	49	21.10	21.16	21.10	
10	16QAM	25	0	20.25	20.32	20.30	21
10	16QAM	25	12	20.14	20.14	20.07	
10	16QAM	25	25	20.16	20.16	20.15	
10	16QAM	50	0	20.27	20.27	20.18	21
10	64QAM	1	0	20.98	20.92	20.94	
10	64QAM	1	25	20.88	20.85	20.82	
10	64QAM	1	49	20.80	20.81	20.87	20
10	64QAM	25	0	19.84	19.85	19.83	
10	64QAM	25	12	19.84	19.82	19.87	
10	64QAM	25	25	19.89	19.85	19.83	20
10	64QAM	25	0	19.98	19.92	19.99	
Channel				23035	23095	23155	
Frequency (MHz)				701.5	707.5	713.5	
5	QPSK	1	0	22.21	22.22	22.23	
5	QPSK	1	12	21.95	22.00	21.88	23
5	QPSK	1	24	21.93	21.94	21.89	
5	QPSK	12	0	21.18	21.26	21.23	
5	QPSK	12	7	21.07	21.08	21.04	22
5	QPSK	12	13	21.21	21.22	21.13	
5	QPSK	25	0	21.28	21.23	21.23	
5	16QAM	1	0	21.17	21.15	21.10	22
5	16QAM	1	12	21.00	21.04	20.98	
5	16QAM	1	24	21.07	21.08	21.04	
5	16QAM	12	0	20.24	20.29	20.29	21
5	16QAM	12	7	20.07	20.11	20.05	
5	16QAM	12	13	20.10	20.13	20.06	
5	16QAM	25	0	20.20	20.24	20.16	21
5	64QAM	1	0	20.91	20.85	20.94	
5	64QAM	1	12	20.84	20.75	20.73	
5	64QAM	1	24	20.74	20.76	20.86	20
5	64QAM	12	0	19.82	19.77	19.83	
5	64QAM	12	7	19.81	19.79	19.81	
5	64QAM	12	13	19.84	19.83	19.81	20
5	64QAM	12	0	19.98	19.82	19.95	
Channel				23025	23095	23165	
Frequency (MHz)				700.5	707.5	714.5	
3	QPSK	1	0	22.15	22.15	22.17	
3	QPSK	1	8	21.86	22.00	21.78	23
3	QPSK	1	14	21.92	21.90	21.82	
3	QPSK	8	0	21.12	21.26	21.21	
3	QPSK	8	4	21.01	21.04	20.97	22



3	QPSK	8	7	21.11	21.14	21.10	
3	QPSK	15	0	21.25	21.14	21.18	
3	16QAM	1	0	21.09	21.13	21.10	
3	16QAM	1	8	20.94	20.95	20.96	22
3	16QAM	1	14	20.98	21.05	20.94	
3	16QAM	8	0	20.16	20.29	20.27	
3	16QAM	8	4	20.04	20.01	19.99	21
3	16QAM	8	7	20.06	20.04	19.99	
3	16QAM	15	0	20.16	20.14	20.11	
3	64QAM	1	0	20.94	20.86	20.92	21
3	64QAM	1	8	20.86	20.85	20.80	
3	64QAM	1	14	20.71	20.77	20.87	
3	64QAM	8	0	19.79	19.78	19.77	20
3	64QAM	8	4	19.78	19.81	19.83	
3	64QAM	8	7	19.85	19.79	19.79	
3	64QAM	15	0	19.89	19.87	19.89	
Channel				23017	23095	23173	
Frequency (MHz)				699.7	707.5	715.3	
1.4	QPSK	1	0	22.13	22.14	22.16	23
1.4	QPSK	1	3	21.79	21.99	21.75	
1.4	QPSK	1	5	21.92	21.84	21.73	
1.4	QPSK	3	0	21.04	21.20	21.12	
1.4	QPSK	3	1	21.00	21.03	21.05	
1.4	QPSK	3	3	21.10	21.06	21.02	
1.4	QPSK	6	0	21.24	21.11	21.14	22
1.4	16QAM	1	0	21.06	21.04	21.02	22
1.4	16QAM	1	3	20.91	20.93	20.90	
1.4	16QAM	1	5	20.90	21.00	20.93	
1.4	16QAM	3	0	20.13	20.27	20.25	
1.4	16QAM	3	1	20.04	20.07	20.08	
1.4	16QAM	3	3	20.01	20.00	20.08	
1.4	16QAM	6	0	20.08	20.06	20.10	21
1.4	64QAM	1	0	20.99	20.95	20.96	21
1.4	64QAM	1	3	20.89	20.91	20.90	
1.4	64QAM	1	5	20.92	20.91	21.00	
1.4	64QAM	3	0	20.01	20.04	20.10	
1.4	64QAM	3	1	19.97	20.01	20.13	
1.4	64QAM	3	3	19.91	20.00	19.89	
1.4	64QAM	6	0	19.86	19.96	19.86	20

<LTE Band 13>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23230			Tune-up limit (dBm)
Frequency (MHz)				782			
10	QPSK	1	0		22.56		
10	QPSK	1	25		22.26		23
10	QPSK	1	49		22.28		
10	QPSK	25	0		21.22		
10	QPSK	25	12		21.18		22
10	QPSK	25	25		21.27		
10	QPSK	50	0		21.26		
10	16QAM	1	0		21.78		22
10	16QAM	1	25		21.47		



10	16QAM	1	49		21.33		
10	16QAM	25	0		20.27		21
10	16QAM	25	12		20.17		
10	16QAM	25	25		20.23		
10	16QAM	50	0		20.34		
10	64QAM	1	0		20.87		21
10	64QAM	1	25		20.83		
10	64QAM	1	49		20.89		
10	64QAM	25	0		19.85		20
10	64QAM	25	12		19.81		
10	64QAM	25	25		19.82		
10	64QAM	50	0		19.82		
Channel				23205	23230	23255	Tune-up limit (dBm)
Frequency (MHz)				779.5	782	784.5	
5	QPSK	1	0	22.30	22.42	22.46	23
5	QPSK	1	12	22.03	22.16	22.06	
5	QPSK	1	24	22.12	22.06	22.14	
5	QPSK	12	0	21.10	21.07	21.08	22
5	QPSK	12	7	20.97	21.01	21.05	
5	QPSK	12	13	21.07	21.06	21.21	
5	QPSK	25	0	21.13	21.26	21.19	
5	16QAM	1	0	21.66	21.66	21.61	22
5	16QAM	1	12	21.35	21.40	21.30	
5	16QAM	1	24	21.27	21.18	21.18	
5	16QAM	12	0	20.25	20.08	20.09	21
5	16QAM	12	7	20.03	20.06	20.02	
5	16QAM	12	13	20.06	20.10	20.05	
5	16QAM	25	0	20.13	20.23	20.23	
5	64QAM	1	0	20.92	20.93	20.92	21
5	64QAM	1	12	20.85	20.83	20.86	
5	64QAM	1	24	20.96	20.97	20.92	
5	64QAM	12	0	19.83	19.84	19.89	20
5	64QAM	12	7	19.93	19.90	19.94	
5	64QAM	12	13	19.91	19.96	19.92	
5	64QAM	25	0	19.92	19.97	20.00	

<LTE Band 14>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23330			
Frequency (MHz)				793			
10	QPSK	1	0		22.35		23
10	QPSK	1	25		22.16		
10	QPSK	1	49		22.32		
10	QPSK	25	0		21.28		22
10	QPSK	25	12		21.21		
10	QPSK	25	25		21.18		
10	QPSK	50	0		21.28		22
10	16QAM	1	0		21.46		
10	16QAM	1	25		21.23		
10	16QAM	1	49		21.34		21
10	16QAM	25	0		20.29		
10	16QAM	25	12		20.22		
10	16QAM	25	25		20.10		



10	16QAM	50	0		20.19		
10	64QAM	1	0		20.90		21
10	64QAM	1	25		20.86		
10	64QAM	1	49		20.82		
10	64QAM	25	0		19.81		20
10	64QAM	25	12		19.89		
10	64QAM	25	25		19.88		
10	64QAM	50	0		19.85		
Channel				23305	23330	23355	Tune-up limit (dBm)
Frequency (MHz)				790.5	793	795.5	
5	QPSK	1	0	22.19	22.24	22.29	23
5	QPSK	1	12	21.98	21.97	22.04	
5	QPSK	1	24	22.25	22.19	22.30	
5	QPSK	12	0	21.14	21.25	21.14	22
5	QPSK	12	7	21.18	21.19	21.08	
5	QPSK	12	13	21.17	21.13	21.08	
5	QPSK	25	0	21.25	21.18	21.18	
5	16QAM	1	0	21.35	21.37	21.42	22
5	16QAM	1	12	21.05	21.12	21.10	
5	16QAM	1	24	21.31	21.14	21.18	
5	16QAM	12	0	20.19	20.25	20.24	21
5	16QAM	12	7	20.09	20.11	20.05	
5	16QAM	12	13	20.02	19.98	20.06	
5	16QAM	25	0	20.03	20.05	20.07	
5	64QAM	1	0	20.87	20.83	20.89	21
5	64QAM	1	12	20.84	20.82	20.86	
5	64QAM	1	24	20.80	20.72	20.72	
5	64QAM	12	0	19.74	19.75	19.79	20
5	64QAM	12	7	19.89	19.84	19.88	
5	64QAM	12	13	19.84	19.78	19.80	
5	64QAM	25	0	19.76	19.83	19.79	

<LTE Band 17>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23780	23790	23800	Tune-up limit (dBm)
Frequency (MHz)				709	710	711	
10	QPSK	1	0	22.32	22.38	22.36	23
10	QPSK	1	25	22.20	22.22	22.21	
10	QPSK	1	49	22.32	22.33	22.29	
10	QPSK	25	0	21.31	21.36	21.34	22
10	QPSK	25	12	21.22	21.29	21.21	
10	QPSK	25	25	21.08	21.12	21.10	
10	QPSK	50	0	21.03	21.04	20.94	
10	16QAM	1	0	21.34	21.38	21.29	22
10	16QAM	1	25	21.26	21.26	21.19	
10	16QAM	1	49	21.38	21.43	21.43	
10	16QAM	25	0	20.17	20.27	20.27	21
10	16QAM	25	12	20.12	20.22	20.13	
10	16QAM	25	25	20.15	20.16	20.15	
10	16QAM	50	0	20.24	20.27	20.25	
10	64QAM	1	0	20.99	20.89	20.93	21
10	64QAM	1	25	20.90	20.94	20.84	
10	64QAM	1	49	20.91	20.93	20.89	



10	64QAM	25	0	19.87	19.92	19.89	20
10	64QAM	25	12	19.82	19.92	19.90	
10	64QAM	25	25	19.67	19.72	19.64	
10	64QAM	50	0	19.85	19.91	19.83	
Channel				23755	23790	23825	Tune-up limit (dBm)
Frequency (MHz)				706.5	710	713.5	
5	QPSK	1	0	22.30	22.36	22.31	23
5	QPSK	1	12	22.13	22.17	22.18	
5	QPSK	1	24	22.31	22.27	22.21	
5	QPSK	12	0	21.24	21.34	21.27	22
5	QPSK	12	7	21.22	21.28	21.16	
5	QPSK	12	13	20.98	21.03	21.05	
5	QPSK	25	0	21.00	20.95	20.94	
5	16QAM	1	0	21.34	21.28	21.22	22
5	16QAM	1	12	21.25	21.16	21.14	
5	16QAM	1	24	21.32	21.41	21.36	
5	16QAM	12	0	20.11	20.17	20.22	21
5	16QAM	12	7	20.09	20.17	20.07	
5	16QAM	12	13	20.06	20.15	20.05	
5	16QAM	25	0	20.17	20.18	20.23	
5	64QAM	1	0	20.98	20.87	20.92	21
5	64QAM	1	12	20.82	20.90	20.81	
5	64QAM	1	24	20.82	20.92	20.87	
5	64QAM	12	0	19.80	19.83	19.89	20
5	64QAM	12	7	19.72	19.89	19.82	
5	64QAM	12	13	19.64	19.69	19.57	
5	64QAM	25	0	19.75	19.87	19.83	

<LTE Band 25>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				26140	26340	26590	
Frequency (MHz)				1860	1880	1905	
20	QPSK	1	0	21.22	21.04	21.24	22
20	QPSK	1	49	20.78	20.88	20.82	
20	QPSK	1	99	20.75	20.74	20.76	
20	QPSK	50	0	20.01	20.05	20.04	21
20	QPSK	50	24	19.97	19.99	19.99	
20	QPSK	50	50	19.81	19.91	19.90	
20	QPSK	100	0	19.86	19.93	19.87	
20	16QAM	1	0	20.14	20.17	20.16	21
20	16QAM	1	49	20.11	20.15	20.11	
20	16QAM	1	99	20.06	20.08	19.98	
20	16QAM	50	0	18.98	19.05	18.97	20
20	16QAM	50	24	19.05	19.07	18.97	
20	16QAM	50	50	18.91	18.98	18.93	
20	16QAM	100	0	18.87	18.94	18.93	
20	64QAM	1	0	19.93	19.96	19.98	20
20	64QAM	1	49	19.98	19.91	19.99	
20	64QAM	1	99	19.82	19.83	19.73	
20	64QAM	50	0	18.85	18.94	18.84	19
20	64QAM	50	24	18.92	18.93	18.87	
20	64QAM	50	50	18.80	18.82	18.82	
20	64QAM	100	0	18.69	18.70	18.63	



Channel				26115	26340	26615	Tune-up limit (dBm)
Frequency (MHz)				1857.5	1880	1907.5	
15	QPSK	1	0	21.11	20.99	21.16	22
15	QPSK	1	37	20.70	20.80	20.80	
15	QPSK	1	74	20.68	20.67	20.66	
15	QPSK	36	0	20.00	20.00	19.98	21
15	QPSK	36	20	19.88	19.98	19.89	
15	QPSK	36	39	19.76	19.82	19.88	
15	QPSK	75	0	19.84	19.84	19.82	21
15	16QAM	1	0	20.05	20.09	20.14	
15	16QAM	1	37	20.04	20.15	20.11	
15	16QAM	1	74	19.98	19.99	19.90	20
15	16QAM	36	0	18.98	19.02	18.90	
15	16QAM	36	20	19.02	18.97	18.95	
15	16QAM	36	39	18.82	18.95	18.91	20
15	16QAM	75	0	18.86	18.92	18.93	
15	64QAM	1	0	19.92	19.93	19.94	
15	64QAM	1	37	19.98	19.94	19.90	20
15	64QAM	1	74	19.74	19.82	19.65	
15	64QAM	36	0	18.82	18.84	18.76	
15	64QAM	36	20	18.88	18.85	18.86	19
15	64QAM	36	39	18.76	18.76	18.79	
15	64QAM	75	0	18.62	18.64	18.56	
Channel				26090	26340	26640	Tune-up limit (dBm)
Frequency (MHz)				1855	1880	1910	
10	QPSK	1	0	21.09	20.93	21.08	22
10	QPSK	1	25	20.67	20.77	20.71	
10	QPSK	1	49	20.68	20.60	20.64	
10	QPSK	25	0	20.00	19.95	19.98	21
10	QPSK	25	12	19.78	19.89	19.82	
10	QPSK	25	25	19.69	19.79	19.80	
10	QPSK	50	0	19.81	19.81	19.75	21
10	16QAM	1	0	19.97	20.07	20.09	
10	16QAM	1	25	19.95	20.07	20.01	
10	16QAM	1	49	19.98	19.95	19.83	20
10	16QAM	25	0	18.90	19.00	18.80	
10	16QAM	25	12	19.01	18.90	18.85	
10	16QAM	25	25	18.75	18.86	18.82	20
10	16QAM	50	0	18.78	18.88	18.85	
10	64QAM	1	0	19.93	19.92	19.90	
10	64QAM	1	25	19.96	19.84	19.87	20
10	64QAM	1	49	19.71	19.72	19.63	
10	64QAM	25	0	18.79	18.77	18.73	
10	64QAM	25	12	18.84	18.85	18.81	19
10	64QAM	25	25	18.71	18.76	18.74	
10	64QAM	50	0	18.52	18.54	18.52	
Channel				26065	26340	26665	Tune-up limit (dBm)
Frequency (MHz)				1852.5	1880	1912.5	
5	QPSK	1	0	21.05	20.92	21.03	22
5	QPSK	1	12	20.62	20.66	20.67	
5	QPSK	1	24	20.56	20.59	20.61	
5	QPSK	12	0	19.97	19.83	19.89	21
5	QPSK	12	7	19.76	19.86	19.84	
5	QPSK	12	13	19.62	19.75	19.80	
5	QPSK	25	0	19.79	19.66	19.77	21
5	16QAM	1	0	20.02	19.97	20.09	



5	16QAM	1	12	19.91	20.04	19.98	
5	16QAM	1	24	19.92	19.86	19.81	
5	16QAM	12	0	18.85	18.94	18.82	
5	16QAM	12	7	18.94	18.89	18.88	20
5	16QAM	12	13	18.81	18.89	18.83	
5	16QAM	25	0	18.79	18.75	18.85	
5	64QAM	1	0	19.91	19.94	19.84	20
5	64QAM	1	12	19.84	19.87	19.81	
5	64QAM	1	24	19.56	19.62	19.57	
5	64QAM	12	0	18.77	18.81	18.70	19
5	64QAM	12	7	18.78	18.79	18.76	
5	64QAM	12	13	18.66	18.63	18.68	
5	64QAM	25	0	18.59	18.62	18.48	
Channel				26055	26340	26675	Tune-up limit (dBm)
Frequency (MHz)				1851.5	1880	1913.5	
3	QPSK	1	0	20.90	20.90	20.92	22
3	QPSK	1	8	20.54	20.63	20.65	
3	QPSK	1	14	20.58	20.57	20.56	
3	QPSK	8	0	19.83	19.77	19.80	21
3	QPSK	8	4	19.67	19.80	19.80	
3	QPSK	8	7	19.61	19.65	19.71	
3	QPSK	15	0	19.82	19.64	19.80	
3	16QAM	1	0	20.00	19.93	20.10	21
3	16QAM	1	8	19.91	19.98	19.91	
3	16QAM	1	14	19.92	19.78	19.75	
3	16QAM	8	0	18.82	18.90	18.73	20
3	16QAM	8	4	18.88	18.78	18.81	
3	16QAM	8	7	18.62	18.82	18.72	
3	16QAM	15	0	18.83	18.72	18.79	
3	64QAM	1	0	19.92	19.95	19.74	
3	64QAM	1	8	19.83	19.82	19.71	20
3	64QAM	1	14	19.63	19.69	19.59	
3	64QAM	8	0	18.70	18.70	18.61	
3	64QAM	8	4	18.77	18.74	18.74	19
3	64QAM	8	7	18.62	18.62	18.59	
3	64QAM	15	0	18.57	18.45	18.36	
Channel				26047	26340	26683	
Frequency (MHz)				1850.7	1880	1914.3	
1.4	QPSK	1	0	20.87	20.80	20.89	22
1.4	QPSK	1	3	20.54	20.56	20.65	
1.4	QPSK	1	5	20.55	20.54	20.46	
1.4	QPSK	3	0	20.81	20.70	20.86	
1.4	QPSK	3	1	20.45	20.46	20.56	
1.4	QPSK	3	3	20.52	20.54	20.37	
1.4	QPSK	6	0	19.81	19.64	19.77	21
1.4	16QAM	1	0	19.92	19.84	20.04	21
1.4	16QAM	1	3	19.86	19.97	19.85	
1.4	16QAM	1	5	19.86	19.75	19.68	
1.4	16QAM	3	0	19.92	19.76	19.98	
1.4	16QAM	3	1	19.76	19.87	19.82	
1.4	16QAM	3	3	19.83	19.65	19.68	
1.4	16QAM	6	0	18.75	18.72	18.79	20
1.4	64QAM	1	0	19.93	19.89	19.71	20
1.4	64QAM	1	3	19.79	19.77	19.71	
1.4	64QAM	1	5	19.53	19.69	19.54	
1.4	64QAM	3	0	18.60	18.60	18.61	



1.4	64QAM	3	1	18.72	18.64	18.70	
1.4	64QAM	3	3	18.55	18.57	18.56	
1.4	64QAM	6	0	18.50	18.41	18.31	

<LTE Band 26>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				26765	26865	26965	
Frequency (MHz)				821.5	831.5	841.5	
15	QPSK	1	0	22.34	22.57	22.20	23.5
15	QPSK	1	37	22.38	22.44	22.42	
15	QPSK	1	74	22.32	22.42	22.32	
15	QPSK	36	0	21.53	21.55	21.53	22.5
15	QPSK	36	20	21.28	21.38	21.37	
15	QPSK	36	39	21.22	21.28	21.26	
15	QPSK	75	0	21.33	21.40	21.33	22.5
15	16QAM	1	0	21.50	21.55	21.45	
15	16QAM	1	37	21.31	21.31	21.29	
15	16QAM	1	74	21.46	21.47	21.40	21.5
15	16QAM	36	0	20.52	20.57	20.54	
15	16QAM	36	20	20.19	20.27	20.27	
15	16QAM	36	39	20.17	20.24	20.21	21.5
15	16QAM	75	0	20.27	20.27	20.20	
15	64QAM	1	0	21.40	21.44	21.36	
15	64QAM	1	37	21.13	21.21	21.15	21.5
15	64QAM	1	74	21.03	21.03	21.01	
15	64QAM	36	0	20.49	20.44	20.42	
15	64QAM	36	20	20.20	20.29	20.28	20.5
15	64QAM	36	39	20.15	20.23	20.22	
15	64QAM	75	0	20.07	20.17	20.08	
Channel				26740	26865	26990	Tune-up limit (dBm)
Frequency (MHz)				819	831.5	844	
10	QPSK	1	0	22.28	22.47	22.18	23.5
10	QPSK	1	25	22.38	22.41	22.34	
10	QPSK	1	49	22.31	22.34	22.23	
10	QPSK	25	0	21.50	21.45	21.49	22.5
10	QPSK	25	12	21.27	21.37	21.36	
10	QPSK	25	25	21.15	21.19	21.19	
10	QPSK	50	0	21.30	21.37	21.23	22.5
10	16QAM	1	0	21.49	21.55	21.43	
10	16QAM	1	25	21.23	21.30	21.27	
10	16QAM	1	49	21.42	21.45	21.38	21.5
10	16QAM	25	0	20.51	20.51	20.49	
10	16QAM	25	12	20.18	20.20	20.19	
10	16QAM	25	25	20.14	20.15	20.17	21.5
10	16QAM	50	0	20.23	20.26	20.15	
10	64QAM	1	0	21.39	21.36	21.27	
10	64QAM	1	25	21.12	21.18	21.06	21.5
10	64QAM	1	49	20.97	20.94	20.97	
10	64QAM	25	0	20.48	20.41	20.48	
10	64QAM	25	12	20.11	20.19	20.23	20.5
10	64QAM	25	25	20.09	20.16	20.21	
10	64QAM	50	0	20.04	20.17	20.08	
Channel				26715	26865	27015	Tune-up limit



FCC SAR TEST REPORT

Report No. : FA000714-06

Frequency (MHz)				816.5	831.5	846.5	(dBm)
5	QPSK	1	0	22.26	22.44	22.16	23.5
5	QPSK	1	12	22.33	22.33	22.41	
5	QPSK	1	24	22.21	22.33	22.26	
5	QPSK	12	0	21.47	21.46	21.48	22.5
5	QPSK	12	7	21.25	21.24	21.29	
5	QPSK	12	13	21.04	21.10	21.20	
5	QPSK	25	0	21.17	21.33	21.28	22.5
5	16QAM	1	0	21.37	21.45	21.35	
5	16QAM	1	12	21.16	21.20	21.23	
5	16QAM	1	24	21.33	21.35	21.36	21.5
5	16QAM	12	0	20.40	20.46	20.52	
5	16QAM	12	7	20.10	20.15	20.23	
5	16QAM	12	13	20.11	20.04	20.09	21.5
5	16QAM	25	0	20.13	20.26	20.17	
5	64QAM	1	0	21.17	21.24	21.29	
5	64QAM	1	12	21.05	21.07	21.06	21.5
5	64QAM	1	24	20.92	20.84	20.94	
5	64QAM	12	0	20.45	20.50	20.35	
5	64QAM	12	7	20.12	20.29	20.16	20.5
5	64QAM	12	13	20.06	20.18	20.10	
5	64QAM	25	0	19.99	19.98	19.97	
Channel				26705	26865	27025	Tune-up limit (dBm)
Frequency (MHz)				815.5	831.5	847.5	
3	QPSK	1	0	22.20	22.39	22.11	23.5
3	QPSK	1	8	22.27	22.34	22.42	
3	QPSK	1	14	22.17	22.29	22.18	
3	QPSK	8	0	21.45	21.46	21.39	22.5
3	QPSK	8	4	21.18	21.19	21.24	
3	QPSK	8	7	21.08	21.17	21.14	
3	QPSK	15	0	21.25	21.35	21.29	22.5
3	16QAM	1	0	21.39	21.54	21.38	
3	16QAM	1	8	21.15	21.27	21.23	
3	16QAM	1	14	21.32	21.41	21.34	21.5
3	16QAM	8	0	20.50	20.46	20.45	
3	16QAM	8	4	20.02	20.19	20.24	
3	16QAM	8	7	20.12	20.10	20.04	21.5
3	16QAM	15	0	20.14	20.23	20.08	
3	64QAM	1	0	21.27	21.23	21.28	
3	64QAM	1	8	21.09	21.09	21.06	21.5
3	64QAM	1	14	20.84	20.87	20.91	
3	64QAM	8	0	20.47	20.50	20.41	
3	64QAM	8	4	20.11	20.28	20.20	20.5
3	64QAM	8	7	20.07	20.15	20.10	
3	64QAM	15	0	19.95	20.01	19.97	
Channel				26697	26865	27033	Tune-up limit (dBm)
Frequency (MHz)				814.7	831.5	848.3	
1.4	QPSK	1	0	22.25	22.45	22.14	23.5
1.4	QPSK	1	3	22.31	22.33	22.41	
1.4	QPSK	1	5	22.12	22.35	22.20	
1.4	QPSK	3	0	22.24	22.44	22.05	22.5
1.4	QPSK	3	1	22.21	22.29	22.37	
1.4	QPSK	3	3	22.11	22.33	22.17	
1.4	QPSK	6	0	21.18	21.33	21.21	22.5
1.4	16QAM	1	0	21.43	21.48	21.34	
1.4	16QAM	1	3	21.21	21.20	21.19	



1.4	16QAM	1	5	21.31	21.38	21.35	
1.4	16QAM	3	0	21.37	21.47	21.32	
1.4	16QAM	3	1	21.20	21.10	21.17	
1.4	16QAM	3	3	21.29	21.30	21.27	
1.4	16QAM	6	0	20.19	20.19	20.14	21.5
1.4	64QAM	1	0	21.33	21.38	21.28	21.5
1.4	64QAM	1	3	21.11	21.09	21.06	
1.4	64QAM	1	5	20.94	20.91	20.89	
1.4	64QAM	3	0	20.46	20.48	20.38	
1.4	64QAM	3	1	20.11	20.25	20.18	
1.4	64QAM	3	3	20.03	20.17	20.15	
1.4	64QAM	6	0	19.96	20.05	19.95	20.5

<LTE Band 66>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				132072	132322	132572	
Frequency (MHz)				1720	1745	1770	
20	QPSK	1	0	21.21	21.48	21.17	22
20	QPSK	1	49	21.15	21.25	21.20	
20	QPSK	1	99	21.41	21.46	21.39	
20	QPSK	50	0	20.04	20.13	20.10	21
20	QPSK	50	24	20.21	20.21	20.14	
20	QPSK	50	50	20.17	20.22	20.19	
20	QPSK	100	0	20.07	20.16	20.16	21
20	16QAM	1	0	20.19	20.19	20.19	
20	16QAM	1	49	20.07	20.16	20.13	
20	16QAM	1	99	20.35	20.45	20.41	20
20	16QAM	50	0	19.19	19.26	19.25	
20	16QAM	50	24	19.30	19.31	19.29	
20	16QAM	50	50	19.25	19.30	19.28	20
20	16QAM	100	0	19.13	19.18	19.12	
20	64QAM	1	0	19.94	19.92	19.98	
20	64QAM	1	49	19.91	19.93	19.94	20
20	64QAM	1	99	19.99	19.99	19.93	
20	64QAM	50	0	18.90	18.95	18.94	
20	64QAM	50	24	18.89	18.84	18.88	19
20	64QAM	50	50	18.92	18.95	18.93	
20	64QAM	100	0	18.91	18.97	18.88	
Channel				132047	132322	132597	
Frequency (MHz)				1717.5	1745	1772.5	
15	QPSK	1	0	21.20	21.42	21.15	22
15	QPSK	1	37	21.08	21.21	21.10	
15	QPSK	1	74	21.34	21.45	21.38	
15	QPSK	36	0	19.96	20.03	20.01	21
15	QPSK	36	20	20.18	20.19	20.04	
15	QPSK	36	39	20.11	20.22	20.09	
15	QPSK	75	0	19.98	20.10	20.06	21
15	16QAM	1	0	20.15	20.11	20.17	
15	16QAM	1	37	20.05	20.10	20.05	
15	16QAM	1	74	20.33	20.44	20.37	20
15	16QAM	36	0	19.09	19.21	19.25	
15	16QAM	36	20	19.24	19.24	19.21	
15	16QAM	36	39	19.18	19.27	19.26	



FCC SAR TEST REPORT

Report No. : FA000714-06

15	16QAM	75	0	19.08	19.10	19.02	
15	64QAM	1	0	19.92	19.84	19.95	20
15	64QAM	1	37	19.85	19.87	19.92	
15	64QAM	1	74	19.98	19.96	19.91	
15	64QAM	36	0	18.86	18.93	18.84	19
15	64QAM	36	20	18.87	18.81	18.88	
15	64QAM	36	39	18.90	18.86	18.85	
15	64QAM	75	0	18.82	18.89	18.84	
Channel				132022	132322	132622	Tune-up limit (dBm)
Frequency (MHz)				1715	1745	1775	
10	QPSK	1	0	21.13	21.42	21.11	22
10	QPSK	1	25	21.09	21.17	21.18	
10	QPSK	1	49	21.38	21.38	21.31	
10	QPSK	25	0	19.97	20.12	20.10	21
10	QPSK	25	12	20.17	20.14	20.14	
10	QPSK	25	25	20.08	20.16	20.17	
10	QPSK	50	0	20.01	20.08	20.10	
10	16QAM	1	0	20.11	20.16	20.17	21
10	16QAM	1	25	20.04	20.14	20.13	
10	16QAM	1	49	20.29	20.38	20.33	
10	16QAM	25	0	19.09	19.24	19.25	20
10	16QAM	25	12	19.27	19.30	19.23	
10	16QAM	25	25	19.20	19.23	19.25	
10	16QAM	50	0	19.13	19.18	19.05	
10	64QAM	1	0	19.89	19.89	19.93	20
10	64QAM	1	25	19.91	19.83	19.88	
10	64QAM	1	49	19.89	19.95	19.85	
10	64QAM	25	0	18.88	18.95	18.88	19
10	64QAM	25	12	18.85	18.78	18.79	
10	64QAM	25	25	18.88	18.90	18.88	
10	64QAM	50	0	18.86	18.89	18.86	
Channel				131997	132322	132647	Tune-up limit (dBm)
Frequency (MHz)				1712.5	1745	1777.5	
5	QPSK	1	0	21.13	21.47	21.12	22
5	QPSK	1	12	21.13	21.17	21.10	
5	QPSK	1	24	21.32	21.44	21.29	
5	QPSK	12	0	19.94	20.10	20.10	21
5	QPSK	12	7	20.11	20.12	20.05	
5	QPSK	12	13	20.09	20.14	20.09	
5	QPSK	25	0	20.03	20.15	20.08	
5	16QAM	1	0	20.12	20.14	20.09	21
5	16QAM	1	12	20.06	20.14	20.13	
5	16QAM	1	24	20.34	20.38	20.31	
5	16QAM	12	0	19.15	19.25	19.19	20
5	16QAM	12	7	19.23	19.21	19.26	
5	16QAM	12	13	19.25	19.20	19.21	
5	16QAM	25	0	19.09	19.08	19.11	
5	64QAM	1	0	19.91	19.92	19.94	20
5	64QAM	1	12	19.84	19.92	19.93	
5	64QAM	1	24	19.89	19.98	19.93	
5	64QAM	12	0	18.85	18.88	18.88	19
5	64QAM	12	7	18.79	18.78	18.86	
5	64QAM	12	13	18.85	18.94	18.90	
5	64QAM	25	0	18.83	18.96	18.83	
Channel				131987	132322	132657	Tune-up limit (dBm)
Frequency (MHz)				1711.5	1745	1778.5	



3	QPSK	1	0	21.19	21.43	21.10	22
3	QPSK	1	8	21.09	21.23	21.14	
3	QPSK	1	14	21.37	21.41	21.29	
3	QPSK	8	0	20.00	20.09	20.07	21
3	QPSK	8	4	20.12	20.15	20.09	
3	QPSK	8	7	20.13	20.15	20.16	
3	QPSK	15	0	20.03	20.08	20.13	21
3	16QAM	1	0	20.15	20.10	20.15	
3	16QAM	1	8	20.07	20.06	20.11	
3	16QAM	1	14	20.31	20.36	20.32	20
3	16QAM	8	0	19.18	19.19	19.15	
3	16QAM	8	4	19.22	19.24	19.25	
3	16QAM	8	7	19.23	19.26	19.27	20
3	16QAM	15	0	19.06	19.18	19.09	
3	64QAM	1	0	19.87	19.91	19.94	
3	64QAM	1	8	19.88	19.86	19.84	20
3	64QAM	1	14	19.98	19.94	19.83	
3	64QAM	8	0	18.89	18.93	18.88	
3	64QAM	8	4	18.82	18.77	18.82	19
3	64QAM	8	7	18.84	18.87	18.88	
3	64QAM	15	0	18.84	18.88	18.80	
Channel				131979	132322	132665	Tune-up limit (dBm)
Frequency (MHz)				1710.7	1745	1779.3	
1.4	QPSK	1	0	21.20	21.41	21.09	22
1.4	QPSK	1	3	21.07	21.19	21.20	
1.4	QPSK	1	5	21.37	21.42	21.30	
1.4	QPSK	3	0	21.06	20.10	20.07	
1.4	QPSK	3	1	20.15	20.14	20.05	
1.4	QPSK	3	3	20.11	20.17	20.17	
1.4	QPSK	6	0	19.99	20.10	20.11	21
1.4	16QAM	1	0	20.10	20.09	20.10	21
1.4	16QAM	1	3	20.03	20.16	20.11	
1.4	16QAM	1	5	20.27	20.35	20.34	
1.4	16QAM	3	0	19.19	19.19	19.21	
1.4	16QAM	3	1	19.21	19.29	19.25	
1.4	16QAM	3	3	19.24	19.21	19.18	
1.4	16QAM	6	0	19.04	19.13	19.02	20
1.4	64QAM	1	0	19.91	19.89	19.87	20
1.4	64QAM	1	3	19.97	19.95	19.84	
1.4	64QAM	1	5	19.90	19.95	19.93	
1.4	64QAM	3	0	18.90	19.10	19.05	
1.4	64QAM	3	1	19.10	19.21	19.08	
1.4	64QAM	3	3	19.10	19.09	19.04	
1.4	64QAM	6	0	18.92	18.90	18.89	19



<LTE Band 71>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	
Channel				133222	133322	133372		
Frequency (MHz)				673	683	688		
20	QPSK	1	0	22.23	22.25	22.22		
20	QPSK	1	49	22.14	22.15	22.10	23	
20	QPSK	1	99	22.00	22.09	22.02		
20	QPSK	50	0	21.06	21.08	21.08		
20	QPSK	50	24	20.97	21.04	20.98	22	
20	QPSK	50	50	20.88	20.98	20.94		
20	QPSK	100	0	20.72	20.82	20.76		
20	16QAM	1	0	21.38	21.42	21.32	22	
20	16QAM	1	49	21.24	21.24	21.15		
20	16QAM	1	99	21.12	21.13	21.04		
20	16QAM	50	0	20.16	20.17	20.08	21	
20	16QAM	50	24	20.10	20.12	20.09		
20	16QAM	50	50	20.00	20.04	19.95		
20	16QAM	100	0	19.90	19.96	19.90	21	
20	64QAM	1	0	20.89	20.87	20.88		
20	64QAM	1	49	20.88	20.93	20.86		
20	64QAM	1	99	20.78	20.80	20.75	20	
20	64QAM	50	0	20.00	19.91	19.93		
20	64QAM	50	24	19.90	20.00	19.94		
20	64QAM	50	50	19.85	19.95	19.87	20	
20	64QAM	100	0	19.93	19.95	19.99		
Channel				133197	133297	133397		Tune-up limit (dBm)
Frequency (MHz)				670.5	680.5	690.5	23	
15	QPSK	1	0	22.19	22.15	22.12		
15	QPSK	1	37	22.07	22.08	22.03		
15	QPSK	1	74	21.91	21.99	21.98	22	
15	QPSK	36	0	21.00	20.99	21.06		
15	QPSK	36	20	20.90	20.95	20.91		
15	QPSK	36	39	20.80	20.93	20.87	22	
15	QPSK	75	0	20.67	20.74	20.73		
15	16QAM	1	0	21.34	21.35	21.22		
15	16QAM	1	37	21.17	21.14	21.11	22	
15	16QAM	1	74	21.10	21.03	20.99		
15	16QAM	36	0	20.10	20.12	20.06		
15	16QAM	36	20	20.09	20.05	19.99	21	
15	16QAM	36	39	19.98	19.97	19.92		
15	16QAM	75	0	19.83	19.92	19.81		
15	64QAM	1	0	20.99	20.98	20.99	21	
15	64QAM	1	37	20.79	20.83	20.84		
15	64QAM	1	74	20.69	20.74	20.73		
15	64QAM	36	0	19.93	19.95	19.87	20	
15	64QAM	36	20	19.84	20.00	19.87		
15	64QAM	36	39	19.76	19.88	19.85		
15	64QAM	75	0	19.99	19.92	19.98	20	
Channel				133172	133297	133422		Tune-up limit (dBm)
Frequency (MHz)				668	680.5	693		
10	QPSK	1	0	22.22	22.15	22.18	23	
10	QPSK	1	25	22.08	22.13	22.03		
10	QPSK	1	49	21.95	22.03	21.95		
10	QPSK	25	0	21.05	21.01	21.04	22	
10	QPSK	25	12	20.97	20.97	20.95		



10	QPSK	25	25	20.82	20.92	20.90	
10	QPSK	50	0	20.71	20.78	20.74	
10	16QAM	1	0	21.30	21.36	21.28	
10	16QAM	1	25	21.22	21.20	21.10	22
10	16QAM	1	49	21.05	21.10	21.00	
10	16QAM	25	0	20.08	20.09	19.98	
10	16QAM	25	12	20.08	20.02	20.01	21
10	16QAM	25	25	19.97	19.97	19.92	
10	16QAM	50	0	19.80	19.87	19.81	
10	64QAM	1	0	20.97	20.91	21.00	21
10	64QAM	1	25	20.87	20.90	20.84	
10	64QAM	1	49	20.69	20.79	20.67	
10	64QAM	25	0	19.90	20.00	19.88	20
10	64QAM	25	12	19.86	19.94	19.88	
10	64QAM	25	25	19.79	19.94	19.83	
10	64QAM	50	0	20.00	19.92	19.99	
Channel				133147	133297	133447	
Frequency (MHz)				665.5	680.5	695.5	
5	QPSK	1	0	22.23	22.17	22.12	23
5	QPSK	1	12	22.12	22.08	22.05	
5	QPSK	1	24	21.90	22.08	22.01	
5	QPSK	12	0	20.98	21.04	20.98	22
5	QPSK	12	7	20.93	21.02	20.95	
5	QPSK	12	13	20.82	20.97	20.94	
5	QPSK	25	0	20.71	20.82	20.76	
5	16QAM	1	0	21.37	21.37	21.28	
5	16QAM	1	12	21.22	21.16	21.06	22
5	16QAM	1	24	21.02	21.12	21.01	
5	16QAM	12	0	20.08	20.13	20.04	
5	16QAM	12	7	20.06	20.05	20.02	21
5	16QAM	12	13	19.96	20.02	19.85	
5	16QAM	25	0	19.90	19.90	19.82	
5	64QAM	1	0	20.95	20.91	20.94	
5	64QAM	1	12	20.80	20.88	20.78	
5	64QAM	1	24	20.69	20.78	20.71	21
5	64QAM	12	0	19.93	19.95	19.92	
5	64QAM	12	7	19.85	19.92	19.94	
5	64QAM	12	13	19.79	19.94	19.85	
5	64QAM	25	0	19.93	19.91	19.90	
5	64QAM	25	0	19.93	19.91	19.90	20
5	64QAM	12	7	19.85	19.92	19.94	
5	64QAM	12	13	19.79	19.94	19.85	
5	64QAM	25	0	19.93	19.91	19.90	
5	64QAM	25	0	19.93	19.91	19.90	

<TDD LTE SAR Measurement>

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- a. 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- b. "special subframe S" contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- c. Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$			$7680 \cdot T_s$		
5	$6592 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$20480 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-		
9	$13168 \cdot T_s$			-		

Special subframe (30720·T_s): Normal cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~4	7.13%	8.33%
	5~9	14.3%	16.7%

Special subframe(30720·T_s): Extended cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

The highest duty factor is resulted from:

- i. Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- ii. special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- iii. for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is: $(3+0.167)/5 = 63.3\%$
- iv. for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is: $(3+0.143)/5 = 62.9\%$
- v. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.



<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Low Middle Ch. / Freq.	Power Middle Ch. / Freq.	Power High Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				39750	40185	40620	41055	41490	
Frequency (MHz)				2506	2549.5	2593	2636.5	2680	
20	QPSK	1	0	20.77	20.83	20.36	20.80	20.48	21.5
20	QPSK	1	49	20.38	20.42	20.44	20.42	20.35	
20	QPSK	1	99	20.17	20.18	20.21	20.18	20.19	
20	QPSK	50	0	19.75	19.81	19.84	19.77	19.76	20.5
20	QPSK	50	24	19.78	19.75	19.79	19.79	19.78	
20	QPSK	50	50	19.51	19.51	19.59	19.55	19.49	
20	QPSK	100	0	19.44	19.41	19.49	19.48	19.47	20.5
20	16QAM	1	0	19.55	19.48	19.55	19.53	19.48	
20	16QAM	1	49	19.61	19.66	19.71	19.69	19.71	
20	16QAM	1	99	19.28	19.22	19.30	19.27	19.28	20.5
20	16QAM	50	0	18.76	18.73	18.76	18.67	18.70	
20	16QAM	50	24	18.83	18.80	18.87	18.87	18.80	
20	16QAM	50	50	18.60	18.62	18.64	18.59	18.57	20.5
20	16QAM	100	0	18.64	18.70	18.73	18.70	18.65	
20	64QAM	1	0	18.99	19.05	19.08	18.99	19.05	
20	64QAM	1	49	19.21	19.21	19.22	19.15	19.17	20.5
20	64QAM	1	99	18.91	19.00	19.01	18.94	18.94	
20	64QAM	50	0	18.56	18.61	18.61	18.56	18.51	
20	64QAM	50	24	18.72	18.72	18.73	18.69	18.69	19.5
20	64QAM	50	50	18.56	18.58	18.60	18.57	18.60	
20	64QAM	100	0	18.69	18.68	18.69	18.68	18.59	
Channel				39725	40173	40620	41068	41515	Tune-up limit (dBm)
Frequency (MHz)				2503.5	2548.3	2593	2637.8	2682.5	
15	QPSK	1	0	20.66	20.60	20.28	20.61	20.38	21.50
15	QPSK	1	37	20.33	20.42	20.39	20.38	20.29	
15	QPSK	1	74	20.18	20.19	20.17	20.16	20.17	
15	QPSK	36	0	19.73	19.73	19.83	19.74	19.70	20.5
15	QPSK	36	20	19.76	19.75	19.69	19.72	19.73	
15	QPSK	36	39	19.48	19.51	19.57	19.52	19.40	
15	QPSK	75	0	19.36	19.38	19.48	19.42	19.39	20.5
15	16QAM	1	0	19.46	19.47	19.53	19.50	19.43	
15	16QAM	1	37	19.59	19.66	19.66	19.66	19.67	
15	16QAM	1	74	19.19	19.20	19.28	19.27	19.19	20.5
15	16QAM	36	0	18.73	18.65	18.76	18.66	18.69	
15	16QAM	36	20	18.77	18.74	18.80	18.87	18.76	
15	16QAM	36	39	18.53	18.60	18.57	18.56	18.56	20.5
15	16QAM	75	0	18.63	18.67	18.72	18.70	18.59	
15	64QAM	1	0	18.89	18.99	19.04	18.91	19.04	
15	64QAM	1	37	19.17	19.19	19.17	19.09	19.07	20.5
15	64QAM	1	74	18.82	18.90	19.00	18.85	18.88	
15	64QAM	36	0	18.56	18.53	18.61	18.48	18.44	
15	64QAM	36	20	18.63	18.62	18.73	18.66	18.62	19.5
15	64QAM	36	39	18.48	18.49	18.50	18.54	18.54	
15	64QAM	75	0	18.66	18.63	18.69	18.62	18.59	
Channel				39700	40160	40620	41080	41540	Tune-up limit (dBm)
Frequency (MHz)				2501	2547	2593	2639	2685	
10	QPSK	1	0	20.46	20.47	20.18	20.47	20.38	21.50
10	QPSK	1	25	20.28	20.40	20.35	20.33	20.29	
10	QPSK	1	49	20.07	20.06	20.17	20.13	20.10	
10	QPSK	25	0	19.70	19.70	19.75	19.69	19.70	20.5
10	QPSK	25	12	19.67	19.71	19.59	19.70	19.63	



FCC SAR TEST REPORT

Report No. : FA000714-06

10	QPSK	25	25	19.47	19.46	19.49	19.49	19.34	
10	QPSK	50	0	19.33	19.28	19.39	19.41	19.32	
10	16QAM	1	0	19.46	19.40	19.45	19.42	19.38	20.5
10	16QAM	1	25	19.54	19.57	19.59	19.56	19.60	
10	16QAM	1	49	19.14	19.14	19.22	19.18	19.16	
10	16QAM	25	0	18.70	18.64	18.68	18.56	18.60	20.5
10	16QAM	25	12	18.72	18.67	18.73	18.82	18.67	
10	16QAM	25	25	18.50	18.50	18.52	18.53	18.51	
10	16QAM	50	0	18.60	18.57	18.67	18.69	18.55	
10	64QAM	1	0	18.84	18.89	19.02	18.86	18.98	20.5
10	64QAM	1	25	19.08	19.09	19.09	19.05	19.07	
10	64QAM	1	49	18.74	18.90	18.99	18.83	18.86	
10	64QAM	25	0	18.56	18.50	18.56	18.41	18.44	19.5
10	64QAM	25	12	18.62	18.61	18.66	18.62	18.56	
10	64QAM	25	25	18.46	18.41	18.47	18.52	18.48	
10	64QAM	50	0	18.58	18.62	18.59	18.61	18.55	
Channel				39675	40148	40620	41093	41565	Tune-up limit (dBm)
Frequency (MHz)				2498.5	2545.8	2593	2640.30	2687.5	
5	QPSK	1	0	20.40	20.45	20.10	20.46	20.36	21.50
5	QPSK	1	12	20.19	20.34	20.29	20.33	20.22	
5	QPSK	1	24	19.98	20.00	20.15	20.05	20.00	
5	QPSK	12	0	19.66	19.70	19.68	19.67	19.69	20.5
5	QPSK	12	7	19.66	19.63	19.57	19.68	19.53	
5	QPSK	12	13	19.38	19.40	19.46	19.45	19.26	
5	QPSK	25	0	19.25	19.26	19.39	19.41	19.28	
5	16QAM	1	0	19.45	19.30	19.35	19.38	19.29	20.5
5	16QAM	1	12	19.51	19.55	19.56	19.55	19.58	
5	16QAM	1	24	19.11	19.14	19.22	19.08	19.11	
5	16QAM	12	0	18.64	18.61	18.61	18.52	18.60	20.5
5	16QAM	12	7	18.62	18.63	18.64	18.82	18.65	
5	16QAM	12	13	18.59	18.50	18.61	18.53	19.63	
5	16QAM	25	0	18.51	18.54	18.61	18.64	19.58	
5	64QAM	1	0	18.84	18.86	18.98	18.76	18.97	20.5
5	64QAM	1	12	19.00	19.07	19.03	19.04	19.01	
5	64QAM	1	24	18.69	18.90	18.94	18.74	18.78	
5	64QAM	12	0	18.48	18.47	18.46	18.38	18.37	19.5
5	64QAM	12	7	18.61	18.51	18.65	18.62	18.53	
5	64QAM	12	13	18.37	18.31	18.42	18.44	18.40	
5	64QAM	25	0	18.58	18.62	18.55	18.55	18.52	



12. WiFi/Bluetooth Output Power (Unit: dBm)

General Note:

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. 18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

<2.4GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	no required	15.00	no required
		6	2437		14.00	
		11	2462		14.00	
	802.11g 6Mbps	1	2412		14.00	
		6	2437		13.00	
		11	2462		13.00	
	802.11n-HT20 MCS0	1	2412		14.00	
		6	2437		13.00	
		11	2462		13.00	
	802.11n-HT40 MCS0	3	2422		13.00	
		6	2437		13.00	
		9	2452		12.00	



<5GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	
5.2GHz WLAN	802.11a 6Mbps	36	5180	no required	13.50	no required	
		40	5200		13.50		
		44	5220		13.50		
		48	5240		13.50		
	802.11n-HT20 MCS0	36	5180		13.50		
		40	5200		13.50		
		44	5220		13.50		
		48	5240		13.50		
	802.11n-HT40 MCS0	38	5190	13.30	13.50	86.00	
		46	5230	13.30	13.50	86.00	
	802.11ac-VHT20 MCS0	36	5180	no required	13.50	no required	
		40	5200		13.50		
		44	5220		13.50		
		48	5240		13.50		
802.11ac-VHT40 MCS0	38	5190	13.50		13.50		no required
	46	5230	13.50		13.50		no required
802.11ac-VHT80 MCS0	42	5210	12.50		12.50		no required

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %		
5.3GHz WLAN	802.11a 6Mbps	52	5260	no required	13.50	no required		
		56	5280		13.50			
		60	5300		13.50			
		64	5320		13.50			
	802.11n-HT20 MCS0	52	5260		13.50			
		56	5280		13.50			
		60	5300		13.50			
		64	5320		13.50			
	802.11n-HT40 MCS0	54	5270	13.40	13.50	86.00		
		62	5310	13.40	13.50	86.00		
	802.11ac-VHT20 MCS0	52	5260	no required	13.50	no required		
		56	5280		13.50			
		60	5300		13.50			
		64	5320		13.50			
	802.11ac-VHT40 MCS0	54	5270		13.50		13.50	no required
		62	5310		13.50		13.50	no required
802.11ac-VHT80 MCS0	58	5290	13.00		13.00		no required	



	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %		
5.5GHz WLAN	802.11a 6Mbps	100	5500	no required	12.50	no required		
		116	5580		12.50			
		124	5620		12.50			
		132	5660		12.50			
		140	5700		12.50			
	802.11n-HT20 MCS0	100	5500		12.50			
		116	5580		12.50			
		124	5620		12.50			
		132	5660		12.50			
		140	5700		12.50			
	802.11n-HT40 MCS0	102	5510	12.90	13.00	86.00		
		110	5550	no required	13.00	no required		
		126	5630		13.00			
	134	5670	13.00					
	802.11ac-VHT20 MCS0	100	5500		12.50			
		116	5580		12.50			
		124	5620		12.50			
		132	5660		12.50			
	802.11ac-VHT40 MCS0	102	5510		no required		12.50	no required
		110	5550				13.00	
126		5630	13.00					
134		5670	13.00					
802.11ac-VHT80 MCS0	106	5530	12.50					
	122	5610	12.50					

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.8GHz WLAN	802.11a 6Mbps	149	5745	no required	12.50	no required
		157	5785		12.50	
		165	5825		12.50	
	802.11n-HT20 MCS0	149	5745		12.50	
		157	5785		12.50	
		165	5825		12.50	
	802.11n-HT40 MCS0	151	5755	11.00	12.50	86.00
		159	5795	no required	12.50	no required
	802.11ac-VHT20 MCS0	149	5745		12.50	
		157	5785		12.50	
	802.11ac-VHT40 MCS0	165	5825		12.50	
		151	5755		12.50	
	802.11ac-VHT80 MCS0	159	5795		12.50	
155		5775	11.50			




<2.4GHz Bluetooth>

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	8.26	no required	no required
	CH 39	2441	7.59		
	CH 78	2480	7.54		
Tune-up Limit			9	7	7


Mode	Channel	Frequency (MHz)	Average power (dBm)
			GFSK
LE	CH 00	2402	no required
	CH 19	2440	
	CH 39	2480	
Tune-up Limit			1

General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 76.83% considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.



13. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	Yes	Yes	No	Yes	No	Yes
BT&WLAN	Yes	Yes	Yes	No	No	Yes

General Note:

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge



14. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
 - e. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The Reported TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
5. For 5.3GHz / 5.5GHz WLAN product specific SAR is necessary too, due to an overall diagonal dimension is > 16 cm.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq 1/4$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $1/4$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4/B12/B26 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 2/4/5/17 SAR test was covered by Band 25/66/26/12; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, WLAN5.2GHz SAR testing is not required when the WLAN5.3GHz band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for WLAN5.2GHz band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

14.1 Head SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
01	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9262	1852.4	21.25	22.50	1.334	-0.01	0.389	0.519
02	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1513	1752.6	21.77	23.00	1.327	-0.14	0.436	0.579
03	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4132	826.4	22.08	23.00	1.236	0.02	0.139	0.172

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
04	LTE Band 7	20M	QPSK	1	0	Right Cheek	0mm	21350	2560	21.33	22.50	1.309	-0.06	0.039	0.051
05	LTE Band 12	10M	QPSK	1	0	Left Cheek	0mm	23095	707.5	22.31	23.00	1.172	0.09	0.199	0.233
06	LTE Band 13	10M	QPSK	1	0	Left Cheek	0mm	23230	782	22.56	23.00	1.107	-0.11	0.115	0.127
07	LTE Band 14	10M	QPSK	1	0	Left Cheek	0mm	23330	793	22.35	23.00	1.161	-0.09	0.118	0.137
08	LTE Band 25	20M	QPSK	1	0	Left Cheek	0mm	26590	1905	21.24	22.00	1.191	-0.16	0.326	0.388
09	LTE Band 26	15M	QPSK	1	0	Left Cheek	0mm	26865	831.5	22.57	23.50	1.239	-0.18	0.155	0.192
10	LTE Band 66	20M	QPSK	1	0	Left Cheek	0mm	132572	1770	21.17	22.00	1.211	-0.09	0.343	0.415
11	LTE Band 71	20M	QPSK	1	0	Left Cheek	0mm	133322	683	22.25	23.00	1.189	-0.17	0.156	0.185

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
12	LTE Band 41	20M	QPSK	1	0	Right Cheek	0mm	40620	2593	20.36	21.50	1.300	62.9	1.006	0.02	0.054	0.071

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
13	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	1	2412	14.75	15.00	1.059	97.6	1.025	0.03	0.036	0.039
14	WLAN5GHz	802.11n-HT40 MCS0	Right Cheek	0mm	62	5310	13.40	13.50	1.023	86	1.163	-0.03	0.037	0.044
15	WLAN5GHz	802.11n-HT40 MCS0	Right Cheek	0mm	102	5510	12.90	13.00	1.023	86	1.163	-0.07	0.050	0.060
16	WLAN5GHz	802.11n-HT40 MCS0	Right Cheek	0mm	151	5755	11.00	12.50	1.413	86	1.163	-0.09	0.007	0.011

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Right Cheek	0mm	0	2402	8.26	9.00	1.186	76.83	1.084	-0.09	0.006	0.008
17	Bluetooth	1Mbps	Right Cheek	0mm	39	2441	7.59	9.00	1.384	76.83	1.084	-0.05	0.009	0.013
	Bluetooth	1Mbps	Right Cheek	0mm	78	2480	7.54	9.00	1.400	76.83	1.084	0.11	0.007	0.011
	Bluetooth	1Mbps	Right Tilted	0mm	0	2402	8.26	9.00	1.186	76.83	1.084	0.17	0.005	0.006
	Bluetooth	1Mbps	Left Cheek	0mm	0	2402	8.26	9.00	1.186	76.83	1.084	-0.16	0.001	0.001
	Bluetooth	1Mbps	Left Tilted	0mm	0	2402	8.26	9.00	1.186	76.83	1.084	0.1	0.001	0.001



14.2 Hotspot SAR

<WCDMA SAR>

Table with 13 columns: Plot No., Band, Mode, Test Position, Gap (mm), Ch., Freq. (MHz), Average Power (dBm), Tune-Up Limit (dBm), Tune-up Scaling Factor, Power Drift (dB), Measured 1g SAR (W/kg), Reported 1g SAR (W/kg). Rows 18-20.

<FDD LTE SAR>

Table with 15 columns: Plot No., Band, BW (MHz), Modulation, RB Size, RB offset, Test Position, Gap (mm), Ch., Freq. (MHz), Average Power (dBm), Tune-Up Limit (dBm), Tune-up Scaling Factor, Power Drift (dB), Measured 1g SAR (W/kg), Reported 1g SAR (W/kg). Rows 21-28.

<TDD LTE SAR>

Table with 16 columns: Plot No., Band, BW (MHz), Modulation, RB Size, RB offset, Test Position, Gap (mm), Ch., Freq. (MHz), Average Power (dBm), Tune-Up Limit (dBm), Tune-up Scaling Factor, Duty Cycle %, Duty Cycle Scaling Factor, Power Drift (dB), Measured 1g SAR (W/kg), Reported 1g SAR (W/kg). Row 29.

<WLAN SAR>

Table with 15 columns: Plot No., Band, Mode, Test Position, Gap (mm), Ch., Freq. (MHz), Average Power (dBm), Tune-Up Limit (dBm), Tune-up Scaling Factor, Duty Cycle %, Duty Cycle Scaling Factor, Power Drift (dB), Measured 1g SAR (W/kg), Reported 1g SAR (W/kg). Rows 30-32.

<Bluetooth SAR>

Table with 15 columns: Plot No., Band, Mode, Test Position, Gap (mm), Ch., Freq. (MHz), Average Power (dBm), Tune-Up Limit (dBm), Tune-up Scaling Factor, Duty Cycle %, Duty Cycle Scaling Factor, Power Drift (dB), Measured 1g SAR (W/kg), Reported 1g SAR (W/kg). Rows 33-39.

14.3 Body Worn Accessory SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
34	WCDMA II	RMC 12.2Kbps	Back	10mm	9262	1852.4	21.25	22.50	1.334	0	0.605	0.807
	WCDMA II	RMC 12.2Kbps	Back	10mm	9400	1880	21.11	22.50	1.377	0.18	0.528	0.727
	WCDMA II	RMC 12.2Kbps	Back	10mm	9538	1907.6	21.38	22.50	1.294	-0.13	0.490	0.634
35	WCDMA IV	RMC 12.2Kbps	Back	10mm	1513	1752.6	21.77	23.00	1.327	-0.18	0.641	0.851
	WCDMA IV	RMC 12.2Kbps	Back	10mm	1312	1712.4	21.51	23.00	1.409	0.17	0.436	0.614
	WCDMA IV	RMC 12.2Kbps	Back	10mm	1413	1732.6	21.38	23.00	1.452	0.05	0.573	0.832
36	WCDMA V	RMC 12.2Kbps	Back	10mm	4233	846.6	22.23	23.00	1.194	-0.18	0.088	0.105

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
37	LTE Band 7	20M	QPSK	1	0	Back	10mm	21100	2535	21.08	22.50	1.387	0.01	0.649	0.900
	LTE Band 7	20M	QPSK	1	0	Back	10mm	20850	2510	21.26	22.50	1.330	0.01	0.643	0.855
	LTE Band 7	20M	QPSK	1	0	Back	10mm	21350	2560	21.33	22.50	1.309	-0.06	0.567	0.743
38	LTE Band 12	10M	QPSK	1	0	Back	10mm	23095	707.5	22.31	23.00	1.172	-0.07	0.335	0.393
39	LTE Band 13	10M	QPSK	1	0	Back	10mm	23230	782	22.56	23.00	1.107	0.05	0.195	0.216
40	LTE Band 14	10M	QPSK	1	0	Back	10mm	23330	793	22.35	23.00	1.161	-0.06	0.178	0.207
41	LTE Band 25	20M	QPSK	1	0	Back	10mm	26340	1880	21.04	22.00	1.247	-0.05	0.496	0.619
42	LTE Band 26	15M	QPSK	1	0	Back	10mm	26865	831.5	22.57	23.50	1.239	-0.05	0.123	0.152
43	LTE Band 66	20M	QPSK	1	0	Back	10mm	132572	1770	21.17	22.00	1.211	-0.04	0.588	0.712
44	LTE Band 71	20M	QPSK	1	0	Back	10mm	133322	683	22.25	23.00	1.189	0	0.316	0.376

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
45	LTE Band 41	20M	QPSK	1	0	Back	10mm	41490	2680	20.48	21.50	1.265	62.9	1.006	0.07	0.348	0.443

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
46	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	1	2412	14.75	15.00	1.059	97.6	1.025	-0.13	0.050	0.054
47	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	62	5310	13.40	13.50	1.023	86	1.163	-0.04	0.034	0.040
48	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	102	5510	12.90	13.00	1.023	86	1.163	-0.05	0.049	0.058
49	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	151	5755	11.00	12.50	1.413	86	1.163	-0.04	0.010	0.016

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	0	2402	8.26	9.00	1.186	76.83	1.084	-0.07	0.001	0.001
	Bluetooth	1Mbps	Back	10mm	0	2402	8.26	9.00	1.186	76.83	1.084	-0.01	0.012	0.015
	Bluetooth	1Mbps	Back	10mm	39	2441	7.59	9.00	1.384	76.83	1.084	0.04	0.015	0.022
50	Bluetooth	1Mbps	Back	10mm	78	2480	7.54	9.00	1.400	76.83	1.084	-0.04	0.026	0.039

14.4 Product Specific SAR

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
51	WLAN5GHz	802.11n-HT40 MCS0	Left Side	0mm	62	5310	13.40	13.50	1.023	86	1.163	-0.04	0.087	0.104
52	WLAN5GHz	802.11n-HT40 MCS0	Left Side	0mm	102	5510	12.90	13.00	1.023	86	1.163	-0.03	0.094	0.112

15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset			
		Head	Body-worn	Hotspot	Product Specific
1.	WWAN + 2.4GHz WLAN + Bluetooth	Yes	Yes	Yes	Yes
2.	WWAN + 5GHz WLAN + Bluetooth	Yes	Yes	Yes	Yes
3.	WWAN + 2.4GHz WLAN + 5GHz WLAN	Yes	Yes	Yes	Yes

General Note:

1. This device WLAN 2.4GHz / 5.2GHz / 5.8GHz supports Hotspot operation support tethering applications.
2. The Scaled SAR summation is calculated based on the same configuration and test position.
3. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.



15.1 Head Exposure Conditions

WWAN Band	Exposure Position	1	2	3	4	1+2+4 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)	1+2+3 Summed 1g SAR (W/kg)
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
WCDMA II	Right Cheek	0.154	0.039	0.060	0.013	0.206	0.227	0.253
	Right Tilted	0.165	0.003	0.022	0.006	0.174	0.193	0.190
	Left Cheek	0.519	0.020	0.029	0.001	0.540	0.549	0.568
	Left Tilted	0.140	0.002	0.019	0.001	0.143	0.160	0.161
WCDMA IV	Right Cheek	0.216	0.039	0.060	0.013	0.268	0.289	0.315
	Right Tilted	0.111	0.003	0.022	0.006	0.120	0.139	0.136
	Left Cheek	0.579	0.020	0.029	0.001	0.600	0.609	0.628
	Left Tilted	0.151	0.002	0.019	0.001	0.154	0.171	0.172
WCDMA V	Right Cheek	0.060	0.039	0.060	0.013	0.112	0.133	0.159
	Right Tilted	0.001	0.003	0.022	0.006	0.010	0.029	0.026
	Left Cheek	0.172	0.020	0.029	0.001	0.193	0.202	0.221
	Left Tilted	0.001	0.002	0.019	0.001	0.004	0.021	0.022
LTE Band 7	Right Cheek	0.262	0.039	0.060	0.013	0.314	0.335	0.361
	Right Tilted	0.094	0.003	0.022	0.006	0.103	0.122	0.119
	Left Cheek	0.119	0.020	0.029	0.001	0.140	0.149	0.168
	Left Tilted	0.115	0.002	0.019	0.001	0.118	0.135	0.136
LTE Band 12	Right Cheek	0.136	0.039	0.060	0.013	0.188	0.209	0.235
	Right Tilted	0.102	0.003	0.022	0.006	0.111	0.130	0.127
	Left Cheek	0.233	0.020	0.029	0.001	0.254	0.263	0.282
	Left Tilted	0.133	0.002	0.019	0.001	0.136	0.153	0.154
LTE Band 13	Right Cheek	0.094	0.039	0.060	0.013	0.146	0.167	0.193
	Right Tilted	0.070	0.003	0.022	0.006	0.079	0.098	0.095
	Left Cheek	0.127	0.020	0.029	0.001	0.148	0.157	0.176
	Left Tilted	0.087	0.002	0.019	0.001	0.090	0.107	0.108
LTE Band 14	Right Cheek	0.085	0.039	0.060	0.013	0.137	0.158	0.184
	Right Tilted	0.062	0.003	0.022	0.006	0.071	0.090	0.087
	Left Cheek	0.137	0.020	0.029	0.001	0.158	0.167	0.186
	Left Tilted	0.088	0.002	0.019	0.001	0.091	0.108	0.109
LTE Band 25	Right Cheek	0.146	0.039	0.060	0.013	0.198	0.219	0.245
	Right Tilted	0.142	0.003	0.022	0.006	0.151	0.170	0.167
	Left Cheek	0.388	0.020	0.029	0.001	0.409	0.418	0.437
	Left Tilted	0.117	0.002	0.019	0.001	0.120	0.137	0.138
LTE Band 26	Right Cheek	0.082	0.039	0.060	0.013	0.134	0.155	0.181
	Right Tilted	0.001	0.003	0.022	0.006	0.010	0.029	0.026
	Left Cheek	0.192	0.020	0.029	0.001	0.213	0.222	0.241
	Left Tilted	0.001	0.002	0.019	0.001	0.004	0.021	0.022
LTE Band 41	Right Cheek	0.135	0.039	0.060	0.013	0.187	0.208	0.234
	Right Tilted	0.046	0.003	0.022	0.006	0.055	0.074	0.071
	Left Cheek	0.062	0.020	0.029	0.001	0.083	0.092	0.111
	Left Tilted	0.065	0.002	0.019	0.001	0.068	0.085	0.086
LTE Band 66	Right Cheek	0.134	0.039	0.060	0.013	0.186	0.207	0.233
	Right Tilted	0.082	0.003	0.022	0.006	0.091	0.110	0.107
	Left Cheek	0.415	0.020	0.029	0.001	0.436	0.445	0.464
	Left Tilted	0.092	0.002	0.019	0.001	0.095	0.112	0.113
LTE Band 71	Right Cheek	0.191	0.039	0.060	0.013	0.243	0.264	0.290
	Right Tilted	0.126	0.003	0.022	0.006	0.135	0.154	0.151
	Left Cheek	0.301	0.020	0.029	0.001	0.322	0.331	0.350
	Left Tilted	0.183	0.002	0.019	0.001	0.186	0.203	0.204



15.2 Hotspot Exposure Conditions

WWAN Band	Exposure Position	1	2	3	4	1+2+4 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)	1+2+3 Summed 1g SAR (W/kg)
		WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)			
WCDMA II	Front	0.283	0.001	0.045	0.001	0.285	0.329	0.329
	Back	0.807	0.058	0.056	0.019	0.884	0.882	0.921
	Left side	0.236	0.038	0.094	0.035	0.309	0.365	0.368
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.341			0.002	0.343	0.343	0.341
WCDMA IV	Front	0.605	0.001	0.045	0.001	0.607	0.651	0.651
	Back	0.851	0.058	0.056	0.019	0.928	0.926	0.965
	Left side	0.318	0.038	0.094	0.035	0.391	0.447	0.450
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.355			0.002	0.357	0.357	0.355
WCDMA V	Front	0.070	0.001	0.045	0.001	0.072	0.116	0.116
	Back	0.163	0.058	0.056	0.019	0.240	0.238	0.277
	Left side	0.064	0.038	0.094	0.035	0.137	0.193	0.196
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.056			0.002	0.058	0.058	0.056
LTE Band 7	Front	0.250	0.001	0.045	0.001	0.252	0.296	0.296
	Back	0.900	0.058	0.056	0.019	0.977	0.975	1.014
	Left side	0.103	0.038	0.094	0.035	0.176	0.232	0.235
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.386			0.002	0.388	0.388	0.386
LTE Band 12	Front	0.111	0.001	0.045	0.001	0.113	0.157	0.157
	Back	0.393	0.058	0.056	0.019	0.470	0.468	0.507
	Left side	0.095	0.038	0.094	0.035	0.168	0.224	0.227
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.078			0.002	0.080	0.080	0.078
LTE Band 13	Front	0.079	0.001	0.045	0.001	0.081	0.125	0.125
	Back	0.216	0.058	0.056	0.019	0.293	0.291	0.330
	Left side	0.082	0.038	0.094	0.035	0.155	0.211	0.214
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.049			0.002	0.051	0.051	0.049
LTE Band 14	Front	0.077	0.001	0.045	0.001	0.079	0.123	0.123
	Back	0.207	0.058	0.056	0.019	0.284	0.282	0.321
	Left side	0.078	0.038	0.094	0.035	0.151	0.207	0.210
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.010			0.002	0.012	0.012	0.010
LTE Band 25	Front	0.263	0.001	0.045	0.001	0.265	0.309	0.309
	Back	0.619	0.058	0.056	0.019	0.696	0.694	0.733
	Left side	0.242	0.038	0.094	0.035	0.315	0.371	0.374
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.274			0.002	0.276	0.276	0.274
LTE Band 26	Front	0.079	0.001	0.045	0.001	0.081	0.125	0.125
	Back	0.152	0.058	0.056	0.019	0.229	0.227	0.266
	Left side	0.042	0.038	0.094	0.035	0.115	0.171	0.174



	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.002			0.002	0.004	0.004	0.002
LTE Band 41	Front	0.200	0.001	0.045	0.001	0.202	0.246	0.246
	Back	0.461	0.058	0.056	0.019	0.538	0.536	0.575
	Left side	0.043	0.038	0.094	0.035	0.116	0.172	0.175
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.285			0.002	0.287	0.287	0.285
LTE Band 66	Front	0.305	0.001	0.045	0.001	0.307	0.351	0.351
	Back	0.712	0.058	0.056	0.019	0.789	0.787	0.826
	Left side	0.234	0.038	0.094	0.035	0.307	0.363	0.366
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.184			0.002	0.186	0.186	0.184
LTE Band 71	Front	0.293	0.001	0.045	0.001	0.295	0.339	0.339
	Back	0.411	0.058	0.056	0.019	0.488	0.486	0.525
	Left side	0.167	0.038	0.094	0.035	0.240	0.296	0.299
	Right side				0.003	0.003	0.003	0.000
	Top side		0.001	0.047	0.011	0.012	0.058	0.048
	Bottom side	0.145			0.002	0.147	0.147	0.145



15.3 Body-Worn Accessory Exposure Conditions

WWAN Band	Exposure Position	1	2	3	4	1+2+4 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)	1+2+3 Summed 1g SAR (W/kg)
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
WCDMA II	Front	0.283	0.001	0.032	0.001	0.285	0.316	0.316
	Back	0.807	0.058	0.058	0.039	0.904	0.904	0.923
WCDMA IV	Front	0.605	0.001	0.032	0.001	0.607	0.638	0.638
	Back	0.851	0.058	0.058	0.039	0.948	0.948	0.967
WCDMA V	Front	0.070	0.001	0.032	0.001	0.072	0.103	0.103
	Back	0.163	0.058	0.058	0.039	0.260	0.260	0.279
LTE Band 7	Front	0.250	0.001	0.032	0.001	0.252	0.283	0.283
	Back	0.900	0.058	0.058	0.039	0.997	0.997	1.016
LTE Band 12	Front	0.111	0.001	0.032	0.001	0.113	0.144	0.144
	Back	0.393	0.058	0.058	0.039	0.490	0.490	0.509
LTE Band 13	Front	0.079	0.001	0.032	0.001	0.081	0.112	0.112
	Back	0.216	0.058	0.058	0.039	0.313	0.313	0.332
LTE Band 14	Front	0.077	0.001	0.032	0.001	0.079	0.110	0.110
	Back	0.207	0.058	0.058	0.039	0.304	0.304	0.323
LTE Band 25	Front	0.263	0.001	0.032	0.001	0.265	0.296	0.296
	Back	0.619	0.058	0.058	0.039	0.716	0.716	0.735
LTE Band 26	Front	0.079	0.001	0.032	0.001	0.081	0.112	0.112
	Back	0.152	0.058	0.058	0.039	0.249	0.249	0.268
LTE Band 41	Front	0.200	0.001	0.032	0.001	0.202	0.233	0.233
	Back	0.461	0.058	0.058	0.039	0.558	0.558	0.577
LTE Band 66	Front	0.305	0.001	0.032	0.001	0.307	0.338	0.338
	Back	0.712	0.058	0.058	0.039	0.809	0.809	0.828
LTE Band 71	Front	0.293	0.001	0.032	0.001	0.295	0.326	0.326
	Back	0.411	0.058	0.058	0.039	0.508	0.508	0.527

15.4 Product Specific Exposure Conditions

Exposure Position	1	2	3	4	1+2+4 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)	1+2+3 Summed 1g SAR (W/kg)
	WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
Front			0.028		0.000	0.028	0.028
Back			0.043		0.000	0.043	0.043
Left side			0.112		0.000	0.112	0.112
Right side					0.000	0.000	0.000
Top side			0.027		0.000	0.027	0.027
Bottom side					0.000	0.000	0.000

Test Engineer : Sing Lim, Kells Chen and Chris Yang



16. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

Declaration of Conformity:

The test results with all measurement uncertainty excluded is presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [11] FCC KDB 941225 D07 v01r02, " SAR Evaluation Procedures for UMPC Mini-Tablet Devices", Oct 2015.
- [12] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [13] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.