

FCC PART 15, SUBPART B and C
TEST REPORT

for

VERSA REMOTE TX MODULE
MODEL: VRTXM

Prepared for

KAR-TECH, INC.
111 ENTERPRISE ROAD
DELAFIELD, WISCONSIN 53018

Prepared by: Kyle Fujimoto

KYLE FUJIMOTO

Approved by: Michael P. Christensen

MICHAEL CHRISTENSEN

COMPATIBLE ELECTRONICS INC.
114 OLINDA DRIVE
BREA, CALIFORNIA 92823
(714) 579-0500

DATE: DECEMBER 5, 2002

	REPORT BODY	APPENDICES					TOTAL
		A	B	C	D	E	
PAGES	16	2	2	2	10	11	43

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



TABLE OF CONTENTS

Section / Title	PAGE
GENERAL REPORT SUMMARY	4
SUMMARY OF TEST RESULTS	4
1. PURPOSE	5
2. ADMINISTRATIVE DATA	6
2.1 Location of Testing	6
2.2 Traceability Statement	6
2.3 Cognizant Personnel	6
2.4 Date Test Sample was Received	6
2.5 Disposition of the Test Sample	6
2.6 Abbreviations and Acronyms	6
3. APPLICABLE DOCUMENTS	7
4. Description of Test Configuration	8
4.1 Description of Test Configuration - EMI	8
4.1.1 Cable Construction and Termination	9
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	10
5.1 EUT and Accessory List	10
5.2 EMI Test Equipment	11
6. TEST SITE DESCRIPTION	12
6.1 Test Facility Description	12
6.2 EUT Mounting, Bonding and Grounding	12
7. Test Procedures	13
7.1 Radiated Emissions (Spurious and Harmonics) Test	13
7.2 Band Edges	15
8. CONCLUSIONS	16



LIST OF APPENDICES

APPENDIX	TITLE
A	Laboratory Recognitions
B	Modifications to the EUT
C	Additional Models Covered Under This Report
D	Diagrams, Charts, and Photos <ul style="list-style-type: none">• Test Setup Diagrams• Radiated Emissions Photos• Antenna and Effective Gain Factors
E	Data Sheets

LIST OF FIGURES

FIGURE	TITLE
1	Plot Map And Layout of Test Site



GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used to claim product endorsement by NVLAP or any other agency of the U.S. Government.

Device Tested: Versa Remote Tx Module
Model: VRTXM
S/N: N/A

Product Description: See Expository Statement.

Modifications: The EUT was not modified during the testing.

Manufacturer: Kar-Tech, Inc.
111 Enterprise Road
Delafield, Wisconsin 53018

Test Date: December 2, 2002

Test Specifications: EMI requirements
CFR Title 47, Part 15 Subpart B; and Subpart C, Sections 15.205, 15.209, and 15.249

Test Procedure: ANSI C63.4: 1992

Test Deviations: The test procedure was not deviated from during the testing.

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Conducted RF Emissions, 450 kHz - 30 MHz	This test was not performed because the EUT operates on DC power only and cannot be plugged into the AC public mains.
2	Radiated RF Emissions, 10 kHz - 9300 MHz	Complies with the Class B limits of CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.249.



1. PURPOSE

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the Versa Remote Tx Module Model: VRTXM. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4: 1992. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the **Class B** specification limits defined by CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.249.



2. ADMINISTRATIVE DATA

2.1 Location of Testing

The EMI tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Kar-Tech, Inc.

Aaron Oestreich General Manager

Compatible Electronics, Inc.

Kyle Fujimoto Test Engineer

Michael Christensen Test Engineer

2.4 Date Test Sample was Received

The test sample was received on November 27, 2002.

2.5 Disposition of the Test Sample

The sample has not been returned to Kar-Tech, Inc. as of December 5, 2002.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
CML	Corrected Meter Limit
LISN	Line Impedance Stabilization Network



3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this EMI Test Report.

SPEC	TITLE
CFR Title 47, Part 15	FCC Rules – Radio frequency devices (including digital devices)
ANSI C63.4 1992	Methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz.



4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description of Test Configuration - EMI

Setup and operation of the equipment under test.

Specifics of the EUT and Peripherals Tested

The Versa Remote Tx Module Model: VRTXM (EUT) was tested as a stand alone unit and was continuously transmitting. The EUT was only connected to a DC Power Supply and three buttons to provide power and to lock the transmitter at a particular channel (low, middle, or high). The antenna connector is a reverse polarity SMA.

The final radiated data was taken in the mode above. Please see Appendix E for the data sheets.



4.1.1 Cable Construction and Termination

Cables 1-2 These are 1 meter unshielded cables connecting the EUT to the yellow button. They are hard wired at each end.

Cable 3 This is a 1 meter unshielded cable connecting the EUT to the green button. It is hard wired at each end.

Cable 4 This is a 1 meter unshielded cable connecting the EUT to the red button. It is hard wired at each end.

Cables 5-6 These are 1 meter unshielded cable connecting the EUT to the DC Power Supply. They are hard wired at each end.



5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT**5.1 EUT and Accessory List**

EQUIPMENT	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID
VERSA REMOTE TX MODULE (EUT)	KAR-TECH, INC.	VRTXM	N/A	P4U-VRTXM
DC POWER SUPPLY	KAR-TECH, INC.	6012B	3212A-03876	DoC
ANTENNA	LINX TECHNOLOGIES	N/A	N/A	N/A
YELLOW BUTTON	N/A	N/A	N/A	N/A
GREEN BUTTON	N/A	N/A	N/A	N/A
RED BUTTON	N/A	N/A	N/A	N/A



5.2 EMI Test Equipment

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. DUE DATE
Radiated Emissions Manual Test – Radiated	Compatible Electronics	N/A	N/A	N/A	N/A
Spectrum Analyzer – Main Section	Hewlett Packard	8566B	2727A04757	Nov. 9, 2001	Nov. 9, 2002
Spectrum Analyzer – Display Section	Hewlett Packard	85662A	2648A15455	Nov. 9, 2001	Nov. 9, 2002
Spectrum Analyzer – Quasi-Peak Adapter	Hewlett Packard	85650A	3303A01688	Nov. 9, 2001	Nov. 9, 2002
Preamplifier	Com Power	PA-102	1017	Dec. 31, 2001	Dec. 31, 2002
Biconical Antenna	Com Power	AB-100	1548	Sept. 19, 2002	Sept. 19, 2003
Log Periodic Antenna	Com Power	AL-100	16089	Oct. 4, 2002	Oct. 4, 2003
Computer	Hewlett Packard	D5251A 888	US74458128	N/A	N/A
Printer	Hewlett Packard	C5886A	SG7CM1P090	N/A	N/A
Monitor	Hewlett Packard	D5258A	DK74889705	N/A	N/A
Loop Antenna	Com-Power	AL-130	17070	June 19, 2002	June 19, 2003
Horn Antenna	Com-Power	AH-118	10073	Jan. 21, 2002	Jan. 21, 2003
Microwave Preamplifier	Com-Power	PA-122	25195	Jan. 7, 2002	Jan. 7, 2003



6. TEST SITE DESCRIPTION**6.1 Test Facility Description**

Please refer to section 2.1 and 7.1 of this report for EMI test location.

6.2 EUT Mounting, Bonding and Grounding

The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane.

The EUT was not grounded.



7. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 Radiated Emissions (Spurious and Harmonics) Test

The spectrum analyzer was used as a measuring meter along with the quasi-peak adapter. Amplifiers were used to increase the sensitivity of the instrument. The Com Power Preamplifier Model: PA-102 was used for frequencies from 30 MHz to 1 GHz, and the Com-Power Microwave Preamplifier Model: PA-122 was used for frequencies above 1 GHz. The spectrum analyzer was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the spectrum analyzer records the highest measured reading over all the sweeps.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE	EFFECTIVE MEASUREMENT BANDWIDTH	TRANSDUCER
9 kHz to 150 kHz	200 Hz	Active Loop Antenna
150 kHz to 30 MHz	9 kHz	Active Loop Antenna
30 MHz to 300 MHz	120 kHz	Biconical Antenna
300 MHz to 1 GHz	120 kHz	Log Periodic Antenna
1 GHz to 9.3 GHz	1 MHz	Horn Antenna

The open field test site of Compatible Electronics, Inc. was used for radiated emission testing. This test site is set up according to ANSI C63.4: 1992. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna in order to ensure accurate results. The loop antenna was also rotated in the horizontal and vertical axis in order to ensure accurate results.



Radiated Emissions (Spurious and Harmonics) Test (con't)

The presence of ambient signals was verified by turning the EUT off. In case an ambient signal was detected, the measurement bandwidth was reduced temporarily and verification was made that an additional adjacent peak did not exist. This ensures that the ambient signal does not hide any emissions from the EUT. The EUT was tested at a 3 meter test distance to obtain final test data. The final qualification data sheets are located in Appendix E.



7.2 Band Edges

Spectral plots of both the low and high channels were taken of the EUT to show that the emissions at the band edges (902 and 928 MHz) were attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in FCC Title 47, Subpart C, section 15.209, whichever is the lesser attenuation. A preamplifier was used to boost the signal level at the band edges for easier comparison to the spec limit. The spectral plots and data sheets are located in Appendix D.



8. CONCLUSIONS

The Versa Remote Tx Module Model: VRTXM meets all of the **Class B** specification limits defined in CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.249.



APPENDIX A

LABORATORY RECOGNITIONS



LABORATORY RECOGNITIONS

Compatible Electronics has the following agency accreditations:

National Voluntary Laboratory Accreditation Program - Lab Code: 200528-0

Voluntary Control Council for Interference - Registration Numbers: R-983, C-1026, R-984 and C-1027

Bureau of Standards and Metrology Inspection - Reference Number: SL2-IN-E-1031

Conformity Assessment Body for the EMC Directive Under the US/EU MRA Appointed by NIST

Compatible Electronics is recognized or on file with the following agencies:

Federal Communications Commission

Industry Canada

Radio-Frequency Technologies (Competent Body)



APPENDIX B

MODIFICATIONS TO THE EUT




MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC 15.249 specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made to the EUT during the testing.



APPENDIX C

***ADDITIONAL MODELS COVERED
UNDER THIS REPORT***



ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

Versa Remote Tx Module
Model: VRTXM
S/N: N/A

There were no additional models covered under this report.




APPENDIX D

DIAGRAMS, CHARTS, AND PHOTOS



FIGURE 1: PLOT MAP AND LAYOUT OF RADIATED SITE

OPEN LAND > 15 METERS



OPEN LAND > 15 METERS

- | | | | |
|----------|--------------------------|--|-----------------|
| X | = GROUND RODS | | = GROUND SCREEN |
| D | = TEST DISTANCE (meters) | | = WOOD COVER |



COM-POWER AB-100

BICONICAL ANTENNA

S/N: 01548

CALIBRATION DATE: SEPTEMBER 19, 2002

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	14.30	120	10.70
35	14.00	125	11.40
40	13.70	140	12.70
45	12.00	150	12.50
50	11.40	160	12.90
60	9.70	175	14.10
70	8.30	180	14.70
80	7.60	200	15.10
90	7.80	250	16.90
100	8.60	300	19.10



COM-POWER AL-100**LOG PERIODIC ANTENNA**

S/N: 16089

CALIBRATION DATE: OCTOBER 4, 2002

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
300	13.10	700	17.70
350	14.40	750	19.60
400	14.30	800	20.50
450	15.70	850	21.20
500	16.60	900	21.20
550	16.60	950	22.50
600	17.30	1000	24.60
650	18.80		



COM-POWER PA-102**PREAMPLIFIER**

S/N: 1017

CALIBRATION DATE: DECEMBER 31, 2001

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	38.5	300	38.5
40	38.5	350	38.4
50	38.5	400	38.2
60	38.5	450	37.8
70	38.5	500	38.0
80	38.5	550	38.2
90	38.3	600	38.2
100	38.3	650	38.0
125	38.6	700	38.1
150	38.5	750	37.7
175	38.4	800	37.4
200	38.5	850	37.9
225	38.5	900	37.2
250	38.4	950	36.8
275	38.4	1000	37.3



COM-POWER PA-122**MICROWAVE PREAMPLIFIER**

S/N: 25195

CALIBRATION DATE: JANUARY 7, 2002

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	33.7	9.5	31.8
1.1	33.4	10.0	32.2
1.2	33.1	11.0	31.4
1.3	33.1	12.0	30.2
1.4	33.2	13.0	32.9
1.5	32.5	14.0	33.9
1.6	32.7	15.0	32.4
1.7	32.3	16.0	32.2
1.8	32.3	17.0	31.5
1.9	31.4	18.0	32.2
2.0	32.8	19.0	31.2
2.5	33.3	20.0	31.3
3.0	31.7	21.0	31.7
3.5	31.6	22.0	29.7
4.0	31.2		
4.5	31.2		
5.0	31.0		
5.5	31.3		
6.0	32.1		
6.5	32.1		
7.0	31.8		
7.5	32.0		
8.0	33.1		
8.5	32.0		
9.0	30.8		



ANTENNA RESEARCH DRG-118/A**HORN ANTENNA**

S/N: 1053

CALIBRATION DATE: JANUARY 13, 2002

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	25.5	9.5	39.1
1.5	26.6	10.0	39.7
2.0	29.4	10.5	40.9
2.5	30.4	11.0	40.7
3.0	31.2	11.5	42.4
3.5	32.3	12.0	42.6
4.0	32.9	12.5	42.4
4.5	33.0	13.0	41.5
5.0	34.8	13.5	41.0
5.5	35.2	14.0	40.5
6.0	36.4	14.5	43.6
6.5	36.6	15.0	43.7
7.0	38.8	15.5	43.3
7.5	38.8	16.0	42.8
8.0	38.0	16.5	43.0
8.5	38.1	17.0	42.7
9.0	39.9	17.5	44.0
		18.0	41.8



COM-POWER AL-130**LOOP ANTENNA**

S/N: 17070

CALIBRATION DATE: JUNE 19, 2002

FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)
0.009	-40.4	11.1
0.01	-40.3	11.2
0.02	-41.2	10.3
0.05	-41.6	9.9
0.07	-41.4	10.1
0.1	-41.7	9.8
0.2	-44.0	7.5
0.3	-41.6	9.9
0.5	-41.3	10.2
0.7	-41.4	10.1
1	-40.9	10.6
2	-40.6	10.9
3	-40.5	11.0
4	-40.8	10.7
5	-40.2	11.3
10	-40.7	10.8
15	-41.4	10.1
20	-41.6	9.9
25	-41.7	9.8
30	-42.9	8.6





FRONT VIEW

KAR-TECH, INC.
VERSA REMOTE TX MODULE
MODEL: VRTXM
FCC SUBPART B AND C - RADIATED EMISSIONS – 12-02-02

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**






REAR VIEW

KAR-TECH, INC.
VERSA REMOTE TX MODULE
MODEL: VRTXM
FCC SUBPART B AND C - RADIATED EMISSIONS – 12-02-02

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**





RADIATED EMISSIONS

DATA SHEETS



RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	KAR-TECH, INC.	DATE	12/2/02
EUT	VERSA REMOTE TRANSMITTER MODULE	DUTY CYCLE	N/A %
MODEL	VRTXM	PEAK TO AVG	N/A dB
S/N	N/A	TEST DIST.	3 Meters
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
903.3000	97.0	QP	H	1.0	0	X	LOW	21.3	5.0	37.1	0.0	0.0	86.2	-7.8	94.0	
903.3000	100.2	QP	H	1.0	180	Y	LOW	21.3	5.0	37.1	0.0	0.0	89.4	-4.6	94.0	
903.3000	99.9	QP	H	1.0	180	Z	LOW	21.3	5.0	37.1	0.0	0.0	89.1	-4.9	94.0	
903.3000	104.7	104.3 QP	V	1.0	270	X	LOW	21.3	5.0	37.1	0.0	0.0	93.5	-0.5	94.0	
903.3000	104.1	103.6 QP	V	1.0	270	Y	LOW	21.3	5.0	37.1	0.0	0.0	92.8	-1.2	94.0	
903.3000	104.6	104.3 QP	V	1.0	270	Z	LOW	21.3	5.0	37.1	0.0	0.0	93.5	-0.5	94.0	
909.3800	97.0	QP	H	1.0	180	X	MED.	21.5	5.2	37.1	0.0	0.0	86.5	-7.5	94.0	
909.3800	96.6	QP	H	1.0	180	Y	MED.	21.5	5.2	37.1	0.0	0.0	86.1	-7.9	94.0	
909.3800	99.7	QP	H	1.0	180	Z	MED.	21.5	5.2	37.1	0.0	0.0	89.2	-4.8	94.0	
909.3800	104.8	104.4 QP	V	1.0	270	X	MED.	21.5	5.2	37.1	0.0	0.0	93.9	-0.1	94.0	
909.3800	103.3	102.5 QP	V	1.0	270	Y	MED.	21.5	5.2	37.1	0.0	0.0	92.0	-2.0	94.0	
909.3800	104.5	104.2 QP	V	1.0	180	Z	MED.	21.5	5.2	37.1	0.0	0.0	93.7	-0.3	94.0	
921.3000	95.3	QP	H	1.0	0	X	HIGH	21.8	5.4	37.0	0.0	0.0	85.5	-8.5	94.0	
921.3000	97.9	QP	H	1.0	180	Y	HIGH	21.8	5.4	37.0	0.0	0.0	88.1	-5.9	94.0	
921.3000	95.4	QP	H	1.0	180	Z	HIGH	21.8	5.4	37.0	0.0	0.0	85.6	-8.4	94.0	
921.3000	104.3	103.5 QP	V	1.0	270	X	HIGH	21.8	5.4	37.0	0.0	0.0	93.7	-0.3	94.0	
921.3000	102.1	101.5 QP	V	1.0	270	Y	HIGH	21.8	5.4	37.0	0.0	0.0	91.7	-2.3	94.0	
921.3000	102.6	102.0 QP	V	1.0	270	Z	HIGH	21.8	5.4	37.0	0.0	0.0	92.2	-1.8	94.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN

** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	KAR-TECH, INC.	DATE	12/2/02
EUT	VERSA REMOTE TRANSMITTER MODULE	DUTY CYCLE	N/A %
MODEL	VRTXM	PEAK TO AVG	N/A dB
S/N	N/A	TEST DIST.	3 Meters
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
1806.6000	52.3	A	H	1.0	270	X	LOW	28.3	3.4	34.0	0.0	0.0	50.0	-4.0	54.0	
1806.6000	51.4	41.7 A	H	1.0	270	Y	LOW	28.3	3.4	34.0	0.0	0.0	39.4	-14.6	54.0	
1806.6000	49.3	41.5 A	H	2.0	180	Z	LOW	28.3	3.4	34.0	0.0	0.0	39.2	-14.8	54.0	
1806.6000	55.0	51.5 A	V	1.0	180	X	LOW	28.3	3.4	34.0	0.0	0.0	49.1	-4.9	54.0	
1806.6000	57.1	55.0 A	V	1.0	180	Y	LOW	28.3	3.4	34.0	0.0	0.0	52.7	-1.3	54.0	
1806.6000	55.9	51.1 A	V	1.0	180	Z	LOW	28.3	3.4	34.0	0.0	0.0	48.8	-5.2	54.0	
1818.7600	54.4	47.6 A	H	2.0	180	X	MED.	28.4	3.4	34.1	0.0	0.0	45.3	-8.7	54.0	
1818.7600	52.1	44.8 A	H	1.0	180	Y	MED.	28.4	3.4	34.1	0.0	0.0	42.5	-11.5	54.0	
1818.7600	56.6	51.9 A	H	1.0	180	Z	MED.	28.4	3.4	34.1	0.0	0.0	49.6	-4.4	54.0	
1818.7600	56.1	51.7 A	V	1.0	180	X	MED.	28.4	3.4	34.1	0.0	0.0	49.4	-4.6	54.0	
1818.7600	56.9	53.0 A	V	1.0	180	Y	MED.	28.4	3.4	34.1	0.0	0.0	50.7	-3.3	54.0	
1818.7600	54.4	48.4 A	V	1.0	180	Z	MED.	28.4	3.4	34.1	0.0	0.0	46.1	-7.9	54.0	
1842.6000	53.3	46.2 A	H	1.0	180	X	HIGH	28.5	3.4	34.2	0.0	0.0	43.9	-10.1	54.0	
1842.6000	52.6	42.9 A	H	1.0	180	Y	HIGH	28.5	3.4	34.2	0.0	0.0	40.7	-13.3	54.0	
1842.6000	51.2	44.9 A	H	1.0	180	Z	HIGH	28.5	3.4	34.2	0.0	0.0	42.7	-11.3	54.0	
1842.6000	53.1	44.9 A	V	1.0	180	X	HIGH	28.5	3.4	34.2	0.0	0.0	42.7	-11.3	54.0	
1842.6000	56.3	51.9 A	V	1.0	180	Y	HIGH	28.5	3.4	34.2	0.0	0.0	49.6	-4.4	54.0	
1842.6000	55.2	47.8 A	V	1.0	180	Z	HIGH	28.5	3.4	34.2	0.0	0.0	45.5	-8.5	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN

** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	KAR-TECH, INC.	DATE	12/2/02
EUT	VERSA REMOTE TRANSMITTER MODULE	DUTY CYCLE	N/A %
MODEL	VRTXM	PEAK TO AVG	N/A dB
S/N	N/A	TEST DIST.	3 Meters
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2709.9000	54.9	49.3 A	H	1.0	180	X	LOW	30.7	4.2	33.9	0.0	0.0	50.3	-3.7	54.0	
2709.9000	54.8	49.5 A	H	1.0	180	Y	LOW	30.7	4.2	33.9	0.0	0.0	50.5	-3.5	54.0	
2709.9000	51.8	50.4 A	H	1.0	180	Z	LOW	30.7	4.2	33.9	0.0	0.0	51.3	-2.7	54.0	
2709.9000	56.4	51.5 A	V	1.0	180	X	LOW	30.7	4.2	33.9	0.0	0.0	52.5	-1.5	54.0	
2709.9000	49.4	47.3 A	V	1.0	180	Y	LOW	30.7	4.2	33.9	0.0	0.0	48.2	-5.8	54.0	
2709.9000	49.0	46.7 A	V	1.0	180	Z	LOW	30.7	4.2	33.9	0.0	0.0	47.6	-6.4	54.0	
2728.1400	54.2	46.9 A	H	1.0	180	X	MED.	30.8	4.2	33.9	0.0	0.0	47.9	-6.1	54.0	
2728.1400	55.2	51.0 A	H	1.0	180	Y	MED.	30.8	4.2	33.9	0.0	0.0	52.1	-1.9	54.0	
2728.1400	56.1	51.5 A	H	1.0	180	Z	MED.	30.8	4.2	33.9	0.0	0.0	52.6	-1.4	54.0	
2728.1400	54.3	48.8 A	V	1.0	180	X	MED.	30.8	4.2	33.9	0.0	0.0	49.9	-4.1	54.0	
2728.1400	49.9	48.1 A	V	1.0	180	Y	MED.	30.8	4.2	33.9	0.0	0.0	49.2	-4.8	54.0	
2728.1400	52.5	51.6 A	V	1.0	180	Z	MED.	30.8	4.2	33.9	0.0	0.0	52.7	-1.3	54.0	
2763.9000	52.4	51.3 A	H	1.0	180	X	HIGH	30.8	4.4	33.9	0.0	0.0	52.6	-1.4	54.0	
2763.9000	52.0	50.1 A	H	1.0	180	Y	HIGH	30.8	4.4	33.9	0.0	0.0	51.4	-2.6	54.0	
2763.9000	52.6	50.8 A	H	1.0	180	Z	HIGH	30.8	4.4	33.9	0.0	0.0	52.1	-1.9	54.0	
2763.9000	56.6	51.3 A	V	1.0	180	X	HIGH	30.8	4.4	33.9	0.0	0.0	52.5	-1.5	54.0	
2763.9000	52.3	50.1 A	V	1.0	180	Y	HIGH	30.8	4.4	33.9	0.0	0.0	51.4	-2.6	54.0	
2763.9000	52.0	50.2 A	V	1.0	180	Z	HIGH	30.8	4.4	33.9	0.0	0.0	51.5	-2.5	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN

** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	KAR-TECH, INC.	DATE	12/2/02
EUT	VERSA REMOTE TRANSMITTER MODULE	DUTY CYCLE	N/A %
MODEL	VRTXM	PEAK TO AVG	N/A dB
S/N	N/A	TEST DIST.	3 Meters
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
3613.2000	49.3	38.2	A	H	180	X	LOW	32.4	5.1	32.8	0.0	0.0	42.9	-11.1	54.0	
3613.2000	48.8	39.3	A	H	180	Y	LOW	32.4	5.1	32.8	0.0	0.0	44.0	-10.0	54.0	
3613.2000	42.6		A	H	180	Z	LOW	32.4	5.1	32.8	0.0	0.0	47.3	-6.7	54.0	
3613.2000	49.5	39.0	A	V	180	X	LOW	32.4	5.1	32.8	0.0	0.0	43.7	-10.3	54.0	
3613.2000	44.4	36.7	A	V	180	Y	LOW	32.4	5.1	32.8	0.0	0.0	41.4	-12.6	54.0	
3613.2000	44.1	40.4	A	V	180	Z	LOW	32.4	5.1	32.8	0.0	0.0	45.1	-8.9	54.0	
3637.5200	47.5	37.8	A	H	180	X	MED.	32.5	5.1	32.8	0.0	0.0	42.6	-11.4	54.0	
3637.5200	47.1	38.2	A	H	180	Y	MED.	32.5	5.1	32.8	0.0	0.0	43.0	-11.0	54.0	
3637.5200	50.9	43.0	A	H	180	Z	MED.	32.5	5.1	32.8	0.0	0.0	47.8	-6.2	54.0	
3637.5200	48.9	37.9	A	V	180	X	MED.	32.5	5.1	32.8	0.0	0.0	42.7	-11.3	54.0	
3637.5200	50.6	43.4	A	V	180	Y	MED.	32.5	5.1	32.8	0.0	0.0	48.2	-5.8	54.0	
3637.5200	49.9	38.2	A	V	180	Z	MED.	32.5	5.1	32.8	0.0	0.0	43.0	-11.0	54.0	
3685.2000	49.5	38.5	A	H	180	X	HIGH	32.5	5.1	32.7	0.0	0.0	43.5	-10.5	54.0	
3685.2000	44.0	39.1	A	H	180	Y	HIGH	32.5	5.1	32.7	0.0	0.0	44.1	-9.9	54.0	
3685.2000	45.0	40.4	A	H	180	Z	HIGH	32.5	5.1	32.7	0.0	0.0	45.3	-8.7	54.0	
3685.2000	50.0	38.9	A	V	180	X	HIGH	32.5	5.1	32.7	0.0	0.0	43.8	-10.2	54.0	
3685.2000	50.0	39.4	A	V	180	Y	HIGH	32.5	5.1	32.7	0.0	0.0	44.4	-9.6	54.0	
3685.2000	49.7	40.6	A	V	180	Z	HIGH	32.5	5.1	32.7	0.0	0.0	45.5	-8.5	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN

** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	KAR-TECH, INC.	DATE	12/2/02
EUT	VERSA REMOTE TRANSMITTER MODULE	DUTY CYCLE	N/A %
MODEL	VRTXM	PEAK TO AVG	N/A dB
S/N	N/A	TEST DIST.	3 Meters
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	Distance Factor (dB)	Mixer Factor (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
4516.5000	49.2	39.0 A	H	1.0	270	X	LOW	34.1	6.2	32.0	0.0	0.0	47.2	-6.8	54.0	
4516.5000	48.7	38.6 A	H	1.0	270	Y	LOW	34.1	6.2	32.0	0.0	0.0	46.9	-7.1	54.0	
4516.5000	44.5	39.6 A	H	1.0	180	Z	LOW	34.1	6.2	32.0	0.0	0.0	47.9	-6.1	54.0	
4516.5000	44.5	40.0 A	V	1.0	180	X	LOW	34.1	6.2	32.0	0.0	0.0	48.3	-5.7	54.0	
4516.5000	43.9	37.1 A	V	1.0	180	Y	LOW	34.1	6.2	32.0	0.0	0.0	45.4	-8.6	54.0	
4516.5000	44.3	38.4 A	V	1.0	180	Z	LOW	34.1	6.2	32.0	0.0	0.0	46.7	-7.3	54.0	
4546.9000	46.4	38.6 A	H	1.0	180	X	MED.	34.2	6.1	32.0	0.0	0.0	46.9	-7.1	54.0	
4546.9000	48.9	39.5 A	H	1.0	180	Y	MED.	34.2	6.1	32.0	0.0	0.0	47.7	-6.3	54.0	
4546.9000	46.9	38.6 A	H	1.0	180	Z	MED.	34.2	6.1	32.0	0.0	0.0	46.9	-7.1	54.0	
4546.9000	50.5	39.8 A	V	1.0	180	X	MED.	34.2	6.1	32.0	0.0	0.0	48.0	-6.0	54.0	
4546.9000	50.3	38.9 A	V	1.0	180	Y	MED.	34.2	6.1	32.0	0.0	0.0	47.2	-6.8	54.0	
4546.9000	49.6	39.6 A	V	1.0	180	Z	MED.	34.2	6.1	32.0	0.0	0.0	47.8	-6.2	54.0	
4606.5000	50.1	39.1 A	H	1.0	180	X	HIGH	34.4	5.9	32.1	0.0	0.0	47.3	-6.7	54.0	
4606.5000	43.9	37.9 A	H	1.0	180	Y	HIGH	34.4	5.9	32.1	0.0	0.0	46.1	-7.9	54.0	
4606.5000	50.7	41.7 A	H	1.0	270	Z	HIGH	34.4	5.9	32.1	0.0	0.0	49.8	-4.2	54.0	
4606.5000	49.3	38.7 A	V	1.0	180	X	HIGH	34.4	5.9	32.1	0.0	0.0	46.9	-7.1	54.0	
4606.5000	49.2	38.5 A	V	1.0	180	Y	HIGH	34.4	5.9	32.1	0.0	0.0	46.6	-7.4	54.0	
4606.5000	50.1	38.8 A	V	1.0	180	Z	HIGH	34.4	5.9	32.1	0.0	0.0	47.0	-7.0	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN

** DELTA = SPEC LIMIT - CORRECTED READING

No Harmonics Found after the 5th Harmonic


PAGE 5 of PAGE 5

Page: 1 of 1

Test location: Compatible Electronics
Customer : KAR-TECH, INC. Date : 12/ 2/2002
Manufacturer : KAR-TECH, INC. Time : 16.53
EUT name : VERSA REMOTE TRANSMITTER MODULE Model: VRTXM
Specification: Fcc_B Test distance: 3.0 mtrs Lab: D
Distance correction factor(20*log(test/spec)) : 0.00
Test Mode :
SPURIOUS EMISSIONS 10 kHz to 9300 MHz
VERTICAL and HORIZONTAL POLARIZATIONS
TEMPERATURE 69 DEGREES F., RELATIVE HUMIDITY 42%
TESTED BY: KYLE FUJIMOTO

NO SPURIOUS EMISSIONS FOUND BETWEEN 10 kHz AND 9300 MHz IN EITHER POLARIZATION
FOR THE EUT





hp

BAND EDGE OF LOW CHANNEL
REF 117.0 dB μ V ATTEN 20 dB

MKR 902.000 MHz
53.90 dB μ V

10 dB/

DL
104.7
dB μ V

MARKER
902.000 MHz
53.90 dB μ V

CORR'D


CENTER 902.37 MHz

RES BW 1 MHz

VBW 1 MHz

SPAN 5.00 MHz

SWP 20.0 msec




hp

BAND EDGE OF HIGH CHANNEL
REF 117.0 dBμV ATTN 20 dB

MKR 928.00 MHz
43.30 dBμV

10 dB/

DL
102.0
dBμV



CENTER 924.0 MHz

RES BW 1 MHz

VBW 1 MHz

SPAN 10.0 MHz
SWP 20.0 msec