

TEST REPORT



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-02783
Page (1) / (28) Pages

1. Client

- Name : Samsung SDS Co., Ltd.
- Address : (Sincheon-Dong) 125, Olympic-Ro, 35-Gil, Songpa-Gu Seoul,
Republic of Korea
- Date of Receipt : 2019-06-14

2. Manufacturer

- Name : Seongji Industrial Co., Ltd.
- Address : 54-33, Dongtanhana 1-gil, Hwaseong-si, Gyeonggi-do, Korea

3. Use of Report : For FCC Certification

4. Test Sample / Model : Digital door lock / 365plusZ3



5. Date of Test : 2019-07-19 to 2019-07-22

6. Test Standard(method) used : FCC 47 CFR part 15 subpart C 15.247

7. Testing Environment : Temp.: (23 ± 1) °C, Humidity: (51 ± 3) % R.H.

8. Test Results : Compliance

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Tested by Bong-seok Kim : (Signature) 	Technical Manager Young-taek Lee : (Signature) 
-------------	--	---

2019-07-22

Republic of KOREA **CTK Co., Ltd.**



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-02783
Page (2) / (28) Pages

REPORT REVISION HISTORY

Date	Revision	Page No
2019-07-22	Issued (CTK-2019-02783)	all

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-02783
Page (3) / (28) Pages

CONTENTS

1. General Product Description	4
1.1 Client Information	4
1.2 Product Information.....	4
1.3 Peripheral Devices	4
2. Facility and Accreditations.....	5
2.1 Test Facility.....	5
2.2 Laboratory Accreditations and Listings	5
2.3 Calibration Details of Equipment Used for Measurement	5
3. Test Specifications	6
3.1 Standards.....	6
3.2 Mode of operation during the test	6
3.3 Maximum Measurement Uncertainty	7
4. Technical Characteristic Test.....	8
4.1 6dB Bandwidth.....	8
4.2 Maximum peak Conducted Output Power	11
4.3 Power Spectral Density	13
4.4 Band Edge & Conducted Spurious emission.....	15
4.5 Radiated Emission	19
APPENDIX A – Test Equipment Used For Tests	27
APPENDIX B – EUT Photographs	28



CTK Co., Ltd.
 (Ho-dong), 113, Yejik-ro, Cheoin-gu,
 Yongin-si, Gyeonggi-do, Korea
 Tel: +82-31-339-9970
 Fax: +82-31-624-9501

Report No.:
 CTK-2019-02783
 Page (4) / (28) Pages

1. General Product Description

1.1 Client Information

Company	Samsung SDS Co., Ltd.
Contact Point	(Sincheon-Dong) 125, Olympic-Ro, 35-Gil, Songpa-Gu Seoul, Republic of Korea
Contact Person	Name: Myoung Kue Lee E-mail: myoungkue.lee@samsung.com Tel : +82-02-6155-6392

1.2 Product Information

FCC ID	P4Y365PLUSZ3
Product Description	Digital door lock
Model name	365plusZ3
Derivative model	-
Operating Frequency	Zigbee : 2 405 MHz - 2 480 MHz (DSSS) RFID : 13.3601 MHz
RF Output Power	Zigbee : 9.51 dBm (8.933 mW) RFID : 44.44 dBuV
Antenna Specification	Zigbee -Antenna type : Wire Antenna -Peak Gain : 2.5 dBi RFID -Antenna type : PCB Antenna -Peak Gain : -
Number of channels	Zigbee : 16 RFID : 1
Channel Spacing	Zigbee : 5 MHz RFID : -
Type of Modulation	OQPSK, ASK
Power Source	DC 6.0 V(AA Battery * 4 EA)
RF Power setting in Test SW	Initial value

1.3 Peripheral Devices

- For Conducted Measurement and Radiated Measurement

Device	Manufacturer	Model No.	Serial No.
Note Computer	HP	HP Probook 650 G1	5CG5114K13
AC/DC Adapter	HP	PPP012D-S	677777-003



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-02783
Page (5) / (28) Pages

2. Facility and Accreditations

2.1 Test Facility

The measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yong-in-si, Gyeonggi-do, Korea.

2.2 Laboratory Accreditations and Listings

Country	Agency	Registration Number
USA	FCC	805871
CANADA	ISED	8737A-2
KOREA	NRRA	KR0025

2.3 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.



CTK Co., Ltd.
 (Ho-dong), 113, Yejik-ro, Cheoin-gu,
 Yongin-si, Gyeonggi-do, Korea
 Tel: +82-31-339-9970
 Fax: +82-31-624-9501

Report No.:
 CTK-2019-02783
 Page (6) / (28) Pages

3. Test Specifications

3.1 Standards

Section in RSS	Requirement(s)	Status (Note 1)	Test Condition
15.247(a)	6 dB Bandwidth	C	Conducted
15.247(e)	Transmitter power spectral density	C	
15.247(b)	Maximum peak conducted output power	C	
15.247(d)	Unwanted emission	C	
15.209	Transmitter emission	C	Radiated
15.207	AC Conducted Emission	NA(Note 3)	Line Conducted
<i>Note 1:</i> C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable			
<i>Note 2:</i> The data in this test report are traceable to the national or international standards.			
<i>Note 3:</i> The equipment is operated on battery power only.			
<i>Note 4:</i> The sample was tested according to the following specification: FCC Part 15.247, ANSI C63.10-2013			
<i>Note 5:</i> The tests were performed according to the method of measurements prescribed in KDB No.558074.			

3.2 Mode of operation during the test

The EUT is operated in a manner representative of the typical of the equipments. During at testing, system components were manipulated within the confines of typical usage to maximize each emission. All modulation modes were tests. The results are only attached worst cases.

Test Frequency

F1	F2	F3
2 405 MHz	2 425 MHz	2 445 MHz
F4	F5	F6
2 450 MHz	2 475 MHz	2 480 MHz

Test mode

Modulation	Duty Cycle
OQPSK	0.27 %



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-02783
Page (7) / (28) Pages

3.3 Maximum Measurement Uncertainty

The value of the measurement uncertainty for the measurement of each parameter.
Coverage factor $k = 2$, Confidence levels of 95 %

Description	Uncertainty
Conducted RF Output Power	1.5 dB
Occupied Bandwidth	0.1 MHz
Unwanted Emission(conducted)	3.0 dB
Radiated Emissions ($f \leq 1$ GHz)	4.0 dB
Radiated Emissions ($f > 1$ GHz)	5.0 dB



4. Technical Characteristic Test

4.1 6dB Bandwidth

Test Procedures(ANSI C63.10-2013 6.9.2)

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Procedures(ANSI C63.10-2013 6.9.3)

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

Test Settings :

Center frequency = the highest, middle and the lowest channels

- a) RBW = 100 kHz
- b) VBW $\geq 3 \times$ RBW
- c) Detector = peak
- d) Trace mode = Max hold
- e) Sweep = auto couple
- f) Allow trace to fully stabilize
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Limit :

6 dB Bandwidth > 500 kHz



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-02783
Page (9) / (28) Pages


Test Data :

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Result
F1	2 405	1.65	Complies
F2	2 425	1.69	Complies
F3	2 445	1.68	Complies
F4	2 450	1.67	Complies
F5	2 475	1.65	Complies
F6	2 480	1.67	Complies

See next pages for actual measured spectrum plots.


6 dB Bandwidth

F1 (2 405 MHz)




Date: 19.JUL.2019 18:27:07

F2 (2 425 MHz)




Date: 19.JUL.2019 18:39:17

F3 (2 445 MHz)




Date: 19.JUL.2019 18:30:24

F4 (2 450 MHz)




Date: 19.JUL.2019 18:43:34

F5 (2 475 MHz)



Date: 19.JUL.2019 18:45:57

F6 (2 480 MHz)



Date: 19.JUL.2019 18:35:43

4.2 Maximum peak Conducted Output Power

Test Procedures(ANSI C63.10-2013 11.9.1)

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth:

Test Settings:

Center frequency = the highest, middle and the lowest channels

- a) RBW \geq DTS Bandwidth
- b) VBW \geq 3 x RBW
- c) span \geq 3 x RBW
- d) Sweep time = auto couple
- e) Detector = peak
- f) Trace mode= max hold
- g) Allow trace to fully stabilize
- h) Use peak marker function to determine the peak amplitude level.

Limit :

Maximum Output Power < 1 W (30 dBm)


Test Data :

Channel	Frequency [MHz]	Measurement data [dBm]	Limit [dBm]	Result
F1	2 405	9.45	30	Complies
F2	2 425	9.41	30	Complies
F3	2 445	9.51	30	Complies
F4	2 450	9.45	30	Complies
F5	2 475	9.11	30	Complies
F6	2 480	4.32	30	Complies

See next pages for actual measured spectrum plots.


Output Power

F1 (2 405 MHz)




Date: 19.JUL.2019 18:26:35

F2 (2 425 MHz)




Date: 19.JUL.2019 18:38:46

F3 (2 445 MHz)




Date: 19.JUL.2019 18:29:53

F4 (2 450 MHz)




Date: 19.JUL.2019 18:43:02

F5 (2 475 MHz)



Date: 19.JUL.2019 18:45:26

F6 (2 480 MHz)



Date: 19.JUL.2019 18:35:12



4.3 Power Spectral Density

Test Procedures(ANSI C63.10-2013 11.10.2)

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

Test Settings:

Center frequency = the highest, middle and the lowest channels

- a) RBW : $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- b) VBW $\geq 3 \times \text{RBW}$
- c) span $\geq 1.5 \times \text{DTS bandwidth}$
- d) Sweep time = auto couple
- e) Detector = peak
- f) Trace mode = max hold
- g) Allow trace to fully stabilize
- h) Use the peak marker function to determine the maximum amplitude level within the RBW.

Limit :

Power Spectral Density < 8 dBm @ 3 kHz BW

Test Data :


Test mode

Channel	Frequency [MHz]	Measurement data [dBm]	Limit [dBm]	Result
F1	2 405	-6.24	8	Complies
F2	2 425	-7.13	8	Complies
F3	2 445	-5.73	8	Complies
F4	2 450	-7.13	8	Complies
F5	2 475	-6.30	8	Complies
F6	2 480	-11.51	8	Complies

See next pages for actual measured spectrum plots.


Power Spectral Density

F1 (2 405 MHz)




Date: 19.JUL.2019 18:26:52

F2 (2 425 MHz)




Date: 19.JUL.2019 18:39:03

F3 (2 445 MHz)



Date: 19.JUL.2019 18:30:10

F4 (2 450 MHz)




Date: 19.JUL.2019 18:43:19

F5 (2 475 MHz)



Date: 19.JUL.2019 18:45:42

F6 (2 480 MHz)



Date: 19.JUL.2019 18:35:29



4.4 Band Edge & Conducted Spurious emission

Test Procedures(ANSI C63.10-2013 11.11.3)

The Unwanted emission from the EUT were measured according to the dictates PKPSD measurement procedure in section 11.11 of ANSI C63.10-2013.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Settings:

Center frequency = the highest, middle and the lowest channels

- a) RBW = 100 kHz
- b) VBW $\geq 3 \times$ RBW
- c) Detector = peak
- d) Sweep time = auto couple
- e) Trace mode= max hold
- f) Allow trace to fully stabilize
- g) Use the peak marker function to determine the maximum amplitude level.

Limit :


Emission level < 20 dBc

Test results: Complies


- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest in-band spectral density. Therefore the applying equipment meets the requirement.

See next pages for actual measured spectrum plots.

Band-edge





Date: 19.JUL.2019 18:28:07



Date: 19.JUL.2019 18:36:44

Conducted Spurious emission(Test mode : Transmit)



F1 (2 405 MHz)



Date: 19.JUL.2019 18:27:37

Date: 19.JUL.2019 18:27:51



F2 (2 425 MHz)



Date: 19.JUL.2019 18:39:47

Date: 19.JUL.2019 18:40:01


F3 (2 445 MHz)




Date: 19.JUL.2019 18:30:54

Date: 19.JUL.2019 18:31:06

F4 (2 450 MHz)




Date: 19.JUL.2019 10:44:04




Date: 19.JUL.2019 10:44:10

F5 (2 475 MHz)




Date: 19.JUL.2019 10:46:27




Date: 19.JUL.2019 10:46:41

F6 (2 480 MHz)



Date: 19.JUL.2019 10:36:13



Date: 19.JUL.2019 10:36:20



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-02783
Page (19) / (28) Pages

4.5 Radiated Emission

Test Location

- 10 m SAC (test distance : 10 m, 3 m)
 3 m SAC (test distance : 3 m)

Test Procedures

- 1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency range above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

Instrument Settings

Frequency Range = 9 kHz ~ 25 GHz (2.4 GHz 10th harmonic)

- a) RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz, 9 kHz for $f < 30$ MHz
- b) VBW \geq RBW
- c) Sweep time = auto couple



CTK Co., Ltd.
 (Ho-dong), 113, Yejik-ro, Cheoin-gu,
 Yongin-si, Gyeonggi-do, Korea
 Tel: +82-31-339-9970
 Fax: +82-31-624-9501

Report No.:
 CTK-2019-02783
 Page (20) / (28) Pages

Limit :

Unwanted emissions that do not fall within the restricted frequency bands of Table 1 shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.

Table 1. Restricted Frequency Bands *

MHz	MHz	MHz	MHz	MHz	GHz
0.09-0.11	8.37626-8.38675	73-74.6	399.9-410	2690-2900	10.6-12.7
¹ 0.495-0.505	8.41425-8.41475	74.8-75.2	608-614	3260-3267	13.25-13.4
2.1735-2.1905	12.29-12.293	108-121.94	960-1240	3332-3339	14.47-14.5
4.125-4.128	12.51975-12.52025	123-138	1300-1427	3345.8-3358	15.35-16.2
4.17725-4.17775	12.57675-12.57725	149.9-150.05	1435-1626.5	3600-4400	17.7-21.4
4.20725-4.20775	13.36-13.41	156.52475-156.52525	1645.5-1646.5	4500-5150	22.01-23.12
6.215-6.218	16.42-16.423	156.7-156.9	1660-1710	5350-5460	23.6-24
6.26775-6.26825	16.69475-16.69525	162.0125-167.17	1718.8-1722.2	7250-7750	31.2-31.8
6.31175-6.31225	16.80425-16.80475	167.72-173.2	2200-2300	8025-8500	36.43-36.5
8.291-8.294	25.5-25.67	240-285	2310-2390	9000-9200	² Above 38.6
8.362-8.366	37.5-38.25	322-335.4	2483.5-2500	9300-9500	

* Certain frequency bands listed in Table 6 and in band above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to the devices are set out in the 200- and 300-series of RSSs, such as RSS-210 and RSS-310, which contain the requirements that apply to licence-exempt radio apparatus.



Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in Table 2. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

Table 2. General Field Strength Limits for Licence-Exempt Transmitters


Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m	Deasurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705-30	30	-	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Note :


- 1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- 2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3m (AV) and 74 dBuV/m@3m (PK)
- 3) For measurement above 1GHz, the resolution bandwidth is set to 1 MHz and video bandwidth is set to 1 MHz for peak measurement and 10 Hz for average measurement.(Duty Cycle is > 98%,)
- 4) Duty Cycle is < 98%, VBW setting will need to > 1/T.

Test Setup:


- 1) For field strength of emissions from 9 kHz to 30 MHz



- 2) For field strength of emissions from 30 MHz to 1 GHz



3) For field strength of emissions above 1 GHz






Test Data :
1) 9 kHz to 30 MHz

Test mode : Transmit, F1(Worst case)

The requirements are:
 Complies



Final Result

No.	Frequency [MHz]	(P)	Reading [dB(uV)]	c.f [dB(1/m)]	Result [dB(uV/m)]	Limit [dB(uV/m)]	Margin [dB]	Height [cm]	Angle [deg]
1	0.014	H	27.6	25.0	52.6	124.7	72.1	100.0	0.0

Note :

1. Measuring position : EUT stand-up position(X)
2. Result = Reading + c.f(correction factor) + Duty cycle c.f
3. Correction factor = Antenna factor + Cable loss - Amp Gain
4. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)


2) 30 MHz to 1 GHz

Test mode : Transmit, F1(Worst case)

The requirements are:

Complies

Test Data



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	48.551	V	20.8	-14.8	6.0	40.0	34.0	200.0	321.0
2	191.990	V	30.3	-13.9	16.4	43.5	27.1	101.0	66.0
3	463.832	V	26.1	-3.4	22.7	46.0	23.3	399.0	240.0
4	524.215	V	24.7	-2.0	22.7	46.0	23.3	200.0	1.0
5	970.051	H	23.3	6.8	30.1	54.0	23.9	300.0	0.0
6	993.210	V	23.2	7.5	30.7	54.0	23.3	101.0	278.0

Remark :

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain
4. This data is the Peak(PK) value.




3) 1 GHz to 26.5 GHz

Test mode : Transmit, F4(Worst case)

The requirements are:

Complies

Test Data



Final Result

No.	Frequency [MHz]	(P)	Reading AV [dB (µV)]	Reading PK [dB (µV)]	c.f [dB (1/m)]	Result AV [dB (µV/m)]	Result PK [dB (µV/m)]	Limit AV [dB (µV/m)]	Limit PK [dB (µV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [°]
1	1726.440	H	42.6	-----	-6.3	36.3	-----	54.0	74.0	17.7	-----	226.3	146.2
2	2449.080	H	-----	62.7	-2.4	-----	60.3	54.0	74.0	-----	13.7	99.8	268.5
3	2449.080	V	-----	62.8	-2.4	-----	60.4	54.0	74.0	-----	13.6	359.7	263.6
4	2449.080	V	56.6	-----	-2.4	54.2	-----	54.0	74.0	-0.2	-----	464.2	268.3
5	2449.080	H	56.9	-----	-2.4	54.5	-----	54.0	74.0	-0.5	-----	342.8	292.5
6	4898.440	H	36.8	-----	1.3	38.1	-----	54.0	74.0	15.9	-----	342.8	313.5
7	4898.440	H	-----	46.1	1.3	-----	47.4	54.0	74.0	-----	26.6	356.5	172.5
8	4898.440	V	38.7	-----	1.3	40.0	-----	54.0	74.0	14.0	-----	226.0	223.1
9	4898.440	V	-----	47.7	1.3	-----	49.0	54.0	74.0	-----	25.0	234.7	269.1

Remarks

- The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
- No.2 and No.3, No.4, No.5 are the carrier Frequencies.



CTK Co., Ltd.
 (Ho-dong), 113, Yejik-ro, Cheoin-gu,
 Yongin-si, Gyeonggi-do, Korea
 Tel: +82-31-339-9970
 Fax: +82-31-624-9501

Report No.:
 CTK-2019-02783
 Page (27) / (28) Pages

APPENDIX A – Test Equipment Used For Tests

No.	Name of Equipment	Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date
1	Signal Analyzer	R&S	FSV30	100925	2019-01-21	2020-01-21
2	EMI Test Receiver	Rohde & Schwarz	ESCI7	100814	2018-10-25	2019-10-25
3	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-126	2019-01-17	2021-01-17
4	Bilog Antenna	Schaffner	CBL6111C	2551	2019-04-17	2021-04-17
5	AMPLIFIER	SONOMA	310	291721	2019-01-28	2020-01-28
6	6dB Attenuator	R&S	DNF	272.4110.50-2	2018-10-25	2019-10-25
7	EMI Test Receiver	Rohde & Schwarz	ESU40	100336	2019-01-29	2020-01-29
8	Horn Antenna	ETS-Lindgren	3117	00154525	2019-02-22	2021-02-22
9	Preamplifier	Agilent	8449B	3008A02011	2018-12-03	2019-12-03
10	Band Reject Filter	Micro Tronics	G233	BRM50702	2019-01-28	2020-01-28

No.	Name of Equipment	Manufacturer	Model No.	Serial No.	Check Date
1	RF Cable (conducted)	Junkosha Inc.	MWX221	1510S087	2019-02-02
2	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 104	MY27558/4	2019-02-02
3	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 104	N/A (below 1GHz)	2019-02-02
4	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 104	MY27573/4	2018-11-30
5	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 106	N/A (above 1GHz)	2018-11-30

APPENDIX B – EUT Photographs

