

Maximum Permissible Exposure Evaluation

Test Report No : CSTS-A13-FCC0048-1

Equipment Name : OCU (On-board Controller Unit)
Model No. : SAM-OCU-14
Applicant : SAMSUNG SDS Co., Ltd.
Address : 707-19, Yoksam 2-dong, Gangnam-gu, Seoul, Korea,
135-918

This report applies only to the product named in the title of this report manufactured at the location indicated. Test results apply only to the particular equipment and functionality described in this test report.

Prepared by :



S.J. Yang / RF Engineer

Date of Issue : December 12, 2013

Reviewed by :



Ik Seon, Jeong / Principle Engineer

Date of Issue : December 12, 2013

CERTIFICATION SERVICE TECHNOLOGY INC.

181, Manhaero, Danwan-gu, Ansan-city, Kyeonggi-do, 425-839, Korea
Tel: +82 31 493 2001 Fax: +82 31 493 2055

1. General Description of EUT

Item	Specification	note
Dimension	230mm x 176.2 mm x 46.9 mm	
RF spec	Frequency Range	2412 MHz ~ 2472 MHz (802.11 b, g, n(HT20)), 2422 MHz ~ 2462 MHz (802.11 n(HT40))
	Channel	13 (802.11 b, g, n(HT20)), 9 (802.11 n(HT40))
	Modulation Type	DSSS(802.11b), OFDM (802.11g, n(HT20), n(HT40))
	Power	0.02897 W (802.11b) 0.02773 W (802.11g) 0.02387 W (802.11n(HT20)) 0.00939 W (802.11n(HT40)) * It is maximum peak conducted power in band
	Antenna Gain	2.5 dBi
Power Source	DC 24V	

NOTE:

1. This report is issued as a supplementary report of the original report.
2. The EUT, operates in the 2.4GHz frequency range, lets you connect WiFi devices to the network.
3. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

2. General Information of Test

Certification Service Technology Inc. (CSTech)	
Test Site Location	1055, Singil-dong ,Danwon-gu ,Ansan-si, Gyeonggi-do, Korea 425-839 TEL : +82-31-493-2001 FAX : +82-31-493-2055

3. RF Exposure Measurement

3.1 Introduction & Standard

RF Exposure Requirements	: 47 CFR §1.1307(b)
RF Radiation Exposure Limits	: 47 CFR §1.1310
RF Radiation Exposure Guidelines	: FCC OST/OET Bulletin Number 65
EUT Frequency Band	: 2412 MHz ~ 2472 MHz (WiFi)
Limits for General Population/Uncontrolled Exposure in the band of	: 1500 MHz ~ 100000 MHz
Power Density Limit	: 1 mW/cm ²

3.2 Compliance criteria

Evaluating for Power flux density

Equations are accurate in the far-field if antenna but will over-predict in the near field.

Under above describe specification of EUT and Antenna, Equivalent plane wave power density is calculated as below underlined quotation formula ;

$$S = PG/4\pi R^2$$

S = power density (mW/cm²)

P = output power (mW)

G = antenna gain relative to isotropic (convert to numeric gain)

R = distance from transmitting antenna (cm)

or

$$S = (PG)/(4 \pi d^2)$$

S = power density (W/m²)

P = output power (W)

G = antenna gain relative to isotropic (convert to numeric gain)

R = distance from transmitting antenna (m)

3.2.1 Accordingly as a result of calculated value

- P(W) = 28.97 mW
- G(dBi) = 2.5 dBi (Conversion 2.5 dBi to Linearity value is 1.778)
- r(m) = setting a distance (20cm) from the antenna to calibrated tuned receiving antenna in far field

$$S_{eq}(\text{mW}/\text{cm}^2) : (28.97 \times 1.778)/(4 \times 3.14 \times 20^2) = \underline{\underline{0.0102525 \text{ mW}/\text{cm}^2}}$$

So, above calculated 0.0102525 mW/cm² is comply with the value required standard