

FCC Test Report

Test report no.: EMC_624FCC22-24_2004_GSM

FCC Part 22,24 / RSS 133 Model: MBS1000-2

FCC ID: P5IMBS2A IC ID: 1478A-MBS2A



Accredited according to ISO/IEC 17025



Bluetooth Qualification Test Facility (BQTF)



FCC listed # 101450

IC recognized # 3925

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecomusa.com • http://www.cetecom.com CETECOM Inc. is a Delaware Corporation with Corporation number: 2113686

Board of Directors: Dr. Harald Ansorge, Dr. Klaus Matkey, Hans Peter May



Table of Contents

1	C 1	· C	- 4
1	General	Intorm	amon

- 1.1 Notes
- 1.2 Testing laboratory
- 1.3 Details of applicant
- 1.4 Application details
- 1.5 Test item
- 1.6 Test standards
- 2 Technical test
- 2.1 Summary of test results
- 2.2 Test report
- 1 General information
- 1.1 Notes

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM Inc. does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM Inc.

TEST REPORT PREPARED BY: EMC Engineer: Harpreet Sidhu

1.2 Testing laboratory

CETECOM Inc.

411 Dixon Landing Road, Milpitas, CA-95035, USA Phone: +1 408 586 6200 Fax: +1 408 586 6299

E-mail: lothar.schmidt@cetecomusa.com

Internet: www.cetecom.com



1.3 Details of applicant

Name : Wireless Matrix Corporation
Street : 12369-B Sunrise Valley Drive

City / Zip Code : Reston, VA 20164

Country : USA

Contact:Darryl StruckoTelephone:703 262 4021Tele-fax:703 262 3085

e-mail : darryl.strucko@wrx-us.com

1.4 Application details

Date of receipt test item : 2004-03-01

Date of test : 2004-03-01/02/03

1.5 Test item

Manufacturer : Applicant

Marketing Name : Mobile Base Station 2

Model No. : MBS1000-2

Description : Mobile base station with GSM 850/1900, WLAN 802.11b &

Satellite Transmitters.

FCC-ID : P5IMBS2A IC-ID : 1478A-MBS2A

Additional information

Frequency : 824.2MHz – 848.8MHz for GSM 850,

1850.2MHz – 1909.8MHz for PCS 1900

Type of modulation : GMSK

Number of channels : 124 for GSM-850, 299 for PCS-1900

Antenna : Monopole for GSM

Power supply : 13.6VDC Nominal voltage

Output power : 27.2dBm (524.8mW) max. ERP measured in GSM-850

32.79dBm (1.9W) max. EIRP measured in PCS-1900

Extreme temp. Tolerance : Lower: -20°C Upper: +60°C

1.6 Test standards

FCC Part 22,24 / RSS133 r1

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

The EUT (Mobile Base Station 2) carries pre-certified Motorola GSM module model# DB1 with FCC ID: IHDT56DB1 & IC ID: 109O-DB1

This test report covers full radiated testing as per FCC 22/24 on EUT with GSM module. All conducted measurements are covered under *test report# 10361-1*.



Test report no.: EMC_624FCC22-24_2004_GSM	Issue date: 2004-03-12	Page 4 (55)
---	------------------------	-------------

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests Performed		
Final Verdict: (only "passed" if all single measurements are "passed")	Passed	

Technical responsibility for area of testing:

2004-03-12	EMC & Radio	Lothar Schmidt (Technical Manager)	lduni de
Date	Section	Name	Signature

Responsible for test report and project leader:

2004-03-12	EMC & Radio	Harpreet Sidhu (EMC Engineer)	\
Date	Section	Name	Signature



2.2 Test report

TEST REPORT

Test report no.: EMC_624FCC22-24_2004_GSM Model: MBS1000-2



TEST REPORT REFERENCE

PARAMETER TO BE MEASURED	PARAGRAPH	PAGE
POWER OUTPUT	§22.913(a) / § 24.232 (b)	7
EMISSION LIMITS TRANSMITTER	§2.1051 / §24.238	16
RECEIVER RADIATED EMISSIONS	§2.1053 / RSS-133	48
CONDUCTED EMISSIONS	§15.107/207	53
TEST EQUIPMENT AND ANCILLARII	ES USED FOR TESTS	54
BLOCK DIAGRAMS		55



POWER OUTPUT

§ 22.913(a) / § 24.232 (b)

Summary:

During the process of testing, the EUT was controlled via Rhode & Schwarz Universal Radio Communication tester (CMU 200) to ensure max. Power transmission and proper modulation.

This paragraph contains average output power, peak output power, EIRP & ERP measurements for the EUT. In all cases, the peak output power is within the specified limits.

Method of Measurements:

The EUT was set up for the max. Output power with pseudo random data modulation.

The power was measured with R&S Spectrum Analyzer ESIB 40 (peak)

These measurements were done at 3 frequencies,

824.2 MHz, 836.6 MHz and 848.8 MHz (bottom, middle and top of operational frequency range) for GSM-850 1850.2 MHz, 1880.0 MHz and 1909.8 MHz (bottom, middle and top of operational frequency range) for PCS-1900



ERP (GSM-850) §22.913(a)

Limits:

Power Control Level	Burst Peak ERP
5	≤38.45dBm (7W)


EIRP

Frequency	Power Control Level	Burst Peak	
(MHz)		(dBm)	
		EIRP ERP	
824.2	5	28.38	26.24
836.6	5	29.34	27.2
848.8	5	29.18	27.04
Measurement uncertainty	±0.5 dB		

ANALYZER SETTINGS: RBW = VBW = 3MHz




EIRP (GSM-850) CHANNEL 128 §22.913(a)






EIRP (GSM-850) CHANNEL 190 §22.913(a)





EIRP (GSM-850) CHANNEL 251 §22.913(a)





EIRP (PCS-1900) §24.232(b)

Limits:

Power Control Level	Burst Peak EIRP
0	≤33dBm (1W)


EIRP

Frequency	Power Control Level	Burst Peak	
(MHz)		(dBm)	
		EIRP	
1850.2	0	32.41	
1880.0	0	32.79	
1909.8	0	32.57	
Measurement uncertainty	±0.5 dB		

ANALYZER SETTINGS: RBW = VBW = 3MHz




EIRP (PCS-1900) CHANNEL 512 §24.232(b)






EIRP (PCS-1900) CHANNEL 661 §24.232(b)





EIRP (PCS-1900) CHANNEL 810 §24.232(b)





EMISSION LIMITS TRANSMITTER

§2.1051 / §24.238

Measurement Procedure:

The following steps outline the procedure used to measure the radiated emissions from the EUT. The site is constructed in accordance with ANSI C63.4 – 1992 requirements and is recognised by the FCC. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 848.8MHz for GSM-850 & 1910 MHz for PCS-1900 The resolution bandwidth is set as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the GSM-850 & PCS-1900 bands.

The final Radiated emission test procedure is as follows:

- a) The test item was placed on a 0. 8 meter high non-conductive stand at a 3 meter test distance from the receive antenna
- b) The antenna output was terminated in a 50-ohm load.
- c) A double-ridged wave guide antenna was placed on an adjustable height antenna mast 3 meters from the test item for emission measurements.
- d) Detected emissions were maximized at each frequency by rotating the test item and adjusting the receive antenna height and polarization. The maximum meter reading was recorded. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth. If the harmonic could not be detected above the noise floor, the ambient level was recorded. The equivalent power into a dipole antenna was determined by the substitution method described for ERP measurements.

Measurement Limit:

Sec. 24.238 Emission Limits.

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Measurement Results:

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the GSM-850 & PCS-1900 bands. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the GSM-850 & PCS-1900 band into any of the other blocks respectively. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.



RESULTS OF RADIATED TESTS GSM-850:

Harmonics	Tx ch-128 Freq. (MHz)	Level (dBm)	Tx ch-190 Freq. (MHz)	Level (dBm)	Tx ch-251 Freq. (MHz)	Level (dBm)
2	1648.4	-31.26	1673.2	-32	1697.6	-34.46
3	2472.6	-32.90	2509.8	-36.87	2546.4	-36.86
4	3296.8	nf	3346.4	nf	3395.2	nf
5	4121	nf	4183	nf	4244	nf
6	4945.2	nf	5019.6	nf	5092.8	nf
7	5769.4	nf	5856.2	nf	5941.6	nf
8	6593.6	nf	6692.8	nf	6790.4	nf
9	7417.8	nf	7529.4	nf	7639.2	nf
10	8242	nf	8366	nf	8488	nf



RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ 824.2MHz: 30MHz - 1GHz

Spurious emission limit -13dBm

Antenna: vertical

SWEEP TABLE: "FCC 22 Spur 30M-1G"

Start Stop Detector Meas. RBW/VBW


Frequency Frequency Time

30MHz 1GHz Max Peak Coupled 1 MHz

Note:

1. The peak above the limit line is the carrier freq.

2. This plot is valid for low, mid & high channels (worst-case plot)





RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ 824.2MHz: 30MHz - 1GHz

Spurious emission limit -13dBm

Antenna: horizontal

SWEEP TABLE: "FCC 22 Spur 30M-1G"

Start Stop Detector Meas. RBW/VBW


Frequency Frequency Time

30MHz 1GHz Max Peak Coupled 1 MHz

Note:

1. The peak above the limit line is the carrier freq.

2. This plot is valid for low, mid & high channels (worst-case plot)





RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ Error! Reference source not found.MHz: 1GHz - 1.58GHz


Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1-1.58G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1GHz 1.58GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ Error! Reference source not found.MHz: 1.58GHz – 3GHz


Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1.58-3G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1.58GHz 3GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (GSM-850)

 $Tx @ \mbox{Error!}$ Reference source not found. MHz: 3GHz - 9GHz


Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 3-9G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

3GHz 9GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ Error! Reference source not found.MHz: 1GHz - 1.58GHz


Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1-1.58G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1GHz 1.58GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ Error! Reference source not found.MHz: 1.58GHz – 3GHz


Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1.58-3G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1.58GHz 3GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ Error! Reference source not found.MHz: 3GHz – 9GHz


Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 3-9G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

3GHz 9GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ Error! Reference source not found.MHz: 1GHz - 1.58GHz


Spurious emission limit -13dBm

SWEEP TABLE: "FCC 22 Spur 1-1.58G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1GHz 1.58GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ Error! Reference source not found.MHz: 1.58GHz – 3GHz


Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1.58-3G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1.58GHz 3GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ Error! Reference source not found.MHz: 3GHz - 9GHz


Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 3-9G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

3GHz 9GHz Max Peak Coupled 1 MHz





RESULTS OF RADIATED TESTS PCS-1900:

Harmonic	Tx ch-512 Freq.(MHz)	Level (dBm)	Tx ch-661 Freq. (MHz)	Level (dBm)	Tx ch-810 Freq. (MHz)	Level (dBm)
2	3700.4	-47.07	3760	-54.41	3819.6	-54.78
3	5550.6	-49.52	5640	-45.22	5729.4	-39.04
4	7400.8	-44.69	7520	nf	7639.2	nf
5	9251	nf	9400	nf	9549	nf
6	11101.2	nf	11280	nf	11458.8	nf
7	12951.4	nf	13160	nf	13368.6	nf
8	14801.6	nf	15040	nf	15278.4	nf
9	16651.8	nf	16920	nf	17188.2	nf
10	18502	nf	18800	nf	19098	nf



RADIATED SPURIOUS EMISSIONS

Tx @ Error! Reference source not found.MHz: 30MHz - 1GHz

Spurious emission limit –13dBm

Antenna: vertical


SWEEP TABLE: "FCC 24 Spur 30M-1G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

30MHz 1GHz Max Peak Coupled 1 MHz

Note: This plot is valid for low, mid & high channels (worst-case plot)





RADIATED SPURIOUS EMISSIONS

Tx @ Error! Reference source not found.MHz: 30MHz - 1GHz

Spurious emission limit –13dBm

Antenna: horizontal


SWEEP TABLE: "FCC 24 Spur 30M-1G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

30MHz 1GHz Max Peak Coupled 1 MHz

Note: This plot is valid for low, mid & high channels (worst-case plot)





RADIATED SPURIOUS EMISSIONS

Tx @ Error! Reference source not found.MHz: 1GHz – 3GHz

Spurious emission limit -13dBm


SWEEP TABLE: "FCC Spuri 1-3G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1GHz 3GHz Max Peak Coupled 1 MHz

Note: The peak above the limit line is the carrier freq. at ch-512.





RADIATED SPURIOUS EMISSIONS

Tx @ Error! Reference source not found.MHz: 3GHz – 18GHz


Spurious emission limit -13dBm

SWEEP TABLE: "FCC Spuri 3-18G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

3GHz 18GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS

Tx @ Error! Reference source not found.MHz: 1GHz – 3GHz Spurious emission limit –13dBm


SWEEP TABLE: "FCC Spuri 1-3G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1GHz 3GHz Max Peak Coupled 1 MHz

Note: The peak above the limit line is the carrier freq. at ch-661.





RADIATED SPURIOUS EMISSIONS

Tx @ Error! Reference source not found.MHz: 3GHz - 18GHz


Spurious emission limit -13dBm

SWEEP TABLE: "FCC Spuri 3-18G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

3GHz 18GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS

Tx @ Error! Reference source not found.MHz: 1GHz – 3GHz Spurious emission limit –13dBm


SWEEP TABLE: "FCC Spuri 1-3G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1GHz 3GHz Max Peak Coupled 1 MHz

Note: The peak above the limit line is the carrier freq. at ch-810.





RADIATED SPURIOUS EMISSIONS

Tx @ Error! Reference source not found.MHz: 3GHz - 18GHz


Spurious emission limit –13dBm

SWEEP TABLE: "FCC Spuri 3-18G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

3GHz 18GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS

18GHz – 19.1GHz

Spurious emission limit -13dBm


SWEEP TABLE: "FCC 24 spuri 18-19.1G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

18GHz 19.1GHz Max Peak Coupled 1 MHz

Note: This plot is valid for low, mid & high channels (worst-case plot)





RADIATED SPURIOUS EMISSIONS (IDLE MODE – GSM 850)

EUT in Idle Mode: 30MHz – 1GHz

Spurious emission limit -13dBm


Note: This plot is valid for both polarities (worst-case plot)

SWEEP TABLE: "FCC 22 Spur 30M-1G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

30MHz 1GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (IDLE MODE – GSM 850)

EUT in Idle Mode: 1GHz – 1.58GHz


Spurious emission limit -13dBm

SWEEP TABLE: "FCC Spuri 1-1.58G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1GHz 1.58GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (IDLE MODE – GSM 850)

EUT in Idle Mode: 1.58GHz – 3GHz


Spurious emission limit -13dBm

SWEEP TABLE: "FCC 24 spuri 1.58-3G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1.58GHz 3GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (IDLE MODE – GSM 850)

EUT in Idle Mode: 3GHz – 9GHz


Spurious emission limit -13dBm

SWEEP TABLE: "FCC 24 spuri 3-9G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

3GHz 9GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (IDLE MODE – GSM 1900)

Antenna: vertical

EUT in Idle Mode: 30MHz – 1GHz


Spurious emission limit -13dBm

SWEEP TABLE: "FCC 24 Spur 30M-1G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

30MHz 1GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (IDLE MODE – GSM 1900)

Antenna: horizontal

EUT in Idle Mode: 30MHz – 1GHz


Spurious emission limit -13dBm

SWEEP TABLE: "FCC 24 Spur 30M-1G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

30MHz 1GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (IDLE MODE – GSM 1900)

EUT in Idle Mode: 1GHz – 3GHz


Spurious emission limit -13dBm

SWEEP TABLE: "FCC Spuri 1-3G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1GHz 3GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (IDLE MODE – GSM 1900)

EUT in Idle Mode: 3GHz – 18GHz


Spurious emission limit -13dBm

SWEEP TABLE: "FCC 24 spuri 3-18G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

3GHz 18GHz Max Peak Coupled 1 MHz





RADIATED SPURIOUS EMISSIONS (IDLE MODE – GSM 1900)

EUT in Idle Mode: 18GHz – 19.1GHz


Spurious emission limit –13dBm

SWEEP TABLE: "FCC 24 spuri 18-19.1G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

18GHz 19.1GHz Max Peak Coupled 1 MHz





RECEIVER RADIATED EMISSIONS

§ 2.1053 / RSS-133

NOTE:

1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 3GHz and 26.5GHz very short cable connections to the antenna was used to minimize the noise level.

2. Receiver radiated emissions were done on both 850/1900 bands, but only worst-case plots are submitted in the test reports.

Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (μV/m)	Measurement distance (m)	
0.009 - 0.490	2400/F (kHz)	300	
0.490 - 1.705	24000/F (kHz)	30	
1.705 - 30.0	30	30	
30 - 88	100	3	
88 - 216	150	3	
216 - 960	200	3	
Above 960	500	3	



RECEIVER RADIATED EMISSIONS EUT in Idle Mode: 30MHz – 1GHz

Antenna: vertical


SWEEP TABLE: "FCC 24 Spur 30M-1G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

30MHz 1GHz Max Peak Coupled 100KHz

Note: This plot is valid for both polarities (worst-case plot)





RECEIVER RADIATED EMISSIONS EUT in Idle Mode: 1GHz – 3GHz


Note: marked peak is downlink from the base station

SWEEP TABLE: "FCC Spuri 1-3G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

1GHz 3GHz Max Peak Coupled 1 MHz





RECEIVER RADIATED EMISSIONS EUT in Idle Mode: 3GHz – 18GHz


SWEEP TABLE: "FCC 24 spuri 3-18G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

3GHz 18GHz Max Peak Coupled 1 MHz

Detector: Mode:






RECEIVER RADIATED EMISSIONS EUT in Idle Mode: 18GHz – 26.5GHz

SWEEP TABLE: "FCC 24 spuri 18-26.5G"

Start Stop Detector Meas. RBW/VBW

Frequency Frequency Time

18GHz 26.5GHz Max Peak Coupled 1 MHz





CONDUCTED EMISSIONS

This test is not applicable for the EUT

§ 15.107/207



TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	ESIB 40	Rohde & Schwarz	100107
02	Spectrum Analyzer	FSEM 30	Rohde & Schwarz	826880/010
03	Signal Generator	SMY02	Rohde & Schwarz	836878/011
04	Power-Meter	NRVD	Rohde & Schwarz	0857.8008.02
05	Biconilog Antenna	3141	EMCO	0005-1186
06	Horn Antenna (1-18GHz)	SAS-200/571	AH Systems	325
07	Horn Antenna (18-26.5GHz)	3160-09	EMCO	1240
08	Power Splitter	11667B	Hewlett Packard	645348
09	Climatic Chamber	VT4004	Voltsch	G1115
10	High Pass Filter	5HC2700	Trilithic Inc.	9926013
11	High Pass Filter	4HC1600	Trilithic Inc.	9922307
12	Pre-Amplifier	JS4-00102600	Miteq	00616
13	Power Sensor	URV5-Z2	Rohde & Schwarz	DE30807
14	Digital Radio Comm. Tester	CMD-55	Rohde & Schwarz	847958/008
15	Universal Radio Comm. Tester	CMU 200	Rohde & Schwarz	832221/06



BLOCK DIAGRAMS Radiated Testing

ANECHOIC CHAMBER

