

JOB NO.
465

ERICSSON
G30a

CE 0889
UL US
L1000
T.T.E
E229282

INPUT: 7.5V = 0.8A
TYPE: FWTG32 * * A *
FCC ID: P5L-FWTG32
IC: 2871-FWTG32
KRC 161 080/0 P3A

S/N: TU 8A305538

IMEI: 353211-00-117308-8

MADE IN Poland

Calibration Parameter	850	1900	Date
Frequency Calibration	✓	✓	2/27/12
RX Calibration	✓	✓	
RX Coarse	✓	✓	
RX Fine	✓	✓	
RX Linearity	✓	✓	
GMSK			
Burst Shape (All PCL)	✓	✓	
Peak Power Alignment (All PCL)	✓	✓	
Origin Offset Calibration	✓	✓	
Linearity			
Room Temperature			
+55 Degrees Celsius			
-10 Degrees Celsius			
HighPCL and LowPCL			
8PSK			
Peak Power Alignment (All PCL)			
TXAGC E [0.6, 1.2, 1.8, 2.4, 3.0]			
-12.5 <= BBIA GC <= -1.5			
Origin Offset Calibration for all TXAGC			
Linearity			
Room Temperature			
+55 Degrees Celsius			
-10 Degrees Celsius			
HighPCL and LowPCL			

www.f-global.com





CAUTION: HIGH VOLTAGE
DO NOT TOUCH THE POWER SUPPLY UNIT
OR THE POWER CORDS
CE

JOB NO. 932a
ON BOARD

JOB NO. 932a

JOB NO. 932a







