

## Exposure of humans to RF fields

As per Section 1.1310 mobile transmitters are required to be operated in a manner that ensures the public is not exposed to RF energy levels in accordance with OST/OET Bulletin Number 65.

Calculations have been made using the General Public/Uncontrolled Exposure limits.

Minimum safe distances have been calculated below.

Power density,  $\text{mW/m}^2 = E^2/3770$

- Occupational / Controlled Exposure limit will be  $10 \text{ mW/m}^2$  or  $60 \text{ V/m}$
- General Population / Uncontrolled exposure limit will be  $2 \text{ mW/m}^2$  or  $28 \text{ V/m}$

The minimum distance from the antenna at which the MPE is met is calculated from the equation relating field strength in  $\text{V/m}$ , transmit power in watts, transmit antenna gain, transmitter duty cycle and separation distance in metres:

$$E, \text{V/m} = (\sqrt{30 * P * G * DC}) / d$$

The rated maximum transmitter power = 5 watts.

Transmitter is operated using an antenna with a gain of up to 20 (13dB).

The client has declared a duty cycle of 100%

### Controlled

$$d = \sqrt{30 * P * G * DC} / E$$

$$d = \sqrt{30 * 5 * 20 * 1} / 60$$

$$d = 0.91 \text{ metres or } 91 \text{ cm}$$

### Uncontrolled

$$d = \sqrt{30 * 5 * 20 * 1} / 28$$

$$d = 1.95 \text{ metres or } 195 \text{ cm}$$

**Result:** Complies if the safe distances defined for each environment are applied.