

RF	EXP	OSI	JRE	REP	ORT
					• • • •

REPORT NO.: SA941117L05D MODEL NO.: BT2-USB

ACCORDING: FCC Guidelines for Human Exposure IEEE C95.1

APPLICANT : AmbiCom, Inc

ADDRESS: 405 River Oaks Parkway San Jose, CA 95134 USA

- **ISSUED BY :** Advance Data Technology Corporation
- LAB ADDRESS : No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang 244, Taipei Hsien, Taiwan, R.O.C.
- **TEST LOCATION :** No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

FCC ID: P5T-BT2USB



No Evaluation Required if power is below this threshold:

F(G	Hz)	mW	
Low	2.402	24.58	
High	2.480	24.30	

Maximum measured transmitter power:

Pout (dBm	Pout (mW)	
Conducted Power	3.79	2.393
EIRP Power	4.11	2.576

*Note: The antenna is printed antenna with 0.32dBi gain

Threshold for no SAR evaluation is 24.58mW Transmitter power is 2.576mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold