

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15C_RM-582V_03.doc	Date of Report:	16-Jun-2010
Number of pages:	38	Customer's Contact person:	Swapna Murala
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Customer:	Nokia Corporation P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880
FCC listing no.:	94436		
IC recognition no.:	661AK-1		
Tested devices/ accessories:	Phone RM-582V / Battery BP-4LV / Charger AC-31 / Data cable CA-10V / Headset WH-1V		
FCC ID:	P7QRM-582V	IC:	4299A-RM582V
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards RSS-GEN (Issue 2, June 2007) and RSS-210 (Issue 7, June 2007). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Hannu Söderholm, Senior Engineer, EMC

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	7-Jun-2010
Testing completed	10-Jun-2010
The customer's contact person	Swapna Murala
Test Plan referred to	T:\Projects\RM-582V\TestPlan\RS_testplan_RM-582V_EMC_FCC_SAR.xls
Notes	
Document name	FCC15C_RM-582V_03.doc

1.1. EUT and Accessory Information

The EUT is a 8-band (GSM850/900/1800/1900 and WCDMA Band I/II(1900)/V(850)/VI) mobile phone with GPRS, EGPRS, Bluetooth and WLAN. Bluetooth and WLAN are tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-582V	004401108596764	B3	-	031.711	42281
Phone	RM-582V	004401108596046	B3	-	031.711	42277
Battery	BP-4LV	2010/03/26	-	-	-	42271
Charger	AC-31	091314-11	-	-	-	42274
Data cable	CA-101V	0730642935501300228	-	-	-	42275
Headset	WH-1V	-	0.8	0.9	-	42278

1.2. Summary of Test Results

Bluetooth:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8.4 (2)	Conducted peak output power	PASSED
15.247(d)	A8.5	Band edge compliance of RF emissions	PASSED
15.247(d)	A8.5	Spurious RF conducted emissions	PASSED
15.247(d), 15.209	A8.5	Spurious radiated emissions	PASSED
15.207	7.2.2	AC powerline conducted emissions	PASSED
15.247(a)(1)	A8.1 (a)	20 dB bandwidth	PASSED
15.247(a)(1)	A8.1 (b)	Carrier frequency separation	PASSED
15.247(a)(1)(iii)	A8.1 (d)	Number of hopping frequencies	PASSED
15.247(a)(1)(iii)	A8.1 (d)	Time of occupancy	PASSED

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Nokia Tampere Laboratory.


CONTENTS

1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Test setups.....	5
2.1. Conducted RF test setup	5
2.2. AC powerline conducted emissions test setup.....	5
2.3. Radiated test setup	5
3. Conducted peak output power (FCC §15.247(b)(1), RSS-210 A8.4 (2))	6
3.1. Test method and limit.....	6
3.2. Bluetooth Test results	7
4. Band edge compliance of RF emissions (FCC §15.247(d), RSS-210 A8.5).....	10
4.1. Test method and limit.....	10
4.2. Bluetooth Test results	11
5. Spurious RF conducted emissions (FCC §15.247(d), RSS-A8.5).....	15
5.1. Test method and limit.....	15
5.2. Bluetooth Test results	16
6. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5).....	19
6.1. Test method and limit.....	19
6.2. Bluetooth Test results	20
7. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)	22
7.1. Test method and limit.....	22
7.2. Bluetooth Test results	23
8. 20 dB bandwidth (FCC §15.247(a)(1), RSS-210 A8.1 (a))	24
8.1. Test method and limit.....	24
8.2. Bluetooth Test results	25
9. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1 (b)).....	28
9.1. Test method and limit.....	28
9.2. Bluetooth Test results	29
10. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (d)).....	31
10.1. Test method and limit.....	31
10.2. Bluetooth Test results	32
11. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (d))	34
11.1. Test method and limit.....	34
11.2. Bluetooth test results.....	35


12.	Test Equipment	37
12.1.	Conducted measurements	37
12.2.	Radiated measurements	37

2. Test setups


2.1. Conducted RF test setup



2.2. AC powerline conducted emissions test setup



2.3. Radiated test setup



3. Conducted peak output power (FCC §15.247(b)(1), RSS-210 A8.4 (2))

EUT with DUT number	RM-582V DUT 42277
Accessories with DUT numbers	BP-4LV DUT 42272
Operation Voltage [V] / [Hz]	Nominal
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 50 / 99.3
Date of measurements	08-Jun-2010
Measured by	Jari Jantunen

3.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for conducted peak output power measurements


Frequency range [MHz]	Limit [W]	Limit [dBm]
2400 – 2483.5	≤ 1	≤ 30

3.2. Bluetooth Test results


3.2.1 GFSK modulation, PRBS packet type

Channel / f_c [MHz]	P [dBm]	P [mW]	Result
0 / 2402	0.10	1.023	PASSED
40 / 2442	0.50	1.122	PASSED
78 / 2480	0.50	1.122	PASSED


Channel 0 / 2402 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



Channel 40 / 2442 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)




Channel 78 / 2480 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)




3.2.2 8DPSK modulation, PRBS packet type

Channel / f_c [MHz]	P [dBm]	P [mW]	Result
0 / 2402	1.80	1.514	PASSED
40 / 2442	2.20	1.660	PASSED
78 / 2480	2.10	1.622	PASSED


Channel 0 / 2402 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



Channel 40 / 2442 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



Channel 78 / 2480 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



4. Band edge compliance of RF emissions (FCC §15.247(d), RSS-210 A8.5)

EUT with DUT number	RM-582V DUT42281
Accessories with DUT numbers	BP-4LV DUT42271, AC-31 DUT42274, CA-101V DUT42275, WH-1V DUT42278
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	24 / 47 / 101.5
Date of measurements	10-Jun-2010
Measured by	Hannu Söderholm

4.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.


Limits for band edge compliance of RF emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit Average [dBμV/m]	Limit Peak [dBμV/m]
Below 2390 and above 2483.5	≤ 54	≤ 74

4.2. Bluetooth Test results


4.2.1 GFSK modulation, PRBS packet type

Channel 0 / 2402 MHz




Detector (RBW: 1 MHz)	E [dBμV/m]	Result
Peak	40.00	PASSED
Average	25.90	PASSED

Channel 78 / 2480 MHz




Detector (RBW: 1 MHz)	E [dBμV/m]	Result
Peak	41.10	PASSED
Average	26.70	PASSED

Hopping on, low end



Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	41.90	PASSED
Average	29.30	PASSED


Hopping on, high end



Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	42.90	PASSED
Average	32.60	PASSED


4.2.2 8DPSK modulation, PRBS packet type

Channel 0 / 2402 MHz




Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	39.80	PASSED
Average	26.00	PASSED

Channel 78 / 2480 MHz




Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	41.10	PASSED
Average	26.90	PASSED

Hopping on, low end



Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	42.50	PASSED
Average	29.70	PASSED

Hopping on, high end



Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	43.00	PASSED
Average	33.70	PASSED

5. Spurious RF conducted emissions (FCC §15.247(d), RSS-A8.5)

EUT with DUT number	RM-582V DUT 42277
Accessories with DUT numbers	BP-4LV DUT 42272
Operation Voltage [V] / [Hz]	Nominal
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 50 / 99.3
Date of measurements	08-Jun-2010
Measured by	Jari Jantunen

5.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.


Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	≤ -20

5.2. Bluetooth Test results

5.2.1 GFSK modulation, PRBS packet type


Channel 0 / 2402 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4928.525641	-36.368336	PASSED
7321.153846	-35.168336	PASSED
7500.000000	-36.368336	PASSED


Channel 40 / 2442 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4911.217949	-36.693970	PASSED
7305.288462	-35.893970	PASSED
7500.000000	-36.493970	PASSED

Channel 78 / 2480 MHz




Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4883.653846	-35.677353	PASSED
7332.692308	-36.377353	PASSED
7500.000000	-34.577353	PASSED

5.2.2 8DPSK modulation, PRBS packet type


Channel 0 / 2402 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4815.064103	-35.099622	PASSED
7360.096154	-34.799622	PASSED
7500.000000	-35.099622	PASSED


Channel 40 / 2442 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4934.294872	-35.124733	PASSED
7325.961538	-34.024733	PASSED
7500.000000	-35.224733	PASSED

Channel 78 / 2480 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4918.589744	-36.739873	PASSED
7358.653846	-35.439873	PASSED
7500.000000	-35.339873	PASSED

6. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5)

EUT with DUT number	RM-582V DUT42281
Accessories with DUT numbers	BP-4LV DUT42271, AC-31 DUT42274, CA-101V DUT42275, WH-1V DUT42278
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	24 / 47 / 101.5
Date of measurements	10-Jun-2010
Measured by	Hannu Söderholm

6.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu\text{V/m}] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + AF - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu\text{V/m}$]	Limit [dB $\mu\text{V/m}$]	Detector
30 – 88	100	40	Quasi peak
88 – 216	150	43.5	Quasi peak
216 – 960	200	46	Quasi peak
960 – 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

6.2. Bluetooth Test results

6.2.1 GFSK modulation, PRBS packet type

TX mode, channel 0 / 2402 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	43.60	151.36	44.60	-1.0	HORIZONTAL	PASSED
7206.000000	46.40	208.93	44.00	2.4	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	30.90	35.08	31.90	-1.0	HORIZONTAL	PASSED
7206.000000	32.60	42.66	30.20	2.4	VERTICAL	PASSED

TX mode, channel 40 / 2442 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4884.269539	46.90	221.31	48.10	-1.2	HORIZONTAL	PASSED
7301.095190	43.20	144.54	40.30	2.9	HORIZONTAL	PASSED
7325.653307	43.80	154.88	40.90	2.9	VERTICAL	PASSED
17479.965932	53.00	446.68	34.30	18.7	VERTICAL	PASSED
17981.459920	54.80	549.54	33.90	20.9	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4884.269539	38.20	81.28	39.40	-1.2	HORIZONTAL	PASSED
7298.595190	29.70	30.55	26.90	2.8	HORIZONTAL	PASSED
7325.153307	30.80	34.67	27.90	2.9	VERTICAL	PASSED
17484.465932	39.60	95.50	20.90	18.7	VERTICAL	PASSED
17983.459920	42.10	127.35	21.20	20.9	VERTICAL	PASSED

TX mode, channel 78 / 2480 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	50.30	327.34	50.80	-0.5	HORIZONTAL	PASSED
7440.000000	43.30	146.22	40.10	3.2	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	29.60	30.20	30.10	-0.5	VERTICAL	PASSED
7440.000000	29.90	31.26	26.70	3.2	VERTICAL	PASSED

6.2.2 8DPSK modulation, PRBS packet type

TX mode, channel 0 / 2402 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	43.90	156.68	44.90	-1.0	VERTICAL	PASSED
7206.000000	46.80	218.78	44.40	2.4	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	32.80	43.65	33.80	-1.0	VERTICAL	PASSED
7206.000000	34.00	50.12	31.60	2.4	HORIZONTAL	PASSED

TX mode, channel 40 / 2442 MHz

Quasi peak (RBW: 120 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
37.995391	18.90	8.81	33.00	-14.1	VERTICAL	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4883.769539	47.60	239.88	48.80	-1.2	HORIZONTAL	PASSED
7310.115230	43.20	144.54	40.20	3.0	HORIZONTAL	PASSED
7325.653307	45.90	197.24	43.00	2.9	VERTICAL	PASSED
17470.937876	52.50	421.70	33.90	18.6	VERTICAL	PASSED
17969.437876	55.20	575.44	34.30	20.9	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4884.269539	37.80	77.62	39.00	-1.2	HORIZONTAL	PASSED
7309.115230	29.90	31.26	26.90	3.0	HORIZONTAL	PASSED
7325.153307	31.40	37.15	28.50	2.9	VERTICAL	PASSED
17472.437876	39.50	94.41	20.90	18.6	VERTICAL	PASSED
17967.937876	42.20	128.82	21.30	20.9	VERTICAL	PASSED

TX mode, channel 78 / 2480 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	51.70	384.59	52.20	-0.5	HORIZONTAL	PASSED
7440.000000	47.30	231.74	44.10	3.2	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	42.50	133.35	43.00	-0.5	HORIZONTAL	PASSED
7440.000000	34.40	52.48	31.20	3.2	VERTICAL	PASSED

7. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)

EUT with DUT number	RM-582V DUT 42277
Accessories with DUT numbers	BP-4LV DUT 42272
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 50 99.8
Date of measurements	10-Jun-2010
Measured by	Jari Jantunen

7.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-GEN as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.


CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

7.2. Bluetooth Test results

7.2.1 GFSK modulation, PRBS packet type

Channel 40 / 2442 MHz



Quasi peak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.180000	46.20	N	PASSED
0.280000	38.30	L1	PASSED
0.315000	40.70	L1	PASSED
0.515000	36.40	L1	PASSED
2.075000	32.20	L1	PASSED
2.970000	31.00	L1	PASSED
4.950000	30.10	L1	PASSED
7.905000	29.10	N	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.180000	36.50	L1	PASSED
0.320000	31.50	L1	PASSED
0.500000	31.70	L1	PASSED
0.885000	29.40	L1	PASSED
2.060000	23.80	L1	PASSED
3.125000	23.80	L1	PASSED
4.240000	25.80	L1	PASSED
7.065000	27.10	L1	PASSED

8. 20 dB bandwidth (FCC §15.247(a)(1), RSS-210 A8.1 (a))

EUT with DUT number	RM-582V DUT 42277
Accessories with DUT numbers	BP-4LV DUT 42272
Operation Voltage [V] / [Hz]	Nominal
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 50 / 99.3
Date of measurements	08-Jun-2010
Measured by	Jari Jantunen

8.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for 20 dB bandwidth measurements


Limit [MHz]
N/A

8.2. Bluetooth Test results


8.2.1 GFSK modulation, PRBS packet type

Channel / f_c [MHz]	20 dB bandwidth [kHz]	Result
0 / 2402	794.872	PASSED
40 / 2442	833.333	PASSED
78 / 2480	833.333	PASSED


Channel 0 / 2402 MHz



Channel 40 / 2442 MHz




Channel 78 / 2480 MHz




8.2.2 8DPSK modulation, PRBS packet type

Channel / f _c [MHz]	20 dB bandwidth [kHz]	Result
0 / 2402	1314.103	PASSED
40 / 2442	1320.513	PASSED
78 / 2480	1320.513	PASSED


Channel 0 / 2402 MHz



Channel 40 / 2442 MHz



Channel 78 / 2480 MHz



9. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1 (b))

EUT with DUT number	RM-582V DUT 42277
Accessories with DUT numbers	BP-4LV DUT 42272
Operation Voltage [V] / [Hz]	Nominal
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 50 / 99.3
Date of measurements	08-Jun-2010
Measured by	Jari Jantunen

9.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for carrier frequency separation measurements


Limit [MHz]
≥ 0.025 or $2/3$ of the 20 dB bandwidth

9.2. Bluetooth Test results

9.2.1 GFSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
993.59	PASSED


Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz



9.2.2 8DPSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
1001.603	PASSED

Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz



10. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (d))

EUT with DUT number	RM-582V DUT 42277
Accessories with DUT numbers	BP-4LV DUT 42272
Operation Voltage [V] / [Hz]	Nominal
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 50 / 99.3
Date of measurements	08-Jun-2010
Measured by	Jari Jantunen

10.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for number of hopping frequencies measurements


Limit [number]
≥ 15

10.2. Bluetooth Test results

10.2.1 GFSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
79	PASSED


Hopping on, number of hopping frequencies



10.2.2 8DPSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
25	PASSED

Hopping on, number of hopping frequencies



11. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (d))

EUT with DUT number	RM-582V DUT 42277
Accessories with DUT numbers	BP-4LV DUT 42272
Operation Voltage [V] / [Hz]	Nominal
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 50 / 99.3
Date of measurements	08-Jun-2010
Measured by	Jari Jantunen

11.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210 as follows:

The total time of occupancy is get by multiplying the measured number of transmissions occurred during 31.6 second period with the duration of one transmission.

Limits for time of occupancy measurements


Limit [s]
≤ 0.4

11.2. Bluetooth test results


11.2.1 GFSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [μs]	Time of occupancy [s]	Result
86	2 917	0.250833	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz




Hopping on, duration of one transmission, channel 40 / 2442 MHz




11.2.2 8DPSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [μs]	Time of occupancy [s]	Result
91	2 917	0.265417	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz



Hopping on, duration of one transmission, channel 40 / 2442 MHz



12. Test Equipment

12.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM38112	Power supply	6632A	Agilent	22/24/27, 15C
TM38631	Signal Generator	83640L	Agilent	22/24/27, 15C, 15B
OM0631 2	Signal Generator	E4422B	Agilent	22/24
TM37678	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM37773	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM30600	Impulse limiter	ESH3-Z2	R&S	15C, 15B
TM26490	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
TM26491	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
TM37610	Spectrum Analyzer	FSU26	R&S	22/24/27, 15C
TM22806	Battery	BAT 20/E	Fiskars	15C, 15B
TM22805	UPS	PS 20/1.2	Fiskars	15C, 15B
-	Temperature and humidity logger	175-H2	Testo	15C, 15B
-	Temperature and humidity logger	175-H2	Testo	22/24/27, 15C
-	Air pressure and temperature logger	635-2	Testo	22/24/27, 15C, 15B
-	Air pressure sensor	0638-1835	Testo	22/24/27, 15C, 15B
-	Temperature test chamber	VT 4002	Vötsch	22/24
2058	Receiver	ESPC	R&S	15C, 15B
2001	Bluetooth tester	CBT	R&S	22/24/27, 15C, 15B
2002	Communication Tester	CMU200	R&S	22/24/27
2009	LISN 50 µH	ENV216	R&S	15C, 15B
2010	LISN 50 µH	ENV216	R&S	15C, 15B
2012	Power splitter	11667B	Agilent	22/24/27, 15C
2013	Attenuator	8493C	Agilent	22/24/27, 15C
2014	Attenuator	8493C	Agilent	22/24/27, 15C

12.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM38114	Power supply	6632A	Agilent	22/24/27, 15C, 15B
TM38631	Signal Generator	83640L	Agilent	22/24/27, 15C, 15B
TM38323	Preamplifier	PA-02 18-26 GHz	EMC Automation	22/24/27, 15C, 15B
-	Antenna	BBHA 9120 D	Schwarzbeck	22/24/27, 15C
TM26497	Antenna	3115	Emco	22/24/27, 15C, 15B
TM37678	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM37773	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM38845	Receiver	ESIB 26	R&S	22/24/27, 15C, 15B
-	Antenna	HL562	R&S	22/24/27, 15C, 15B
TM26500	Turntable	DS412	Deisel	22/24/27, 15C, 15B
TM30642	Mast/turntable controller	HD-100	Deisel	22/24/27, 15C, 15B
TM38990	Remote switching module	RSM1	EMC Automation	22/24/27, 15C, 15B
TM38341	System interface	SI-300	EMC Automation	22/24/27, 15C, 15B
-	Mini mast	2075-2	ETS Lindgren	22/24/27, 15C, 15B
TM38843	Mini mast	2075	Emco	22/24/27, 15C, 15B
TM38842	Controller	2090	Emco	22/24/27, 15C, 15B
TM39158	Antenna	3116	Emco	22/24/27, 15C, 15B
TM30643	LISN 50 µH	LISN-5-20-2	FCC	22/24/27, 15C, 15B
TM30644	LISN 50 µH	LISN-5-20-2	FCC	22/24/27, 15C, 15B
-	Temperature and humidity logger	175-H2	Testo	22/24/27, 15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
-	Air pressure and temperature logger	635-2	Testo	22/24/27, 15C, 15B
-	Air pressure sensor	0638-1835	Testo	22/24/27, 15C, 15B
TM39180	Laser distance meter	Disto Pro	Leica	22/24/27, 15C, 15B
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	Miteq	22/24/27, 15C, 15B
-	Preamplifier	AFS4-00100300-20-23P6	Miteq	15C
TM37498	Preamplifier	AMF-5D-020180-26-10P	Miteq	22/24/27, 15C, 15B
TM30599	Semi anechoic chambre	UNKNOWN	TDK	22/24/27, 15C, 15B
TM22638	Power supply	OL63743-901	Torqueleader	22/24/27, 15C, 15B
TM38066	High pass filter	4HC3000/18000-3-KK	Trilithic	22/24/27, 15C, 15B
TM26511	Tunable notch filter	WRCA870/	Wainwright	27
TM38215	Band reject filter	WRCD 1920/1980-1918/1982-40/20	Wainwright UMTS	27
TM38214	Band reject filter	WRCT 2402/2480-2400/2483.5-30/	Wainwright ISM	15C
-	Band reject filter	WRCG1877/1883-1870/1890-40/6EE	Wainwright	27
-	Band reject filter	WRCG1729.4/1735.4-1722.4/1742.4-40/6SS	Wainwright	27
-	Band reject filter	WRCG832/838-825/848-40/5SS	Wainwright	27
TM23892	Controller	G-1000SDX	Yaesu	22/24/27
2001	Bluetooth tester	CBT	R&S	22/24/27, 15C, 15B
-	Antenna	SBA 9113	Schwarzbeck	22/24/27
6023	Antenna	VUBA 9117	Schwarzbeck	22/24/27, 15C