## HUIZHOU TCL KING HIGH FRENQUENCY ELECTRONIC CO., LTD

## FCC Modular Approval Request Number: CF305

Version: **V03** Date: 01-08-2011

## To the FCC or FCC TCB handling this application

Hereby we,

Company name (grantee) HUIZHOU TCL KING HIGH FRENQUENCY ELECTRONIC CO., LTD

Addresss

HUA YU RD., NO.75, ZHONGKAI HIGH-TECH DEVELOPMENT AREA, HUIZHOU, CHINA

City / ZIP / State / Country HUIZHOU

request modular approval for the certification of our equipment within this application, identified by:

FCC ID:

City and Country:

HUIZHOU

Date:

08/24/2012

Name:

Yunzi Xiong

(this must be a person)

P96WF71RL

The table below contains the justification for modular approval of this equipment:  Requirement	Explanation from grantee (do not write yes / no but explain why it complies / how it is achieved)
The modular transmitter must have its own RF shielding.	No (The modular do not equip with own RF shielding
<ol><li>The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.</li></ol>	Yes (The modular data inputs are buffered through log or microcontroller connections)
3. The modular transmitter must have its own power supply regulation.	Yes (RF voltage regulation is handled on the module)
4. The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable)	Yes (The modular with permanently antenna, the antenna is Printed Antenna)
5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed.	Yes (The modular during testing with a USB adapter, and the distance is greater than 10cm, so the distance between modular and host system is greater than 10cm)
5. The modular transmitter must be labeled with its own FCC ID number, and, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.	Yes (Please refer to FCC ID label)
The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are ery strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is rohibited, except for operation under Section 15.231(e), in which case there are eparate field strength level and timing requirements. Compliance with these equirements must be assured.	Yes (Please refer to the modular installation muanual)
or example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15,	Yes (Please see the MPE report, the modular meets MPE calculation of 47 CFR 1.107 (b)(1).)

Function:

Technology Director

Signature:

能运

(or official company stamp)

Yunzi Xion