# 4 FCC §15.407(f) & §2.1091 - RF Exposure

### 4.1 Applicable Standard

According to FCC §15.407(f) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)		
Limits for General Population/Uncontrolled Exposure						
0.3-1.34	614	1.63	* (100)	30		
1.34-30	824/f	2.19/f	* (180/f <sup>2</sup> )	30		
30-300	27.5	0.073	0.2	30		
300-1500	/	/	f/1500	30		
1500-100,000	/	/	1.0	30		

Limits for General Population/Uncontrolled Exposure

f = frequency in MHz

\* = Plane-wave equivalent power density

# 4.2 MPE Prediction

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

 $\mathbf{R}$  = distance to the center of radiation of the antenna

### 4.3 MPE Results

#### 5.2 GHz Band:

Maximum peak output	power at antenna input terminal (	(dBm):	27.9
• •	* *		

Maximum peak output power at antenna input terminal (mW): 616.59

Prediction distance (cm): 20

Prediction frequency (MHz): 5200

Maximum Antenna Gain, typical (dBi): 8

Maximum Antenna Gain (numeric): 6.31

Power density of prediction frequency at 20 cm (mW/cm<sup>2</sup>): 0.774

<u>MPE limit for uncontrolled exposure at prediction frequency (mW/cm<sup>2</sup>):</u> <u>1.0</u>

Report Number: R1409231-407 W52W58 Rev A

# 5.8 GHz Band:

Maximum peak output power at antenna input terminal (dBm):		
Maximum peak output power at antenna input terminal (mW):	<u>628.06</u>	
Prediction distance (cm):	<u>20</u>	
Prediction frequency (MHz):	<u>5785</u>	
Maximum Antenna Gain, typical (dBi):	<u>8</u>	
Maximum Antenna Gain (numeric):	<u>6.31</u>	
Power density of prediction frequency at 20 cm (mW/cm <sup>2</sup> ):	0.788	
MPE limit for uncontrolled exposure at prediction frequency (mW/cm <sup>2</sup> ):	<u>1.0</u>	

The device meets FCC MPE requirement for uncontrolled exposure environment at 20 cm distance.