







TEST PLOT OF OUT OF BAND EMISSIONS FOR MODULATION IN 5825MHz









FOR 802.11N40 MODULATION



TEST PLOT OF OUT OF BAND EMISSIONS FOR MODULATION IN 5190MHz








TEST PLOT OF OUT OF BAND EMISSIONS FOR MODULATION IN 5230MHz








TEST PLOT OF OUT OF BAND EMISSIONS FOR MODULATION IN 5755MHz







TEST PLOT OF OUT OF BAND EMISSIONS FOR MODULATION IN 5795M









FOR 802.11AC80 MODULATION



TEST PLOT OF OUT OF BAND EMISSIONS FOR MODULATION IN 5210MHz





TEST PLOT OF OUT OF BAND EMISSIONS FOR MODULATION IN 5775MHz





Note: All the 20MHz bandwidth modulation had been tested, the 802.11a20 was the worst case and record in his test report. All the 40MHz bandwidth modulation had been tested, the 802.11N40 was the worst case and record in his test report. All the 80MHz bandwidth modulation had been tested, the 802.11ac80 was the worst case and record in his test report.

Two transmit chains had been tested, the chain 0 was the worst case and record in the test report.

The spurious emission at chain 0 is more than 3dB below the limits, so the MIMO results for the spurious emissions are comply with the requirement.


12. RADIATED EMISSION

12.1. MEASUREMENT PROCEDURE


1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3M VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

12.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



12.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note: All modes were tested For restricted band radiated emission,
the test records reported below are the worst result compared to other modes.

12.4. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

| | | | |
|-------------|---------------------------|-------------------|----------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11a20 5180MHz | Antenna | Horizontal |



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dBuV/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | | 118.9167 | 5.85 | 17.86 | 23.71 | 43.50 | -19.79 | peak | | | |
| 2 | | 169.0331 | 6.80 | 18.26 | 25.06 | 43.50 | -18.44 | peak | | | |
| 3 | | 353.3333 | 3.59 | 21.34 | 24.93 | 46.00 | -21.07 | peak | | | |
| 4 | | 463.2666 | 4.55 | 24.25 | 28.80 | 46.00 | -17.20 | peak | | | |
| 5 | * | 793.0667 | 3.97 | 30.25 | 34.22 | 46.00 | -11.78 | peak | | | |
| 6 | | 857.7332 | 2.44 | 31.15 | 33.59 | 46.00 | -12.41 | peak | | | |

RESULT: PASS

| | | | |
|--------------------|---------------------------|--------------------------|----------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11a20 5180MHz | Antenna | Vertical |



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dBuV/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | | 84.9664 | 7.03 | 14.96 | 21.99 | 40.00 | -18.01 | peak | | | |
| 2 | | 377.5833 | 7.75 | 22.19 | 29.94 | 46.00 | -16.06 | peak | | | |
| 3 | | 608.7667 | 1.23 | 27.06 | 28.29 | 46.00 | -17.71 | peak | | | |
| 4 | | 684.7500 | 2.61 | 27.97 | 30.58 | 46.00 | -15.42 | peak | | | |
| 5 | * | 794.6831 | 5.51 | 30.29 | 35.80 | 46.00 | -10.20 | peak | | | |
| 6 | | 894.9166 | 3.54 | 31.63 | 35.17 | 46.00 | -10.83 | peak | | | |

RESULT: PASS

Note: All test channels had been tested. The 802.11a20 at 5180MHz is the worst case and recorded in the test report.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin= Limit-Level.

The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION ABOVE 1GHZ

| | | | |
|--------------------|---------------------------|--------------------------|---------------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11a20 5180MHz | Antenna | Horizontal/Vertical |

RADIATED EMISSION ABOVE 1GHZ–Horizontal

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 10360.062 | 45.25 | 7.12 | 52.37 | 74.00 | -21.63 | peak |
| 10360.062 | 40.79 | 7.12 | 47.91 | 54.00 | -6.09 | AVG |
| 15540.093 | 35.78 | 9.84 | 45.62 | 74.00 | -28.38 | peak |
| 15540.093 | 31.85 | 9.84 | 41.69 | 54.00 | -12.31 | AVG |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RADIATED EMISSION ABOVE 1GHZ–Vertical

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 10360.062 | 47.82 | 7.12 | 54.94 | 74.00 | -19.06 | peak |
| 10360.062 | 40.57 | 7.12 | 47.69 | 54.00 | -6.31 | AVG |
| 15540.093 | 35.77 | 9.84 | 45.61 | 74.00 | -28.39 | peak |
| 15540.093 | 33.91 | 9.84 | 43.75 | 54.00 | -10.26 | AVG |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| | | | |
|--------------------|---------------------------|--------------------------|---------------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11a20 5240MHz | Antenna | Horizontal/Vertical |

RADIATED EMISSION ABOVE 1GHZ–Horizontal

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|--------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 10480.062 | 44.62 | 7.12 | 51.74 | 74.00 | -22.26 | peak |
| 10480.062 | 39.68 | 7.12 | 46.80 | 54.00 | -7.20 | AVG |
| 15720.093 | 38.77 | 9.84 | 48.61 | 74.00 | -25.39 | peak |
| 15720.093 | 36.38 | 9.84 | 46.22 | 54.00 | -7.78 | AVG |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RADIATED EMISSION ABOVE 1GHZ–Vertical

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|--------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 10480.062 | 44.66 | 7.12 | 51.78 | 74.00 | -22.22 | peak |
| 10480.062 | 41.69 | 7.12 | 48.81 | 54.00 | -5.19 | AVG |
| 15720.093 | 37.17 | 9.84 | 47.01 | 74.00 | -27.00 | peak |
| 15720.093 | 33.71 | 9.84 | 43.55 | 54.00 | -10.45 | AVG |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| | | | |
|-------------|---------------------------|-------------------|---------------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11a20 5745MHz | Antenna | Horizontal/Vertical |

RADIATED EMISSION ABOVE 1GHZ–Horizontal

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 11490.062 | 46.63 | 7.12 | 53.75 | 74.00 | -20.25 | peak |
| 11490.062 | 40.93 | 7.12 | 48.05 | 54.00 | -5.95 | AVG |
| 17235.093 | 36.78 | 9.84 | 46.62 | 74.00 | -27.38 | peak |
| 17235.093 | 33.16 | 9.84 | 43.00 | 54.00 | -11.00 | AVG |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RADIATED EMISSION ABOVE 1GHZ–Vertical

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 11490.062 | 47.59 | 7.12 | 54.71 | 74.00 | -19.29 | peak |
| 11490.062 | 41.49 | 7.12 | 48.61 | 54.00 | -5.39 | AVG |
| 17235.093 | 35.22 | 9.84 | 45.06 | 74.00 | -28.94 | peak |
| 17235.093 | 34.07 | 9.84 | 43.91 | 54.00 | -10.09 | AVG |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| | | | |
|--------------------|---------------------------|--------------------------|---------------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11a20 5825MHz | Antenna | Horizontal/Vertical |

RADIATED EMISSION ABOVE 1GHZ–Horizontal

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 11650.062 | 44.62 | 7.12 | 51.74 | 74.00 | -22.26 | peak |
| 11650.062 | 38.50 | 7.12 | 45.62 | 54.00 | -8.38 | AVG |
| 17475.093 | 38.67 | 9.84 | 48.51 | 74.00 | -25.49 | peak |
| 17475.093 | 35.86 | 9.84 | 45.70 | 54.00 | -8.30 | AVG |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

RADIATED EMISSION ABOVE 1GHZ–Vertical

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 11650.062 | 45.59 | 7.12 | 52.71 | 74.00 | -21.29 | peak |
| 11650.062 | 41.50 | 7.12 | 48.62 | 54.00 | -5.38 | AVG |
| 17475.093 | 39.21 | 9.84 | 49.05 | 74.00 | -24.95 | peak |
| 17475.093 | 36.82 | 9.84 | 46.66 | 54.00 | -7.34 | AVG |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

Note: All the case had been tested. The 802.11a modulation is the worst case and recorded in the test report.
Other frequencies radiation emission from 1GHz to 40GHz at least have 20dB margin and not recorded in the test report.
Factor = Antenna Factor + Cable loss - Amplifier gain, Margin= Limit-Level.
The “Factor” value can be calculated automatically by software of measurement system.

13. BAND EDGE EMISSION


13.1. MEASUREMENT PROCEDURE

1. The EUT operates at transmitting mode. The operate channel is tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
2. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
(a) PEAK: RBW=1MHz, VBW=3MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz ; VBW=1/on time(1KHz) / Sweep=AUTO
3. Other procedures refer to clause 11.2.

Note:

1. Factor=Antenna Factor + Cable loss - Amplifier gain. Field Strength=Factor + Reading level
2. The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μ V) to represent the Amplitude. Use the F dB(μ V/m) to represent the Field Strength. So A=F.
3. Only the data of band edge emission at the restricted band 4.5GHz-5.15GHz record in the report. Other restricted band 5.35GHz-5.46GHz and 7.25GHz-7.77GHz were considered as ambient noise. No recording in the test report.


13.2. TEST SET-UP




13.3. TEST RESULT

| | | | |
|-------------|---------------------------|-------------------|----------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11a20 5180MHz | Antenna | Horizontal |

PK Value




AV Value




| | | | |
|-------------|---------------------------|-------------------|----------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11a20 5180MHz | Antenna | Vertical |

PK Value




AV Value




| | | | |
|-------------|---------------------------|-------------------|----------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n40 5190MHz | Antenna | Horizontal |

PK Value



AV Value



| | | | |
|-------------|---------------------------|-------------------|----------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n40 5190MHz | Antenna | Vertical |

PK Value




AV Value




| | | | |
|-------------|---------------------------|-------------------|----------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11ac80 5210MHz | Antenna | Horizontal |

PK Value



AV Value




| | | | |
|-------------|---------------------------|-------------------|----------------|
| EUT | ac2x2+BT5.0 USB2.0 module | Model Name | CM-8822CU |
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11ac80 5210MHz | Antenna | Vertical |

PK Value



AV Value



RESULT: PASS


Note: All the 20MHz bandwidth modulation had been tested, the 802.11a20 was the worst case and record in his test report. All the 40MHz bandwidth modulation had been tested, the 802.11N40 was the worst case and record in his test report.

14. FREQUENCY STABILITY

14.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the operation frequency.
3. Set SPA Centre Frequency = Operation Frequency. SPAN=enough to measure the emission is maintained within the band
4. Set SPA Trace 1 Max hold, then View.
5. Extreme temperature rule is -10°C~60°C.

14.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



14.3. MEASUREMENT RESULTS

| Test Mode | Temperature | Measurement Frequency (MHz) | Result | Conclusion |
|-----------|-------------|-----------------------------|-----------------|------------|
| 802.11a | - 10°C | 5180 | within the band | PASS |
| | 0°C | 5180 | within the band | PASS |
| | 10°C | 5180 | within the band | PASS |
| | 20°C | 5180 | within the band | PASS |
| | 30°C | 5180 | within the band | PASS |
| | 40°C | 5180 | within the band | PASS |
| | 50°C | 5180 | within the band | PASS |
| | 60°C | 5180 | within the band | PASS |
| | - 10°C | 5240 | within the band | PASS |
| | 0°C | 5240 | within the band | PASS |
| | 10°C | 5240 | within the band | PASS |
| | 20°C | 5240 | within the band | PASS |
| | 30°C | 5240 | within the band | PASS |
| | 40°C | 5240 | within the band | PASS |
| | 50°C | 5240 | within the band | PASS |
| | 60°C | 5240 | within the band | PASS |
| | - 10°C | 5745 | within the band | PASS |
| | 0°C | 5745 | within the band | PASS |
| | 10°C | 5745 | within the band | PASS |
| | 20°C | 5745 | within the band | PASS |
| | 30°C | 5745 | within the band | PASS |
| | 40°C | 5745 | within the band | PASS |
| | 50°C | 5745 | within the band | PASS |
| | 60°C | 5240 | within the band | PASS |
| | - 10°C | 5825 | within the band | PASS |
| | 0°C | 5825 | within the band | PASS |
| | 10°C | 5825 | within the band | PASS |
| | 20°C | 5825 | within the band | PASS |
| | 30°C | 5825 | within the band | PASS |
| | 40°C | 5825 | within the band | PASS |
| | 50°C | 5825 | within the band | PASS |
| | 60°C | 5825 | within the band | PASS |

| Test Mode | Temperature | Measurement Frequency (MHz) | Result | Conclusion |
|-----------|-------------|-----------------------------|-----------------|------------|
| 802.11n20 | - 10°C | 5180 | within the band | PASS |
| | 0°C | 5180 | within the band | PASS |
| | 10°C | 5180 | within the band | PASS |
| | 20°C | 5180 | within the band | PASS |
| | 30°C | 5180 | within the band | PASS |
| | 40°C | 5180 | within the band | PASS |
| | 50°C | 5180 | within the band | PASS |
| | 60°C | 5180 | within the band | PASS |
| | - 10°C | 5240 | within the band | PASS |
| | 0°C | 5240 | within the band | PASS |
| | 10°C | 5240 | within the band | PASS |
| | 20°C | 5240 | within the band | PASS |
| | 30°C | 5240 | within the band | PASS |
| | 40°C | 5240 | within the band | PASS |
| | 50°C | 5240 | within the band | PASS |
| | 60°C | 5240 | within the band | PASS |
| | - 10°C | 5745 | within the band | PASS |
| | 0°C | 5745 | within the band | PASS |
| | 10°C | 5745 | within the band | PASS |
| | 20°C | 5745 | within the band | PASS |
| | 30°C | 5745 | within the band | PASS |
| | 40°C | 5745 | within the band | PASS |
| | 50°C | 5745 | within the band | PASS |
| | 60°C | 5240 | within the band | PASS |
| | - 10°C | 5825 | within the band | PASS |
| | 0°C | 5825 | within the band | PASS |
| | 10°C | 5825 | within the band | PASS |
| | 20°C | 5825 | within the band | PASS |
| | 30°C | 5825 | within the band | PASS |
| | 40°C | 5825 | within the band | PASS |
| | 50°C | 5825 | within the band | PASS |
| | 60°C | 5825 | within the band | PASS |

| Test Mode | Temperature | Measurement Frequency (MHz) | Result | Conclusion |
|------------|-------------|-----------------------------|-----------------|------------|
| 802.11ac20 | - 10°C | 5180 | within the band | PASS |
| | 0°C | 5180 | within the band | PASS |
| | 10°C | 5180 | within the band | PASS |
| | 20°C | 5180 | within the band | PASS |
| | 30°C | 5180 | within the band | PASS |
| | 40°C | 5180 | within the band | PASS |
| | 50°C | 5180 | within the band | PASS |
| | 60°C | 5180 | within the band | PASS |
| | - 10°C | 5240 | within the band | PASS |
| | 0°C | 5240 | within the band | PASS |
| | 10°C | 5240 | within the band | PASS |
| | 20°C | 5240 | within the band | PASS |
| | 30°C | 5240 | within the band | PASS |
| | 40°C | 5240 | within the band | PASS |
| | 50°C | 5240 | within the band | PASS |
| | 60°C | 5240 | within the band | PASS |
| | - 10°C | 5745 | within the band | PASS |
| | 0°C | 5745 | within the band | PASS |
| | 10°C | 5745 | within the band | PASS |
| | 20°C | 5745 | within the band | PASS |
| | 30°C | 5745 | within the band | PASS |
| | 40°C | 5745 | within the band | PASS |
| | 50°C | 5745 | within the band | PASS |
| | 60°C | 5240 | within the band | PASS |
| | - 10°C | 5825 | within the band | PASS |
| | 0°C | 5825 | within the band | PASS |
| | 10°C | 5825 | within the band | PASS |
| | 20°C | 5825 | within the band | PASS |
| | 30°C | 5825 | within the band | PASS |
| | 40°C | 5825 | within the band | PASS |
| | 50°C | 5825 | within the band | PASS |
| | 60°C | 5825 | within the band | PASS |

| Test Mode | Temperature | Measurement Frequency (MHz) | Result | Conclusion |
|-----------|-------------|-----------------------------|-----------------|------------|
| 802.11n40 | - 10°C | 5190 | within the band | PASS |
| | 0°C | 5190 | within the band | PASS |
| | 10°C | 5190 | within the band | PASS |
| | 20°C | 5190 | within the band | PASS |
| | 30°C | 5190 | within the band | PASS |
| | 40°C | 5190 | within the band | PASS |
| | 50°C | 5190 | within the band | PASS |
| | 60°C | 5190 | within the band | PASS |
| | - 10°C | 5230 | within the band | PASS |
| | 0°C | 5230 | within the band | PASS |
| | 10°C | 5230 | within the band | PASS |
| | 20°C | 5230 | within the band | PASS |
| | 30°C | 5230 | within the band | PASS |
| | 40°C | 5230 | within the band | PASS |
| | 50°C | 5230 | within the band | PASS |
| | 60°C | 5230 | within the band | PASS |
| | - 10°C | 5755 | within the band | PASS |
| | 0°C | 5755 | within the band | PASS |
| | 10°C | 5755 | within the band | PASS |
| | 20°C | 5755 | within the band | PASS |
| | 30°C | 5755 | within the band | PASS |
| | 40°C | 5755 | within the band | PASS |
| | 50°C | 5755 | within the band | PASS |
| | 60°C | 5755 | within the band | PASS |
| | - 10°C | 5795 | within the band | PASS |
| | 0°C | 5795 | within the band | PASS |
| | 10°C | 5795 | within the band | PASS |
| | 20°C | 5795 | within the band | PASS |
| | 30°C | 5795 | within the band | PASS |
| | 40°C | 5795 | within the band | PASS |
| | 50°C | 5795 | within the band | PASS |
| | 60°C | 5795 | within the band | PASS |

| Test Mode | Temperature | Measurement Frequency (MHz) | Result | Conclusion |
|------------|-------------|-----------------------------|-----------------|------------|
| 802.11ac40 | - 10°C | 5190 | within the band | PASS |
| | 0°C | 5190 | within the band | PASS |
| | 10°C | 5190 | within the band | PASS |
| | 20°C | 5190 | within the band | PASS |
| | 30°C | 5190 | within the band | PASS |
| | 40°C | 5190 | within the band | PASS |
| | 50°C | 5190 | within the band | PASS |
| | 60°C | 5190 | within the band | PASS |
| | - 10°C | 5230 | within the band | PASS |
| | 0°C | 5230 | within the band | PASS |
| | 10°C | 5230 | within the band | PASS |
| | 20°C | 5230 | within the band | PASS |
| | 30°C | 5230 | within the band | PASS |
| | 40°C | 5230 | within the band | PASS |
| | 50°C | 5230 | within the band | PASS |
| | 60°C | 5230 | within the band | PASS |
| | - 10°C | 5755 | within the band | PASS |
| | 0°C | 5755 | within the band | PASS |
| | 10°C | 5755 | within the band | PASS |
| | 20°C | 5755 | within the band | PASS |
| | 30°C | 5755 | within the band | PASS |
| | 40°C | 5755 | within the band | PASS |
| | 50°C | 5755 | within the band | PASS |
| | 60°C | 5755 | within the band | PASS |
| | - 10°C | 5795 | within the band | PASS |
| | 0°C | 5795 | within the band | PASS |
| | 10°C | 5795 | within the band | PASS |
| | 20°C | 5795 | within the band | PASS |
| | 30°C | 5795 | within the band | PASS |
| | 40°C | 5795 | within the band | PASS |
| | 50°C | 5795 | within the band | PASS |
| | 60°C | 5795 | within the band | PASS |

| Test Mode | Temperature | Measurement Frequency (MHz) | Result | Conclusion |
|------------|-------------|-----------------------------|-----------------|------------|
| 802.11ac80 | - 10°C | 5210 | within the band | PASS |
| | 0°C | 5210 | within the band | PASS |
| | 10°C | 5210 | within the band | PASS |
| | 20°C | 5210 | within the band | PASS |
| | 30°C | 5210 | within the band | PASS |
| | 40°C | 5210 | within the band | PASS |
| | 50°C | 5210 | within the band | PASS |
| | 60°C | 5210 | within the band | PASS |
| | - 10°C | 5775 | within the band | PASS |
| | 0°C | 5775 | within the band | PASS |
| | 10°C | 5775 | within the band | PASS |
| | 20°C | 5775 | within the band | PASS |
| | 30°C | 5775 | within the band | PASS |
| | 40°C | 5775 | within the band | PASS |
| | 50°C | 5775 | within the band | PASS |
| | 60°C | 5775 | within the band | PASS |

15. FCC LINE CONDUCTED EMISSION TEST


15.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Frequency | Maximum RF Line Voltage | |
|---------------|-------------------------|----------------|
| | Q.P.(dBuV) | Average(dBuV) |
| 150kHz~500kHz | 66-56 | 56-46 |
| 500kHz~5MHz | 56 | 46 |
| 5MHz~30MHz | 60 | 50 |

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

15.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



15.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received charging voltage by adapter which received 120V/60Hz power by a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

15.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

15.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

LINE CONDUCTED EMISSION TEST-L




MEASUREMENT RESULT: "TEST_fin"

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.234000 | 28.50 | 10.3 | 62 | 33.8 | QP | L1 | FLO |
| 0.506000 | 36.20 | 10.3 | 56 | 19.8 | QP | L1 | FLO |
| 0.726000 | 31.30 | 10.3 | 56 | 24.7 | QP | L1 | FLO |
| 0.978000 | 31.10 | 10.4 | 56 | 24.9 | QP | L1 | FLO |
| 4.746000 | 32.40 | 10.4 | 56 | 23.6 | QP | L1 | FLO |
| 18.094000 | 36.60 | 11.0 | 60 | 23.4 | QP | L1 | FLO |

MEASUREMENT RESULT: "TEST_fin2"

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.234000 | 20.20 | 10.3 | 52 | 32.1 | AV | L1 | FLO |
| 0.506000 | 27.30 | 10.3 | 46 | 18.7 | AV | L1 | FLO |
| 0.742000 | 23.40 | 10.3 | 46 | 22.6 | AV | L1 | FLO |
| 0.978000 | 22.00 | 10.4 | 46 | 24.0 | AV | L1 | FLO |
| 4.758000 | 24.00 | 10.4 | 46 | 22.0 | AV | L1 | FLO |
| 18.094000 | 26.40 | 11.0 | 50 | 23.6 | AV | L1 | FLO |

LINE CONDUCTED EMISSION TEST-N



MEASUREMENT RESULT: "TESTL1_fin"

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.518000 | 32.40 | 10.3 | 56 | 23.6 | QP | N | FLO |
| 0.862000 | 25.00 | 10.4 | 56 | 31.0 | QP | N | FLO |
| 1.566000 | 23.50 | 10.4 | 56 | 32.5 | QP | N | FLO |
| 3.266000 | 22.60 | 10.4 | 56 | 33.4 | QP | N | FLO |
| 8.338000 | 24.70 | 10.7 | 60 | 35.3 | QP | N | FLO |
| 13.558000 | 23.30 | 10.8 | 60 | 36.7 | QP | N | FLO |

MEASUREMENT RESULT: "TESTL1_fin2"

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.514000 | 26.90 | 10.3 | 46 | 19.1 | AV | N | FLO |
| 0.878000 | 20.20 | 10.4 | 46 | 25.8 | AV | N | FLO |
| 1.546000 | 18.60 | 10.4 | 46 | 27.4 | AV | N | FLO |
| 3.318000 | 17.80 | 10.4 | 46 | 28.2 | AV | N | FLO |
| 8.454000 | 18.50 | 10.7 | 50 | 31.5 | AV | N | FLO |
| 13.558000 | 18.10 | 10.8 | 50 | 31.9 | AV | N | FLO |


RESULT: PASS

APPENDIX A: PHOTOGRAPHS OF TEST SETUP


FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP BELOW 1GHZ



FCC RADIATED EMISSION TEST SETUP ABOVE 1GHZ



----END OF REPORT----