



# RF EXPOSURE REPORT

**REPORT NO.:** SA931004L03A

**MODEL NO.:** WL-2203S-V3

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** CC&C Technologies, Inc.

**ADDRESS:** 8F, 150, Jian Yi Road, Chung Ho City, Taipei  
County, Taiwan 235, R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien,  
Taiwan, R.O.C.



No SAR Evaluation Required if power is below the following threshold:

Tunable Range		Center of Tunable Band (GHz)	60/f SAR Limitation (mW)
F(GHz) Low	F(GHz) High		
2.412	2.462	2.437	24.37

Maximum measured transmitter power:

Pout Conducted (dBm)	Pout Conducted (mW)	Maximum Antenna Gain (dBi)	Pout EIRP (mW)
13.50	22.387	0.32	24.099

Threshold for no SAR evaluation is 24.37 mW

Maximum TX Power is 22.387 mW Conducted and 24.099 mW EIRP

Conclusion: No SAR evaluation required since maximum Transmitter Pout (both conducted and EIRP) is below FCC threshold