



## SGS-CSTC Standards Technical Services Co., Ltd.

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan  
District, Shenzhen, Guangdong, China 518057  
Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM131200702202  
Page: 1 of 6

# SAR Evaluation Report

**Application No.:** SZEM1312007022RF  
**Applicant:** KAN TSANG TECHNOLOGY LIMITED  
**Manufacturer:** Dong Guan Kan Tsang Industrial Co., Ltd.  
**Factory:** Dong Guan Kan Tsang Industrial Co., Ltd.  
**Product Name:** Clock Radio  
**Model No.(EUT):** KT-3128BTU  
**Add Model No.:** KT-3128BT, KT-3098BT, KT-3098BTU  
**FCC ID:** PAZ3128  
**Standards:** 47 CFR Part 1.1307(2013)  
47 CFR Part 2.1093 (2013)  
KDB447498D01 General RF Exposure Guidance v05  
**Date of Receipt:** 2014-01-24  
**Date of Test:** 2014-02-18 to 2014-02-20  
**Date of Issue:** 2014-04-01

|                      |              |
|----------------------|--------------|
| <b>Test Result :</b> | <b>PASS*</b> |
|----------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



## 2 Contents

|                                                       | Page |
|-------------------------------------------------------|------|
| 1 COVER PAGE .....                                    | 1    |
| 2 CONTENTS .....                                      | 2    |
| 3 GENERAL INFORMATION .....                           | 3    |
| 3.1 CLIENT INFORMATION.....                           | 3    |
| 3.2 GENERAL DESCRIPTION OF EUT .....                  | 3    |
| 3.3 TEST LOCATION.....                                | 4    |
| 3.4 TEST FACILITY .....                               | 5    |
| 3.5 DEVIATION FROM STANDARDS .....                    | 5    |
| 3.6 ABNORMALITIES FROM STANDARD CONDITIONS.....       | 5    |
| 3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER ..... | 5    |
| 4 SAR EVALUATION .....                                | 6    |
| 4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....          | 6    |
| 4.1.1 <i>Standard Requirement</i> .....               | 6    |
| 4.1.2 <i>Limits</i> .....                             | 6    |
| 4.1.3 <i>EUT RF Exposure</i> .....                    | 6    |



### 3 General Information

#### 3.1 Client Information

|                          |                                                                                              |
|--------------------------|----------------------------------------------------------------------------------------------|
| Applicant:               | KAN TSANG TECHNOLOGY LIMITED                                                                 |
| Address of Applicant:    | Flat C5, 11/F., Wing Hing Industrial Bldg. 14 Hing Yip Street, Kwun Tong. Kowloon, Hong Kong |
| Manufacturer:            | Dong Guan Kan Tsang Industrial Co., Ltd.                                                     |
| Address of Manufacturer: | No.5, LuYiYi Road, TangXia Town, Dong Guan City, (Keyuan Town A3) China.                     |
| Factory:                 | Dong Guan Kan Tsang Industrial Co., Ltd.                                                     |
| Address of Factory:      | No.5, LuYiYi Road, TangXia Town, Dong Guan City, (Keyuan Town A3) China.                     |

#### 3.2 General Description of EUT

|                       |                                                                                                            |
|-----------------------|------------------------------------------------------------------------------------------------------------|
| Product Name:         | Clock Radio                                                                                                |
| Model No.:            | KT-3128BT, KT-3128BTU, KT-3098BT, KT-3098BTU                                                               |
| Operation Frequency:  | 2402MHz~2480MHz                                                                                            |
| Bluetooth Version:    | V2.1+EDR                                                                                                   |
| Modulation Technique: | Frequency Hopping Spread Spectrum(FHSS)                                                                    |
| Modulation Type:      | GFSK, $\pi/4$ DQPSK, 8DPSK                                                                                 |
| Test Equipment:       | CBT                                                                                                        |
| Number of Channel:    | 79                                                                                                         |
| Hopping Channel Type: | Adaptive Frequency Hopping systems                                                                         |
| Test equipment:       | CBT                                                                                                        |
| Sample Type:          | Portable production                                                                                        |
| Antenna Type:         | Integral                                                                                                   |
| Antenna Gain:         | 0dBi                                                                                                       |
| AC Adapter:           | MODEL: MLF-A00060501000U0021<br>INPUT: 100-240V~ 50/60Hz 0.18Amax<br>OUTPUT: 5V $\overline{\text{---}}$ 1A |
| Power Supply:         | DC 5V 1A<br>DC 3V (2*1.5V "AA" Size battery)                                                               |
| Test Voltage:         | AC 120V 60Hz                                                                                               |
| DC Cable:             | 150cm(Unshielded with one ferrite core)                                                                    |
| FM Antenna:           | 90cm(Unshielded)                                                                                           |



Remark:

Model No.: KT-3128BT, KT-3128BTU, KT-3098BT, KT-3098BTU

Only the model KT-3128BTU was tested, since the circuit design, PCB layout, electrical components used, internal wiring and functions were identical for the above models, with difference on model No., color, clock board dimension and power panel.

Differences are as follows:

- 1) Only the color, model No and clock board dimension of product KT-3128BTU and KT-3098BTU are different, others are the same.
- 2) Only the color, model No and clock board dimension of product KT-3128BT and KT-3098BT are different, others are the same.
- 3) Only the color, model No and power panel of product KT-3128BTU and KT-3128BT are different, others are the same.
- 4) Only the color, model No and power panel of product KT-3098BTU and KT-3098BT are different, others are the same.

Remark: The Bluetooth module are the same in the model KT-3128BT, KT-3128BTU, KT-3098BT and KT-3098BTU.

### 3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.

518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

Radiated Spurious Emission, Conducted Emissions were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory,

198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,

Guangzhou, China 510663

Tel: +86 2082155555 Fax: +86 20 82075059





### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**  
SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.
- **ACMA**  
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.
- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**  
Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.
- **CNAS (Lab Code: L0167)**  
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.
- **FCC (Registration No.: 282399)**  
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.
- **Industry Canada (Registration No.: 4620B-1)**  
The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.
- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**  
The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.
- **CBTL (Lab Code: TL129)**  
SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01:2006-10 and Rules of procedure IECEE 02:2006-10, and the relevant IECEE CB-Scheme Operational documents.

### 3.5 Deviation from Standards

None.

### 3.6 Abnormalities from Standard Conditions

None.

### 3.7 Other Information Requested by the Customer

None.



## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v05

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \cdot \sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 4.1.3 EUT RF Exposure

The Max Conducted Peak Output Power is 3.70dBm in lowest channel(2.402GHz);

The best case gain of the antenna is 0dBi.

$\text{EIRP} = 3.70\text{dBm} + 0\text{dBi} = 3.70\text{dBm}$

3.70dBm logarithmic terms convert to numeric result is nearly 2.3442mW

According to the formula. calculate the EIRP test result:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \cdot \sqrt{f(\text{GHz})} \right]$$

General RF Exposure =  $(2.3442\text{mW} / 5 \text{ mm}) \times \sqrt{2.402\text{GHz}} = 0.7266$  ①

SAR requirement:

$S = 3.0$

② ;

① < ②.

So the SAR report is not required.