



FCC TEST REPORT

REPORT NO.: RF920602H02

MODEL NO.: P120

RECEIVED: Jun. 02, 2003

TESTED: May 31 to Jun. 03, 2003

APPLICANT: Tellus Group Corporation

ADDRESS: 5F, No. 24-25, Industrial E.Rd. Iv, Science-Based Industrial Park, Hsinchu, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien, Taiwan, R.O.C.

This test report consists of 52 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



Lab Code: 200376-0



Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT.....	6
3.2	DESCRIPTION OF TEST MODES.....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	TEST INSTRUMENTS.....	9
4.1.2	TEST PROCEDURES.....	10
4.1.3	DEVIATION FROM TEST STANDARD	10
4.1.4	TEST SETUP	11
4.1.5	EUT OPERATING CONDITIONS	12
4.1.6	TEST RESULTS.....	13
4.2	RADIATED EMISSION MEASUREMENT	19
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	19
4.2.2	TEST INSTRUMENTS.....	20
4.2.3	TEST PROCEDURES.....	21
4.2.4	DEVIATION FROM TEST STANDARD	21
4.2.5	TEST SETUP	22
4.2.6	EUT OPERATING CONDITIONS	22
4.2.7	TEST RESULTS.....	23
4.3	6dB BANDWIDTH MEASUREMENT	30
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	30
4.3.2	TEST INSTRUMENTS.....	30
4.3.3	TEST PROCEDURE.....	31
4.3.4	DEVIATION FROM TEST STANDARD	31
4.3.5	TEST SETUP	31
4.3.6	EUT OPERATING CONDITIONS	31
4.3.7	TEST RESULTS.....	32
4.4	MAXIMUM PEAK OUTPUT POWER.....	36
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	36
4.4.2	INSTRUMENTS	36
4.4.3	TEST PROCEDURES.....	37
4.4.4	DEVIATION FROM TEST STANDARD	37
4.4.5	TEST SETUP	37



4.4.6 EUT OPERATING CONDITIONS 37

4.4.7 TEST RESULTS..... 38

4.4.8 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 39

4.4.9 TEST INSTRUMENTS 39

4.4.10 TEST PROCEDURE..... 40

4.4.11 DEVIATION FROM TEST STANDARD 40

4.4.12 TEST SETUP 40

4.4.13 EUT OPERATING CONDITION..... 40

4.4.14 TEST RESULTS..... 41

4.5 BAND EDGES MEASUREMENT45

4.5.1 LIMITS OF BAND EDGES MEASUREMENT 45

4.5.2 TEST INSTRUMENTS 45

4.5.3 TEST PROCEDURE..... 45

4.5.4 DEVIATION FROM TEST STANDARD 45

4.5.5 EUT OPERATING CONDITION..... 46

4.5.6 TEST RESULTS..... 46

4.6 ANTENNA REQUIREMENT49

4.6.1 STANDARD APPLICABLE..... 49

4.6.2 ANTENNA CONNECTED CONSTRUCTION..... 49

5 PHOTOGRAPHS OF THE TEST CONFIGURATION.....50

6 INFORMATION ON THE TESTING LABORATORIES.....52



1 CERTIFICATION

PRODUCT : Wireless LAN PCI Card
MODEL NO. : P120
BRAND : Tellus
APPLICANT : Tellus Group Corporation
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility on May 31 to Jun. 03, 2003. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

PREPARED BY: *Amanda Chu* , **DATE:** *Jun. 11, 2003*
(Amanda Chu)

APPROVED BY: *Eric Lin* , **DATE:** *Jun. 11, 2003*
(Eric Lin, Manager)



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -18.38dBuV at 0.486MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -3.8dBuV at 2390MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless LAN PCI Card
MODEL NO.	P120
POWER SUPPLY	5VDC from host equipment
MODULATION TYPE	DBPSK for 1Mbps DQPSK for 2Mbps CCK for 5.5/11Mbps
RADIO TECHNOLOGY	DSSS
TRANSFER RATE	1/2/5.5/11Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	15.78dBm
DATA CABLE	NA
ANTENNA TYPE	Dipole Antenna
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

1. For more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Wireless LAN PCI Card. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C. (15.247)

ANSI C63.4 : 1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of 47 CFR Part 15, Subpart B, Class B (DoC). The test report has been issued separately.




3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1	PERSONAL COMPUTER	HP	Brio BA410	SG10602726	FCC DoC
2	MONITOR	ADI	CM100	026058T10200531	FCC DoC
3	PRINTER	EPSON	EPSON	DCGY017079	FCC DoC
4	MODEM	ACEEX	1414	0206026775	IFAXDM1414
5	KEYBOARD	IBM	KB-7953	0192081	NA
6	MOUSE	Logitech	M-S34	23-218850	NA

No.	Signal cable description
1	NA
2	1.8 m braid shielded wire, terminated with VGA connector via metallic frame, w/o core.
3	1.8m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
4	1.3m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.
5	1.4 m foil shielded wire, terminal by frame, PS2 Connector, w/o Core.
6	1.4 m foil shielded wire, terminal by frame, PS2 Connector, w/o Core.

Note: 1. All power cords of the above support units are unshielded (1.8m).



NOTE: 1. Please refer to the photos of test configuration in Item 5 also.



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	CONDUCTED LIMIT (DB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

- NOTES:**
- (1) The lower limit shall apply at the transition frequencies.
 - (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 - (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.1 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	847124/029	Nov. 17, 2003
ROHDE & SCHWARZ LISN (for EUT)	ESHS-Z5	848773/004	Nov. 13, 2003
KYORITSU LISN (for peripheral)	KNW-407	8/1395/12	Jul. 23, 2003
RF Cable (JETBAO)	RG233/U	Cable_CA_01	Jul. 03, 2003
Terminator(for KYORITSU)	50	3	Apr. 11, 2004
Software	Cond-V2e	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in ADT Shielded Room No. A.
 3. The VCCI Con A Registration No. is C-817.




4.1.2 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.5 EUT OPERATING CONDITIONS

- a. Install the EUT into the support unit 1 (PC) which placed on a testing table.
- b. The support unit 1 (PC) ran a test program to enable EUT under transmission condition continuously at specific channel frequency.




4.1.6 TEST RESULTS

EUT	Wireless LAN PCI Card	MODEL	P120
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	24 deg. C, 57%RH, 962 hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.10	42.60	-	42.70	-	64.43	54.43	-21.73	-
2	0.435	0.10	35.40	-	35.50	-	57.15	47.15	-21.65	-
3	0.486	0.10	37.18	-	37.28	-	56.24	46.24	-18.96	-
4	0.591	0.10	36.91	-	37.01	-	56.00	46.00	-18.99	-
5	0.642	0.10	36.06	-	36.16	-	56.00	46.00	-19.84	-
6	0.693	0.10	36.72	-	36.82	-	56.00	46.00	-19.18	-

- NOTES:** (1) "": Undetectable
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.
 (4) The emission levels of other frequencies were very low against the limit.
 (5) Correction Factor = Insertion loss + Cable loss
 (6) Margin value = Emission level - Limit value






EUT	Wireless LAN PCI Card	MODEL	P120
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	24 deg. C, 57%RH, 962 hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.154	0.10	34.87	-	34.97	-	65.79	55.79	-30.82	-
2	0.283	0.10	34.51	-	34.61	-	60.73	50.73	-26.12	-
3	0.486	0.10	37.20	-	37.30	-	56.24	46.24	-18.94	-
4	0.591	0.10	37.13	-	37.23	-	56.00	46.00	-18.77	-
5	0.693	0.10	37.12	-	37.22	-	56.00	46.00	-18.78	-
6	0.795	0.10	36.54	-	36.64	-	56.00	46.00	-19.36	-

- NOTES:** (1) "": Undetectable
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.
 (4) The emission levels of other frequencies were very low against the limit.
 (5) Correction Factor = Insertion loss + Cable loss
 (6) Margin value = Emission level - Limit value






EUT	Wireless LAN PCI Card	MODEL	P120
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	24 deg. C, 57%RH, 962 hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.10	42.66	-	42.76	-	64.43	54.43	-21.67	-
2	0.435	0.10	35.54	-	35.64	-	57.15	47.15	-21.51	-
3	0.486	0.10	37.16	-	37.26	-	56.24	46.24	-18.98	-
4	0.591	0.10	36.47	-	36.57	-	56.00	46.00	-19.43	-
5	0.642	0.10	36.92	-	37.02	-	56.00	46.00	-18.98	-
6	0.693	0.10	36.54	-	36.64	-	56.00	46.00	-19.36	-

- NOTES:** (1) "": Undetectable
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.
 (4) The emission levels of other frequencies were very low against the limit.
 (5) Correction Factor = Insertion loss + Cable loss
 (6) Margin value = Emission level - Limit value






EUT	Wireless LAN PCI Card	MODEL	P120
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	24 deg. C, 57%RH, 962 hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.10	38.83	-	38.93	-	64.43	54.43	-25.50	-
2	0.232	0.10	33.54	-	33.64	-	62.38	52.38	-28.74	-
3	0.490	0.10	36.76	-	36.86	-	56.17	46.17	-19.31	-
4	0.588	0.10	36.33	-	36.43	-	56.00	46.00	-19.57	-
5	0.642	0.10	36.46	-	36.56	-	56.00	46.00	-19.44	-
6	0.795	0.10	36.41	-	36.51	-	56.00	46.00	-19.49	-

- NOTES:** (1) "**": Undetectable
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.
 (4) The emission levels of other frequencies were very low against the limit.
 (5) Correction Factor = Insertion loss + Cable loss
 (6) Margin value = Emission level - Limit value






EUT	Wireless LAN PCI Card	MODEL	P120
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	24 deg. C, 57%RH, 962 hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.10	42.68	-	42.78	-	64.43	54.43	-21.65	-
2	0.435	0.10	35.12	-	35.22	-	57.15	47.15	-21.93	-
3	0.486	0.10	37.76	-	37.86	-	56.24	46.24	-18.38	-
4	0.591	0.10	37.17	-	37.27	-	56.00	46.00	-18.73	-
5	0.692	0.10	36.90	-	37.00	-	56.00	46.00	-19.00	-
6	0.795	0.10	36.63	-	36.73	-	56.00	46.00	-19.27	-

- NOTES:** (1) "": Undetectable
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.
 (4) The emission levels of other frequencies were very low against the limit.
 (5) Correction Factor = Insertion loss + Cable loss
 (6) Margin value = Emission level - Limit value






EUT	Wireless LAN PCI Card	MODEL	P120
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	24 deg. C, 57%RH, 962 hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.10	38.59	-	38.69	-	64.43	54.43	-25.74	-
2	0.435	0.10	35.08	-	35.18	-	57.15	47.15	-21.97	-
3	0.486	0.10	37.47	-	37.57	-	56.24	46.24	-18.67	-
4	0.591	0.10	36.61	-	36.71	-	56.00	46.00	-19.29	-
5	0.642	0.10	35.92	-	36.02	-	56.00	46.00	-19.98	-
6	0.693	0.10	36.77	-	36.87	-	56.00	46.00	-19.13	-

- NOTES:** (1) "": Undetectable
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.
 (4) The emission levels of other frequencies were very low against the limit.
 (5) Correction Factor = Insertion loss + Cable loss
 (6) Margin value = Emission level - Limit value





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
HP Spectrum Analyzer	8594ER	3829U04676	Jul. 14, 2003
ADVANTEST Spectrum Analyzer	R3271A	85060311	May 21, 2004
CHASE RF Pre_Amplifier	CPA9232	1057	Apr. 24, 2004
HP Pre_Amplifier	8449B	3008A01281	June 27, 2004
ROHDE & SCHWARZ Test Receiver	ESVS 10	849231 /019	Nov. 03, 2003
CHASE Broadband Antenna	CBL6111c	2730	Jul 17, 2003
Schwarzbeck Horn_Antenna	BBHA9120-D1	D123	Jul. 31, 2003
SCHWARZBECK Tunable Dipole Antenna	UHAP	897	Mar. 07, 2005
SCHWARZBECK Tunable Dipole Antenna	VHAP	880	Mar. 07, 2005
RF Switches (ARNITSU)	CS-201	1565157	Jul. 29, 2003
RF CABLE (Chaintek) 1GHz-20GHz	Ak 9515-D	001	Aug, 20.2003
RF Cable(RICHTEC)	9913-30M	STCCAB-30M-1GH z-021	Nov. 5, 2003
Software	AS60P8	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
CHANCE MOST Turn Table	TT-100	0203	NA

Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Tunable Dipole Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.

2. * = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. C.
5. The FCC Site Registration No. is 656396.
6. The VCCI Site Registration No. is R-1626.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6



4.2.7 TEST RESULTS

EUT	Wireless LAN PCI Card	MODEL	P120
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	28 deg. C, 48%RH, 962 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	43.38	21.5 QP	40.00	-18.50	1.29 H	58	9.40	12.10
2	124.64	21.1 QP	43.50	-22.40	1.04 H	116	9.00	12.10
3	133.37	23.6 QP	43.50	-19.90	1.29 H	272	11.80	11.90
4	214.80	23.7 QP	43.50	-19.80	1.04 H	49	14.60	9.10
5	232.80	21.9 QP	46.00	-24.10	1.44 H	157	10.90	11.00
6	349.75	32.4 QP	46.00	-13.60	1.13 H	143	16.90	15.50
7	360.00	27.7 QP	46.00	-18.30	1.25 H	12	11.90	15.80
8	392.50	31.6 QP	46.00	-14.40	1.03 H	196	14.80	16.80
9	442.00	28.9 QP	46.00	-17.10	1.38 H	274	10.80	18.10
10	468.80	28.9 QP	46.00	-17.10	1.00 H	276	10.20	18.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	43.94	22.7 QP	40.00	-17.30	1.09 V	252	10.90	11.80
2	110.45	27.3 QP	43.50	-16.20	1.22 V	46	16.20	11.10
3	124.54	24.9 QP	43.50	-18.60	1.21 V	23	12.80	12.10
4	130.81	27.4 QP	43.50	-16.10	1.07 V	122	15.50	11.90
5	148.53	24.7 QP	43.50	-18.80	1.23 V	5	12.90	11.80
6	200.45	23.3 QP	43.50	-20.20	1.02 V	201	14.30	9.00
7	214.78	20.8 QP	43.50	-22.70	1.42 V	206	11.70	9.10
8	369.90	23.5 QP	46.00	-22.50	1.25 V	190	7.40	16.00
9	404.75	28.5 QP	46.00	-17.50	1.24 V	128	11.30	17.20
10	483.04	28.8 QP	46.00	-17.20	1.42 V	217	9.80	19.00

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247



EUT	Wireless LAN PCI Card	MODEL	P120
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	28 deg. C, 48%RH, 962 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2038.00	37.2 PK	74.00	-36.80	1.37 H	66	8.40	28.80
2	2283.00	48.5 PK	74.00	-25.50	1.32 H	7	19.00	29.50
3	2326.00	47.6 PK	74.00	-26.40	1.32 H	88	18.00	29.60
4	2368.00	50.1 PK	74.00	-23.90	1.24 H	111	20.40	29.70
5	2390.00	54.4 PK	74.00	-19.60	1.10 H	18	24.60	29.80
5	2390.00	46.6 AV	54.00	-7.40	1.10 H	18	16.80	28.80
6	*2412.00	100.6 PK			1.16 H	23	70.70	29.90
6	*2412.00	93.2 AV			1.16 H	23	63.30	29.50
7	2496.00	48.2 PK	74.00	-25.80	1.45 H	33	18.00	30.20
8	2541.00	55.0 PK	74.00	-19.00	1.27 H	31	24.70	30.30
8	2541.00	45.2 AV	54.00	-8.80	1.27 H	31	14.90	29.60
9	2588.00	51.6 PK	74.00	-22.40	1.26 H	3	21.20	30.40
9	2588.00	41.1 AV	54.00	-12.90	1.26 H	3	10.70	29.70
10	4076.00	42.4 PK	74.00	-31.60	1.21 H	25	8.40	34.00
11	4824.00	42.4 PK	74.00	-31.60	1.47 H	25	6.20	36.20
12	8152.00	48.5 PK	74.00	-25.50	1.30 H	61	4.80	43.80



ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2038.00	41.0 PK	74.00	-33.00	1.01 V	7	12.20	28.80
2	2283.00	53.5 PK	74.00	-20.50	1.24 V	58	24.00	29.50
2	2283.00	43.8 AV	54.00	-10.20	1.24 V	58	14.40	28.80
3	2326.00	55.2 PK	74.00	-18.80	1.24 V	360	25.60	29.60
3	2326.00	44.4 AV	54.00	-9.60	1.24 V	360	14.80	29.50
4	2368.00	56.0 PK	74.00	-18.00	1.13 V	8	26.30	29.70
4	2368.00	47.3 AV	54.00	-6.70	1.13 V	8	17.60	29.60
5	2390.00	57.4 PK	74.00	-16.60	1.01 V	350	27.60	29.80
5	2390.00	50.2 AV	54.00	-3.80	1.01 V	350	20.40	29.70
6	*2412.00	107.3 PK			1.01 V	354	77.40	29.90
6	*2412.00	100.0 AV			1.01 V	354	70.10	29.80
7	2496.00	51.2 PK	74.00	-22.80	1.38 V	24	21.00	30.20
7	2496.00	46.0 AV	54.00	-8.00	1.38 V	24	15.80	29.90
8	2541.00	56.9 PK	74.00	-17.10	1.24 V	28	26.60	30.30
8	2541.00	47.8 AV	54.00	-6.20	1.24 V	28	17.50	30.20
9	2588.00	54.2 PK	74.00	-19.80	1.26 V	35	23.80	30.40
9	2588.00	44.3 AV	54.00	-9.70	1.26 V	35	13.90	30.30
10	4076.00	42.9 PK	74.00	-31.10	1.20 V	9	8.90	34.00
11	4824.00	42.4 PK	74.00	-31.60	1.38 V	54	6.20	36.20
12	8152.00	53.1 PK	74.00	-20.90	1.25 V	47	9.30	43.80
12	8152.00	45.2 AV	54.00	-8.80	1.25 V	47	1.40	30.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



EUT	Wireless LAN PCI Card	MODEL	P120
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	28 deg. C, 48%RH, 962 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2063.00	38.2 PK	74.00	-35.80	1.12 H	45	9.30	28.90
2	2255.00	49.4 PK	74.00	-24.60	1.18 H	59	20.00	29.40
3	2329.00	47.6 PK	74.00	-26.40	1.32 H	76	18.00	29.60
4	2390.00	39.0 PK	74.00	-35.00	1.09 H	26	9.20	29.80
5	*2437.00	99.9 PK			1.23 H	39	69.90	30.00
5	*2437.00	92.1 AV			1.23 H	39	62.10	28.90
6	2496.00	43.7 PK	74.00	-30.30	1.36 H	77	13.60	30.20
7	2500.00	42.8 PK	74.00	-31.20	1.22 H	36	12.60	30.20
8	2560.00	50.5 PK	74.00	-23.50	1.50 H	166	20.10	30.40
9	2590.00	44.8 PK	74.00	-29.20	1.22 H	6	14.30	30.40
10	4126.00	37.2 PK	74.00	-36.80	1.11 H	62	3.20	34.10
11	4874.00	42.2 PK	74.00	-31.80	1.54 H	11	5.70	36.50
12	8252.00	49.6 PK	74.00	-24.40	1.03 H	5	5.30	44.30



ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2063.00	40.6 PK	74.00	-33.40	1.21 V	18	11.70	28.90
2	2255.00	53.2 PK	74.00	-20.80	1.32 V	358	23.80	29.40
2	2255.00	43.7 AV	54.00	-10.30	1.32 V	358	14.30	28.90
3	2329.00	54.2 PK	74.00	-19.80	1.25 V	47	24.60	29.60
3	2329.00	43.4 AV	54.00	-10.60	1.25 V	47	13.80	29.40
4	2390.00	51.8 PK	74.00	-22.20	1.32 V	68	22.00	29.80
4	2390.00	40.7 AV	54.00	-13.30	1.32 V	68	10.80	29.60
5	*2437.00	107.7 PK			4.00 V	359	77.70	30.00
5	*2437.00	99.9 AV			4.00 V	359	69.90	29.80
6	2496.00	49.2 PK	74.00	-24.80	1.25 V	49	19.10	30.20
7	2500.00	52.9 PK	74.00	-21.10	1.33 V	210	22.70	30.20
7	2500.00	43.1 AV	54.00	-10.90	1.33 V	210	12.90	30.00
8	2560.00	58.0 PK	74.00	-16.00	1.36 V	26	27.60	30.40
8	2560.00	47.4 AV	54.00	-6.60	1.36 V	26	17.00	30.20
9	2596.00	52.4 PK	74.00	-21.60	1.30 V	2	22.00	30.50
9	2596.00	42.4 AV	54.00	-11.60	1.30 V	2	12.00	30.20
10	4126.00	42.7 PK	74.00	-31.30	1.03 V	20	8.70	34.10
11	4874.00	42.1 PK	74.00	-31.90	1.32 V	62	5.60	36.50
12	8252.00	52.8 PK	74.00	-21.20	1.37 V	200	8.50	44.30
12	8252.00	45.3 AV	54.00	-8.70	1.37 V	200	1.00	30.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



EUT	Wireless LAN PCI Card	MODEL	P120
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	28 deg. C, 48%RH, 962 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2088.00	37.4 PK	74.00	-36.60	1.40 H	58	8.50	29.00
2	2244.00	43.1 PK	74.00	-30.90	1.47 H	2	13.70	29.40
3	2332.00	45.7 PK	74.00	-28.30	1.24 H	92	16.10	29.60
4	*2462.00	99.9 PK			1.17 H	34	69.90	30.10
4	*2462.00	92.2 AV			1.17 H	34	62.10	29.00
5	2484.00	54.7 PK	74.00	-19.30	1.13 H	2	24.60	30.10
5	2484.00	45.1 AV	54.00	-8.90	1.13 H	2	15.00	29.40
6	2500.00	47.9 PK	74.00	-26.10	1.42 H	350	17.70	30.20
7	2591.00	52.5 PK	74.00	-21.50	1.32 H	35	22.10	30.40
7	2591.00	43.8 AV	54.00	-10.20	1.32 H	35	13.30	29.60
8	2592.00	52.8 PK	74.00	-21.20	1.39 H	0	22.40	30.40
8	2592.00	42.6 AV	54.00	-11.40	1.39 H	0	12.10	30.10
9	2638.00	49.0 PK	74.00	-25.00	1.29 H	359	18.50	30.60
10	4176.00	42.3 PK	74.00	-31.70	1.32 H	69	8.10	34.20
11	4924.00	43.2 PK	74.00	-30.80	1.11 H	8	6.50	36.70
12	8352.00	48.6 PK	74.00	-25.40	1.50 H	2	3.70	44.90


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2088.00	39.7 PK	74.00	-34.30	1.22 V	19	10.70	29.00
2	2244.00	48.3 PK	74.00	-25.70	1.23 V	31	18.90	29.40
3	2332.00	51.0 PK	74.00	-23.00	1.26 V	72	21.40	29.60
3	2332.00	43.4 AV	54.00	-10.60	1.26 V	72	13.80	29.00
4	*2462.00	106.6 PK			1.15 V	56	76.60	30.10
4	*2462.00	99.6 AV			1.15 V	56	69.50	29.40
5	2484.00	58.8 PK	74.00	-15.20	1.11 V	7	28.70	30.10
5	2484.00	48.7 AV	54.00	-5.30	1.11 V	7	18.60	29.60
6	2500.00	52.2 PK	74.00	-21.80	1.21 V	42	22.10	30.20
6	2500.00	42.6 AV	54.00	-11.40	1.21 V	42	12.40	30.10
7	2591.00	56.8 PK	74.00	-17.20	1.26 V	32	26.30	30.40
7	2591.00	46.3 AV	54.00	-7.70	1.26 V	32	15.90	30.10
8	2593.00	56.5 PK	74.00	-17.50	1.25 V	30	26.10	30.40
8	2593.00	46.4 AV	54.00	-7.60	1.25 V	30	16.00	30.20
9	2638.00	50.2 PK	74.00	-23.80	1.27 V	33	19.60	30.60
10	4176.00	44.7 PK	74.00	-29.30	1.01 V	8	10.60	34.20
11	4924.00	42.3 PK	74.00	-31.70	1.09 V	29	5.60	36.70
12	8352.00	52.8 PK	74.00	-21.20	1.38 V	222	7.90	44.90
12	8352.00	45.8 AV	54.00	-8.20	1.38 V	222	1.00	30.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP	1093.4495.30	Dec. 19, 2003

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




4.3.7 TEST RESULTS

EUT	Wireless LAN PCI Card	MODEL	P120
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	27deg. C, 52%RH, 962 hPa
TEST BY	Eric Lee		

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	11.60	0.5	PASS
6	2437	11.52	0.5	PASS
11	2462	11.48	0.5	PASS




CH1






CH6





CH11





4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SINGLE CHANNEL POWER METER	NRVS	100026	Mar. 06, 2004
PEAK POWER SENSOR	NRV-Z32	100013	Mar. 06, 2004

NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.




4.4.3 TEST PROCEDURES

The transmitter output was connected to the peak power meter.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



4.4.7 TEST RESULTS

EUT	Wireless LAN PCI Card	MODEL	P120
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	27deg.C, 56%RH, 962 hPa
TEST BY	Eric Lee		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	15.78	30	PASS
6	2437	15.32	30	PASS
11	2462	14.89	30	PASS



4.4.8 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.4.9 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP	1093.4495.30	Dec. 19, 2003

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.10 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time = span/3 kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3 kHz for a full response of the mixer in the spectrum analyzer.

4.4.11 DEVIATION FROM TEST STANDARD

No deviation

4.4.12 TEST SETUP



4.4.13 EUT OPERATING CONDITION

Same as Item 4.3.6




4.4.14 TEST RESULTS

EUT	Wireless LAN PCI Card	MODEL	P120
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	27deg. C, 52%RH, 962 hPa
TEST BY	Eric Lee		

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-10.99	8	PASS
6	2437	-11.07	8	PASS
11	2462	-11.30	8	PASS




CH1






CH6





CH11





4.5 BAND EDGES MEASUREMENT

4.5.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP	1093.4495.30	Dec. 19, 2003

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation



4.5.5 EUT OPERATING CONDITION


Same as Item 4.3.6


4.5.6 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

NOTE (1): The band edge emission plot on the following first page shows 48.65dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 99.6dBuV/m, so the maximum field strength in restrict band is $99.6 - 48.65 = 50.95$ dBuV/m which is under 54 dBuV/m limit.

NOTE (2): The band edge emission plot on the following second page shows 47.67dB delta between carrier maximum power and local maximum emission in restrict band (2.4848GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 100dBuV/m, so the maximum field strength in restrict band is $100 - 47.67 = 52.33$ dBuV/m which is under 54 dBuV/m limit.







4.6 ANTENNA REQUIREMENT

4.6.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


4.6.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole Antenna with SMA connector. The maximum Gain of the antenna is 1.5dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.