



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822  
Tel: +82-31-323-6008 Fax: +82-31-323-6010  
<http://www.ltalab.com>



Dates of Tests: April 07 ~ 15, 2008  
Test Report S/N: LR500190804B  
Test Site : LTA CO., LTD.

## CERTIFICATION OF COMPLIANCE

FCC ID.	<b>PBN-ET18K</b>
APPLICANT	<b>ENTER TECH CO.,LTD.</b>

<b>FCC Classification</b>	:	<b>FHSS Sequence Spread Spectrum (FHSS)</b>
<b>Manufacturing Description</b>	:	<b>Magicsing Karaoke(Main Station)</b>
<b>Manufacturer</b>	:	<b>ENTER TECH CO.,LTD.</b>
<b>Model name</b>	:	<b>ET-18K</b>
<b>Test Device Serial No.:</b>	:	<b>Identical prototype</b>
<b>Rule Part(s)</b>	:	<b>FCC Part 15.247 Subpart C; ANSI C-63.4-2003</b>
<b>Frequency Range</b>	:	<b>2405 ~ 2480MHz</b>
<b>RF power</b>	:	<b>1.023mW - Conducted</b>
<b>Data of issue</b>	:	<b>April 22, 2008</b>

This test report is issued under the authority of:

The test was supervised by:

Dong -Min JUNG, Technical Manager

Kyung-Taek LEE, Test Engineer

**This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.**



NVLAP LAB Code.: 200723-0

---

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION'S .....	3
2. INFORMATION'S ABOUT TEST ITEM .....	4
3. TEST REPORT .....	5
3.1 SUMMARY OF TESTS .....	5
3.2 TECHNICAL CHARACTERISTICS TEST .....	6
3.2.1 CARRIER FREQUENCY SEPARATION .....	6
3.2.2 NUMBER OF HOPPING FREQUENCIES .....	8
3.2.3 20 dB BANDWIDTH .....	9
3.2.4 TIME OF OCCUPANCY (Dwell Time) .....	11
3.2.5 TRANSMITTER OUTPUT POWER .....	13
3.2.6 BAND – EDGE .....	15
3.2.7 FIELD STRENGTH OF HARMONICS .....	20
3.2.8 AC CONDUCTED EMISSIONS .....	24
<b>APPENDIX</b>	
APPENDIX TEST EQUIPMENT USED FOR TESTS .....	28

## 1. General information's

### 1-1 Test Performed

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### 1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2008-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2009-06-20	EMC accredited Lab.
FCC	U.S.A	610755	Updating for Renewal	FCC filing
VCCI	JAPAN	R2133, C2307	2008-06-22	VCCI registration
IC	CANADA	IC5799	Updating for Renewal	IC filing

## 2. Information's about test item

### 2-1 Applicant

Company name : ENTER TECH CO.,LTD.  
 Address : Samhwa Bldg. 401-5, Hwagok-7dong, Kangseo-gu,  
 Seoul, 157-887, Korea.  
 Tel / Fax : +82-2-2605-0884 / +82-2-2691-5354

### 2-2 Manufacturer List

Company name : ENTER TECH CO.,LTD.  
 Address : Samhwa Bldg. 401-5, Hwagok-7dong, Kangseo-gu,  
 Seoul, 157-887, Korea.

### 2-3 Equipment Under Test (EUT)

Trade name : Magicsing Karaoke(Main Station)  
 FCC ID : PBN-ET18K  
 Model name : ET-18K  
 Serial number : Identical prototype  
 Date of receipt : April 07, 2008  
 EUT condition : Pre-production, not damaged  
 Antenna Gain : Max Gain 2.118dBi  
 Frequency Range : 2405 ~ 2480MHz  
 RF output power Range : 0.00102 W - Conducted  
 Number of channels : 16  
 Channel spacing : 5MHz  
 Channel Access Protocol : Frequency Hopping  
 Type of Modulation : GFSK  
 Power Source : 9Vdc (by AC/DC Adaptor: M/N: 3A-041WU09A)

### 2-4 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2405	2445	2480

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 15 hops		C
15.247(a)	20 dB Bandwidth	-		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 1Watt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)		Radiated
15.109	Field Strength	-	C	
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:

FCC Parts 15.247, DA 00-705; ANSI C-63.4-2003

## 3.2 Transmitter requirements

### 3.2.1 Carrier Frequency Separation

#### Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 30 kHz (1% of the span or more)      Sweep = auto

VBW = 30 kHz      Detector function = peak

Trace = max hold

#### Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
5.06	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

#### Measurement Setup





Figure 1: Measurement setup for the carrier frequency separation

### Carrier Frequency Separation



### 3.2.2 Number of Hopping Frequencies

**Procedure:**


The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to:

- Frequency range    1: Start = 2389.5MHz,    Stop = 2414.5 MHz
- 2: Start = 2414.5MHz,    Stop = 2439.5 MHz
- 3: Start = 2439.5MHz,    Stop = 2464.5 MHz
- 4: Start = 2464.5MHz,    Stop = 2489.5 MHz
- RBW = 300 kHz (1% of the span or more)      Sweep = auto
- VBW = 300 kHz (VBW ≥ RBW)                    Detector function = peak
- Trace = max hold                                    Span = 25MHz

**Measurement Data: Complies**



<b>Total number of Hopping Channels</b>	16
-----------------------------------------	----

- See next pages for actual measured spectrum plots.

**Minimum Standard:**

At least 15 hopes

**Measurement Setup**

Same as the Chapter 3.2.1 (Figure 1)



### 3.2.3 20 dB Bandwidth

#### Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 2 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

Sweep = auto

VBW = 30 kHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

#### Measurement Data:

Frequency (MHz)	Channel No.	Test Results
		20dB Bandwidth (MHz)
2402	0	1.015
2441	39	1.000
2480	78	1.010

- See next pages for actual measured spectrum plots.




#### Minimum Standard:

The transmitter shall have a maximum 20dB bandwidth of 1 MHz.

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

### 20 dB Bandwidth



### 3.2.4 Time of Occupancy (Dwell Time)

#### Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW  $\geq$  RBW)

Trace = max hold

Detector function = peak

#### Measurement Data:

Channel Frequency (MHz)	Test Results				
	Duration one of Transmission (ms)	Hop.Number (6.4s)	Time of Occupancy @6.4s	Measurement time (s)	Dwell Time (s)
2445	0.7296	17	12.4	6.4	0.0124

- See next pages for actual measured spectrum plots.



#### Minimum Standard:

0.4 seconds

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

**Time of Occupancy for PACKET**



### 3.2.5 Transmitter Output Power

#### Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 1 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 1 MHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data:

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	<b>-1.96</b>	<b>0.637</b>	Complies
2441	39	<b>0.10</b>	<b>1.023</b>	Complies
2480	78	<b>-0.70</b>	<b>0.851</b>	Complies


- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	< 1W
--------------------------	------


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


### Peak Output Power



RL



RL



RL

### 3.2.6 Band Edge – Conducted Measurement

#### Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 10 MHz

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)











**Band - edge (at 20 dB blow) – High channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**



### 3.2.7 Field Strength of Harmonics

#### Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.

RBW = 100 kHz ( 30MHz ~ 1 GHz)

VBW  $\geq$  RBW

= 1 MHz (1 GHz ~ 10<sup>th</sup> harmonic )

Span = 100 MHz

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data: Complies

→ Refer to the next page.

#### Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

**Measurement Data:****1. PEAK data**

Low channel		Mid channel		High channel	
Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)
4810	51.94	4890	52.78	4960	53.11
7215	47.09	7335	49.76	7440	51.59
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
<b>Measurement uncertainty</b>		$\pm 6$ dB			

Remark: No other emissions were detected at a level greater than 20dB below limit.

**2. AVERAGE data**


Low channel		Mid channel		High channel	
Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)
4810	40.61	4890	40.57	4960	41.21
7215	36.37	7335	36.06	7440	37.87
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
<b>Measurement uncertainty</b>		$\pm 6$ dB			

Remark: No other emissions were detected at a level greater than 20dB below limit.



243 Jubug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax:+82-31-3236010

EUT/Model No.: ET-18K(ENG Adapter) TEST MODE: PLAY mode  
-----  
Temp Humi : 20 / 46 Tested by: KIM.B.S  
-----




	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV	dB	OK dBuV/m	dBuV/m	dB	cm	deg	
1	400.02	46.99	-7.48	39.51	46.00	6.49	100	21	HORIZONTAL
2	424.13	45.06	-6.97	38.09	46.00	7.91	100	158	VERTICAL
3	640.61	39.86	-2.38	37.48	46.00	8.52	100	66	VERTICAL
4	649.53	40.35	-2.21	38.14	46.00	7.86	100	69	VERTICAL
5	658.23	39.58	-2.09	37.49	46.00	8.51	100	76	VERTICAL
6	798.16	38.08	0.63	38.71	46.00	7.29	100	88	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



243 Jubug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax:+82-31-3236010

EUT/Model No.: ET-18K(ENG Adapter) TEST MODE: PC mode  
-----  
Temp Humi : 20 / 46 Tested by: KIM.B.S  
-----



	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
1	193.77	49.55	-12.85	36.70	43.50	6.80	153	218	HORIZONTAL
2	387.49	44.05	-7.72	36.33	46.00	9.67	141	117	HORIZONTAL
3	399.86	46.10	-7.48	38.62	46.00	7.38	100	264	VERTICAL
4	600.02	41.40	-2.84	38.56	46.00	7.44	100	211	VERTICAL
5	720.00	39.00	-0.99	38.01	46.00	7.99	180	296	VERTICAL
6	720.00	40.20	-0.99	39.21	46.00	6.79	100	10	HORIZONTAL
7	800.43	38.04	0.67	38.71	46.00	7.29	116	57	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

### 3.2.8 AC Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 10dB below limit.

#### Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency




### AC Conducted Emissions –Line



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel +82-31-323-6008  
Fax:+82-31-323-6010

EUT / Model No. : ET-18K(ENG Adapter)	Phase : LINE
Test Mode : PLAY mode	Test Power : 120 / 60
Temp./Humi. : 21 / 35	Test Engineer : B.S.KIM

Data: 318 File: E:\00\_e3 EMI DATA\2008\LTA\_Conduction\_0804\_1.EMI (524) Date: 2008-04-08



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.175	55.60	48.30	0.38	55.98	48.68	64.72	54.72	8.74	6.04
0.223	50.20	41.40	0.20	50.40	41.60	62.71	52.71	12.30	11.10
0.290	42.70	38.60	0.27	42.97	38.87	60.52	50.52	17.55	11.65
0.348	42.50	40.90	0.33	42.83	41.23	59.01	49.01	16.18	7.78
0.407	39.00	38.10	0.38	39.38	38.48	57.71	47.71	18.33	9.23
0.583	39.40	37.90	0.29	39.69	38.19	56.00	46.00	16.31	7.81

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss


### AC Conducted Emissions -Neutral



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel +82-31-323-6008  
Fax:+82-31-323-6010

EUT / Model No. : ET-18K(ENG Adapter)	Phase : NEUTRAL
Test Mode : PLAY mode	Test Power : 120 / 60
Temp./Humi. : 21 / 35	Test Engineer : B.S.KIM

Data: 316 File: E:\00\_e3 EMI DATA\2008\LTA\_Conduction\_0804\_1.EMI (524) Date: 2008-04-08



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.174	53.00	45.30	0.39	53.39	45.69	64.77	54.77	11.38	9.08
0.216	49.70	41.00	0.20	49.90	41.20	62.97	52.97	13.07	11.77
0.290	42.80	38.30	0.27	43.07	38.57	60.52	50.52	17.45	11.95
0.348	41.20	39.60	0.33	41.53	39.93	59.01	49.01	17.48	9.08
0.407	37.90	36.30	0.38	38.28	36.68	57.71	47.71	19.43	11.03
0.583	38.70	37.00	0.29	38.99	37.29	56.00	46.00	17.01	8.71

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss


### AC Conducted Emissions –Line



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel +82-31-323-6008  
Fax:+82-31-323-6010

EUT / Model No. : ET-18K(ENG Adapter)	Phase : LINE
Test Mode : PC mode	Test Power : 120 / 60
Temp./Humi. : 17 / 45	Test Engineer : B.S.KIM

Data: 364 File: E:\00\_e3 EMI DATA\2008\LTA\_Conduction\_0804\_1.EMI (524) Date: 2008-04-11



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.347	40.10	38.80	0.33	40.43	39.13	59.03	49.03	18.60	9.90
0.578	37.80	37.00	0.29	38.09	37.29	56.00	46.00	17.91	8.71
0.636	38.10	36.90	0.30	38.40	37.20	56.00	46.00	17.60	8.80
0.866	38.40	36.90	0.41	38.81	37.31	56.00	46.00	17.19	8.69
1.098	36.60	34.90	0.32	36.92	35.22	56.00	46.00	19.08	10.78
1.564	38.90	36.00	0.38	39.28	36.38	56.00	46.00	16.72	9.62

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss


## AC Conducted Emissions –Neutral



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel +82-31-323-6008  
Fax:+82-31-323-6010

EUT / Model No. : ET-18K(ENG Adapter)	Phase : NEUTRAL
Test Mode : PC mode	Test Power : 120 / 60
Temp./Humi. : 17 / 45	Test Engineer : B.S.KIM

Data: 366      File: E:\00\_e3 EMI DATA\2008\LTA\_Conduction\_0804\_1.EMI (524)      Date: 2008-04-11



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.346	41.80	40.80	0.33	42.13	41.13	59.06	49.06	16.93	7.93
0.403	39.10	38.00	0.38	39.48	38.38	57.79	47.79	18.31	9.41
0.575	39.30	38.30	0.29	39.59	38.59	56.00	46.00	16.41	7.41
0.634	39.80	38.60	0.30	40.10	38.90	56.00	46.00	15.90	7.10
0.865	40.10	38.50	0.41	40.51	38.91	56.00	46.00	15.49	7.09
1.559	41.40	39.60	0.38	41.78	39.98	56.00	46.00	14.22	6.02

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

## APPENDIX

### TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	8594E	3649A03649	HP	Apr-09
2	Signal Generator	8648C	3623A02597	HP	Apr-09
3	Attenuator (3dB)	8491A	37822	HP	Oct-08
4	Attenuator (10dB)	8491A	63196	HP	Oct-08
5	EMI Test Receiver	ESVD	843748/001	R&S	Aug-08
6	LISN	KNW-407	8-1430-1	Kyoritsu	Oct-08
7	Two-Line V-Network	ESH3-Z5	893045/017	R&S	Oct-08
8	RF Amplifier	8447D	2949A02670	HP	Apr-09
9	RF Amplifier	8447D	2439A09058	HP	Oct-08
10	RF Amplifier	8449B	3008A02126	HP	Apr-09
11	Test Receiver	ESHS10	828404009	R&S	Aug-08
12	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Jul-08
13	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-09
14	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-09
15	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-09
16	Dipole Antenna	VHA9103	2116	Schwarzbeck	Nov-08
17	Dipole Antenna	VHA9103	2117	Schwarzbeck	Nov-08
18	Dipole Antenna	UHA9105	2261	Schwarzbeck	Nov-08
19	Dipole Antenna	UHA9105	2262	Schwarzbeck	Nov-08
20	Spectrum Analyzer	8591E	3649A05888	HP	Oct-08
21	Spectrum Analyzer	8563E	3425A02505	HP	Apr-09
22	Hygro-Thermograph	THB-36	0041557-01	ISUZU	May-08
23	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	Jun-08
24	RF Switch	MP59B	6200414971	ANRITSU	Jun-08
25	RF Switch	MP59B	6200438565	ANRITSU	Jun-08
26	Power Divider	11636A	6243	HP	Oct-08
27	DC Power Supply	6622A	3448A03079	HP	Oct-08
28	Attenuator (30dB)	11636A	6243	HP	Oct-08
29	Frequency Counter	5342A	2826A12411	HP	Apr-09
30	Power Meter	EPM-441A	GB32481702	HP	Apr-09
31	Power Sensor	8481A	2702A64048	HP	Apr-09
32	Audio Analyzer	8903B	3729A18901	HP	Oct-08
33	Modulation Analyzer	8901B	3749A05878	HP	Oct-08
34	TEMP & HUMIDITY Chamber	YJ-500	L05022	JinYoung Tech	Oct-08
35	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-09