

FCC PART 15.249

TEST REPORT

For

OKIN Refined Electric Technology Co., Ltd.

Plant 4, No. 410, Xinyonglian Road, Wangjiangjing Development Zone, Jiaxing, Zhejiang, China

FCC ID: PCU-CU3582PA

| | | | |
|--|--|-------------------------------------|--|
| Report Type: Original Report | | Product Type: Control box | |
| Test Engineer: | Edison Hu | <i>Edison Hu</i> | |
| Report Number: | RSHA180122003-00B | | |
| Report Date: | 2018-02-28 | | |
| Reviewed By: | Oscar Ye RF Leader | <i>Oscar Ye</i> | |
| Test Laboratory: | Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn | | |

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

| | |
|---|-----------|
| GENERAL INFORMATION..... | 3 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 3 |
| OBJECTIVE | 3 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 3 |
| TEST METHODOLOGY | 3 |
| MEASUREMENT UNCERTAINTY | 4 |
| TEST FACILITY | 4 |
| SYSTEM TEST CONFIGURATION..... | 5 |
| JUSTIFICATION | 5 |
| EUT EXERCISE SOFTWARE | 5 |
| SUPPORT EQUIPMENT LIST AND DETAILS | 5 |
| EXTERNAL I/O CABLE..... | 5 |
| BLOCK DIAGRAM OF TEST SETUP | 6 |
| SUMMARY OF TEST RESULTS | 8 |
| TEST EQUIPMENT LIST | 9 |
| FCC§15.203 - ANTENNA REQUIREMENT..... | 10 |
| APPLICABLE STANDARD | 10 |
| ANTENNA CONNECTOR CONSTRUCTION | 10 |
| FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS | 11 |
| APPLICABLE STANDARD | 11 |
| EUT SETUP | 11 |
| EMI TEST RECEIVER SETUP..... | 11 |
| TEST PROCEDURE | 11 |
| CORRECTED FACTOR & MARGIN CALCULATION | 12 |
| TEST RESULTS SUMMARY | 12 |
| TEST DATA | 12 |
| FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION..... | 15 |
| APPLICABLE STANDARD | 15 |
| EUT SETUP | 15 |
| TEST EQUIPMENT SETUP | 16 |
| TEST PROCEDURE | 16 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 17 |
| TEST RESULTS SUMMARY | 17 |
| TEST DATA | 17 |
| FCC §15.215(C) – 20 DB BANDWIDTH TESTING | 24 |
| APPLICABLE STANDARD | 24 |
| TEST PROCEDURE | 24 |
| TEST DATA | 24 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

| | |
|------------------|---|
| Applicant | OKIN Refined Electric Technology Co., Ltd. |
| Tested Model | JLDP.15.005.501 |
| Series Model | JLDP.15.005.502; JLDP.15.005.503; JLDP.15.005.504 |
| Model Difference | Model name |
| Product Type | Control box |
| Dimension | 120mm(L)*98mm(W)*38mm(H) |
| Power Supply | DC 29V from Adapter |

Adapter Information:

Model: 02-290020

Input: AC100-240 V 50/60Hz 1.5A

Output: 29V, 2A

All measurement and test data in this report was gathered from production sample serial number: 20180122003. (Assigned by BACL, Kunshan). The EUT was received on 2018-01-22.

Objective

This type approval report is prepared on behalf of OKIN Refined Electric Technology Co., Ltd. in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

FCC Part15.249 DXX submission with FCC ID: PCU-RF366C.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

| Item | | Uncertainty |
|------------------------------------|-------------|-------------|
| AC Power Lines Conducted Emissions | | 3.19 dB |
| RF conducted test with spectrum | | 0.9dB |
| RF Output Power with Power meter | | 0.5dB |
| Radiated emission | 30MHz~1GHz | 6.11dB |
| | 1GHz~6GHz | 4.45dB |
| | 6GHz~18GHz | 5.23dB |
| | 18GHz~40GHz | 5.65dB |
| Occupied Bandwidth | | 0.5kHz |
| Temperature | | 1.0°C |
| Humidity | | 6% |

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Justification

Channel list:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1 | 2403 | 40 | 2442 |
| 2 | 2404 | 41 | 2443 |
| ... | ... | ... | ... |
| 38 | 2440 | 77 | 2479 |
| 39 | 2441 | 78 | 2480 |

EUT was tested with channel 1, 40 and 78.

EUT Exercise Software

No software was used during the test.

Support Equipment List and Details


| Manufacturer | Description | Model | Serial Number |
|--------------|----------------|-------|----------------------|
| OKIN Refined | Motor1 | 73842 | 68000010150A43990093 |
| OKIN Refined | Motor2 | 73851 | 68000009150B18360292 |
| OKIN Refined | Power Down Box | 74389 | 68000087161727012126 |

External I/O Cable


| Cable Description | Length (m) | From Port | To |
|-------------------|------------|-----------|---------|
| Power Cable | 1.0 | EUT | Adapter |

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|--------------------------|--|---------------|
| §15.203 | Antenna Requirement | Compliant |
| §15.207(a) | Conduction Emissions | Compliant |
| 15.205, §15.209, §15.249 | Radiated Emissions& Out of Band Emission | Compliant |
| §15.215 (e) | 20 dB Bandwidth | Compliant |

TEST EQUIPMENT LIST

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--|--------------------|---------------------|---------------|------------------|----------------------|
| Radiated Emission Test (Chamber 1#) | | | | | |
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100195 | 2017-11-12 | 2018-11-11 |
| Sunol Sciences | Broadband Antenna | JB3 | A090413-1 | 2016-12-26 | 2019-12-25 |
| Sonoma Instrument | Pre-amplifier | 310N | 171205 | 2017-08-15 | 2018-08-14 |
| Rohde & Schwarz | Auto test Software | EMC32 | 100361 | / | / |
| MICRO-COAX | Coaxial Cable | Cable-8 | 008 | 2017-08-15 | 2018-08-14 |
| MICRO-COAX | Coaxial Cable | Cable-9 | 009 | 2017-08-15 | 2018-08-14 |
| MICRO-COAX | Coaxial Cable | Cable-10 | 010 | 2017-08-15 | 2018-08-14 |
| Radiated Emission Test (Chamber 2#) | | | | | |
| Rohde & Schwarz | EMI Test Receiver | ESU40 | 100207 | 2017-08-27 | 2018-08-26 |
| ETS-LINDGREN | Horn Antenna | 3115 | 6229 | 2016-01-11 | 2019-01-10 |
| ETS-LINDGREN | Horn Antenna | 3116 | 00084159 | 2016-10-18 | 2019-10-17 |
| SINOSCITE | Band Reject Filter | BSF2400-2483MN-0995 | / | 2017-08-05 | 2018-08-04 |
| Narda | Pre-amplifier | AFS42-00101800 | 2001270 | 2017-12-12 | 2018-12-11 |
| Quinstar | Amplifier | QLW-18405536-J0 | 15964001009 | 2017-12-12 | 2018-12-11 |
| Narda | Attenuator/10dB | 10dB | / | 2017-08-15 | 2018-08-14 |
| Rohde & Schwarz | Auto test Software | EMC32 | 100361 | / | / |
| MICRO-COAX | Coaxial Cable | Cable-6 | 006 | 2017-08-15 | 2018-08-14 |
| MICRO-COAX | Coaxial Cable | Cable-11 | 011 | 2017-08-15 | 2018-08-14 |
| MICRO-COAX | Coaxial Cable | Cable-12 | 012 | 2017-08-15 | 2018-08-14 |
| MICRO-COAX | Coaxial Cable | Cable-13 | 013 | 2017-08-15 | 2018-08-14 |
| RF Conducted Test | | | | | |
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 836131/009 | 2017-09-21 | 2018-09-20 |
| Narda | Attenuator/6dB | 6dB | / | 2017-08-15 | 2018-08-14 |
| OKIN Refined | RF Cable | / | / | / | / |
| Conducted Emission Test | | | | | |
| Rohde & Schwarz | EMI Test Receiver | ESCS30 | 834115/007 | 2017-11-12 | 2018-11-11 |
| Rohde & Schwarz | LISN | ESH3-Z5 | 862770/011 | 2017-11-12 | 2018-11-11 |
| Rohde & Schwarz | LISN | ENV216 | 3560655016 | 2017-11-12 | 2018-11-11 |
| BACL | Auto test Software | BACL-EMC | CE001 | / | / |
| Narda | Attenuator/6dB | 10690812-2 | 26850-6 | 2018-01-10 | 2019-01-09 |
| MICRO-COAX | Coaxial Cable | Cable-15 | 015 | 2017-08-15 | 2018-08-14 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has a PCB antenna and antenna gain is 0 dBi, which was permanently attached ,fulfill the requirement of this section, please refer to the EUT photos.

Result: Compliant.


FINAL

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Corrected Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Reading}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 24.6°C |
| Relative Humidity: | 52% |
| ATM Pressure: | 101.3 kPa |

The testing was performed by Edison Hu on 2018-01-25.


EUT operation mode: Transmitting in low channel (worst case)

AC 120V/60 Hz, Line



| Frequency (MHz) | Reading (dBµV) | Detector (PK/AV/QP) | Bandwidth (kHz) | Line | Corrected Factor (dB) | Limit (dBµV) | Margin (dB) | Comment |
|-----------------|----------------|---------------------|-----------------|------|-----------------------|--------------|-------------|-----------|
| 0.150 | 58.79 | QP | 9.000 | L1 | 16.06 | 66.00 | 7.21 | Compliant |
| 0.150 | 43.62 | AV | 9.000 | L1 | 16.06 | 56.00 | 12.38 | Compliant |
| 0.395 | 43.53 | QP | 9.000 | L1 | 16.06 | 59.00 | 15.47 | Compliant |
| 0.395 | 35.64 | AV | 9.000 | L1 | 16.06 | 49.00 | 13.36 | Compliant |
| 1.000 | 36.86 | QP | 9.000 | L1 | 15.88 | 56.00 | 19.14 | Compliant |
| 1.000 | 22.94 | AV | 9.000 | L1 | 15.88 | 46.00 | 23.06 | Compliant |
| 2.750 | 29.00 | QP | 9.000 | L1 | 15.85 | 56.00 | 27.00 | Compliant |
| 2.750 | 20.79 | AV | 9.000 | L1 | 15.85 | 46.00 | 25.21 | Compliant |
| 5.450 | 35.38 | QP | 9.000 | L1 | 15.88 | 60.00 | 24.62 | Compliant |
| 5.500 | 26.01 | AV | 9.000 | L1 | 15.88 | 50.00 | 23.99 | Compliant |
| 14.750 | 32.37 | QP | 9.000 | L1 | 16.20 | 60.00 | 27.63 | Compliant |
| 14.850 | 28.07 | AV | 9.000 | L1 | 16.21 | 50.00 | 21.93 | Compliant |

AC 120V/60 Hz, Neutral



| Frequency (MHz) | Reading (dBμV) | Detector (PK/AV/QP) | Bandwidth (kHz) | Line | Corrected Factor (dB) | Limit (dBμV) | Margin (dB) | Comment |
|-----------------|----------------|---------------------|-----------------|------|-----------------------|--------------|-------------|-----------|
| 0.150 | 53.97 | QP | 9.000 | N | 16.06 | 66.00 | 12.03 | Compliant |
| 0.150 | 36.08 | AV | 9.000 | N | 16.06 | 56.00 | 19.92 | Compliant |
| 0.400 | 44.04 | QP | 9.000 | N | 16.09 | 58.86 | 14.82 | Compliant |
| 0.400 | 40.26 | AV | 9.000 | N | 16.09 | 48.86 | 8.60 | Compliant |
| 1.200 | 28.40 | QP | 9.000 | N | 15.93 | 56.00 | 27.60 | Compliant |
| 1.200 | 20.04 | AV | 9.000 | N | 15.93 | 46.00 | 25.96 | Compliant |
| 3.050 | 26.72 | QP | 9.000 | N | 15.90 | 56.00 | 29.28 | Compliant |
| 3.050 | 19.24 | AV | 9.000 | N | 15.90 | 46.00 | 26.76 | Compliant |
| 5.450 | 33.61 | QP | 9.000 | N | 15.88 | 60.00 | 26.39 | Compliant |
| 5.450 | 25.45 | AV | 9.000 | N | 15.88 | 50.00 | 24.55 | Compliant |
| 12.500 | 31.25 | QP | 9.000 | N | 16.00 | 60.00 | 28.75 | Compliant |
| 12.500 | 26.01 | AV | 9.000 | N | 16.00 | 50.00 | 23.99 | Compliant |

Note:

- 1) Corrected Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation
- 2) Margin = Limit – Reading

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:


| Fundamental frequency | Field strength of fundamental (millivolts/meter) | Field strength of harmonics (microvolts/meter) |
|-----------------------|--|--|
| 902–928 MHz | 50 | 500 |
| 2400–2483.5 MHz | 50 | 500 |
| 5725–5875 MHz | 50 | 500 |
| 24.0–24.25 GHz | 250 | 2500 |

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Test Equipment Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Detector |
|-------------------|---------|-----------|---------|----------|
| 30 MHz – 1000 MHz | 120 kHz | 300 kHz | 120 kHz | QP |
| Above 1GHz | 1MHz | 3 MHz | / | PK |
| | 1MHz | 3 MHz | / | Ave |

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode from 30MHz to 1GHz, Peak and average detection mode above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 & 15.205 & 15.249.

Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 24.6°C |
| Relative Humidity: | 52% |
| ATM Pressure: | 101.2 kPa |


The testing was performed by Edison Hu on 2018-01-31.

Test Mode: Transmitting (Scan with X-Axis, Y-Axis and Z-Axis position, the worst case X-Axis was recorded)

Spurious Emission Test:

30MHz-1GHz

*(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in X-axis of orientation was recorded)*



| Frequency (MHz) | Corrected Amplitude | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | Quasi-peak (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 45.536120 | 12.49 | 199.0 | H | 104.0 | -14.9 | 40.00 | 27.51 |
| 49.927280 | 31.55 | 101.0 | V | 111.0 | -17.9 | 40.00 | 8.45 |
| 52.494830 | 31.06 | 101.0 | V | 0.0 | -18.1 | 40.00 | 8.94 |
| 135.488350 | 9.60 | 199.0 | V | 192.0 | -12.2 | 43.50 | 33.90 |
| 193.063100 | 10.20 | 199.0 | V | 124.0 | -13.2 | 43.50 | 33.30 |
| 222.064580 | 17.35 | 101.0 | H | 153.0 | -12.7 | 46.00 | 28.65 |

1GHz-18GHz


(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)

Note:

1. This test was performed with the 2.4-2.4835GHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit – Corrected. Amplitude

Low Channel: 2403MHz


Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|-------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV /m) | Average (dBμV /m) | Height (cm) | Polar (H/V) | | | | |
| 1200.600000 | 34.31 | --- | 150.0 | H | 150.0 | -10.4 | 74.00 | 39.69 |
| 1200.600000 | --- | 25.66 | 150.0 | H | 150.0 | -10.4 | 54.00 | 28.34 |
| 3597.600000 | 37.74 | --- | 200.0 | V | 308.0 | -0.6 | 74.00 | 36.26 |
| 3597.600000 | --- | 31.85 | 200.0 | V | 308.0 | -0.6 | 54.00 | 22.15 |
| 4806.000000 | 50.39 | --- | 200.0 | H | 195.0 | 2.5 | 74.00 | 23.61 |
| 4806.000000 | --- | 40.43 | 200.0 | H | 195.0 | 2.5 | 54.00 | 13.57 |
| 7209.000000 | 49.13 | --- | 150.0 | H | 102.0 | 9.8 | 74.00 | 24.87 |
| 7209.000000 | --- | 40.10 | 150.0 | H | 102.0 | 9.8 | 54.00 | 13.90 |
| 9612.200000 | 51.11 | --- | 150.0 | V | 123.0 | 14.9 | 74.00 | 22.89 |
| 9612.200000 | --- | 41.98 | 150.0 | V | 123.0 | 14.9 | 54.00 | 12.02 |
| 12016.000000 | 53.51 | --- | 150.0 | H | 102.0 | 16.5 | 74.00 | 20.49 |
| 12016.000000 | --- | 44.84 | 150.0 | H | 102.0 | 16.5 | 54.00 | 9.16 |

Middle Channel: 2442MHz


Full Spectrum



| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|-------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV /m) | Average (dBμV /m) | Height (cm) | Polar (H/V) | | | | |
| 1221.000000 | 34.49 | --- | 150.0 | H | 157.0 | -10.2 | 74.00 | 39.51 |
| 1221.000000 | --- | 21.76 | 150.0 | H | 157.0 | -10.2 | 54.00 | 32.24 |
| 3597.600000 | 36.32 | --- | 200.0 | V | 212.0 | -0.6 | 74.00 | 37.68 |
| 3597.600000 | --- | 31.95 | 200.0 | V | 212.0 | -0.6 | 54.00 | 22.05 |
| 4884.000000 | 47.43 | --- | 150.0 | H | 126.0 | 2.7 | 74.00 | 26.57 |
| 4884.000000 | --- | 37.33 | 150.0 | H | 126.0 | 2.7 | 54.00 | 16.67 |
| 7326.000000 | 49.31 | --- | 200.0 | H | 85.0 | 10.0 | 74.00 | 24.69 |
| 7326.000000 | --- | 39.28 | 150.0 | H | 110.0 | 10.0 | 54.00 | 14.72 |
| 9765.200000 | --- | 42.99 | 200.0 | V | 29.0 | 14.9 | 54.00 | 11.01 |
| 9765.200000 | 52.46 | --- | 200.0 | V | 29.0 | 14.9 | 74.00 | 21.54 |
| 12206.400000 | 53.17 | --- | 200.0 | H | 149.0 | 16.8 | 74.00 | 20.83 |
| 12206.400000 | --- | 44.01 | 150.0 | H | 48.0 | 16.8 | 54.00 | 9.99 |

High Channel: 2480MHz

Full Spectrum




| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBμV/m) | Average (dBμV/m) | Height (cm) | Polar (H/V) | | | | |
| 1238.000000 | 33.36 | --- | 200.0 | H | 165.0 | -10.1 | 74.00 | 40.64 |
| 1238.000000 | --- | 24.39 | 200.0 | H | 165.0 | -10.1 | 54.00 | 29.61 |
| 3597.600000 | 35.96 | --- | 200.0 | V | 56.0 | -0.6 | 74.00 | 38.04 |
| 3597.600000 | --- | 33.04 | 200.0 | V | 56.0 | -0.6 | 54.00 | 20.96 |
| 4960.000000 | 47.31 | --- | 150.0 | H | 149.0 | 2.8 | 74.00 | 26.69 |
| 4960.000000 | --- | 36.08 | 150.0 | H | 149.0 | 2.8 | 54.00 | 17.92 |
| 7440.000000 | 52.01 | --- | 150.0 | H | 86.0 | 10.1 | 74.00 | 21.99 |
| 7440.000000 | --- | 42.96 | 150.0 | H | 86.0 | 10.1 | 54.00 | 11.04 |
| 9921.600000 | 50.81 | --- | 150.0 | V | 338.0 | 14.9 | 74.00 | 23.19 |
| 9921.600000 | --- | 42.49 | 150.0 | V | 338.0 | 14.9 | 54.00 | 11.51 |
| 12400.200000 | 53.05 | --- | 150.0 | H | 117.0 | 17.0 | 74.00 | 20.95 |
| 12400.200000 | --- | 44.52 | 200.0 | H | 349.0 | 17.0 | 54.00 | 9.48 |

18GHz-25GHz


(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case low channel of operation in X-axis of orientation was recorded)

Horizontal



Date: 31.JAN.2018 10:52:12

Vertical



Date: 31.JAN.2018 10:24:24

Fundamental Test & Restricted Bands Emissions Test:

(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)

Note:

1. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
2. Corrected Amplitude = Corrected Factor + Reading
3. Margin = Limit - Corrected. Amplitude

| Frequency (MHz) | Corrected Amplitude | | Rx Antenna | | Turntable Degree | Corrected Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|--------------------------------|---------------------|-------------------|-------------|-------------|------------------|-------------------------|----------------|-------------|
| | MaxPeak (dBµV /m) | Average (dBµV /m) | Height (cm) | Polar (H/V) | | | | |
| Low Channel: 2403MHz | | | | | | | | |
| 2390.00 | 48.69 | --- | 200 | H | 161 | 5.1 | 74 | 25.31 |
| 2390.00 | --- | 39.28 | 200 | H | 161 | 5.1 | 54 | 14.72 |
| 2403.00 | 92.97 | --- | 200 | H | 128 | 5.1 | 114 | 21.03 |
| 2403.00 | --- | 92.93 | 200 | H | 128 | 5.1 | 94 | 1.07 |
| Middle Channel: 2442MHz | | | | | | | | |
| 2442.00 | 93.96 | --- | 250 | H | 231 | 5.2 | 114 | 20.04 |
| 2442.00 | --- | 92.75 | 250 | H | 231 | 5.2 | 94 | 1.25 |
| High Channel: 2480MHz | | | | | | | | |
| 2480.00 | --- | 92.54 | 150 | H | 50 | 5.3 | 94 | 1.46 |
| 2480.00 | 94.57 | --- | 150 | H | 50 | 5.3 | 114 | 19.43 |
| 2483.50 | 50.71 | --- | 200 | H | 36 | 5.3 | 74 | 23.29 |
| 2483.50 | --- | 40.17 | 200 | H | 36 | 5.3 | 54 | 13.83 |

FCC §15.215(c) – 20 dB BANDWIDTH TESTING

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

| | |
|---------------------------|----------|
| Temperature: | 24.2°C |
| Relative Humidity: | 51 % |
| ATM Pressure: | 101.2kPa |

The testing was performed by Edison Hu on 2018-01-29 to 2018-02-07.


Test Result: Compliant.

Test Mode: Transmitting


| Channel | Frequency (MHz) | 20 dB Bandwidth (MHz) |
|---------|-----------------|-----------------------|
| Low | 2403.00 | 0.902 |
| Middle | 2442.00 | 0.980 |
| High | 2480.00 | 0.944 |

20 dB Bandwidth:


Low Channel



Middle Channel



High Channel



***** END OF REPORT *****