Results tables:

Mode	Rate	Channel	Frequency [MHz]	Antenna	PSD Peak [dBm]
		,	2412	SISO CHAIN A	-3.46
		1		SISO CHAIN B	-3.02
		7	2442	SISO CHAIN A	-1.92
				SISO CHAIN B	-2.00
000 441	4841		2462	SISO CHAIN A	-3.59
802.11b	1Mbps	11		SISO CHAIN B	-3.68
		40	0.407	SISO CHAIN A	-5.51
		12	2467	SISO CHAIN B	-5.66
		13	2472	SISO CHAIN A	-7.26
		13	2472	SISO CHAIN B	-7.19
		1	2442	SISO CHAIN A	-4.84
		1	2412	SISO CHAIN B	-4.20
		7	2442	SISO CHAIN A	-3.16
		/	2442	SISO CHAIN B	-2.97
902.114	6Mbpa	11	0.400	SISO CHAIN A	-5.16
802.11g	6Mbps	11	2462	SISO CHAIN B	-5.15
		12	2467	SISO CHAIN A	-9.79
		12		SISO CHAIN B	-8.22
		13	2472	SISO CHAIN A	-25.56
				SISO CHAIN B	-26.73
	НТ0	1	2412	SISO CHAIN A	-5.07
				SISO CHAIN B	-4.61
		7	2442	SISO CHAIN A	-2.44
				SISO CHAIN B	-2.29
802.11n20		11	2462	SISO CHAIN A	-7.00
802.111120				SISO CHAIN B	-6.76
		12	2467	SISO CHAIN A	-11.28
				SISO CHAIN B	-11.51
		13	2472	SISO CHAIN A	-24.30
		13		SISO CHAIN B	-26.20
		3F	2/122	SISO CHAIN A	-8.99
		JI	2422	SISO CHAIN B	-8.64
802.11n40	HT0	7F	2442	SISO CHAIN A	-9.30
		7 -	Z44Z	SISO CHAIN B	-9.21
		9F	2452	SISO CHAIN A	-10.54
				SISO CHAIN B	-10.97
		10F	2457	SISO CHAIN A	-13.65
				SISO CHAIN B	-14.13
		11F	2462	SISO CHAIN A	-28.69
			2702	SISO CHAIN B	-27.71


Rev. 00

MIMO modes					PSD Peak [dBm]		
Mode	Rate	СН	Freq. [MHz]	Antenna	Measured Conducted	MIMO Combined +10·log(N _{ant})	
		1	2412	CHAIN A	-7.20	-4.19	
				CHAIN B	-5.53	-2.52	
		7	2442	CHAIN A	-5.78	-2.77	
		,	2442	CHAIN B	-6.05	-3.04	
002 11520	НТ8	44	2462	CHAIN A	-7.82	-4.81	
802.11n20		11		CHAIN B	-7.82	-4.81	
		12	2467	CHAIN A	-12.85	-9.84	
				CHAIN B	-12.57	-9.56	
		13	2472	CHAIN A	-29.38	-26.37	
				CHAIN B	-30.21	-27.20	
	НТ8	3F	2422	CHAIN A	-11.38	-8.37	
				CHAIN B	-9.67	-6.66	
		7F	2442	CHAIN A	-9.65	-6.64	
				CHAIN B	-9.44	-6.43	
000 11510		9F	2452	CHAIN A	-10.77	-7.76	
802.11n40				CHAIN B	-10.57	-7.56	
		10F	2457	CHAIN A	-14.82	-11.01	
			2457	CHAIN B	-14.47	-11.46	
		11F	2462	CHAIN A	-31.21	-28.20	
			2462	CHAIN B	-30.92	-27.91	




Results screenshot:


802.11b, 1Mbps



























802.11g, 6Mbps



















802.11n20, HT0 (SISO)
























802.11n20, HT8 (MIMO)



























802.11n40, HT0 (SISO)



















802.11n40, HT8 (MIMO)





















B.4 Out-of-band emissions (conducted)

Test limits:

FCC part	RSS part	Limits						
15.247 (d)	RSS-247 Clause 5.5	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.						
15.209	RSS-247 Clause 6.2.2 (2)	the peak conducted power limits. Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a): Freq Range						

Test procedure:

The setup below was used to measure the out-of-band emissions. The antenna terminal of the EUT is connected to the spectrum analyzer through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

The Band Edge High, was measured using the method according to point 13.3 (Integration Method) of KDB 558074 D01 DTS Meas Guidance v03r05.


In case of Band Edge measurements falling in restricted bands, the declared Antenna Gain is also compensated in the graph. The declared maximum antenna gain is 3.24dBi.

For Band Edge measurements falling in restricted bands, the following limits in dBm were applied for the average detector after the conversion from the limits detailed above in dB μ V/m, according to FCC 47 CFR part 15 - Subpart C – §15.209(a). The limits in dBm for peak detector are 20dB above the indicated values in the table.

	§15.209(a)		Converted values		
Freq Range (MHz)	Distance (m)	Field strength (microvolts/meter)	Field strength (dB microvolts/meter)	Power (dBm)	
Above 960	3	500	54.0	-41.2	



The setup below was used to measure the out-of-band emissions. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.



Note: these PSD_{Peak} values are shown just as a reference for the compliance of the Out-of-band Measurements. Thus the RBW used for these measurements was 100kHz.

Mode	Rate	Measured Duty Cycle [%]	Channel	Frequency [MHz]	Antenna	PSD Peak [dBm]
			1	2412	SISO CHAIN A	9.8
			ı	2412	SISO CHAIN B	10.28
			7	2437	SISO CHAIN A	11.54
			,		SISO CHAIN B	11.32
802.11b	1Mbpc		11	0.460	SISO CHAIN A	9.71
602.110	1Mbps		11	2462	SISO CHAIN B	9.71
			10	2467	SISO CHAIN A	7.98
			12		SISO CHAIN B	7.76
				13 2472	SISO CHAIN A	6.01
			13		SISO CHAIN B	6.17
802.11g	6Mbps		6 11	2412	SISO CHAIN A	8.31
				2412	SISO CHAIN B	8.97
				2437	SISO CHAIN A	10.52
					SISO CHAIN B	10.35
				2462	SISO CHAIN A	8
					SISO CHAIN B	8.06
				0.407	SISO CHAIN A	3.64
		12	2467	SISO CHAIN B	5.05	
			13	2472	SISO CHAIN A	-12.11
					SISO CHAIN B	-13.41




Mode	Rate	Measured Duty Cycle [%]	Channel	Frequency [MHz]	Antenna	PSD Peak [dBm]
			1	2412	SISO CHAIN A	7.89
					SISO CHAIN B	8.69
			_		SISO CHAIN A	10.41
			7	2442	SISO CHAIN B	10.51
	LITO		4.4	2462	SISO CHAIN A	5.58
	HT0	96.7	11		SISO CHAIN B	5.61
			40		SISO CHAIN A	1.16
			12	2467	SISO CHAIN B	1.11
			40	0.470	SISO CHAIN A	-11.62
000 44 : 00			13	2472	SISO CHAIN B	-13.29
802.11n20			4	0440	MIMO CHAIN A	6.74
			1	2412	MIMO CHAIN B	7.39
			7	2442	MIMO CHAIN A	7.79
			7	2442	MIMO CHAIN B	7.49
		07.4	4.4	0.460	MIMO CHAIN A	5.82
	HT8	97.4	11	2462	MIMO CHAIN B	5.69
			40	2467	MIMO CHAIN A	1
			12		MIMO CHAIN B	1.12
			13	2472	MIMO CHAIN A	-15.23
					MIMO CHAIN B	-16.64
	НТ0	97.0	3F	2422	SISO CHAIN A	6.21
				2422	SISO CHAIN B	5.77
			7F	2442	SISO CHAIN A	5.58
				2442	SISO CHAIN B	5.22
			9F	2452	SISO CHAIN A	3.62
			9F	2452	SISO CHAIN B	4.13
			10F	2457	SISO CHAIN A	1.21
			101		SISO CHAIN B	0.93
			11F	2462	SISO CHAIN A	-14.74
802.11n40					SISO CHAIN B	-14.87
802.111140			3F	2422	MIMO CHAIN A	1.71
			JI		MIMO CHAIN B	3.57
			フ Γ	2442	MIMO CHAIN A	4.29
			7F	2442	MIMO CHAIN B	3.92
	HT8	07.2	ΩE	2452	MIMO CHAIN A	2.66
		97.2	9F	2452	MIMO CHAIN B	2.99
			10F	2457	MIMO CHAIN A	-1.2
					MIMO CHAIN B	-1.14
			11F	2462	MIMO CHAIN A	-17.95
					MIMO CHAIN B	-17.81



Band Edge results Screenshot:


802.11b, 1Mbps





































802.11g, 6Mbps





Rev 00



































802.11n20 (SISO), HT0



































802.11n20 (MIMO), HT8







































802.11n40 (SISO), HT0






Rev 00
































802.11n40 (MIMO), HT8





































Conducted Spurious results Screenshot:












Rev 00









Day 00




intel




Test Report N°160830-01.TR04




intel



Rev 00







Ray 00

