



N° 1-6736  
Scope available  
on www.cofrac.fr



# TEST REPORT

EUT Description	Wireless Module installed in Laptop
Brand Name	Intel® Wi-Fi 6E AX210
Model Name	AX210NGW
FCC/IC ID	FCC ID: PD9AX210NG; IC ID :1000M-AX210NG
Date of Test Start/End	2021-06-28 / 2021-07-02
Features	802.11ax, Dual Band, 2x2 Wi-Fi + Bluetooth® 5.2 (see section 5)
Description	Platform: P107F + HongBo / SPEED antennas

Applicant	Intel Mobile Communications
Address	100 Center Point Circle, Suite 200 / Columbia, SC 29210 / United States
Contact Person	Steven Hackett
Telephone/Fax/ Email	steven.c.hackett@intel.com

Reference Standards	FCC 47 CFR Part §2.1093 RSS-102, issue 5 (see section 1)	
RF Exposure Environment	Portable devices - General population/uncontrolled exposure	
Exposure Conditions	Body worn	
	SAR Result	SAR Limit
Maximum SAR Result & Limit	0.91 W/kg (1g)	1.60 W/kg (1g)
Min. test separation distance	0mm to phantom, 1.41mm to antenna edge	

Test Report identification	210419-11.TR01
Revision Control	Rev. 00 This test report revision replaces any previous test report revision (see section 8)

The test results relate only to the samples tested.

Reference to accreditation shall be used only by full reproduction of test report.

Issued by \_\_\_\_\_

Reviewed by \_\_\_\_\_

Vaso KACULINI  
(Test Engineer Lead)

Cheiel IN  
(Technical Manager Deputy)

Intel Corporation S.A.S – WRF Lab  
425 rue de Goa – Le Cargo B6 - 06600 Antibes, France  
Tel. +33493001400 / Fax +33493001401

# Table of Contents

---

<b>1. Standards, reference documents and applicable test methods .....</b>	<b>4</b>
<b>2. General conditions, competences and guarantees .....</b>	<b>4</b>
<b>3. Environmental Conditions .....</b>	<b>5</b>
<b>4. Test samples .....</b>	<b>5</b>
<b>5. EUT Features.....</b>	<b>6</b>
<b>6. Remarks and comments .....</b>	<b>8</b>
<b>7. Test Verdicts summary .....</b>	<b>8</b>
<b>8. Document Revision History .....</b>	<b>8</b>
<b>Annex A. Test &amp; System Description.....</b>	<b>9</b>
A.1 SAR DEFINITION.....	9
A.2 SPEAG SAR MEASUREMENT SYSTEM .....	10
A.2.1 SAR Measurement Setup.....	10
A.2.2 E-Field Measurement Probe.....	11
A.2.3 SAM Phantom .....	11
A.2.4 Flat Phantom .....	12
A.2.5 Device Positioner.....	12
A.3 DATA EVALUATION .....	13
A.4 SYSTEM AND LIQUID CHECK .....	15
A.4.1 System Check .....	15
A.4.2 Liquid Check.....	16
A.5 TEST EQUIPMENT LIST .....	17
A.5.1 Tissue Simulant Liquid .....	17
A.6 MEASUREMENT UNCERTAINTY EVALUATION .....	18
A.7 RF EXPOSURE LIMITS .....	19
<b>Annex B. Test Results .....</b>	<b>20</b>
B.1 TEST CONDITIONS.....	20
B.1.1 Test SAR Test positions relative to the phantom.....	20
B.1.2 Test signal, Output power and Test Frequencies .....	20
B.1.3 Evaluation Exclusion and Test Reductions.....	21
B.2 CONDUCTED POWER MEASUREMENTS .....	23
B.2.1 WLAN 2.4GHz.....	23
B.2.2 WLAN 5GHz (U-NII) .....	24
B.2.3 Bluetooth .....	30
B.3 TISSUE PARAMETERS MEASUREMENT .....	31
B.4 SYSTEM CHECK MEASUREMENTS .....	31
B.5 SAR TEST RESULTS .....	32
B.5.1 Bluetooth & 802.11b/g/n/ax – 2.4GHz – DTS – BT (DSS).....	32
B.5.2 802.11a/n/ac/ax – 5.3 GHz – U-NII-2A.....	32
B.5.3 802.11a/n/ac/ax – 5.6 GHz – U-NII-2C.....	32
B.5.4 802.11a/n/ac/ax – 5.8 GHz – U-NII-3 .....	32
B.5.5 SAR Measurement Variability.....	33
B.5.6 Simultaneous Transmission SAR Evaluation.....	34
<b>Annex C. Test System Plots.....</b>	<b>35</b>
<b>Annex D. TSL Dielectric Parameters.....</b>	<b>44</b>
D.1 BODY DTS 2450MHz .....	44
D.2 BODY 5180MHz-5900MHz .....	45

<b>Annex E. Calibration Certificates .....</b>	<b>47</b>
<b>Annex F. Photographs .....</b>	<b>49</b>
F.1 TEST SAMPLE .....	49
F.2 TEST POSITIONS.....	50
F.3 ANTENNA HOST PLATFORM LOCATION AND ADJACENT EDGE POSITIONS RELATIVE TO THE BODY .....	51
F.4 PHANTOM LIQUID LEVEL DURING MEASUREMENTS .....	53

## 1. Standards, reference documents and applicable test methods

FCC	<ol style="list-style-type: none"> <li>1. FCC Title 47 CFR Part §2.1093 – Radiofrequency radiation exposure evaluation: portable devices. 2019-10-01 Edition</li> <li>2. FCC OET KDB 248227 D01 v02r02 – SAR guidance for IEEE 802.11 (Wi-Fi) transmitters.</li> <li>3. FCC OET KDB 447498 D01 v06 –RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices.</li> <li>4. FCC OET KDB 616217 D04 v01r02 – SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers.</li> <li>5. FCC OET KDB 865664 D01 v01r04 – SAR Measurement Requirements for 100 MHz to 6 GHz.</li> <li>6. FCC OET KDB 865664 D02 v01r02 – RF Exposure Compliance Reporting and Documentation Considerations.</li> <li>7. TCB Workshop April 2019 – RF Exposure Procedures (802.11ax SAR Testing)</li> <li>8. IEEE Std 1528-2013 – IEEE Recommended Practice Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communication Devices: Measurement Techniques...</li> </ol>
ISED	<ol style="list-style-type: none"> <li>1. ISED RSS 102, Issue 5 – Radio Frequency (RF) Exposure Compliance of Radio communication Apparatus (All Frequency Bands)</li> <li>2. ISED RSS-102 Supplementary Procedures SPR-001 SAR testing requirements with regard to bystanders for laptop type computers with antennas built-In on display screen (Laptop Mode / Tablet Mode)</li> <li>3. ISED Notice 2016-DRS001 – Applicability of latest FCC RF Exposure KDB Procedures and Other Procedures.</li> <li>4. ISED Notice 2020-DRS0020 – Applicability of IEC/IEEE62209-1528 and IEC62209-3 Standard</li> <li>5. ISED Notice 2012-DRS0529 – SAR correction for measured conductivity and relative permittivity based on IEC 62209-2 standard.</li> <li>6. FCC OET KDB 248227 D01 v02r02 – SAR guidance for IEEE 802.11 (Wi-Fi) transmitters.</li> <li>7. FCC OET KDB 447498 D01 v06 –RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices.</li> <li>8. FCC OET KDB 616217 D04 v01r02– SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers.</li> <li>9. IEC/IEEE 62209-1528:2020 - Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)</li> </ol>

## 2. General conditions, competences and guarantees

- ✓ Tests performed under FCC standards identified in section 1 are covered by A2LA accreditation.
- ✓ Tests performed under ISED standards identified in section 1 are covered by Cofrac accreditation.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an ISO/IEC 17025:2017 laboratory accredited by the American Association for Laboratory Accreditation (A2LA) with the certificate number 3478.01.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an Accredited Test Firm recognized by the FCC, with Designation Number FR0011.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an ISO/IEC 17025:2017 testing laboratory accredited by the French Committee for Accreditation (Cofrac) with the certificate number 1-6736.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is a Registered Test Site listed by ISED, with ISED #1000Y.
- ✓ Intel WRF Lab declines any responsibility with respect to the identified information provided by the customer and that may affect the validity of results.
- ✓ Intel WRF Lab only provides testing services and is committed to providing reliable, unbiased test results and interpretations.
- ✓ Intel WRF Lab is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.
- ✓ Intel WRF Lab has developed calibration and proficiency programs for its measurement equipment to ensure correlated and reliable results to its customers.
- ✓ This report is only referred to the item that has undergone the test.
- ✓ This report does not imply an approval of the product by the Certification Bodies or competent Authorities.

### 3. Environmental Conditions

- ✓ At the site where the measurements were performed the following limits were not exceeded during the tests:

Temperature	21.5°C ± 2°C
Humidity	45.0% ± 10%
Liquid Temperature	21.0°C ± 2°C

### 4. Test samples

Sample	Control #	Description	Model	Serial #	Date of receipt	Note
#01	210419-11. S01	Wireless Module installed in Laptop	AX210NGW+P107F	2020121517940	2021-05-10	HB Antenna
#02	210419-11. S02	Wireless Module installed in Laptop	AX210NGW+P107F	2020121517933	2021-05-10	SPEED Antenna

## 5. EUT Features

The herein information is provided by the customer

Brand Name	Intel® Wi-Fi 6E AX210		
Model Name	AX210NGW		
Software Version	22.35010.0.0-01763		
Driver Version	22.10.0.7		
Prototype / Production	Production		
Host Identification	P107F		
Supported Radios	802.11b/g/n/ax 802.11a/n/ac/ax Bluetooth 5.2	2.4GHz (2400.0 – 2483.5 MHz) 5.2GHz (5150.0 – 5350.0 MHz) 5.6GHz (5470.0 – 5725.0 MHz) 5.8GHz (5725.0 – 5850.0 MHz) 2.4GHz (2400.0 – 2483.5 MHz)	
Antenna Information	Transmitter	Main	Aux
	Manufacturer	HB	HB
	Antenna type	PIFA	PIFA
	Part number	260-29073	260-29078
	Transmitter	Main	Aux
	Manufacturer	SPEED	SPEED
	Antenna type	PIFA	PIFA
	Part number	F-0G-FS-6107-001-00	F-0G-FS-6107-002-00
See Annex F for more details on antennas location.			
Simultaneous Transmission Configurations	WLAN 2.4GHz Main + BT Aux WLAN 2.4GHz Main + WLAN 2.4GHz Aux WLAN 5GHz Main + BT Aux WLAN 5GHz Main + WLAN 5GHz Aux WLAN 5GHz Main + WLAN 5GHz Aux + BT Aux		
Additional Information	No WWAN transmitter is considered in this report		
	5.60-5.65 GHz band (TDWR) is supported by the device		
	Band gap is supported by the device		

### Supported Radios

Mode	Duty Cycle	Modulation	Band	UL Freq Range (MHz)	Measured Max. Conducted Power (dBm)
802.11b/g/n/ax	100%	BPSK QPSK 16QAM 64QAM	2.4GHz	2400-2483.5	15.97
802.11a/n/ac/ax	100%	BPSK QPSK 16QAM 64QAM 256QAM	5.2GHz	5150-5250	NM
			5.3GHz	5250-5350	11.00
			5.6GHz	5475-5725	10.96
			5.8GHz	5725-5850	10.96
BDR/EDR v5.2	25%	GFSK $\pi/4$ DQPSK 8DPSK	2.4GHz	2400-2483.5	11.49
Bluetooth LE v5.2	55%	GFSK	2.4GHz	2400-2483.5	NM

NM: Not Measured

Maximum Output power specification + Tune up tolerance limit, as specified by the client			SISO mode	
Equipment Class	Mode	BW (MHz)	Main (dBm)	Aux (dBm)
DTS	802.11b	20	16.00	16.00
	802.11g	20	16.00	16.00
	802.11n20	20	16.00	16.00
	802.11ax20	20	16.00	16.00
	802.11n40	40	16.00	16.00
	802.11ax40	40	16.00	16.00
U-NII-1	802.11a	20	11.00	11.00
	802.11n20	20	11.00	11.00
	802.11ax20	20	11.00	11.00
	802.11n40	40	11.00	11.00
	802.11ax40	40	11.00	11.00
	802.11ac80	80	11.00	11.00
	802.11ax80	80	11.00	11.00
U-NII-2A	802.11a	20	11.00	11.00
	802.11n20	20	11.00	11.00
	802.11ax20	20	11.00	11.00
	802.11n40	40	11.00	11.00
	802.11ax40	40	11.00	11.00
	802.11ac80	80	11.00	11.00
	802.11ax80	80	11.00	11.00
	802.11ac160	160	11.00	11.00
	802.11ax160	160	11.00	11.00
U-NII-2C	802.11a	20	11.00	11.00
	802.11n20	20	11.00	11.00
	802.11ax20	20	11.00	11.00
	802.11n40	40	11.00	11.00
	802.11ax40	40	11.00	11.00
	802.11ac80	80	11.00	11.00
	802.11ax80	80	11.00	11.00
	802.11ac160	160	11.00	11.00
U-NII-3	802.11a	20	11.00	11.00
	802.11n20	20	11.00	11.00
	802.11ax20	20	11.00	11.00
	802.11n40	40	11.00	11.00
	802.11ax40	40	11.00	11.00
	802.11ac80	80	11.00	11.00
	802.11ax80	80	11.00	11.00
BT	Bluetooth v5.2 BDR	1		11.50
	Bluetooth v5.2 EDR2	1		11.00
	Bluetooth v5.2 EDR3	1		11.00
	BLE	2		10.00

## 6. Remarks and comments

1. The conducted values are obtained by applying the BIOS SAR power values to the AX210NGW Intel module installed in the P107F identified in this report, as requested by the customer
2. Variability and simultaneous transmission results shown in this report are based on the highest SAR value obtained among all antenna manufacturers.
3. Only the plots for the test positions with the highest measured SAR per band/mode are included in Annex C as required per FCC OET KDB 865664 D02, paragraph 2.3.h

## 7. Test Verdicts summary

The statement of conformity to applicable standards in the table below are based on the measured values, without taking into account the measurement uncertainties.

Standard	Band	Highest Reported SAR (1g) (W/kg)	Verdict
802.11b/g/n/ax	2.4GHz	0.34	P
802.11a/n/ac/ax	5.2GHz	NM	NA
	5.3GHz	0.48	P
	5.6GHz	0.71	P
	5.8GHz	0.91	P
	Bluetooth	0.11	P

P: Pass

F: Fail

NM: Not Measured

NA: Not Applicable

According to the FCC OET KDB 690783 D01, this is the summary of the values for the Grant Listing:

Exposure Condition	Highest Reported SAR (1g) (W/kg)		
	DTS	DSS	U-NII
Body Worn	0.34	0.11	0.91
Simultaneous Tx	Sum-SAR: 0.67	Sum-SAR: 1.69 SPLSR: 0.01	Sum-SAR: 1.69 SPLSR: 0.01

Considering the results of the performed test according to FCC 47CFR Part 2.1093 and ISED RSS 102, Issue 5 the item under test is IN COMPLIANCE with the requested specifications specified in Section1. Standards, reference documents and applicable test methods

## 8. Document Revision History

Revision #	Modified by	Revision Details
Rev. 00	R. LUCIANI	First Issue

# Annex A. Test & System Description

---

## A.1 SAR Definition

Specific Absorption rate is defined as the time derivative of the incremental energy ( $dW$ ) absorbed by (dissipated in) and incremental mass ( $dm$ ) contained in a volume element ( $dV$ ) of a given density ( $\rho$ ).

$$SAR = \frac{d}{dt} \cdot \left( \frac{dW}{dm} \right) = \frac{d}{dt} \cdot \left( \frac{dW}{\rho \cdot dV} \right)$$

SAR is expressed in units of watts per kilogram (W/kg). SAR can be related to the electric field at a point by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:

$\sigma$  = Conductivity of the tissue (S/m)


$\rho$  = Mass density of the tissue (kg/m<sup>3</sup>)

E = RMS electric field strength (V/m)

## A.2 SPEAG SAR Measurement System

### A.2.1 SAR Measurement Setup

The DASY6 system for performing compliance tests consists of the following items:



- ✓ A standard high precision 6-axis robot (Staubli TX/RX family) with controller, teach pendant and software. It includes an arm extension for accommodating the data acquisition electronics (DAE)
- ✓ An isotropic field probe optimized and calibrated for the targeted measurements.
- ✓ A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- ✓ The Electro-optical Converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. The EOC signal is transmitted to the measurement server.
- ✓ The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movements interrupts.
- ✓ The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- ✓ A computer running Win7 professional operating system and the DASY6 software.
- ✓ Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- ✓ The phantom, the device holder and other accessories according to the targeted measurement.
- ✓ MAIA is a hardware interface (Antenna) used to evaluate the modulation and audio interference characteristics of RF signals.
- ✓ ANT is an ultra-wideband antenna for use with the base station simulators over 698 MHz to 6GHz.
- ✓ The base station simulator is an equipment used for SAR cellular tests in order to emulate the cellular signals characteristics and behavior between a regular base station and the equipment under test.
- ✓ Tissue simulating liquid.
- ✓ System Validation dipoles.
- ✓ Network emulator or RF test tool.

### A.2.2 E-Field Measurement Probe

The probe is constructed using three orthogonal dipole sensors arranged on an interlocking, triangular prism core. The probe has built-in shielding against static charges and is contained within a PEEK cylindrical enclosure material at the tip.



The probe's characteristics are:


Frequency Range	30MHz – 6GHz
Length	337 mm
Probe tip external diameter	2.5 mm
Typical distance between dipoles and the probe tip	1 mm
Axial Isotropy (in human-equivalent liquids)	$\pm 0.3$ dB
Hemispherical Isotropy (in human-equivalent liquids)	$\pm 0.5$ dB
Linearity	$\pm 0.2$ dB
Maximum operating SAR	100 W/kg
Lower SAR detection threshold	0.001 W/kg

### A.2.3 SAM Phantom

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528, IEC/IEEE 62209-1528:2020 and IEC 62209-1. It enables the dosimetric evaluation of left and right-hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

The phantom's characteristics are:

Material	Vinylester, glass fiber reinforced (VE-GF)
Shell thickness	2 mm $\pm 0.2$ mm
Shell thickness at ERP	6 $\pm 0.2$ mm
Filling volume	25 Liters
Dimensions	Length: 1000mm / Width: 500mm




#### A.2.4 Flat Phantom

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

The phantom's characteristics are:

Material	Vinylester, glass fiber reinforced (VE-GF)
Shell thickness	2 mm ± 0.2 mm
Filling volume	30 Liters approx.
Dimensions	Major axis: 600mm / Minor axis: 400mm



#### A.2.5 Device Positioner

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of 0.5 mm would produce a SAR uncertainty of 20%. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.



The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon=3$  and loss tangent  $\delta=0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

A simple but effective and easy-to-use extension for the Mounting Device; facilitates testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.); lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin SAM, ELI and other Flat Phantoms.

### A.3 Data Evaluation

- **Power Reference measurement**

The robot measures the E field in a specified reference position that can be either the selected section's grid reference point or a user point in this section at 4mm of the inner surface of the phantom, 2mm for frequencies above 3GHz.

- **Area Scan**

Measurement procedures for evaluating SAR from wireless handsets typically start with a coarse measurement grid to determine the approximate location of the local peak SAR values. This is known as the area-scan procedure. The SAR distribution is scanned along the inside surface of one side of the phantom head, at least for an area larger than the projection of the handset and antenna. The distance between the measured points and phantom surface should be less than 8 mm, and should remain constant (with variation less than  $\pm 1$  mm) during the entire scan in order to determine the locations of the local peak SAR with sufficient accuracy. The angle between the probe axis and the surface normal line is recommended but not required to be less than 30°. If this angle is larger than 30° and the closest point on the probe-tip housing to the phantom surface is closer than a probe diameter, the boundary effect may become larger and polarization dependent. This additional uncertainty needs to be analyzed and accounted for. To achieve this, modified test procedures and additional uncertainty analyses not described in this recommended practice may be required. The measurement and interpolation point spacing should be chosen such as to allow identification of the local peak locations to within one-half of the linear dimension of a side of the zoom-scan volume. Because a local peak having specific amplitude and steep gradients may produce a lower peak spatial-average SAR compared to peaks with slightly lower amplitude and less steep gradients, it is necessary to evaluate these other peaks as well. However, since the spatial gradients of local SAR peaks are a function of the wavelength inside the tissue-equivalent liquid and the incident magnetic field strength, it is not necessary to evaluate local peaks that are less than 2 dB or more below the global maximum peak. Two-dimensional spline algorithms (Brishoual et al. 2001; Press et al., 1996) are typically used to determine the peaks and gradients within the scanned area. If a peak is found at a distance from the scan border of less than one-half the edge dimension of the desired 1 g or 10 g cube, the measurement area should be enlarged if possible.

- **Zoom Scan**

To evaluate the peak spatial-average SAR values for 1 g or 10 g cubes, fine resolution volume scans, called zoom scans, are performed at the peak SAR locations identified during the area scan. The minimum zoom scan volume size should extend at least 1.5 times the edge dimension of a 1 g cube in all directions from the center of the scan volume, for both 1 g and 10 g peak spatial-average SAR evaluations. Along the phantom curved surfaces, the front face of the volume facing the tissue/liquid interface conforms to the curved boundary, to ensure that all SAR peaks are captured. The back face should be equally distorted to maintain the correct averaging mass. The flatness and orientation of the four side faces are unchanged from that of a cube whose orientation is within  $\pm 30$ ° of the line normal to the phantom at the center of the cube face next to the phantom surface. The peak local SAR locations that were determined in the area scan (interpolated values) should be used for the centers of the zoom scans. If a scan volume cannot be centered due to proximity of a phantom shape feature, the probe should be tilted to allow scan volume enlargement. If probe tilt is not feasible, the zoom-scan origin may be shifted, but not by more than half of the 1 g or 10 g cube edge dimension.

After the zoom-scan measurement, extrapolations from the closest measured points to the surface, for example along lines parallel to the zoom-scan centerline, and interpolations to a finer resolution between all measured and extrapolated points are performed. Extrapolation algorithm considerations are described in 6.5.3, and 3-D spline methods (Brishoual et al., 2001; Kreyszig, 1983; Press et al., 1996) can be used for interpolation. The peak spatial-average SAR is finally determined by a numerical averaging of the local SAR values in the interpolation grid, using for example a trapezoidal algorithm for the integration (averaging).

In some areas of the phantom, such as the jaw and upper head regions, the angle of the probe with respect to the line normal to the surface may be relatively large, e.g., greater than  $\pm 30$ °, which could increase the boundary effect error to a larger level. In these cases, during the zoom scan a change in the orientation of the probe, the phantom, or both is recommended but not required for the duration of the zoom scan, so that the angle between the probe axis and the line normal to the surface is within 30° for all measurement points.

- **Power Drift measurement**

The robot re-measures the E-Field in the same reference location measured at the Power Reference. The drift measurement gives the field difference in dB from the first to the last reference reading. This allows a user to monitor the power drift of the device under test that must remain within a maximum variation of  $\pm 5\%$ .

- **Post-processing**

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1528, IEC/IEEE 62209-1528:2020 and IEC 62209-1/2 standards. It can be conducted for 1g and 10g.

The software allows evaluations that combine measured data and robot positions, such as:

- ✓ Maximum search
- ✓ Extrapolation
- ✓ Boundary correction
- ✓ Peak search for averaged SAR

Interpolation between the measured points is performed when the resolution of the grid is not fine enough to compute the average SAR over a given mass.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation.


## A.4 System and Liquid Check

### A.4.1 System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results.

The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

In the simplified setup for system check, the EUT is replaced by a calibrated dipole and the power source is replaced by a controlled continuous wave generated by a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the phantom at the correct distance.



The equipment setup is shown below:

- ✓ Signal Generator
- ✓ Amplifier
- ✓ Directional coupler
- ✓ Power meter
- ✓ Calibrated dipole

First, the power meter PM1 (including attenuator Att1) is connected to the cable to measure the forward power at the location of the connector (x) to the system check source. The signal generator is adjusted for the desired forward power at the connector as read by power meter PM1 after attenuation Att1 and also as coupled through Att2 to PM2. After connecting the cable to the source, the signal generator is readjusted for the same reading at power meter PM2.

SAR results are normalized to a forward power of 1W to compare the values with the calibration reports results as described at IEEE 1528, IEC/IEEE 62209-1528:2020 and IEC 62209 standards.

#### A.4.2 Liquid Check

The dielectric parameters check is done prior to the use of the tissue simulating liquid. The verification is made by comparing the relative permittivity and conductivity to the values recommended by the applicable standards.

The liquid verification was performed using the following test setup:

- ✓ VNA (Vector Network Analyzer)
- ✓ Open-Short-Load calibration kit
- ✓ RF Cable
- ✓ Open-Ended Coaxial probe
- ✓ DAK software tool
- ✓ SAR Liquid
- ✓ De-ionized water
- ✓ Thermometer

These are the target dielectric properties of the tissue-equivalent liquid material as defined in FCC OET KDB 865664 D01.

Frequency (MHz)	Body SAR	
	$\epsilon_r$ (F/m)	$\sigma$ (S/m)
150	61.9	0.80
300	58.2	0.92
450	56.7	0.94
835	55.2	0.97
900	55.0	1.05
1450	54.0	1.30
1800-2000	53.3	1.52
2450	52.7	1.95
3000	52.0	2.73
5800	48.2	6.00

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho$  = 1000 kg/m<sup>3</sup>)

The measurement system implement a SAR error compensation algorithm as documented in IEEE Std 1528-2013, IEC/IEEE 62209-1528:2020 (equivalent to draft standard IEEE P1528-2011) to automatically compensate the measured SAR results for deviations between the measured and required tissue dielectric parameters (applied to only scale up the measured SAR, and not downward) so, according to FCC OET KDB 865664 D01, the tolerance for  $\epsilon_r$  and  $\sigma$  may be relaxed to  $\pm 10\%$ .

## A.5 Test Equipment List

### SAR system #3

ID #	Device	Type/Model	Serial Number	Manufacturer	Cal. Date	Cal. Due Date
003-000	6-Axis Robot	TX60 Lspeag	F17/59RCB1/A/01	STAÜBLI	NA	NA
003-001	Robot Controller	CS8C	F17/59RCB1/C/01	STAÜBLI	NA	NA
003-002	Oval Flat Phantom	ELI V5.0	1260	SPEAG	NA	NA
003-003	Light Beam Unit	SE UKS 030 AA	1170	Di-soric	NA	NA
003-004	Measurement Server	DASY6	1547	SPEAG	NA	NA
003-005	Electro Optical Converter	EOC60	1104	SPEAG	NA	NA
003-006	Measurement Software	DASY6 v6.8	9-5ED1AC01	SPEAG	NA	NA
004-006	Dosimetric E-Field probe 750-5800MHz	EX3DV4	7604	SPEAG	2020-08-07	2021-08-07
004-007	Data Acquisition Electronics	DAE4	1628	SPEAG	2020-07-30	2021-07-30
003-009	Laptop Holder	N/A	N/A	SPEAG	NA	NA

### Shared equipment

ID #	Device	Type/Model	Serial Number	Manufacturer	Cal. Date	Cal. Due Date
123-000	USB Power Sensor	NRP-Z81	102278	R&S	2021-04-13	2023-04-13
124-000	USB Power Sensor	NRP-Z81	102279	R&S	2021-04-13	2023-04-13
126-000	Vector Signal Generator	ESG E4438C	MY45092885	Agilent	2021-05-27	2023-05-27
198-000	Power Amplifier	TVA-82-213A+	2004003	Mini-circuits	n/a	n/a
099-000	Liquid measurement SW	DAK-3.5 V2.6.0.5	9-2687B491	SPEAG	n/a	n/a
069-000	Dielectric Probe Kit	DAK-3.5	1037	SPEAG	2019-07-16	2021-07-16
070-000	2450MHz System Validation Dipole	D2450V2	937	SPEAG	2020-05-12	2022-05-12
077-000	Coupler	CD0.5-8-20-30	1251-002	Amd-group	n/a	n/a
078-000	RF Cable	ST-18/SMAm/SMAm/48	1158830	Huber & Suhner	2021-02-15	2021-08-15
079-000	RF Cable	ST-18/SMAm/SMAm/48	1158831	Huber & Suhner	2021-02-15	2021-08-15
141-000	USB Power Sensor	NRP-Z81	104381	R&S	2020-06-03	2022-06-03
068-000	5GHz System Validation Dipole	D5GHzv2	1164	SPEAG	2020-03-10	2022-03-10
089-000	Vector Reflectometer	PLANAR R140	0190616	Copper Mountain Technologies	2019-08-07	2021-08-07
327-000	Temp & Humidity Logger	RA32E-TH1-RAS	RA32-F0DEF9	AVTECH	2021-03-09	2023-03-09
095-000	Thermometer	TESTO 925	34822881	Testo	2019-11-19	2021-11-19

### A.5.1 Tissue Simulant Liquid

TSL	Manufacturer / Model	Freq Range (MHz)	Main Ingredients
Body WideBand	SPEAG MBBL600-6000V6 Batch 180206-4	600-6000	Ethanediol, Sodium petroleum sulfonate, Hexylene Glycol / 2-Methyl-pentane-2,4-diol, Alkoxylated alcohol

## A.6 Measurement Uncertainty Evaluation

The system uncertainty evaluation is shown in the table below with a coverage factor of  $k = 2$  to indicate a 95% level of confidence:

SPEAG DASY6 Uncertainty Budget According to IEC/IEEE 62209-1528 (4 MHz - 6 GHz) including IEEE 1528-2013 and IEC 62209-1/2016, IEC 62209-2/2010								
Symbol	Error Description	Uncert. Value	Prob Dist.	Div.	(ci) 1g	(ci) 10g	Std Unc. (1g)	Std Unc. (10g)
<b>Measurement System Errors</b>								
CF	Probe Calibration	±14.0 %	N	2	1	1	±7.0 %	±7.0 %
CF <sub>drift</sub>	Probe Calibration Drift	±1.0 %	N	1	1	1	±1.0 %	±1.0 %
LIN	Probe Linearity	±4.7 %	R	√3	1	1	±2.7 %	±2.7 %
BBS	Broadband Signal	±3.0 %	N	2	1	1	±1.5 %	±1.5 %
ISO	Axial Isotropy	±4.7 %	R	√3	0.5	0.5	±1.4 %	±1.4 %
ISO	Hemispherical Isotropy	±9.6 %	R	√3	0.5	0.5	±2.8 %	±2.8 %
DAE	Data Acquisition	±0.3 %	N	1	1	1	±0.3 %	±0.3 %
AMB	RF Ambient	±1.8 %	N	1	1	1	±1.8 %	±1.8 %
Δ <sub>sys</sub>	Probe Positioning	±0.2 %	N	1	0.33	0.33	±0.1 %	±0.1 %
DAT	Data Processing	±2.3 %	N	1	1	1	±2.3 %	±2.3 %
<b>Phantom and Device Errors</b>								
LIQ(σ)	Conductivity (meas.) <sub>DAK</sub>	±2.5 %	N	1	0.78	0.71	±2.0 %	±1.8 %
LIQ(T <sub>σ</sub> )	Conductivity (temp.) <sub>BB</sub>	±3.4 %	R	√3	0.78	0.71	±1.5 %	±1.4 %
EPS	Phantom Permittivity	±14.0 %	R	√3	0.25	0.25	±2.0 %	±2.0 %
DAS	Distance DUT - TSL	±2.0 %	N	1	2	2	±4.0 %	±4.0 %
H	Device Holder	±3.6 %	N	1	1	1	±3.6 %	±3.6 %
MOD	DUT Modulation <sub>m</sub>	±2.4 %	R	√3	1	1	±1.4 %	±1.4 %
TAS	Time-average SAR	±2.6 %	R	√3	1	1	±1.5 %	±1.5 %
RF <sub>drift</sub>	DUT drift	±5.0 %	N	1	1	1	±2.9 %	±2.9 %
<b>Correction to the SAR results</b>								
C(ε, σ)	Deviation to Target	±1.9 %	N	1	1	0.84	±1.9 %	±1.6 %
Combined Std. Uncertainty							±11.5 %	±11.4 %
<b>Expanded STD Uncertainty</b>							<b>±23.1 %</b>	<b>±22.9 %</b>

## A.7 RF Exposure Limits

SAR assessments have been made in line with the requirements of FCC 47CFR Part 2.1093 and ISED RSS 102 issue 5 on the limitation of exposure of the general population / uncontrolled exposure for portable devices.

Exposure Type	General Population / Uncontrolled Environment
Peak spatial-average SAR (averaged over any 1 gram of tissue)	<b>1.6 W/kg</b>
Whole body average SAR	<b>0.08 W/kg</b>
Peak spatial-average SAR (extremities) (averaged over any 10 grams of tissue)	<b>4.0 W/kg</b>

# Annex B. Test Results

---

The herein test results were performed by:

Test case measurement	Test Personnel
Conducted measurement	Z. Ouachicha
SAR measurement	R. Luciani

## B.1 Test Conditions

### B.1.1 Test SAR Test positions relative to the phantom

The device under test was an Intel® Wi-Fi 6E AX210 card inside a Laptop host platform (P107F) using a set of PIFA antennas. The card was operated utilizing proprietary software (DRTU version 22.35010.0.0-01763) and each channel was measured using a broadband power meter to determine the maximum average power.

According to FCC OET KDB 616217 D04, laptop position should be tested for SAR compliance with the display screen opened at an angle of 90° to the keyboard compartment and the notebook bottom surface must be touching the phantom.

See B.1.3.1 for a more detailed list of the applied reductions.

See F.2 *Test positions* section for more information on the tested positions.

### B.1.2 Test signal, Output power and Test Frequencies

For 802.11 transmission modes the device was put into operation by using an own control software to program the test mode required to select the continuous transmission with 100% duty cycle.

The output power of the device was set to transmit at maximum power for all tests.

### B.1.3 Evaluation Exclusion and Test Reductions

#### B.1.3.1 SAR evaluation exclusion

The SAR Test Exclusion Threshold in FCC OET KDB 447498 D01 v06 can be applied to determine SAR test exclusion for adjacent edge configurations. For 100MHz to 6GHz and test separation distances  $\leq 50\text{mm}$ , the 1-g and 10-g SAR test exclusion thresholds are determined by the following formula:

$$[(\text{max. power of channel, including tune - up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \left[ \sqrt{f_{(\text{GHz})}} \right] \leq 3.0 \text{ for 1g SAR, and } \leq 7.5 \text{ for 10g extremity SAR} \quad (1)$$

Where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50\text{ mm}$ , and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5\text{ mm}$ , a distance of 5 mm is applied to determine SAR test exclusion.

For test separation distances  $> 50\text{ mm}$ , the 1-g and 10-g SAR test exclusion thresholds are determined using the following formulas:

$$\langle (\text{Power allowed at numeric threshold for } 50\text{ mm in (1)}) + (\text{test separation distance} - 50\text{ mm}) \cdot (f_{\text{MHz}}/150) \rangle \text{mW,} \quad (2)$$

*for 100MHz to 1500MHz*

$$\langle (\text{Power allowed at numeric threshold for } 50\text{ mm in (1)}) + (\text{test separation distance} - 50\text{ mm}) \cdot 10 \rangle \text{mW,} \quad (3)$$

*for 1500MHz and } \leq 6\text{GHz}*

LAN Antenna	Band Name	Output power		Laptop	Laptop
		dBm	mW		
WLAN Main	DTS	16.0	39.8	<50	T
	U-NII-1	11.0	12.6	<50	R
	U-NII-2A	11.0	12.6	<50	T
	U-NII-2C	11.0	12.6	<50	T
	U-NII-3	11.0	12.6	<50	T
WLAN Aux	DTS	16.0	39.8	<50	T
	U-NII-1	11.0	12.6	<50	R
	U-NII-2A	11.0	12.6	<50	T
	U-NII-2C	11.0	12.6	<50	T
	U-NII-3	11.0	12.6	<50	T
	BT	11.5	14.1	<50	T

T: Tested position

R: Reduced

See Annex F for a more detailed explanation of the separation distance related to the platform.

### B.1.3.2 General SAR test reduction

According to FCC OET KDB 447498 D01, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- $\leq 0.8 \text{ W/kg}$  or  $2.0 \text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is  $\leq 100 \text{ MHz}$
- $\leq 0.6 \text{ W/kg}$  or  $1.5 \text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is between  $100 \text{ MHz}$  and  $200 \text{ MHz}$
- $\leq 0.4 \text{ W/kg}$  or  $1.0 \text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is  $\geq 200 \text{ MHz}$

### WLAN SAR Test reduction

Transmission Mode	SAR test exclusion/reduction
DSSS	<p>According to FCC OET KDB 248227 D01, SAR is measured for 2.4 GHz 802.11b, SAR test reduction is determined according to the following:</p> <ul style="list-style-type: none"> <li>▪ When the reported SAR of the highest measured maximum output power channel for the exposure configuration is <math>\leq 0.8 \text{ W/kg}</math>, no further SAR testing is required for 802.11b DSSS in that exposure configuration.</li> <li>▪ When the reported SAR is <math>&gt; 0.8 \text{ W/kg}</math>, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is <math>&gt; 1.2 \text{ W/kg}</math>, SAR is required for the third channel.</li> </ul> <p>According to FCC OET KDB 248227 D01, SAR is not required for 2.4 GHz OFDM conditions when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is <math>\leq 1.2 \text{ W/kg}</math>.</p>
OFDM	<p>According to FCC OET KDB 248227 D01, 802.11a/g/n/ac modes have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n.</p> <p>According to FCC OET KDB 248227 D01, an <i>initial test configuration</i> is determined for OFDM and DSSS transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. SAR test reduction for subsequent highest output test channels is determined according to reported SAR of the initial test configuration.</p> <p>The <i>initial test configuration</i> for 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures.</p> <p>According to FCC OET KDB 248227 D01, when the reported SAR of the initial test configuration is <math>&gt; 0.8 \text{ W/kg}</math>, SAR measurement is required for subsequent next highest measured output power channel(s) in the initial test configuration until reported SAR is <math>\leq 1.2 \text{ W/kg}</math> or all required channels are tested.</p>

## B.2 Conducted Power Measurements

### B.2.1 WLAN 2.4GHz

Band	Mode	Data Rate	Ch #	Freq (MHz)	Average power (dBm)					SAR Test?	
					Main			Aux			
					HB	SPEED	Tune-up Pwr (dBm)	HB	SPEED		
2.4GHz (DTS)	802.11b	1Mbp s	1	2412	15.89	15.96	16.00	15.90	15.87	16.00	Yes
			6	2437	15.97	15.82	16.00	15.78	15.96	16.00	
			11	2462	15.97	15.84	16.00	15.69	15.89	16.00	
	802.11g	6Mbp s	1	2412	NR <sup>1</sup>			16.00	NR <sup>1</sup>		No <sup>2</sup>
			6	2437				16.00			
			11	2462				16.00			
	802.11n 20	HT0	1	2412				16.00			
			6	2437				16.00			
			11	2462				16.00			
	802.11a x20	HE0	1	2412				16.00			No <sup>2</sup>
			6	2437				16.00			
			11	2462				16.00			
	802.11n 40	HT0	3	2422				16.00			No <sup>2</sup>
			6	2437				16.00			
			9	2452				16.00			
	802.11a x40	HE0	3	2422				16.00			No <sup>2</sup>
			6	2437				16.00			
			9	2452				16.00			

#### Initial test configuration

1. NR: Not Required
2. As per FCC OET KDB 248227 D01, conducted output power and SAR testing are not required for 802.11g/n/ax channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2\text{W/kg}$ .
3. When the reported SAR of the initial test configuration is  $> 0.8 \text{ W/kg}$ , SAR measurement is required for subsequent next highest measured output power channel(s) in the initial test configuration until reported SAR is  $\leq 1.2 \text{ W/kg}$  or all required channels are tested.

## B.2.2 WLAN 5GHz (U-NII)

### B.2.2.1 5.2GHz and 5.3GHz (U-NII-1 and U-NII-2A)

Band	Mode	Data Rate	Ch #	Freq (MHz)	Average power (dBm)					SAR Test?	
					Main			Aux			
					HB	SPEED	Tune-up Pwr (dBm)	HB	SPEED		
5.2GHz (U-NII-1)	802.11a	6Mbps	36	5180	NR <sup>1</sup>	NR <sup>1</sup>	11.00	NR <sup>1</sup>	NR <sup>1</sup>	11.00	No <sup>2</sup>
			40	5200			11.00			11.00	
			44	5220			11.00			11.00	
			48	5240			11.00			11.00	
	802.11n20	HT0	36	5180		NR <sup>1</sup>	11.00		NR <sup>1</sup>	11.00	
			40	5200			11.00			11.00	
			44	5220			11.00			11.00	
			48	5240			11.00			11.00	
	802.11ax20	HE0	52	5260		NR <sup>1</sup>	11.00		NR <sup>1</sup>	11.00	
			56	5280			11.00			11.00	
			60	5300			11.00			11.00	
			64	5320			11.00			11.00	
	802.11n40	HT0	38	5190		NR <sup>1</sup>	11.00		NR <sup>1</sup>	11.00	
			46	5230			11.00			11.00	
	802.11ax40	HE0	38	5190		NR <sup>1</sup>	11.00		NR <sup>1</sup>	11.00	
			46	5230			11.00			11.00	
	802.11ac80	VHT0	42	5210			11.00			11.00	
	802.11ax80	HE0	42	5210			11.00			11.00	

#### Initial test configuration

1. NR: Not Required
2. When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2 \text{ W/kg}$ , SAR is not required for U-NII-1 band (see §B.5.2 in this document).
3. Additional conducted power measurement is required when reported SAR is  $> 1.2\text{W/kg}$ . In case the subsequent test configuration and the channel bandwidth is smaller than the initial test configuration, all channels that overlap with the larger channel bandwidth in the initial configuration should be tested.
4. The initial test configuration for 2.4 GHz and 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, highest order modulation and highest data rate, highest order 802.11 mode is selected (i.e. a, g, n, ac then ax)
5. When the reported SAR of the initial test configuration is  $> 0.8\text{W/kg}$ , SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until reported SAR is  $=1.2\text{W/kg}$  or all required channels are tested.
6. When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure requirements, is adjusted by the ratio of the subsequent test configuration to the initial test configuration specified maximum output power and the adjusted SAR is  $\leq 1.2 \text{ W/Kg}$ , SAR is not required for that subsequent test configuration
7. SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the reported SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is  $>1.2 \text{ W/Kg}$  or until all required channels are tested.

Band	Mode	Data Rate	Ch #	Freq (MHz)	Average power (dBm)							SAR Test?	
					Main			Aux					
					HB	SPEED	Tune-up Pwr (dBm)	HB	SPEED	Tune-up Pwr (dBm)			
5.3GHz (U-NII-2A)	802.11a	6Mbps	52	5260	NR <sup>1</sup>	NR <sup>1</sup>	11.00	NR <sup>1</sup>	NR <sup>1</sup>	11.00	No <sup>4,6</sup>		
			56	5280			11.00			11.00			
			60	5300			11.00			11.00			
			64	5320			11.00			11.00			
	802.11n 20	HT0	52	5260			11.00			11.00			
			56	5280			11.00			11.00			
			60	5300			11.00			11.00			
			64	5320			11.00			11.00			
	802.11a x20	HE0	52	5260			11.00			11.00			
			56	5280			11.00			11.00			
			60	5300			11.00			11.00			
			64	5320			11.00			11.00			
	802.11n 40	HT0	54	5270			11.00			11.00			
			62	5310			11.00			11.00			
	802.11a x40	HE0	54	5270			11.00			11.00			
			62	5310			11.00			11.00			
	802.11a c80	VHT0	58	5290			11.00			11.00			
	802.11a x80	HE0	58	5290			11.00			11.00			
	802.11a c160	VHT0	50	5250			11.00			11.00			
	802.11a x160	HE0	50	5250	10.96	11.00	11.00	10.95	11.00	11.00		Yes	

#### Initial test configuration

1. NR: Not Required
2. The initial test configuration for 2.4 GHz and 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, highest order modulation and highest data rate, highest order 802.11 mode is selected (i.e. a, g, n, ac then ax)
3. Additional conducted power measurement is required when reported SAR is > 1.2W/kg. In case the subsequent test configuration and the channel bandwidth is smaller than the initial test configuration, all channels that overlap with the larger channel bandwidth in the initial configuration should be tested.
4. When the reported SAR of the initial test configuration is > 0.8W/kg, SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until reported SAR is ≤ 1.2W/kg or all required channels are tested.
5. When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure requirements, is adjusted by the ratio of the subsequent test configuration to the initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/Kg, SAR is not required for that subsequent test configuration.
6. SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the reported SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is >1.2 W/Kg or until all required channels are tested.

**B.2.2.2 5.6 (U-NII-2C)**

Band	Mode	Data Rate	Ch #	Freq (MHz)	Average power (dBm)						SAR Test ?	
					Main			Aux				
					HB	SPEED	Tune-up Pwr (dBm)	HB	SPEED	Tune-up Pwr (dBm)		
5.6GHz (U-NII-2C)	802.11a	6Mbps	100	5500	NR <sup>1</sup>	NR <sup>1</sup>	11.00	NR <sup>1</sup>	NR <sup>1</sup>	11.00	No <sup>4, 6</sup>	
			104	5520			11.00			11.00		
			108	5540			11.00			11.00		
			112	5560			11.00			11.00		
			116	5580			11.00			11.00		
			120	5600			11.00			11.00		
			124	5620			11.00			11.00		
			128	5640			11.00			11.00		
	802.11n 20	HT0	100	5500			11.00			11.00		
			104	5520			11.00			11.00		
			108	5540			11.00			11.00		
			112	5560			11.00			11.00		
			116	5580			11.00			11.00		
			120	5600			11.00			11.00		
			124	5620			11.00			11.00		
			128	5640			11.00			11.00		
	802.11a x40	HE0	100	5500			11.00			11.00		
			104	5520			11.00			11.00		
			108	5540			11.00			11.00		
			112	5560			11.00			11.00		
			116	5580			11.00			11.00		
			120	5600			11.00			11.00		
			124	5620			11.00			11.00		
			128	5640			11.00			11.00		
	802.11n 40	HT0	102	5510			11.00			11.00		
			110	5550			11.00			11.00		
			118	5590			11.00			11.00		
			126	5630			11.00			11.00		
	802.11a x40	HE0	102	5510			11.00			11.00		
			110	5550			11.00			11.00		
			118	5590			11.00			11.00		
			126	5630			11.00			11.00		
	802.11a c80	VHT0	106	5530			11.00			11.00		
	122	5610	11.00	11.00								
	802.11a x80	HE0	106	5530			11.00			11.00		
	122	5610	11.00	11.00								
	802.11a c160	VHT0	114	5570			11.00			11.00		
	802.11a x160	HE0	114	5570	10.90	10.96	11.00	10.75	10.95	11.00	Yes	

**Initial test configuration**

1. NR: Not Required
2. When band gap channels between U-NII-2C and U-NII-3 band are supported channels in U-NII-2C band below 5.65 GHz are considered as one band and channels above 5.65 GHz, together with channels in 5.8 GHz U-NII-3 or §15.247 band, are considered as a separate band
3. Additional conducted power measurement is required when reported SAR is > 1.2W/kg. In case the subsequent test configuration and the channel bandwidth is smaller than the initial test configuration, all channels that overlap with the larger channel bandwidth in the initial configuration should be tested
4. The initial test configuration for 2.4 GHz and 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, highest order modulation and highest data rate, highest order 802.11 mode is selected (i.e. a, g, n, ac then ax)
5. When the reported SAR of the initial test configuration is > 0.8W/kg, SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until reported SAR is ≤1.2W/kg or all required channels are tested.
6. When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure requirements, is adjusted by the ratio of the subsequent test configuration to the initial test configuration specified maximum output power and the adjusted SAR is≤1.2 W/Kg, SAR is not required for that subsequent test configuration.
7. SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the reported SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is >1.2 W/Kg or until all required channels are tested.

**B.2.2.3 5.8GHz (U-NII-3)**

Band	Mode	Data Rate	Ch #	Freq (MHz)	Average power (dBm)						SAR Test?	
					Main			Aux				
					HB	SPEED	Tune-up Pwr (dBm)	HB	SPEED	Tune-up Pwr (dBm)		
5.6-5.8GHz (U-NII-3)	802.11 a	6Mbps	132	5660	NR <sup>1</sup>	NR <sup>1</sup>	11.00	NR <sup>1</sup>	NR <sup>1</sup>	11.00	No <sup>4,6</sup>	
			136	5680			11.00			11.00		
			140	5700			11.00			11.00		
			149	5745			11.00			11.00		
			153	5765			11.00			11.00		
			157	5785			11.00			11.00		
			161	5805			11.00			11.00		
			165	5825			11.00			11.00		
	802.11 n20	HT0	132	5660			11.00			11.00		
			136	5680			11.00			11.00		
			140	5700			11.00			11.00		
			149	5745			11.00			11.00		
			153	5765			11.00			11.00		
			157	5785			11.00			11.00		
			161	5805			11.00			11.00		
			165	5825			11.00			11.00		
	802.11 ax20	HE0	132	5660	NR <sup>1</sup>	NR <sup>1</sup>	11.00	NR <sup>1</sup>	NR <sup>1</sup>	11.00	No <sup>4,6</sup>	
			136	5680			11.00			11.00		
			140	5700			11.00			11.00		
			149	5745			11.00			11.00		
			153	5765			11.00			11.00		
			157	5785			11.00			11.00		
			161	5805			11.00			11.00		
			165	5825			11.00			11.00		
	802.11 n40	HT0	134	5670			11.00			11.00		
			142	5710			11.00			11.00		
			151	5755			11.00			11.00		
			159	5795			11.00			11.00		
	802.11 ax40	HE0	134	5670			11.00			11.00		
			142	5710			11.00			11.00		
			151	5755			11.00			11.00		
			159	5795			11.00			11.00		
	802.11 ac80	VHT0	138	5690	10.90	10.90	11.00	10.75	10.90	11.00	Yes	
			155	5775			11.00			10.90		
	802.11 ax80	HE0	138	5690	10.96	10.90	11.00	10.75	10.90	11.00	Yes	
			155	5775	10.92	10.90	11.00	10.88	10.90	11.00		

**Initial test configuration**

1. NR: Not Required
2. When band gap channels between U-NII-2C and U-NII-3 band are supported channels in U-NII-2C band below 5.65 GHz are considered as one band and channels above 5.65 GHz, together with channels in 5.8 GHz U-NII-3 or §15.247 band, are considered as a separate band
3. Additional conducted power measurement is required when reported SAR is > 1.2W/kg. In case the subsequent test configuration and the channel bandwidth is smaller than the initial test configuration, all channels that overlap with the larger channel bandwidth in the initial configuration should be tested
4. The initial test configuration for 2.4 GHz and 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, highest order modulation and highest data rate, highest order 802.11 mode is selected (i.e. a, g, n, ac then ax)
5. When the reported SAR of the initial test configuration is > 0.8W/kg, SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until reported SAR is ≤1.2W/kg or all required channels are tested.
6. When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure requirements, is adjusted by the ratio of the subsequent test configuration to the initial test configuration specified maximum output power and the adjusted SAR is ≤1.2 W/Kg, SAR is not required for that subsequent test configuration.
7. SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the reported SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is >1.2 W/Kg or until all required channels are tested.

### B.2.3 Bluetooth

Band	Mode	Data Rate	Channel	Frequency (MHz)	Antenna	HB	SPEED	Tune-up Pwr (dBm)
2.4GHz	Bluetooth v5.2	Basic rate GFSK	0	2402	Aux	11.00	11.30	11.50
			39	2441		11.02	11.49	11.50
			78	2480		11.20	10.85	11.50
	Bluetooth v5.2	Basic rate π/4 DQPSK	0	2402				11.00
			39	2441				11.00
			78	2480				11.00
	Bluetooth v5.2	Basic rate 8-DPSK	0	2402				11.00
			39	2441				11.00
			78	2480				11.00
	Bluetooth v5.2	Low energy GFSK	0	2412				10.00
			20	2442				10.00
			39	2480				10.00

Initial test configuration

1. NR: Not Required

### B.3 Tissue Parameters Measurement

#### Body TSL

Freq. (MHz)	Target Parameters		Measured TSL Parameters		Deviation (%)		Date
	$\epsilon'$ (F/m)	$\sigma$ (S/m)	$\epsilon'$ (F/m)	$\sigma$ (S/m)	$\epsilon'$	$\sigma$	
2450	52.70	1.95	51.95	2.04	-1.42	4.62	2021-06-29
5300	48.88	5.42	47.03	5.45	-3.78	0.55	
5600	48.47	5.77	46.43	6.00	-4.21	3.99	
5800	48.20	6.00	46.30	6.07	-3.94	1.17	

See Annex D for more details.

### B.4 System Check Measurements

#### Body Measurements

Frequency (MHz)	Average	Target SAR (W/Kg)	Measured SAR (W/Kg)	Deviation to target (%)	Limit (%)	Date
2450	1g	48.60	50.80	4.53	$\pm 10$	2021-06-29
	10g	23.00	23.60	2.61		
5300	1g	71.70	71.40	-0.42	$\pm 10$	2021-06-30
	10g	20.00	20.20	1.00		
5600	1g	76.50	75.65	-1.11	$\pm 10$	2021-06-30
	10g	21.20	21.96	3.57		
5800	1g	73.40	72.46	-1.29	$\pm 10$	2021-06-30
	10g	20.00	20.56	2.79		

See Annex C for more details.

## B.5 SAR Test Results

### B.5.1 Bluetooth & 802.11b/g/n/ax – 2.4GHz – DTS – BT (DSS)

Manufacturer	Mode Data rate	BW (MHz)	Ch #	Freq (MHz)	Position	Antenna	Correct. Factor (dB)	SAR 1g (W/kg)	Reported SAR 1g (W/kg)	Plot #
HongBo	802.11b 1Mbps	20	11	2462	Laptop	Main	0.03	0.31	0.31	
			1	2412		Aux	0.10	0.33	0.34	1
	802.15 DH5	1	78	2480		Aux	0.30	0.10	0.11	
	802.11b 1Mbps	20	1	2412		Main	0.04	0.33	0.33	
			6	2437		Aux	0.04	0.24	0.24	
	802.15 DH5	1	39	2441		Aux	0.01	0.10	0.10	

### B.5.2 802.11a/n/ac/ax – 5.3 GHz – U-NII-2A

Manufacturer	Mode Data rate	BW (MHz)	Ch #	Freq (MHz)	Position	Antenna	Correct. Factor (dB)	SAR 1g (W/kg)	Reported SAR 1g (W/kg)	Plot #	
HongBo	802.11ax HE0	160	50	5250	Laptop	Main	0.04	0.28	0.29		
						Aux	0.05	0.48	0.48	2	
	802.11ax HE0	160	50	5250		Main	0.00	0.29	0.29		
						Aux	0.00	0.22	0.22		

### B.5.3 802.11a/n/ac/ax – 5.6 GHz – U-NII-2C

Manufacturer	Mode Data rate	BW (MHz)	Ch #	Freq (MHz)	Position	Antenna	Correct. Factor (dB)	SAR 1g (W/kg)	Reported SAR 1g (W/kg)	Plot #	
HongBo	802.11ax HE0	160	114	5570	Laptop	Main	0.10	0.43	0.44		
						Aux	0.25	0.63	0.67		
	802.11ax HE0	160	114	5570		Main	0.04	0.70	0.71	3	
						Aux	0.05	0.29	0.30		

### B.5.4 802.11a/n/ac/ax – 5.8 GHz – U-NII-3

Manufacturer	Mode Data rate	BW (MHz)	Ch #	Freq (MHz)	Position	Antenna	Correct. Factor (dB)	SAR 1g (W/kg)	Reported SAR 1g (W/kg)	Plot #
HongBo	802.11ax HE0	80	138	5690	Laptop	Main	0.04	0.70	0.72	
			155	5775		Aux	0.12	0.43	0.44	
	802.11ax HE0	80	155	5775		Main	0.10	0.89	0.91	4
			138	5690		Aux	0.10	0.79	0.81	
			138	5690		Aux	0.10	0.25	0.25	

### B.5.5 SAR Measurement Variability

According to FCC OET KDB 865664, SAR Measurement variability is assessed when the maximum initial measured SAR is  $\geq 0.8$  W/kg for a certain band mode. If the measured SAR value of the initial repeated measurement is  $< 1.45$  W/kg with  $< 20\%$  variation, only one repeated measurement is required to confirm that the results are not expected to have substantial variations.

A second repeated measurement is required only if the measured results for the initial repeated measurement are within 10% of the SAR limit or vary by more than 20%.

A third repeated measurement is required only if the original, first or second repeated measurement  $\geq 1.5$  W/Kg and the ratio of largest to smallest SAR for the original, first and second repeated measurement is  $> 1.2$ .

Band / Mode	Position	Ch #	Freq. (MHz)	Measured SAR 1g (W/kg)	1 <sup>st</sup> Repeated SAR 1g (W/Kg)	2 <sup>nd</sup> Repeated SAR 1g (W/Kg)	Highest Ratio
5.8GHz 802.11ax80 HE0	Laptop	155	5775	0.89	0.89		1.00

### B.5.6 Simultaneous Transmission SAR Evaluation

According to FCC OET KDB 447498 D01, when the sum of 1g SAR for all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit, SAR test exclusion applies to that simultaneous transmission configuration.

All the values stated in the table below are the worst case found for standalone measurement with disregard of the transmission mode or channel where the worst case was found

Antenna	Position	Highest Reported SAR (1g) (W/Kg)		
		WLAN 2.4GHz	WLAN 5GHz	Bluetooth
Main	Laptop	0.33	0.91	
Aux		0.34	0.67	0.11

Position	Simultaneous Tx Antenna Combination		$\Sigma$ SAR 1g (W/Kg)	Limit (W/kg)
	Main Antenna	Aux Antenna		
Laptop	WLAN 5GHz	WLAN 5GHz	1.58	1.6
	WLAN 5GHz	WLAN 5GHz + BT	<b>1.69</b>	
	WLAN 5GHz	BT	1.02	
	WLAN 2.4GHz	WLAN 2.4GHz	0.67	
	WLAN 2.4GHz	BT	0.44	

In case the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio:

Position	Antenna	Reported SAR 1g (W/kg)	$\Sigma$ SAR 1g (W/Kg)	Peak Location (mm) (x,y,z)	SAR to peak location separation ratio	Limit
Laptop	Main WLAN 5GHz	0.91	1.69	(48.0 ; 172.5 ; -180.9)	0.01	0.04
	WLAN 5GHz + BT	0.78		(49.5 ; -167.5 ; -180.6)		

Considering the results described above and according to the simultaneous transmission evaluation exclusions described in FCC OET KDB 447498 D01, enlarged zoom scan measurements are not required

# Annex C. Test System Plots

---

1. DTS - 802.11b, CH1, HongBo Antenna, Aux transmitter.....	36
2. U-NII-2A - 802.11ax160, CH50, Hongbo Antenna, Aux transmitter .....	37
3. U-NII-2C - 802.11ax160, CH114, SPEED Antenna, Main transmitter .....	38
4. U-NII-3 - 802.11ax80, CH155, SPEED Antenna, Main transmitter .....	39
5. System Check Body Liquid 2450MHz .....	40
6. System Check Body Liquid 5300MHz .....	41
7. System Check Body Liquid 5600MHz .....	42
8. System Check Body Liquid 5800MHz .....	43

## 1. DTS - 802.11b, CH1, HongBo Antenna, Aux transmitter

**Device under Test Properties**

Name, Manufacturer	Dimensions [mm]	S/N	DUT Type
DELL P107F	355.0 x 248.0 x 19.0	2020121517940	Laptop

**Exposure Conditions**

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, MSL	FRONT, 0.00	WLAN 2.4GHz	WLAN, 10315-AAB	2412.0, 1	8.16	2.00	52.0

**Hardware Setup**


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) -	MBBL-600-6000, 2021-Jun-29	EX3DV4 - SN7604, 2020-08-07	DAE4 Sn1628, 2020-07-30

**Scan Setup**

	Area Scan	Zoom Scan
Grid Extents [mm]	200.0 x 120.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	10.0 x 10.0	5.0 x 5.0 x 1.5
Sensor Surface [mm]	3.0	1.4
Graded Grid	No	Yes
Grading Ratio	n/a	1.5
MAIA	Confirmed by MAIA	Confirmed by MAIA
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

**Measurement Results**

	Area Scan	Zoom Scan
Date	2021-06-29, 12:33	2021-06-29, 12:40
psSAR1g [W/Kg]	0.319	0.327
psSAR10g [W/Kg]	0.170	0.163
Power Drift [dB]	0.01	0.05
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	Positive Only	Positive Only
M2/M1 [%]		
Dist 3dB Peak [mm]	67.5	9.0



## 2. U-NII-2A - 802.11ax160, CH50, Hongbo Antenna, Aux transmitter

**Device under Test Properties**

Name, Manufacturer	Dimensions [mm]	S/N	DUT Type
DELL P107F	355.0 x 248.0 x 19.0	2020121517940	Laptop

**Exposure Conditions**


Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, MSL	FRONT, 0.00	WLAN 5GHz	WLAN, 10743-AAB	5250.0, 50	4.72	5.36	47.1

**Hardware Setup**

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) -	MBBL-600-6000, 2021-Jun-29	EX3DV4 - SN7604, 2020-08-07	DAE4 Sn1628, 2020-07-30

**Scan Setup**

	Area Scan	Zoom Scan	Measurement Results	Area Scan	Zoom Scan
Grid Extents [mm]	200.0 x 120.0	22.0 x 22.0 x 22.0	Date	2021-06-29,	2021-06-29, 14:19
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4		14:12	
Sensor Surface [mm]	3.0	1.4	psSAR1g [W/Kg]	0.437	0.477
Graded Grid Grading Ratio	No n/a	Yes 1.4	psSAR10g [W/Kg]	0.123	0.118
MAIA Surface Detection Scan Method	Confirmed by MAIA VMS + 6p	Confirmed by MAIA VMS + 6p	Power Drift [dB]	-0.02	-0.01
	Measured	Measured	Power Scaling	Disabled	Disabled
			Scaling Factor [dB]		
			TSL Correction	Positive Only	Positive Only
			M2/M1 [%]		64.0
			Dist 3dB Peak [mm]		4.7



### 3. U-NII-2C - 802.11ax160, CH114, SPEED Antenna, Main transmitter

**Device under Test Properties**

Name, Manufacturer	Dimensions [mm]	S/N	DUT Type
DELL P107F	355.0 x 248.0 x 19.0	2020121517933	Laptop

**Exposure Conditions**


Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, MSL	FRONT, 0.00	WLAN 5GHz	WLAN, 10743-AAB	5570.0, 114	4.29	5.93	46.4

**Hardware Setup**

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) -	MBBL-600-6000, 2021-Jun-29	EX3DV4 - SN7604, 2020-08-07	DAE4 Sn1628, 2020-07-30

**Scan Setup**

	Area Scan	Zoom Scan	Measurement Results
Grid Extents [mm]	200.0 x 120.0	22.0 x 22.0 x 22.0	Date 2021-06-30, 10:54
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4	psSAR1g [W/Kg] 0.601
Sensor Surface [mm]	3.0	1.4	psSAR10g [W/Kg] 0.157
Graded Grid	No	Yes	Power Drift [dB] -0.01
Grading Ratio	n/a	1.4	Power Scaling Disabled
MAIA	Confirmed by MAIA	Confirmed by MAIA	Scaling Factor [dB]
Surface Detection	VMS + 6p	VMS + 6p	TSL Correction
Scan Method	Measured	Measured	M2/M1 [%]
			Dist 3dB Peak [mm]
			Positive Only
			Positive Only
			62.6
			5.1



## 4. U-NII-3 - 802.11ax80, CH155, SPEED Antenna, Main transmitter

**Device under Test Properties**

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
DELL P107F	355.0 x 248.0 x 19.0	2020121517933	Laptop

**Exposure Conditions**

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, MSL	FRONT, 0.00	WLAN 5GHz	WLAN, 10719-AAB	5775.0, 155	4.21	6.08	46.5

**Hardware Setup**


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) -	MBBL-600-6000, 2021-Jun-29	EX3DV4 - SN7604, 2020-08-07	DAE4 Sn1628, 2020-07-30

**Scan Setup**

	Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4
Graded Grid	No	Yes
Grading Ratio	n/a	1.4
MAIA	Confirmed by MAIA	Confirmed by MAIA
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

**Measurement Results**

	Area Scan	Zoom Scan
Date	2021-06-30, 11:09	2021-06-30, 11:16
psSAR1g [W/Kg]	0.744	0.888
psSAR10g [W/Kg]	0.181	0.193
Power Drift [dB]	-0.05	0.00
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	Positive Only	Positive Only
M2/M1 [%]		
Dist 3dB Peak [mm]	61.3	5.1



## 5. System Check Body Liquid 2450MHz

**Device under Test Properties**

Name, Manufacturer	Dimensions [mm]	Serial Number	DUT Type
D2450V2, SPEAG	50.0 x 10.0 x 15.0	937	Validation Dipole

**Exposure Conditions**

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, MSL	,	,	0--	2450.0, 0	8.16	2.04	52.0

**Hardware Setup**


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) -	MBBL-600-6000, 2021-Jun-29	EX3DV4 - SN7604, 2020-08-07	DAE4 Sn1628, 2020-07-30

**Scan Setup**

	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	10.0 x 10.0	5.0 x 5.0 x 1.5
Sensor Surface [mm]	3.0	1.4
Graded Grid	No	Yes
Grading Ratio	n/a	1.5
MAIA	Confirmed by MAIA	Confirmed by MAIA
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

**Measurement Results**

	Area Scan	Zoom Scan
Date	2021-06-29, 10:00	2021-06-29, 10:06
psSAR1g [W/Kg]	2.50	2.54
psSAR10g [W/Kg]	1.14	1.18
Power Drift [dB]	-0.00	0.01
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	Positive Only	Positive Only
M2/M1 [%]		80.1
Dist 3dB Peak [mm]		9.0



## 6. System Check Body Liquid 5300MHz

**Device under Test Properties**

Name, Manufacturer	Dimensions [mm]	Serial Number	DUT Type
D5GHzV2 , SPEAG	50.0 x 10.0 x 8.0	1164	Validation Dipole

**Exposure Conditions**


Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, MSL	,	,	0--	5300.0, 0	4.72	5.45	47.0

**Hardware Setup**

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) -	MBBL-600-6000, 2021-Jun-29	EX3DV4 - SN7604, 2020-08-07	DAE4 Sn1628, 2020-07-30

**Scan Setup**

	Area Scan	Zoom Scan	Measurement Results	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	22.0 x 22.0 x 22.0	Date	2021-06-29,	2021-06-29, 11:01
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4		10:55	
Sensor Surface [mm]	3.0	1.4	psSAR1g [W/Kg]	3.54	3.80
Graded Grid Grading Ratio	No n/a	Yes 1.4	psSAR10g [W/Kg]	1.01	1.08
MAIA Surface Detection Scan Method	Confirmed by MAIA VMS + 6p	Confirmed by MAIA VMS + 6p	Power Drift [dB]	-0.01	-0.01
	Measured	Measured	Power Scaling	Disabled	Disabled
			Scaling Factor [dB]		
			TSL Correction	Positive Only	Positive Only
			M2/M1 [%]		64.8
			Dist 3dB Peak [mm]		7.2



## 7. System Check Body Liquid 5600MHz

**Device under Test Properties**

Name, Manufacturer	Dimensions [mm]	Serial Number	DUT Type
D5GHzV2 , SPEAG	50.0 x 10.0 x 8.0	1164	Validation Dipole

**Exposure Conditions**


Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, MSL	,	,	0--	5600.0, 0	4.29	6.00	46.4

**Hardware Setup**

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) -	MBBL-600-6000, 2021-Jun-29	EX3DV4 - SN7604, 2020-08-07	DAE4 Sn1628, 2020-07-30

**Scan Setup**

	Area Scan	Zoom Scan	Measurement Results	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	22.0 x 22.0 x 22.0	Date	2021-06-30, 12:32	2021-06-30, 12:38
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4	psSAR1g [W/Kg]	3.46	3.79
Sensor Surface [mm]	3.0	1.4	psSAR10g [W/Kg]	0.996	1.10
Graded Grid	No	Yes	Power Drift [dB]	-0.01	0.07
Grading Ratio	n/a	1.4	Power Scaling	Disabled	Disabled
MAIA	Confirmed by MAIA	Confirmed by MAIA	Scaling Factor [dB]		
Surface Detection	VMS + 6p	VMS + 6p	TSL Correction	Positive Only	Positive Only
Scan Method	Measured	Measured	M2/M1 [%]		61.7
			Dist 3dB Peak [mm]		7.5



## 8. System Check Body Liquid 5800MHz

**Device under Test Properties**

Name, Manufacturer	Dimensions [mm]	Serial Number	DUT Type
D5GHzV2 , SPEAG	50.0 x 10.0 x 8.0	1164	Validation Dipole

**Exposure Conditions**


Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, MSL	,	,	0--	5800.0, 0	4.21	6.07	46.3

**Hardware Setup**

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) -	MBBL-600-6000, 2021-Jun-29	EX3DV4 - SN7604, 2020-08-07	DAE4 Sn1628, 2020-07-30

**Scan Setup**


	Area Scan	Zoom Scan	Measurement Results	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	22.0 x 22.0 x 22.0	Date	2021-06-30, 13:34	2021-06-30, 13:40
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4	psSAR1g [W/Kg]	3.24	3.63
Sensor Surface [mm]	3.0	1.4	psSAR10g [W/Kg]	0.942	1.03
Graded Grid	No	Yes	Power Drift [dB]	-0.06	-0.01
Grading Ratio	n/a	1.4	Power Scaling	Disabled	Disabled
MAIA	Confirmed by MAIA	Confirmed by MAIA	Scaling Factor [dB]		
Surface Detection	VMS + 6p	VMS + 6p	TSL Correction	Positive Only	Positive Only
Scan Method	Measured	Measured	M2/M1 [%]		58.9
			Dist 3dB Peak [mm]		7.5



# Annex D. TSL Dielectric Parameters

## D.1 Body DTS 2450MHz


Freq. (MHz)	Target		Measured	
	$\epsilon'$ (F/m)	$\sigma$ (S/m)	$\epsilon'$ (F/m)	$\sigma$ (S/m)
2400	52.77	1.90	52.04	1.98
2410	52.75	1.91	52.02	2.00
2420	52.74	1.92	52.00	2.01
2430	52.73	1.93	51.98	2.02
2440	52.71	1.94	51.97	2.03
2450	52.70	1.95	51.95	2.04
2460	52.69	1.96	51.94	2.05
2470	52.67	1.98	51.93	2.06
2480	52.66	1.99	51.93	2.07
2490	52.65	2.01	51.92	2.08
2500	52.64	2.02	51.92	2.10



## D.2 Body 5180MHz-5900MHz

Freq. (MHz)	Target		Measured	
	$\epsilon'$ (F/m)	$\sigma$ (S/m)	$\epsilon'$ (F/m)	$\epsilon'$ (F/m)
5180.0	49.04	5.28	47.21	5.31
5190.0	49.03	5.29	47.20	5.32
5200.0	49.01	5.30	47.20	5.32
5210.0	49.00	5.31	47.20	5.33
5220.0	48.99	5.32	47.18	5.33
5230.0	48.97	5.33	47.14	5.34
5240.0	48.96	5.35	47.13	5.35
5250.0	48.95	5.36	47.11	5.36
5260.0	48.93	5.37	47.08	5.37
5270.0	48.92	5.38	47.07	5.39
5280.0	48.91	5.39	47.06	5.41
5290.0	48.89	5.40	47.04	5.43
5300.0	48.88	5.42	47.03	5.45
5310.0	48.87	5.43	47.03	5.47
5320.0	48.85	5.44	47.02	5.49
5330.0	48.84	5.45	47.00	5.51
5340.0	48.82	5.46	46.98	5.53
5350.0	48.81	5.47	46.96	5.55
5360.0	48.80	5.49	46.96	5.58
5370.0	48.78	5.50	46.94	5.60
5380.0	48.77	5.51	46.92	5.63
5390.0	48.76	5.52	46.90	5.65
5400.0	48.74	5.53	46.88	5.68
5410.0	48.73	5.54	46.86	5.70
5420.0	48.72	5.56	46.84	5.72
5430.0	48.70	5.57	46.80	5.74
5440.0	48.69	5.58	46.77	5.76
5450.0	48.67	5.59	46.73	5.78
5460.0	48.66	5.60	46.69	5.79
5470.0	48.65	5.61	46.66	5.80
5480.0	48.63	5.63	46.61	5.82
5490.0	48.62	5.64	46.58	5.84
5500.0	48.61	5.65	46.56	5.84
5510.0	48.59	5.66	46.55	5.86
5520.0	48.58	5.67	46.52	5.87
5530.0	48.57	5.68	46.49	5.88
5540.0	48.55	5.70	46.49	5.89
5550.0	48.54	5.71	46.47	5.90
5560.0	48.53	5.72	46.45	5.91
5570.0	48.51	5.73	46.45	5.93
5580.0	48.50	5.74	46.45	5.95
5590.0	48.48	5.75	46.43	5.97
5600.0	48.47	5.77	46.43	6.00
5610.0	48.46	5.78	46.43	6.02
5620.0	48.44	5.79	46.41	6.04
5630.0	48.43	5.80	46.41	6.05
5640.0	48.42	5.81	46.41	6.07
5650.0	48.40	5.82	46.42	6.09
5660.0	48.39	5.84	46.44	6.10
5670.0	48.38	5.85	46.45	6.11
5680.0	48.36	5.86	46.48	6.12
5690.0	48.35	5.87	46.49	6.12

Freq. (MHz)	Target		Measured	
	$\epsilon'$ (F/m)	$\sigma$ (S/m)	$\epsilon'$ (F/m)	$\epsilon'$ (F/m)
5700.0	48.34	5.88	46.51	6.12
5710.0	48.32	5.90	46.53	6.12
5720.0	48.31	5.91	46.53	6.11
5730.0	48.30	5.92	46.54	6.11
5740.0	48.28	5.93	46.54	6.10
5750.0	48.27	5.94	46.52	6.09
5760.0	48.25	5.95	46.51	6.08
5770.0	48.24	5.97	46.48	6.08
5780.0	48.23	5.98	46.44	6.07
5790.0	48.21	5.99	46.37	6.07
5800.0	48.20	6.00	46.30	6.07
5810.0	48.19	6.01	46.22	6.07
5820.0	48.17	6.02	46.14	6.07
5830.0	48.16	6.04	46.05	6.07
5840.0	48.15	6.05	45.95	6.08
5850.0	48.13	6.06	45.85	6.09
5860.0	48.12	6.07	45.75	6.10
5870.0	48.10	6.08	45.65	6.12
5880.0	48.09	6.09	45.57	6.14
5890.0	48.08	6.11	45.48	6.17
5900.0	48.06	6.12	45.40	6.20



# Annex E. Calibration Certificates

ID	Device	Type/Model	Serial Number	Manufacturer	Calibration Certificate
004-006	Dosimetric E-field Probe	EX3DV4	7604	SPEAG	
070-000	2450MHz System Validation Dipole	D2450V2	937	SPEAG	
068-000	5GHz System Validation Dipole	D5GHzV2	1164	SPEAG	

## Dipole calibration

According to the KDB 865664 D01, a dipole must be calibrated using a fully validated SAR system according to the tissue dielectric parameters and SAR probe calibration frequency required for device testing. However, instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements.

1. When the most recent return-loss result, measured at least annually, deviates by less than 20% from the previous measurement (i.e. value in dB  $\times 0.2$ ) or not meeting the required 20 dB minimum return-loss requirement.
2. When the most recent measurement of the real or imaginary parts of the impedance, measured at least annually, deviates by less than 5 Ω from the previous measurement

The below results show the latest return loss and impedance measurements for each dipole performed by the lab:

<b>Dipole ID #070-000</b>			
<b>Dipole 2450MHz Body TSL</b>			
	Return Loss [dB]	Impedance [Ω]	Date
Initial Calibration	-29.7	50.85 + 3.20 j	2020-05-12
Last	-28.5	48.17 – 3.19 j	2021-05-14
<b>Dipole ID #068-000</b>			
<b>Dipole 5200MHz Body TSL</b>			
	Return Loss [dB]	Impedance [Ω]	Date
Initial Calibration	-31.5	50.0 – 2.6 j	2021-05-18
<b>Dipole 5300MHz Body TSL</b>			
	Return Loss [dB]	Impedance [Ω]	Date
Initial Calibration	-31.0	50.7 + 3.0 j	2021-05-18
<b>Dipole 5500MHz Body TSL</b>			
	Return Loss [dB]	Impedance [Ω]	Date
Initial Calibration	-29.9	49.0 + 3.0 j	2021-05-18
<b>Dipole 5600MHz Body TSL</b>			
	Return Loss [dB]	Impedance [Ω]	Date
Initial Calibration	-23.6	53.2 – 6.0 j	2021-05-18
<b>Dipole 5800MHz Body TSL</b>			
	Return Loss [dB]	Impedance [Ω]	Date
Initial Calibration	-20.9	53.8 + 8.6 j	2021-05-18