



EVALUATION REPORT

EUT Description	WLAN and BT, 2x2 PCIe M.2 2230 SD adapter card
Brand Name	Intel® Wi-Fi 6E AX411
Model Name	AX411NGW
FCC ID	PD9AX411NG
Date of Test Start/End	2024-04-26 / 2024-04-26
Features	802.11ax, Tri Band, 2x2 Wi-Fi 6E + Bluetooth® 5.2 + CDB (Concurrent Dual Band simultaneous wi-fi connection) (see section 3)

Applicant	Intel Corporation SAS
Address	425 Rue de Goa – Le Cargo B6 – 06600 Antibes, FRANCE
Contact Person	Benjamin Lavenant
Telephone/Fax/ Email	Benjamin.lavenant@intel.com

Reference Standards	FCC 47 CFR 1.1310 FCC 47 CFR 2.1091 (see section 1)
---------------------	---

Test Report identification	230704-01.TR44
Revision Control	Rev. 00 This test report revision replaces any previous test report revision (see section 4)

Reference to accreditation shall be used only by full reproduction of test report

Issued by _____ Reviewed by _____

Adel LOUNES
(SAR Test Lead Engineer)

Zayd OUACHICHA
(Technical Manager)

Intel Corporation SAS – WRF Lab
425 rue de Goa – Le Cargo B6 - 06600 Antibes, France
Tel. +33493001400 / Fax +33493001401

Table of Contents

- 1. **Standards, reference documents and applicable test methods** 3
- 2. **General conditions, competences and guarantees** 3
- 3. **EUT Features**..... 4
- 4. **Document Revision History** 5
 - A.1 RF EXPOSURE LIMIT 6
 - A.2 EXPOSURE FROM SOURCE WITH MULTIPLE FREQUENCIES 6
 - B.1 DECLARED MAXIMUM OUTPUT POWER 7
 - B.2 RF EXPOSURE EVALUATION RESULTS 7
 - B.2.1 UNII 6GHZ AND BT 7

1. Standards, reference documents and applicable test methods

FCC

FCC 47 CFR Part §1.1310 Radiofrequency radiation exposure limits. Edition October 2021
FCC 47 CFR Part §2.1091 Radiofrequency radiation exposure evaluation: mobile devices. Edition October 2021

2. General conditions, competences and guarantees

- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an ISO/IEC 17025:2017 laboratory accredited by the American Association for Laboratory Accreditation (A2LA) with the certificate number 3478.01.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an Accredited Test Firm recognized by the FCC, with Designation Number FR0011
- ✓ Intel WRF Lab only provides testing services and is committed to providing reliable, unbiased test results and interpretations.
- ✓ Intel WRF Lab is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.
- ✓ Intel WRF Lab has developed calibration and proficiency programs for its measurement equipment to ensure correlated and reliable results to its customers.
- ✓ This report is only referred to the item that has undergone the test.
- ✓ This report does not imply an approval of the product by the Certification Bodies or competent Authorities.

3. EUT Features

The herein information is provided by the customer

Intel WRF Lab declines any responsibility for the accuracy of the stated customer provided information, especially if it has any impact on the correctness of test results presented in this report.

Brand Name	Intel® Wi-Fi 6E AX411		
Model Name	AX411NGW		
Supported Radios	802.11b/g/n/ax 802.11a/n/ac/ax 802.11ax Bluetooth	2.4GHz (2400.0 – 2483.5 MHz) 5.2GHz (5150.0 – 5350.0 MHz) 5.6GHz (5470.0 – 5725.0 MHz) 5.8GHz (5725.0 – 5850.0 MHz) 5.9GHz (5850.0 – 5895.0 MHz) 6.0GHz (5925.0 – 7125.0 MHz) 2.4GHz (2400.0 – 2483.5 MHz)	
Antenna Information	For 6E bands:		
	Transmitter	Main/Chain B	Aux/Chain A
	Manufacturer	Intel WRFLab	Intel WRFLab
	Antenna type	PIFA	PIFA
	Part number	WRF-BR-PIFA-V3.2	WRF-BR-PIFA-V3.2
	Frequency Band		Peak gain w/cable loss (dBi)
	6.2 GHz (5925.0MHz-6425.0MHz)		4.83
	6.5 GHz (6425.0MHz-6525.0MHz)		4.30
	6.7 GHz (6525.0MHz-6875.0MHz)		5.37
	7.0 GHz (6875.0MHz-7125.0MHz)		5.59
For 2.4GHz band:			
Transmitter	Main/Chain B	Aux/Chain A	
Manufacturer	SkyCross	SkyCross	
Antenna type	PIFA	PIFA	
Part number	n/a	n/a	
Frequency Band		Peak gain w/cable loss (dBi)	
2.4 GHz (2300.0MHz-2500.0MHz)		3.54	
Simultaneous Transmission Configurations	Mode	TX Chain B	TX Chain A
	Single Band Mode 2.4GHz		
	2.4GHz MIMO	WLAN 2.4GHz	WLAN 2.4GHz
	2.4GHz SISO / Co-run	WLAN 2.4GHz	BT
	Single Band Mode 5GHz		
	5GHz MIMO	WLAN 5GHz	WLAN 5GHz
	5GHz + BT Co-run	WLAN 5GHz	BT
	5GHz MIMO + BT Co-run	WLAN 5GHz	WLAN 5GHz + BT
	CDB Mode		
	BT Co-run – CDB SISO	WLAN 2.4GHz + WLAN 5GHz	BT
	CDB only SISO	WLAN 2.4GHz + WLAN 5GHz	-
	CDB only SISO	-	WLAN 2.4GHz + WLAN 5GHz
	CDB only MIMO	WLAN 2.4GHz + WLAN 5GHz	WLAN 2.4GHz + WLAN 5GHz
BT Co-run (CDB SISO)	WLAN 2.4GHz	WLAN 5GHz + BT	

4. Document Revision History

Revision #	Modified by	Revision Details
Rev. 00	A.Lounes	First Issue

Annex A. Evaluation Description

A.1 RF Exposure Limit

According to the FCC part 1.1310:

- For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in the table below.

Limits for Maximum Permissible Exposure (MPE) (TABLE 1 TO §1.1310(E)(1))

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500	-	-	f/1500	<30
1,500-100,000	-	-	1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

For the purpose of this evaluation, a distance of 20cm was used to calculate the equivalent plan wave power density, to be compared with the limit described in the table above:

$$S_{eq} = \frac{P_{avg} \cdot G}{4 \cdot \pi \cdot R^2}$$

Where:

S_{eq} = Equivalent Plane Wave Power Density

P_{avg} = Average Power at antenna terminals in Watts

G = Gain of the Transmitting Antenna

R = Distance from the Transmitting Antenna in meters

A.2 Exposure from source with Multiple Frequencies

If the device is designed such that more than one antenna can functionally transmit at the same time, the RF exposure evaluation shall be conducted while all antennas are transmitting. The individual exposure level ratios shall be totaled and used for compliance purposes.:

$$\sum \frac{S_{eq_i}}{S_{Limit_i}} < 1$$

Annex B. RF Exposure Evaluation Results

B.1 Declared Maximum Output Power

According to the applicant, the maximum conducted transmit power (including the upper tolerance) for the EUT under evaluation are as follows:

Mode	Max Output Power (incl. Tolerance) (dBm)
UNII 6GHz	20.50
BT	11.50

B.2 RF Exposure Evaluation Results

Power Density Calculations

Mode	Highest Power Density @ 20cm (mW/cm ²)	Limit (mW/cm ²)	Verdict
UNII 6GHz	0.08	1.00	P
BT	0.01	1.00	P

Collocated Power Density Calculations

Mode	$\sum \frac{\text{Power Density}}{\text{Limit}}$	Ratio Max	Verdict
WLAN + BT	0.17	1.00	P

P: Pass
 F: Fail
 NM: Not Measured
 NA: Not Applicable

B.2.1 UNII 6GHz and BT

Band	Avg Power [dBm]	Peak antenna Gain (dBi)	EIRP Avg [dBm]	EIRP Avg [mW]	Power density @ 20cm [mW/cm ²]	Limit [mW/cm ²]	Ratio (Power density/Limit)
UNII 6GHz	20.50	5.59	26.09	406.44	0.08	1.00	0.08
BT	11.50	3.54	15.04	31.91	0.01	1.00	0.01

Test Report N° 230704-01.TR44

The maximum exposure for collocated transmitters is:

Band	Ratio (Power density/Limit)	\sum Ratio _i	Limit
UNII 6GHz	0.08	0.17	1.00
UNII 6GHz	0.08		
Bluetooth	0.01		

End of the Report

intentionally blank and marks the last page of the test report.