




APPENDIX B – EUT TEST SETUP PHOTOGRAPHS






[Tissue Liquid Depth : 15cm]




[Conducted Power Set-up Photographs]




■ Battery Type: Energizer (Alkaline)

GMRS	
Time	Power Out
0	2,050
2	1,890
4	1,840
6	1,800
8	1,760
10	1,700
12	1,650
14	1,600
16	1,540
18	1,510
20	1,490
22	1,430
24	1,380
26	1,320
28	1,280
30	1,240
32	1,200
34	1,180
36	1,140
38	1,120
40	1,070



■ Battery Type: Rocket (Alkaline)

FRS	
Time	Power Out
0	0.793
2	0.764
4	0.728
6	0.703
8	0.694
10	0.684
12	0.670
14	0.664
16	0.651
18	0.642
20	0.634
22	0.620
24	0.614
26	0.607
28	0.601
30	0.584
32	0.564
34	0.551
36	0.534
38	0.521
40	0.512



Date : December 23, 2002

Federal Communications Commission
Authorization and Evaluation Division
7435 Oskland Mills Road
Columbia, MD21046


Subject : GMRS-122 Battery Type

To whom it may concern

Here we would like to confirm that the 'AAA' type batteries only
should be used

For this subject model GMRS-122.(FCC ID: PDHGMRS122)

Sincerely Yours,
TTI tech Co., Ltd.



President / W. K. You