

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15CFMTX_RM-807_25.docx	Date of Report:	27-Feb-2012
Number of pages:	12	Customer's Contact person:	Huhtala Tero
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Customer:	Nokia Corporation P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880
FCC listing no.:	94436		
IC recognition no.:	661AK-1		
Tested devices/ accessories:	Phone RM-807 / Battery BV-4D / Charger AC-50E / Data Cable CA-190CD		
FCC ID:	PDNRM-807	IC:	661R-RM807
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards, RSS-210 (Issue 8, December 2010). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Jari Jantunen, System Manager, EMC

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	20-Feb-2012
Testing completed	23-Feb-2012
The customer's contact person	Huhtala Tero
Test Plan referred to	T:\Projects\RM-807\TestPlan\RS_testplan_RM-807.xls
Notes	-
Document name	T:\Projects\RM-807\EMC\FCC15CFMTX_RM-807_25.docx

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:

GSM/WCDMA/WLAN/Bluetooth/FM Transmitter

The EUT is tested with maximum rated TX power, modulated with pseudo random bit sequence (PRBS9).

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-807	004402137764209	2010	-	112.010.0903	42790
Battery	BV-4D	4175352012A10401710;0670613	Proto V4 PWB V1.1	-	-	42775
Charger	AC-50E	4090492023260400312;0675619	0.5	0.4	-	42776
Data Cable	CA-190CD	-	-	-	-	42778

1.2. Summary of Test Results

FM TX:

Section in CFR 47	Section in RSS-210	Name of the test	Result
15.239(a)	A2(0.8)	Field strength of the fundamental signal	PASSED
15.239(c)	A2(0.8)	Spurious radiated emissions	PASSED
15.207	6.6	AC powerline conducted emissions	NP
15.239(a)	A2(0.8)	26dB(bandwidth)	PASSED

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Nokia Laboratory.


CONTENTS

1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Field strength of the fundamental signal (FCC §15.239(a), RSS-210 A2.8)	4
2.2. Test method and limit	4
2.3. FMTX Test results	5
3. Spurious radiated emissions (FCC §15.239(c), RSS-210 A2.8)	6
3.2. Test method and limit	6
3.3. FMTX Test results	7
4. 26dB bandwidth (FCC §15.239(a), RSS-210 A2.8)	8
4.2. Test method and limit	8
4.3. FMTX Test results	9
5. Test Equipment.....	11
5.1. Conducted measurements	11
5.2. Radiated measurements	11

2. Field strength of the fundamental signal (FCC §15.239(a), RSS-210 A2.8)

EUT with DUT number	RM-807, DUT 42790
Accessories with DUT numbers	BV-4D, DUT 42775 ; AC-50E, DUT 42776 ; CA-190CD, DUT 42778
Operation Voltage [V] / [Hz]	115 / 60
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 45 / 98.6
Date of measurements	23-Feb-2012
Measured by	Timo Raiskio

2.1.1 Test Setup



2.2. Test method and limit

The measurement is made according to ANSI C63.4 and IC standard RSS-210.

Limits for field strength of the fundamental signal measurements (3 m measurement distance)

Limit [$\mu\text{V/m}$]	Limit [$\text{dB}\mu\text{V/m}$]	Detector
250	47.96	Average
2500	68	Peak

2.3. FMTX Test results

Middle channel / 98.0 MHz

Peak (RBW: 120 kHz, VBW: 300 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
98.033	50.67	341.468	86.13	-35.46	HORIZONTAL	PASSED

Average (RBW: 120 kHz, VBW: 300 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
97.973	47.59	239.552	83.05	-35.46	HORIZONTAL	PASSED

Low channel / 88.1 MHz

Peak (RBW: 120 kHz, VBW: 300 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
88.137	49.83	310.027	86.13	-36.3	HORIZONTAL	PASSED

Average(RBW: 120 kHz, VBW: 300 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
88.077	46.8	218.852	83.1	-36.3	HORIZONTAL	PASSED

High channel / 107.9 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
107.88	49.43	295.972	84.06	-34.63	HORIZONTAL	PASSED


Average(RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
107.88	46.73	217.045	81.36	-34.63	HORIZONTAL	PASSED

3. Spurious radiated emissions (FCC §15.239(c), RSS-210 A2.8)

EUT with DUT number	RM-807, DUT 42790
Accessories with DUT numbers	BV-4D, DUT 42775 ; AC-50E, DUT 42776 ; CA-190CD, DUT 42778
Operation Voltage [V] / [Hz]	115 / 60
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 45 / 98.6
Date of measurements	23-Feb-2012
Measured by	Timo Raiskio

3.1.1 Test Setup



3.2. Test method and limit

The measurement is made according to ANSI C63.4 and IC standard RSS-210 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu V/m] = U_R X + A_{TO} T$$

Where $U_R X$ is receiver reading and $A_{TO} T$ is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TO} T = L_{CABLE} S + A_F - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu\text{V/m}$]	Limit [dB $\mu\text{V/m}$]	Detector
30 - 88	100	40	Quasi peak
88 - 216	150	43.5	Quasi peak
216 - 960	200	46	Quasi peak
960 - 1000	500	54	Quasi peak
1000 - 1100	500	54	Average
1000 - 1100	5000	74	Peak

Spurious radiated emissions shall not exceed the field strength of the fundamental signal at any frequencies.

3.3. FMTX Test results

Middle channel / 98.0 MHz

Quasi peak (RBW: 120 kHz, VBW: 300 kHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
30.24	17.26	7.294	36.86	-19.6	HORIZONTAL	PASSED
30.895	17.52	7.512	37.43	-19.91	HORIZONTAL	PASSED
31.38	17.69	7.662	37.82	-20.13	HORIZONTAL	PASSED
31.563	17.77	7.733	37.99	-20.22	HORIZONTAL	PASSED
31.583	17.72	7.692	37.95	-20.23	HORIZONTAL	PASSED
32.182	17.75	7.714	38.26	-20.51	HORIZONTAL	PASSED
32.398	15.89	6.229	38.31	-22.42	VERTICAL	PASSED
32.805	17.4	7.413	38.2	-20.8	HORIZONTAL	PASSED
32.988	21.47	11.843	44.12	-22.65	VERTICAL	PASSED
33.207	15.38	5.876	38.11	-22.73	VERTICAL	PASSED

Low channel / 88.1 MHz

Quasi peak (RBW: 120 kHz, VBW: 300 kHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
176.2	10.79	3.464	39.05	-28.26	VERTICAL	PASSED
264.3	10.83	3.481	38.39	-27.56	HORIZONTAL	PASSED
352.4	12.9	4.417	37.74	-24.84	HORIZONTAL	PASSED

High channel / 107.9 MHz


Quasi peak (RBW: 120 kHz, VBW: 300 kHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
215.8	13.72	4.85	43.53	-29.81	VERTICAL	PASSED
323.7	13.3	4.624	38.75	-25.45	HORIZONTAL	PASSED
431.6	15.03	5.645	37.93	-22.9	HORIZONTAL	PASSED

4. 26dB bandwidth (FCC §15.239(a), RSS-210 A2.8)

EUT with DUT number	RM-807, DUT 42790
Accessories with DUT numbers	BV-4D, DUT 42775 ; AC-50E, DUT 42776 ; CA-190CD, DUT 42778
Operation Voltage [V] / [Hz]	115 / 60
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 45 / 98.6
Date of measurements	23-Feb-2012
Measured by	Timo Raiskio

4.1.1 Test Setup



4.2. Test method and limit

The measurement is made according to ANSI C63.4 and IC standard RSS-210.


Limits for 26 dB bandwidth measurements

Limit [kHz]
<200


4.3. FMTX Test results

Channel / f_c [MHz]	26 dB bandwidth [kHz]	Result
Middle / 98.0	140.28	PASSED
Low / 88.1	136.272	PASSED
High / 107.9	140.28	PASSED


High channel / 107.9 MHz



Low channel / 88.1 MHz



Middle channel / 98.0 MHz



5. Test Equipment

5.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM38112	Power supply	6632A	Agilent	22/24/27, 15C
TM38631	Signal Generator	83640L	Agilent	22/24/27, 15C, 15B
OM06312	Signal Generator	E4422B	Agilent	22/24
TM37678	Communication Tester	CMU200	R&S	15C, 15B
TM30600	Impulse limiter	ESH3-Z2	R&S	15C, 15B
TM26490	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
TM26491	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
TM37610	Spectrum Analyzer	FSU26	R&S	22/24/27, 15C
TM22806	Battery	BAT 20/E	Fiskars	15C, 15B
TM22805	UPS	PS 20/1.2	Fiskars	15C, 15B
-	Temperature and humidity logger	175-H2	Testo	15C, 15B
-	Temperature and humidity logger	175-H2	Testo	22/24/27, 15C
-	Air pressure and temperature logger	635-2	Testo	22/24/27, 15C, 15B
-	Air pressure sensor	0638-1835	Testo	22/24/27, 15C, 15B
-	Temperature test chamber	VT 4002	Vötsch	22/24
2058	Receiver	ESPC	R&S	15C, 15B
2001	Bluetooth tester	CBT	R&S	22/24/27, 15C, 15B
2002	Communication Tester	CMU200	R&S	22/24/27, 15C
2009	LISN 50 µH	ENV216	R&S	15C, 15B
2010	LISN 50 µH	ENV216	R&S	15C, 15B
2012	Power splitter	11667B	Agilent	22/24/27, 15C
2013	Attenuator	8493C	Agilent	22/24/27, 15C
2014	Attenuator	8493C	Agilent	22/24/27, 15C
2019	Power splitter	ZN2PD-9G-S+	Mini-Circuits	15E
2020	Power splitter	ZN2PD-9G-S+	Mini-Circuits	15E
2023	Spectrum Analyzer	ESMI-RF	R&S	15B/15C
2024	Analyzer display unit	ESAI-D	R&S	15B/15C

5.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM38114	Power supply	6632A	Agilent	22/24/27, 15C, 15B
TM38631	Signal Generator	83640L	Agilent	22/24/27, 15C, 15B
TM38323	Preamplifier	PA-02 18-26 GHz	EMC Automation	22/24/27, 15C, 15B
-	Antenna	BBHA 9120 D	Schwarzbeck	22/24/27, 15C
TM26497	Antenna	3115	Emco	22/24/27, 15C, 15B
TM37773	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM38845	Receiver	ESIB 26	R&S	22/24/27, 15C, 15B
-	Antenna	HL562	R&S	22/24/27, 15C, 15B
-	Turntable	2188	EMCO	22/24/27, 15C, 15B
-	Turntable controller	2090	EMCO	22/24/27, 15C, 15B
-	RF system panel	TS-RSP	R&S	22/24/27, 15C, 15B
-	RF system panel	TS-RSP	R&S	22/24/27, 15C, 15B
-	Mini mast	2075-2	ETS Lindgren	22/24/27, 15C, 15B
TM38843	Mini mast	2075	Emco	22/24/27, 15C, 15B
TM38842	Antenna mast controller	2090	Emco	22/24/27, 15C, 15B
TM30643	LISN 50 µH	LISN-5-20-2	FCC	22/24/27, 15C, 15B
TM30644	LISN 50 µH	LISN-5-20-2	FCC	22/24/27, 15C, 15B
-	Temperature and humidity logger	175-H2	Testo	22/24/27, 15C, 15B
-	Air pressure and temperature logger	635-2	Testo	22/24/27, 15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
-	Air pressure sensor	0638-1835	Testo	22/24/27, 15C, 15B
TM39180	Laser distance meter	Disto Pro	Leica	22/24/27, 15C, 15B
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	Miteq	22/24/27, 15C, 15B
TM37498	Preamplifier	AMF-5D-020180-26-10P	Miteq	22/24/27, 15C, 15B
TM30599	Semi anechoic chambre	UNKNOWN	TDK	22/24/27, 15C, 15B
TM22638	Power supply	OL63743-901	-	22/24/27, 15C, 15B
TM38066	High pass filter	4HC3000/18000-3-KK	Trilithic	22/24/27, 15C, 15B
-	High pass filter	WHKX 1.6/15G-12SS	Wainwright	22/24/27, 15C, 15B
TM37545	Tunable notch filter	800.0/960.0-0.2/40-8SSK	Wainwright	22
TM26512	Tunable notch filter	WRCD1850/1910-0.2/40-10SSK	Wainwright	24
-	Band reject filter	WRCG1877/1883-1870/1890-40/6EE	Wainwright	24
-	Band reject filter	WRCG1729.4/1735.4-1722.4/1742.4-40/6SS	Wainwright	27
-	Band reject filter	WRCG832/838-825/848-40/5SS	Wainwright	22
TM23892	Controller	G-1000SDX	Yaesu	22/24/27
2001	Bluetooth tester	CBT	R&S	22/24/27, 15C, 15B
6023	Antenna	VUBA 9117	Schwarzbeck	22/24/27, 15C