



Willow Run (WR) Test Labs, Inc.
7117 Fieldcrest Drive
Brighton, MI 48116
Phone: (734) 252-9785, Fax (734) 926-9785
e-mail: info@wrtest.com

RF EXPOSURE CALCULATIONS

Requirement:

According to USA CFR 15 §1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. For Canada, RSS-102 sets out the requirements and measurement techniques used to evaluate radio frequency (RF) exposure compliance of radiocommunication apparatus designed to be used within the vicinity of the human body.

USA REF: 1.1310, 2.1091/1093, 447498 D01 General RF Exposure Guidance v06 IC REF: RSS-102 Issue 5, Safety Code 6 Min. Sep. Distance: 20 cm (Mobile)										Test Date: 26-Mar-24	
										Test Engineer: John Nantz	
										EUT: BOSCH PKA2.2	
										EUT Mode: Worst Case	
										Meas. Distance: Conducted	
#	Mode	Freq. MHz	Worst Case EIRP(Pk/Avg)** dBm	Declared Tolerance (dB)	Worst Case EIRP w/ Tolerance dBm	E20cm(Avg) dBuV/m	S20cm(Avg) mW/cm2	Canada ISED RSS-102 MPE SC6 Limit (S20cm) W/m2	USA FCC 1.1310 MPE S Limit mW/cm2	MPE Total (<1):	0.0007157
R0	BLE/BT	2402	5.1	0.2	5.3	124.0	0.00064	5.5	1.00000	0.0006438	
R1	BLE/BT	2440	5.6	0.2	5.8	124.5	0.00072	5.5	1.00000	0.0007157	
R2	BLE/BT	2480	4.0	0.2	4.2	122.9	0.00050	5.5	1.00000	0.0004963	
R3	BLE/BT										
R4											
R5								Complies? Yes			
	C1	C2	C3		C4	C5	C6	C7	C8	C9	C10 C11
(ROW)	(COLUMN) NOTE										
R0	C3	Max of all data rates. As Measured / Computed from highest fundamental emission, see fundamental emission section of this report. Maximum of either EIRP or Pout as measured.									
R0	C5	EIRP (mW) = S (mW/cm^2) x 4 x PI x 20cm^2									

Summary:

The EUT with all transmitters is compliant with both the FCC power density limit and the ISED Exposure Evaluation limits.