

Electromagnetic Emission

FCC MEASUREMENT REPORT

CERTIFICATION OF COMPLIANCE


FCC Part 15 Certification Measurement


PRODUCT : SETTOP BOX
MODEL/Serial No. : DMS2004UHD W/ NONE
MULTIPLE MODEL : DMS2204UHDW, DMS2204UHD W, DMS2004UHDW, WC10HD
FCC ID : PFNDMS2004UHDW
APPLICANT : Digital Multimedia Technology Co., Ltd.
2nd Fl., 926 Gwanyang-Dong, Dongan-Gu, Anyang-Si,
Gyeonggi-Do, 431-060 Korea
Attn.: Jung Hwan Lee / Senior Research Engineer
MANUFACTURER : Hengdi Digital Technology (Shen Zhen) Co., Ltd
A.B Building, Xin Shi Qiao Guanjie Industrial Park, Guihua Community,
Guanlan Street, Bao'an District, Shenzhen City, Guangdong Province,
China, 518-110
EQUIPMENT CLASS : DTS (Part 15 Digital Transmission System)
TYPE OF MODULATION : DSSS
FREQUENCY CHANNEL : Zigbee: 2 425 MHz, 2 450 MHz, 2475 MHz (3 Ch)
ANTENNA TYPE : Internal Antenna (Integral)
ANTENNA GAIN : -2.30 dBi max
RF POWER : 0.187 mW
RULE PART(S) : FCC Part 15 Subpart C
FCC PROCEDURE : ANSI C63.10-2013
TEST REPORT No. : ETLT170118.0010
DATES OF TEST : January 23, 2017 to January 26, 2017
REPORT ISSUE DATE : February 10, 2017
TEST LABORATORY : ETL Inc. (FCC Designation Number : KR0022)

The SETTOP BOX, Model DMS2004UHD W has been tested in accordance with the measurement procedures specified in ANSI C63.10-2013 at the ETL Test Laboratory and has been shown to be complied with the electromagnetic radiated emission limits specified in FCC Rule Part15 Subpart C section 15.247.

I attest to the accuracy of data. All measurement herein was performed by me or was made under my supervision and is correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Prepared by: 
Seok Lyong, Choi (Test Engineer)
February 10, 2017

Reviewed by: 
Kug Kyoung, Yoon (Chief Engineer)
February 10, 2017

ETL Inc.

Head office: #371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea

Open site: #499-1, Sagot-ri, Seosin-myeon, Hwaseong-si, Gyeonggi-do, 445-882, Korea

Tel: 82-2-858-0786 Fax: 82-2-858-0788

The test report merely corresponds to the test sample(s).

This report shall not be reproduced, in whole or in part without the written approval of ETL Inc.

Table of Contents

FCC Measurement Report

- 1. Introduction**
- 2. Product Information**
- 3. Description of Tests**
- 4. Test Condition**
- 5. Test Results**
 - 5.1 Summary of Test Results**
 - 5.2 Spurious Emissions**
 - 5.3 Conducted Emissions Test**
- 6. Sample Calculation**
- 7. List of test Equipment used for Measurement**

FCC MEASUREMENT REPORT

Scope – Measurement and determination of electromagnetic emission (EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission(FCC)

General Information

Applicant Name	: Digital Multimedia Technology Co., Ltd.
Address	: 2nd Fl., 926 Gwanyang-Dong, Dongan-Gu, Anyang-Si, Gyeonggi-Do, 431-060 Korea
Attention	: Jung Hwan Lee / Senior Research Engineer

- **EUT Type** : SETTOP BOX
- **Model Number** : DMS2004UHD W
- **S/N** : NONE
- **Modulation Technique** : DSSS
- **Frequency Channel** : Zigbee: 2 425 MHz, 2 450 MHz, 2 475 MHz (3 Ch)
- **Antenna Type** : Internal Antenna (Integral)
- **Antenna Gain** : -2.30 dBi max
- **RF Power** : 0.187 mW
- **Environmental of Tests** : Temperature: (14.6 ± 13.4) °C
: Humidity: (49 ± 13) % R.H.
: Atmospheric Pressure: (103.0 ± 0.2) kPa
- **FCC Rule Part(s)** : FCC Part 15 Subpart C
- **Test Procedure** : ANSI C63.10-2013
- **Equipment Class** : DTS (Part 15 Digital Transmission System)
- **Place of Tests** : ETL Inc. Testing Lab. (FCC Designation Number : KR0022)

Radiated Emission test 1;
#499-1, Sagot-ri, Seosin-myeon, Hwaseong-si,
Gyeonggi-do, 445-882, Korea

Radiated Emission test 2 and Conducted Emission test;
#371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea
- **Test Report No.** : ETLT170118.0010

1. INTRODUCTION

The measurement test for radiated and conducted emission test was conducted at the ETL Inc. The site is constructed in conformance with the requirements of the ANSI C63.10-2013 and CISPR Publication 16. The ETL has site descriptions on file with the FCC for 3 m and 10 m site configurations. Detailed description of test facility was found to be in compliance with FCC Rules according to the ANSI C63.10-2013 and registered to the Federal Communications Commission (FCC Designation Number : KR0022).

The measurement procedure described in American National Standard for Method of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.10-2013) was used in determining radiated and conducted emissions from the Digital Multimedia Technology Co., Ltd. Model: DMS2004UHD W

2. PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the SETTOP BOX (model: DMS2004UHD W).

The model DMS2004UHD W is basic model that was tested.

The multi models WC10HD, DMS2204UHD W, DMS2004UHDW and DMS2204UHDW are identical to basic model, except for model designation.

The AC/DC Adapter was added. And, it was tested again.

AC/DC Adapter types may be used the one of two type selected by manufacturer.

Model name of AC/DC Adapter	View of AD/DC Adapter		
EDF0500150A1BA (Before)			
CYUS15-050150 (Addition)			

2.2 General Specification

Favorite channel, Parental Lock
Automatic search for newly added transponder (Network Auto Search)
Stores up to 5 000 channels
Plug-and-play data transfer system (DSR to DSR)
Timer function, automatically turns On/Off by setting function (daily, weekly, monthly and one time)
Automatic reserved channel moving system
Provide Electronic program Guide (EPG)
PAL/NTSC automatically conversion
Last channel automatically saving
Support RF4CE application
RF4CE Frequency range: 2 425 MHz ~ 2 475 MHz
Support for various video output: HDMI, RF 3/4 Mod.
HDMI 1.3a with HDCP 1.1
US3/4 Channel
MPEG-2 / MPEG-4 Part 10 / H.264
Video Display format with NTSC/480p/576p/720p/1 080i
Dolby Digital AC3
RF input frequency range: 105 MHz to 1 002 MHz
High Internal Frequency: X-tal → 54 MHz

3. DESCRIPTION OF TESTS

The tests documented in this report were performed in accordance with ANSI C63.10-2013 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

3.1 Radiated Emission Measurement

Radiated emission measurements were made in accordance with § 13 in ANSI C63.10-2013 "Measurement of Intentional radiators". The measurements were performed over the frequency range of 30 MHz to 40 GHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Peak, Quasi-peak, Average" within a bandwidth of 120 kHz and above 1 GHz is 1 MHz.

Preliminary measurements were made at 3 m using broadband antennas, and spectrum analyzer to determine the frequency producing the maximum emission in shielded room. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 MHz to 1 000 MHz using Log-Bicon antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used. Final measurements were made open site or SVSWR chamber at 3 m. The test equipment was placed on a styrofoam table. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8 m high nonmetallic 1.0 m x 1.5 m table. The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 m to 4 m and stopped at the azimuth or height producing the maximum emission.

Varying the mode of operating frequencies of the EUT maximized each emission. The system was tested in all the three orthogonal planes and changing the polarity of the antenna. The worst-case emissions are recorded in the data tables. If necessary, the radiated emission measurement could be performed at a closer distance to ensure higher accuracy and the results were extrapolated to the specified distance using an inverse linear distance extrapolation factor (20 dB/decade) as per section 15.31(f).

Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.

3.2 Conducted Emission Measurement

Conducted emissions measurements were made in accordance with section § 13 in ANSI C63.10-2013 "measurement of intentional radiators". The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50 Ω /50 μ H LISN as the input transducer to a Spectrum Analyzer or a Test Receiver. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 9 kHz or for "quasi-peak" within a bandwidth of 9 kHz.

The line-conducted emission test is conducted inside a shielded anechoic chamber room with 1 m x 1.5 m x 0.8 m wooden table which is placed 0.4 m away from the vertical wall and 1.5 m away from the side wall of the chamber room. Two LISN are bonded to the shielded room. The EUT is powered from the LISN and the support equipment is powered from the other LISN. Power to the LISNs are filtered by a noise cut power line filters. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and these supply lines will be connected to the LISN. Non-inductive bundling to a 1 m length shortened all interconnecting cables more than 1 m. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the EMI Test Receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using to set Quasi-Peak mode by manual, after scanned by automatic Peak mode from 0.15 MHz to 30 MHz. The bandwidth of the spectrum analyzer was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission.

Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.

3.3 FCC Part 15.205 Restricted Bands of Operations

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525 25	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.386 75	156.7 - 156.9	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	162.012 5 - 167.17	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	240 - 285	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	322 - 335.4	3 600 - 4 400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490 MHz - 0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.4 Antenna connection requirement

(1) According to §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

4. TEST CONDITION


4.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the following conditions and configurations were used.

4.2 Description of Test modes

SETTOP BOX that has the control software.

4.3 The setup drawing(s)



5. TEST RESULTS

5.1 Summary of Test Results

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum emission of the EUT are reported.

47 CFR Part 15, Subpart C	Measurement Required	Result
15.209(a)	Spurious Emissions	Pass
15.207	Conducted Emissions	Pass
15.203	Antenna connection requirement	Integral antenna which is permanently attached and cannot be replaced.

The data collected shows that the **Digital Multimedia Technology Co., Ltd. / SETTOP BOX / DMS2004UHD W** with technical requirements of above rules part 15.207, 209 Limits

The equipment is not modified anything, mechanical or circuits to improve EMI status during a measurement. No EMI suppression device(s) was added and/or modified during testing.

5.2 Spurious Emissions

EUT	SETTOP BOX / DMS2004UHD W
Limit apply to	FCC Part 15.209
Test Date	January 23, 2017 to January 26, 2017
Operating Condition	Low CH, Middle CH, High CH Transmission
Result	Passed

Limit

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequencies [MHz]	Field Strength [μV/m]	Measurement Distance [m]
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 MHz - 72 MHz, 76 MHz - 88 MHz, 174 MHz - 216 MHz or 470 MHz - 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

Test Results

- Refer to see the measured plot in next page.

Radiated Emissions Test data

- 9 kHz to 1 GHz


Test Date	January 26, 2017
Environmental of Test	(2.3 ± 1.1) °C, (60 ± 2) % R.H., (102.8 ± 0.0) kPa

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.
Detector mode: CISPR Quasi-Peak mode (100 Hz, 9 kHz) (6 dB Bandwidth: 120 kHz)

Frequency [MHz]	Reading [dB(μV)]	Polarization (*H/**V)	Ant. Factor [dB/m]	Cable Loss [dB(μV)]	Height [cm]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
44.31	54.00	V	13.11	-30.71	100	36.40	40.00	3.60
143.85	47.20	V	12.60	-29.60	107	30.20	43.50	13.30
216.11	58.60	V	10.13	-28.73	111	40.00	46.00	6.00
249.52	52.72	V	11.65	-28.37	113	36.00	46.00	10.00
269.97	55.20	H	12.42	-28.22	342	39.40	46.00	6.60
324.74	51.67	V	14.13	-27.80	120	38.00	46.00	8.00

NOTES:

1. * H : Horizontal polarization, ** V : Vertical polarization
2. The cable loss value was included the Amp. Gain.
3. Result = Reading + Antenna factor + Cable loss
4. Margin value = Limit - Result
5. The measurement was performed for the frequency range above 9 kHz according to FCC Part 15.209.



- Above 1 GHz (1 GHz to 25 GHz)

Test Date	January 25, 2017
Environmental of Test	(24.1 ± 3.8) °C, (40 ± 4) % R.H., (103.1 ± 0.1) kPa

1. Low CH (2 425 MHz)

Frequency [MHz]	Reading [dB(μV)]		Polarity (*H/**V)	Ant. Factor [dB/m]	Cable - Amp. Gain [dB]	Result [dB(μV/m)]		Limit [dB(μV/m)]		Margin [dB]	
	Peak	Average				Peak	Average	Peak	Average	Peak	Average
1 064.64	60.73	38.03	V	24.82	-40.35	45.20	22.50	73.97	53.97	28.77	31.47
1 496.92	55.81	40.51	V	25.30	-39.71	41.40	26.10	73.97	53.97	32.57	27.87
1 593.88	53.28	37.98	V	25.44	-39.52	39.20	23.90	73.97	53.97	34.77	30.07
1 981.72	57.75	45.55	H	26.04	-38.99	44.80	32.60	73.97	53.97	29.17	21.37
5 272.50	61.46	36.26	V	31.66	-34.42	58.70	33.50	73.97	53.97	15.27	20.47
5 496.72	51.40	36.20	V	31.87	-34.17	49.10	33.90	73.97	53.97	24.87	20.07

2. Middle CH (2 450 MHz)

Frequency [MHz]	Reading [dB(μV)]		Polarity (*H/**V)	Ant. Factor [dB/m]	Cable - Amp. Gain [dB]	Result [dB(μV/m)]		Limit [dB(μV/m)]		Margin [dB]	
	Peak	Average				Peak	Average	Peak	Average	Peak	Average
1 060.60	61.05	38.05	V	24.82	-40.37	45.50	22.50	73.97	53.97	28.47	31.47
1 496.92	55.41	41.51	V	25.30	-39.71	41.00	27.10	73.97	53.97	32.97	26.87
1 896.88	55.91	39.11	H	25.91	-39.02	42.80	26.00	73.97	53.97	31.17	27.97
1 945.36	57.01	39.61	H	25.99	-39.00	44.00	26.60	73.97	53.97	29.97	27.37
1 981.72	57.45	42.25	H	26.04	-38.99	44.50	29.30	73.97	53.97	29.47	24.67
5 054.34	50.81	36.31	V	31.46	-34.57	47.70	33.20	73.97	53.97	26.27	20.77

3. High CH (2 475 MHz)

Frequency [MHz]	Reading [dB(μV)]		Polarity (*H/**V)	Ant. Factor [dB/m]	Cable - Amp. Gain [dB]	Result [dB(μV/m)]		Limit [dB(μV/m)]		Margin [dB]	
	Peak	Average				Peak	Average	Peak	Average	Peak	Average
1 060.60	61.15	37.95	V	24.82	-40.37	45.60	22.40	73.97	53.97	28.37	31.57
1 496.92	55.01	40.71	V	25.30	-39.71	40.60	26.30	73.97	53.97	33.37	27.67
1 909.00	55.58	39.18	H	25.93	-39.01	42.50	26.10	73.97	53.97	31.47	27.87
1 949.40	56.11	39.21	H	25.99	-39.00	43.10	26.20	73.97	53.97	30.87	27.77
1 981.72	58.45	46.45	H	26.04	-38.99	45.50	33.50	73.97	53.97	28.47	20.47
5 690.64	50.40	35.90	V	32.10	-34.10	48.40	33.90	73.97	53.97	25.57	20.07



NOTES:

- * H : Horizontal polarization, ** V : Vertical polarization
- Factor = Antenna factor + Cable loss - Amp. Gain
- Result = Reading + Factor
- Margin value = Limit - Result
- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- Spectrum setting:
 - Peak Setting 1 GHz to 10th harmonics of fundamental, RBW = 1 MHz, VBW = 1 MHz, Sweep = Auto
 - AV Setting 1 GHz to 10th harmonics of fundamental, RBW = 1 MHz, VBW = 10 kHz, Sweep = Auto



Plots of Spurious Emissions (Conducted Measurement)

Test Date	January 23, 2017
Environmental of Test	(22.5 ± 0.2) °C, (38 ± 0) % R.H., (103.0 ± 0.0) kPa



[CH Low]



[CH Mid]



[CH High]



5.3 Conducted Emissions Measurement

EUT	SETTOP BOX / DMS2004UHD W
Limit apply to	FCC Part 15.207
Test Date	January 25, 2017
Environmental of Test	(23.8 ± 0.3) °C, (38 ± 1) % R.H., (103.1 ± 0.0) kPa
Operating Condition	RF transmitting continuously during the tested.
Result	Passed by 2.13 dB

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency of Emission [MHz]	Conducted limit [dB(μ V)]	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency.

Test Results

- Refer to see the measured plot in next page.

Conducted Emission Test Data

The following data and graph shows the highest levels of conducted emissions on both polarizations of hot and neutral line.

Detector mode: CISPR Quasi-Peak mode (6 dB Bandwidth: 9 kHz)

NOTES:


1. Please see the measured data and graph in next page.
2. The Level (Result) value was included the reading, LISN factor and cable loss.
3. Delta (Margin) value = Limit - Level (Result)
4. Measurement were performed at the AC Power Inlet in the frequency band of 150 kHz ~ 30 MHz according to the FCC Part 15.207.
5. If the Quasi-Peak limit is met when using a Peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the Quasi-Peak detector receiver is unnecessary.
6. If the average limit is met when using a Quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

Line: HOT

ETL EMC Laboratory
Conducted Emission Test Result

EUT: ETLT170118.0010
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: H

Prescan Measurement:	Detectors:	X QP / + AV
	Meas Time:	see scan settings
	Peaks:	16
	Acc Margin:	10 dB



Report no. ETLT170118.0010, Page 20 of 27

ETL EMC Laboratory

Conducted Emission Test Result

EUT: ETLT170118.0010
 Manuf:
 Op Cond:
 Operator:
 Test Spec:
 Comment: H

Prescan Measurement: Detectors: X QP / + AV
 Meas Time: see scan settings
 Peaks: 16
 Acc Margin: 10 dB

Peak Search Results

Frequency MHz	QP Level dBμV	QP Limit dBμV	QP Delta dB
0.151	54.07	65.94	11.87
0.156	54.31	65.67	11.36
0.186	51.95	64.21	12.26
0.198	50.95	63.69	12.74
0.208	49.68	63.28	13.60
0.249	44.33	61.79	17.46
0.44	42.24	57.06	14.82
0.495	40.85	56.08	15.23
0.616	39.66	56.00	16.34
0.823	39.87	56.00	16.13
0.931	39.17	56.00	16.83
4.19	42.26	56.00	13.74
4.72	48.67	56.00	7.33
4.93	50.24	56.00	5.76
5.17	53.75	60.00	6.25
5.395	55.94	60.00	4.06
5.83	55.98	60.00	4.02
6.1	54.32	60.00	5.68
7.96	43.61	60.00	16.39
9.0	45.48	60.00	14.52
14.19	51.17	60.00	8.83
18.52	39.76	60.00	20.24

Frequency MHz	AV Level dBμV	AV Limit dBμV	AV Delta dB
0.151	42.90	55.94	13.04
0.156	41.43	55.67	14.24
0.186	37.86	54.21	16.35
0.198	40.66	53.69	13.03
0.208	35.72	53.28	17.56
0.249	35.91	51.79	15.88

* limit exceeded

Peak Search Results (continued)

Frequency MHz	AV Level dBμV	AV Limit dBμV	AV Delta dB
0.44	34.01	47.06	13.05
0.495	29.28	46.08	16.80
0.616	29.88	46.00	16.12
0.823	28.13	46.00	17.87
0.931	31.47	46.00	14.53
4.19	35.05	46.00	10.95
4.72	38.32	46.00	7.68
4.93	39.84	46.00	6.16
5.17	44.13	50.00	5.87
5.395	47.03	50.00	2.97
5.83	46.68	50.00	3.32
6.1	43.91	50.00	6.09
7.96	35.37	50.00	14.63
9.0	36.74	50.00	13.26
14.19	44.61	50.00	5.39
18.52	31.68	50.00	18.32


* limit exceeded

Line: Neutral

ETL EMC Laboratory Conducted Emission Test Result

EUT: ETLT170118.0010
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: N

Prescan Measurement: Detectors: X QP / + AV
Meas Time: see scan settings
Peaks: 16
Acc Margin: 10 dB



ETL EMC Laboratory
Conducted Emission Test Result

EUT: ETLT170118.0010
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: N

Prescan Measurement: Detectors: X QP / + AV
Meas Time: see scan settings
Peaks: 16
Acc Margin: 10 dB

Peak Search Results

Frequency MHz	QP Level dBμV	QP Limit dBμV	QP Delta dB
0.156	53.49	65.67	12.18
0.197	52.83	63.74	10.91
0.209	50.95	63.24	12.29
0.245	47.90	61.92	14.02
0.28	46.23	60.82	14.59
0.444	43.60	56.99	13.39
0.822	39.84	56.00	16.16
4.235	41.91	56.00	14.09
4.92	51.73	56.00	4.27
4.93	51.89	56.00	4.11
5.12	52.42	60.00	7.58
5.38	55.62	60.00	4.38
5.4	55.70	60.00	4.30
5.8	55.58	60.00	4.42
6.085	55.88	60.00	4.12
6.445	53.89	60.00	6.11
12.0	53.70	60.00	6.30

Frequency MHz	AV Level dBμV	AV Limit dBμV	AV Delta dB
0.156	33.18	55.67	22.49
0.197	36.97	53.74	16.77
0.209	32.72	53.24	20.52
0.245	32.72	51.92	19.20
0.28	27.51	50.82	23.31
0.444	33.94	46.99	13.05
0.822	27.95	46.00	18.05
4.235	34.66	46.00	11.34
4.92	43.54	46.00	2.46
4.93	43.06	46.00	2.94
5.12	44.38	50.00	5.62

* limit exceeded

Peak Search Results (continued)

Frequency MHz	AV Level dBμV	AV Limit dBμV	AV Delta dB
5.38	47.26	50.00	2.74
5.4	47.87	50.00	2.13
5.8	46.54	50.00	3.46
6.085	46.45	50.00	3.55
6.445	45.88	50.00	4.12
12.0	46.48	50.00	3.52

* limit exceeded

6. SAMPLE CALCULATION

Sample Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor - Preamplifier Factor

$$dB(\mu V) = 20 \log_{10} (\mu V) : \text{Equation}$$

$$dB(\mu V) = dBm + 107$$

Example: @ 44.31 MHz

$$\text{Limit} = 40.00 \text{ dB}(\mu V/m)$$

$$\text{Reading} = 54.00 \text{ dB}(\mu V)$$

$$\text{Reading} + \text{Antenna Factor} + \text{Cable loss} = 54.00 + 13.11 + (-30.71) = 36.40 \text{ dB}(\mu V/m)$$

$$\text{Total} = 36.40 \text{ dB}(\mu V/m)$$

$$\text{Margin} = 40.00 - 36.40 = 3.60 \text{ dB}$$

$$= 3.60 \text{ dB below Limit}$$

7. List of test equipments used for measurements

	Test Equipment	Model	Mfg.	Serial No.	Cal. Date	Cal. Due Date
<input checked="" type="checkbox"/>	EMI Test Receiver	ESCS30	R&S	100087	16.03.15	17.03.15
<input checked="" type="checkbox"/>	Spectrum Analyzer	FSW43	R&S	103794	16.09.06	17.09.06
<input checked="" type="checkbox"/>	EMI Test Receiver	ESCI7	R&S	100851	16.09.01	17.09.01
<input checked="" type="checkbox"/>	EMI Test Receiver	ESPI3	R&S	100478	16.09.01	17.09.01
<input checked="" type="checkbox"/>	Two-Line V-Network	ENV216	R&S	101715	16.03.15	17.03.15
<input checked="" type="checkbox"/>	Two-Line V-Network	ENV216	R&S	102055	16.04.11	17.04.11
<input checked="" type="checkbox"/>	Loop Antenna	6502	EMCO	00033743	16.09.05	18.09.05
<input checked="" type="checkbox"/>	LogBicon Antenna	VULB9160	Schwarzbeck	3164	15.06.08	17.06.08
<input checked="" type="checkbox"/>	Horn Antenna	BBHA 9120D	Schwarzbeck	277	16.10.12	18.10.12
<input checked="" type="checkbox"/>	Horn Antenna	BBHA 9170	Schwarzbeck	BBHA9170444	15.09.03	17.09.03
<input checked="" type="checkbox"/>	PSA Series Spectrum Analyzer	E4440A	Agilent	US40420382	16.09.05	17.09.05
<input checked="" type="checkbox"/>	Amplifier	TK-PA18	TESTEK	120020	16.09.01	17.09.01
<input checked="" type="checkbox"/>	Amplifier	310N	SONOMA INSTRUMENT	284750	16.09.02	17.09.02
<input checked="" type="checkbox"/>	Amplifier	JS44-18004000-45-8P	MITEQ Inc.	1568695	16.09.02	17.09.02
<input checked="" type="checkbox"/>	Attenuator	BW-S10-2W263+	Mini-Circuits	NONE	16.03.15	17.03.15
<input checked="" type="checkbox"/>	AC Power Source	6405-12230-3	Extech Electronics	1390168	N/A	N/A
<input checked="" type="checkbox"/>	Highpass Filter	WHKX3.0 /18G-6SS	Wainwright Instrument	15	16.03.14	17.03.14
<input checked="" type="checkbox"/>	Turn-Table	TT 1.35 SI	SES	-	N/A	N/A
<input checked="" type="checkbox"/>	Antenna Master	AM 4.5	SES	-	N/A	N/A
<input checked="" type="checkbox"/>	Turn-Table	DS1200-S	Innco Systems GmbH	2740311	N/A	N/A
<input checked="" type="checkbox"/>	Controller	HD2000	HD GmbH	C/125	N/A	N/A
<input checked="" type="checkbox"/>	Antenna Master	MA4000	AUDIX	N/A	N/A	N/A