

Appendix J. Radio Frequency Exposure

FCC ID: PFNIPH3004HDM

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limit

Limits for general population/Uncontrolled exposure

Frequency Range [MHz]	Electric Field Strength (E) [V/m]	Magnetic Field Strength (H) [A/m]	Power Density (S) [mW/cm ²]	Averaging Time $ E ^2$, $ H ^2$ or S [minutes]
0.3 - 1.34 1.34 - 30	614 824/f	1.63 2.19/f	(100) (180/f²)	30 30
30 - 300	27.5	0.073	0.2	30
300 - 1 500			f/1 500	30
<mark>1 500 - 100 000</mark>			<mark>1.0</mark>	30

f = frequency in MHz

MPE Prediction

Predication of MPE limit at a given distance.

Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S=PG/4\pi R^2$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Max tune up power : -3.28 dBm (0.469 mW)

Prediction distance : 20 cm
Predication frequency : 2 425 MHz

Antenna gain(Max) : 3.25 dBi (2.113 numeric)

Power density at predication frequency at 20 cm : 0.000 197 57 mW/cm²

MPE Limit for : 1 mW/cm²

Test Result

The power density level at 20 cm is 0.000 197 57 mW/cm² which is below the uncontrolled exposure limit of 1 mW/cm² at 2 425 MHz to 2 475 MHz.

^{*}Plane-wave equivalent power density