



April 07, 2016

TUV SUD BABT FCB  
Octagon House,  
Segensworth Road,  
Fareham,  
Hampshire,  
PO15 5RL

Attention: Director of Certification

**RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices v06 and RSS-102 Issue 5 March 2015**

IC: 9290A-943806  
FCC ID: PH29715

***Portable exposure SAR Exemption Calculation using a 1mm separation distance:***

As per Clause 4.3.1 (a) of KDB 447498 D01 v06:

$$\left( \frac{\text{max.power of channel,including tune-up tolerance,mW}}{\text{min.test separation distance,mm}} \right) \times (\sqrt{f \text{ (GHz)}}) \leq 3.0$$

$$\left( \frac{0.48\text{mW}}{1 \text{ mm}} \right) \times (\sqrt{2.440\text{(GHz)}}) \leq 3.0$$

$$0.750 \leq 3.0 \text{ (complies)}$$

The EUT complies with the exemption limits for routine evaluation based on frequency and separation distance as per Table 1 of RSS-102 Issue 5 March 2015 with an EIRP of 0.575mW. Limit at 2440 MHz with a separation distance of  $\leq 5$  mm is 4.0mW. See separate RSS-102 Annex A exhibit for more details.

All calculations were based on peak power (worst case than source-based time-averaged maximum conducted output power).

Sincerely,

A handwritten signature in black ink, appearing to read 'Ferdie S. Custodio', written over a horizontal line.

Ferdie S. Custodio

Name

Authorized Signatory

Title: Senior EMC/Wireless Test Engineer