



OET Bulletin 65 (MPE) Test Report

Report No.: AGC02X121201F7

FCC ID : PH3-DR138
PRODUCT DESIGNATION : VHF FM MOBILE TRANSCEIVER
BRAND NAME : ALINCO
TEST MODEL : DR-138
CLIENT : Alinco Incorporated, Electronics Division
DATE OF ISSUE : Dec.17, 2012
STANDARD(S) : OET Bulletin 65
REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd.

CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.agc-cert.com/rzcx.asp>



TABALE OF CONTENTS

TABALE OF CONTENTS	2
1. TEST RESULT CERTIFICATION.....	3
2. TECHNICAL INFORMATION.....	4
3. RF EXPOSURE MEASUREMENT.....	5
3.1 INTRODUCTION.....	5
3.2 FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	6
4. CLASSIFICATION OF THE ASSESSMENT METHODS	7
5. EUT OPERATION CONDITION	7
6. TEST RESULTS.....	8

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.agc-cert.com/rzcx.asp>



1. TEST RESULT CERTIFICATION

Applicant Name:	Alinco Incorporated, Electronics Division
Address:	Yodoyabashi Dai-Bldg 13F, 4-4-9 Koraibashi, Chuo-Ku, Osaka 541-0043, Japan
Manufacturer Name:	Alinco Incorporated, Electronics Division
Address:	Yodoyabashi Dai-Bldg 13F, 4-4-9 Koraibashi, Chuo-Ku, Osaka 541-0043, Japan
Product Designation	VHF FM MOBILE TRANSCEIVER
Brand Name	ALINCO
Test Model	DR-138
Hardware Version:	V1.00
Software Version:	V1.00
Test Standard	OET Bulletin 65
File Number:	AGC02X121201F7
Date of Test:	Dec.10, 2012 to Dec.15, 2012

We (AGC), Attestation of Global Compliance Co., Ltd. for compliance with the requirements set forth in the FCC Standard OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01). The results of testing in this report apply to the product/system which was tested only.

Tested by

Wall Huang

Wall Huang

Dec.17, 2012

Checked By

Forrest Lei

Forrest Lei

Dec.17, 2012

Authorized By

Solger Zhang

Solger Zhang

Dec.17, 2012

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.agc-cert.com/rzcx.asp>



2. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

EUT DESCRIPTION

The EUT is a VHF FM MOBILE TRANSCEIVER designed for voice communication. It is designed by way of utilizing the FM modulation achieves the system operating.

A major technical description of EUT is described as following:

Communication Type	Voice / Tone only
Modulation	FM
Emission Type	F3E
Emission Bandwidth	10.76KHz
Peak Frequency Deviation	1.84 KHz
Audio Frequency Response	10.93dB
Maximum Transmitter Power	47.75dBm(Max)
Output power Modification	60W (It was fixed by the manufacturer, any individual can't arbitrarily change it)
Antenna Designation	Detachable
Power Supply	DC 13.8V by DC source
Limiting Voltage	DC 11.73V
Operation Frequency Range and Channel	Frequency Range: 136.000MHz to 173.9975MHz Channel Separation: 12.5KHz
	Top Channel: 173.9975MHz, Centre Channel: 155.025MHz, Bottom Channel: 136.000MHz,
Frequency Tolerance	0.652ppm for 12.5 KHz Channel Separation

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.agc-cert.com/rzcx.asp>



3. RF EXPOSURE MEASUREMENT


3.1 INTRODUCTION

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

The 1992 ANSI/IEEE standard (See Listed limit table) specifies a minimum separation distance of 20 cm for performing reliable field measurements to determine adherence to MPE limits.

If the minimum separation distance between a transmitter and nearby persons is more than 20 cm under normal operating conditions, compliance with MPE limits may be determined at such distance from the transmitter. When applicable, operation instructions and prominent warning labels may be used to alert the exposed persons to maintain a specified distance from the transmitter or to limit their exposure durations and usage conditions to ensure compliance.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.agc-cert.com/rzcx.asp>





3.2 FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f ²)*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

*Note:

1. f= Frequency in MHz * Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessed and confirmed at <http://www.agc-cert.com/rzcx.asp>



4. CLASSIFICATION OF THE ASSESSMENT METHODS

According to user manual, The antenna of the product, under normal use condition is at least 2.0m away from the body of the user. Warning statement to the user for keeping at least 200cm separation distance and the prohibition of operating to a person has been printed on the user's manual. So, this product under normal use is located on electromagnetic far field between the human body.

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

5. EUT OPERATION CONDITION

Make the EUT to transmit at lowest, middle and highest channel individually.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.agc-cert.com/rzcx.asp>



6. TEST RESULTS

Note: report the worst result in this part.

Antenna Gain=1.5dBi (Numeric 1.413), $\Pi=3.141$

Frequency	Output Power	Output Power	Power Density	Power Density Limit	Result
MHz	dBm	mW	mW/cm ²	mW/cm ²	Pass/Fail
136.00	47.75	59566	0.17	0.2	Pass

Note: The output power is refer to AGC02X121201F2.

According to the user manual, the minimum separate distance which used for MPE calculate is 2.0m.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.agc-cert.com/rzcx.asp>