

Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: Alinco, Inc.
Model: DJ-175T
Standards: FCC 15.121
& IC RSS-215
Report: 2008118

Appendix C: FCC Attestation Letter

Please refer to the following page.

ALINCO

Alinco, Inc. Electronics Division

Shin Dai Bldg 9F, 1-2-6 Dujimahama, Kita-ku, Osaka 530-0004 Japan

Tel: 0081-6-4797-2134 Fax: 0081-6-4797-2156

Aug.18,2008

Federal Communications Commissions

RE: PH3 DJ175T / 800MHz analog cellular telephone band blocking

Dear Sir or Madam,

This is to declare that the device in application PH3 DJ175T has been blocked for any and all access of 824.00 to 849.9975MHz and 869.00 to 894.9975MHz.

The device uses double super heterodyne as a receiver circuit and frequency is generated by a PLL synthesizer circuitry. The first local oscillation frequencies are determined by the N value data of the CPU. The 136.000-173.995MHz range is determined by 114.3 to 152.295MHz data, and such values are not able to be changed by any means.

The low-pass filters and the band-pass filters are used to filter-out the unwanted bands. The CPU used in this device, our parts code XA1292, vender's code uPD78F0394GC-8EA-A is exclusively programmed and burned for this US export model. Alinco, Inc exports solely this version to the US market, and this CPU can't be modified by any means to receive the declared cellular frequencies. Moreover, the entire circuitry of this device is not designed to cover the cellular frequencies anyway.

To my best of knowledge being informed by the chief-engineer in charge of PH3 DJ175T, above declared is true.

Sincerely,



Kazuhiro Kusuhara

General manager, Production Section,
Alinco, Inc. Electronics Division