

ATTACHMENT O – SAR TEST PLOTS

Test Laboratory: HCT

Company : AXESSTEL INC.
Mode : CDMA835 / Channel : 1013
Position : Body / Antenna : Fixed
Liquid Temperature : 21.8 °C
Date Tested : August 22, 2006

DUT: PX220


Communication System: CDMA 835MHz FCC; Frequency: 824.7 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 825$ MHz; $\sigma = 0.965$ mho/m; $\epsilon_r = 54$; $\rho = 1000$ kg/m³
Phantom section: Flat Section ; Measurement SW: DASY4, V4.6 Build 23

DASY4 Configuration:

- Probe: ET3DV6 - SN1609; ConvF(6.42, 6.42, 6.42); Calibrated: 2006-03-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn447; Calibrated: 2005-11-30
- Phantom: SAM 835/900 MHz; Type: SAM

Body CDMA 1013ch/Area Scan (101x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (interpolated) = 0.924 mW/g

Body CDMA 1013ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm
Reference Value = 27.3 V/m; Power Drift = 0.004 dB
Peak SAR (extrapolated) = 1.11 W/kg
SAR(1 g) = 0.860 mW/g; SAR(10 g) = 0.621 mW/g
Maximum value of SAR (measured) = 0.905 mW/g



0 dB = 0.905mW/g

Test Laboratory: HCT

Company : AXESSTEL INC.
Mode : CDMA835 / Channel : 363
Position : Body / Antenna : Fixed
Liquid Temperature : 21.8°C
Date Tested : August 22, 2006

DUT: PX220

Communication System: CDMA 835MHz FCC, Frequency: 835.89 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 835.89$ MHz; $\sigma = 0.979$ mho/m; $\epsilon_r = 53.8$; $\rho = 1000$ kg/m³
Phantom section: Flat Section ; Measurement SW: DASY4, V4.6 Build 23

DASY4 Configuration:


- Probe: ET3DV6 - SN1609; ConvF(6.42, 6.42, 6.42); Calibrated: 2006-03-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn447; Calibrated: 2005-11-30
- Phantom: SAM 835/900 MHz; Type: SAM

Body CDMA 363ch/Area Scan (101x111x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (interpolated) = 1.08 mW/g

Body CDMA 363ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 29.8 V/m; Power Drift = -0.016 dB
Peak SAR (extrapolated) = 1.35 W/kg
SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.724 mW/g

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 1.08 mW/g



0 dB = 1.08mW/g

Test Laboratory: HCT

Company : AXESSTEL INC.
Mode : CDMA835 / Channel : 777
Position : Body / Antenna : Fixed
Liquid Temperature : 21.8°C
Date Tested : August 22, 2006

DUT: PX220

Communication System: CDMA 835MHz FCC; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 848.31$ MHz; $\sigma = 0.992$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³
Phantom section: Flat Section ; Measurement SW: DASY4, V4.6 Build 23

DASY4 Configuration:

- Probe: ET3DV6 - SN1609; ConvF(6.42, 6.42, 6.42); Calibrated: 2006-03-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn447; Calibrated: 2005-11-30
- Phantom: SAM 835/900 MHz; Type: SAM


Body CDMA 777ch/Area Scan (101x111x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (interpolated) = 1.08 mW/g

Body CDMA 777ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm
Reference Value = 30.5 V/m; Power Drift = 0.033 dB

Peak SAR (extrapolated) = 1.33 W/kg
SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.727 mW/g

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 1.07 mW/g



Test Laboratory: HCT

Company : AXESSTEL INC.
Mode : CDMA835 / Channel : 1013 (With Charger)
Position : Body / Antenna : Fixed
Liquid Temperature : 21.8°C
Date Tested : August 22, 2006

DUT: PX220


Communication System: CDMA 835MHz FCC, Frequency: 824.7 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 825$ MHz; $\sigma = 0.965$ mho/m; $\epsilon_r = 54$; $\rho = 1000$ kg/m³
Phantom section: Flat Section ; Measurement SW: DASY4, V4.6 Build 23

DASY4 Configuration:

- Probe: ET3DV6 - SN1609; ConvF(6.42, 6.42, 6.42); Calibrated: 2006-03-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn447; Calibrated: 2005-11-30
- Phantom: SAM 835/900 MHz; Type: SAM

Body CDMA 1013ch/Area Scan (101x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (interpolated) = 0.928 mW/g

Body CDMA 1013ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm
Reference Value = 27.2 V/m; Power Drift = -0.073 dB
Peak SAR (extrapolated) = 1.14 W/kg
SAR(1 g) = 0.865 mW/g; SAR(10 g) = 0.623 mW/g
Maximum value of SAR (measured) = 0.916 mW/g



Test Laboratory: HCT

Company : AXESSTEL INC.
Mode : CDMA835 / Channel : 363 (With Charger)
Position : Body / Antenna : Fixed
Liquid Temperature : 21.8 °C
Date Tested : August 22, 2006

DUT: PX220

Communication System: CDMA 835MHz FCC; Frequency: 835.89 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 835.89$ MHz; $\sigma = 0.979$ mho/m; $\epsilon_r = 53.8$; $\rho = 1000$ kg/m³
Phantom section: Flat Section ; Measurement SW: DASY4, V4.6 Build 23

DASY4 Configuration:

- Probe: ET3DV6 - SN1609; ConvF(6.42, 6.42, 6.42); Calibrated: 2006-03-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn447; Calibrated: 2005-11-30
- Phantom: SAM 835/900 MHz; Type: SAM


Body CDMA 363ch/Area Scan (101x111x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (interpolated) = 1.09 mW/g

Body CDMA 363ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm

Reference Value = 30.0 V/m; Power Drift = -0.073 dB
Peak SAR (extrapolated) = 1.33 W/kg
SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.725 mW/g

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 1.06 mW/g



Test Laboratory: HCT

Company : AXESSTEL INC.
Mode : CDMA835 / Channel : 777 (With Charger)
Position : Body / Antenna : Fixed
Liquid Temperature : 21.8°C
Date Tested : August 22, 2006

DUT: PX220

Communication System: CDMA 835MHz FCC, Frequency: 848.31 MHz,Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 848.31$ MHz; $\sigma = 0.992$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³
Phantom section: Flat Section ;Measurement SW: DASY4, V4.6 Build 23

DASY4 Configuration:

- Probe: ET3DV6 - SN1609; ConvF(6.42, 6.42, 6.42); Calibrated: 2006-03-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn447; Calibrated: 2005-11-30
- Phantom: SAM 835/900 MHz; Type: SAM


Body CDMA 777ch/Area Scan (101x111x1): Measurement grid: $\Delta x=15$ mm, $\Delta y=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (interpolated) = 1.09 mW/g

Body CDMA 777ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x=8$ mm, $\Delta y=8$ mm, $\Delta z=5$ mm

Reference Value = 30.9 V/m; Power Drift = -0.045 dB
Peak SAR (extrapolated) = 1.33 W/kg
SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.732 mW/g

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 1.07 mW/g



Test Laboratory: HCT

Company : AXESSTEL INC.
Mode : CDMA835 / Channel : 777 (With Charger)
Position : Body / Antenna : Fixed
Liquid Temperature : 21.8 °C
Date Tested : August 22, 2006

DUT: PX220

Communication System: CDMA 835MHz FCC; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 848.31$ MHz; $\sigma = 0.992$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³
Phantom section: Flat Section ; Measurement SW: DASY4, V4.6 Build 23

DASY4 Configuration:

- Probe: ET3DV6 - SN1609; ConvF(6.42, 6.42, 6.42); Calibrated: 2006-03-23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn447; Calibrated: 2005-11-30
- Phantom: SAM 835/900 MHz; Type: SAM

Body CDMA 777ch/Z Scan (1x1x31): Measurement grid: dx=20mm, dy=20mm, dz=5mm

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 1.05 mW/g

